

GEORGE C. MARSHALL SPACE FLIGHT CENTER

MTP-AERO-62-73

EARTH-MOON TRANSIT STUDIES BASED ON EPHEMERIS DATA AND USING BEST AVAILABLE COMPUTER PROGRAM

PART I: PERISELENUM CONDITIONS AS FUNCTION OF INJECTION CONDITIONS

BYRD TUCKER

ABSTRACT

11809

Based on ephemeris data between 1964 and 1969, free flights from earth to moon are investigated by representative examples as to the relationships between injection conditions and periselenum conditions. Emphasis is placed on injection conditions that are compatible with due east launch from Atlantic Missile Range by means of Saturn class vehicles.

AUTHOR

Available to MASA Offices and

GEORGE C. MARSHALL SPACE FLIGHT CENTER

*

.

. . . .

MTP-AERO-62-73

September 27, 1962

LUNAR FLIGHT STUDY SERIES

VOLUME I

EARTH-MOON TRANSIT STUDIES BASED ON & PHEMERIS DATA AND USING BEST AVAILABLE COMPUTER PROGRAM

PART I: PERISELENUM CONDITIONS AS FUNCTION OF INJECTION CONDITIONS

by

Byrd Tucker

FUTURE PROJECTS BRANCH AEROBALLISTICS DIVISION

TABLE OF CONTENTS

τ.	INTROD	UCTION	Page 3
			•
II.	CONSTRA	INTS AND IMPLEMENTS OF THE STUDY	3
III.	COMMENT	S ON SOME CHARACTERISTICS OF THE MOON'S MOTION	3
IV.	BOUNDS ON DEPA 1. 2.	 FOR THE EFFECT OF THE VARYING EARTH-MOON EPHEMERIS RTURE AND ARRIVAL VELOCITIES FOR VARIOUS TRIP TIMES. Procedure. Results. A. Effects of various arrival patterns on velocities. B. Velocity variations due to varying the arrival altitude. C. Departure and arrival velocity behavior for changes in arrival earth-moon ephemeris and 	5 5 7 7 9
		trip-time	10
v.	BOUNDS 1. 2.	<pre>FOR THE ATTAINABLE ARRIVAL CONIC ORIENTATIONS Procedure Results A. The influence of the varying earth-moon ephemeris at arrival B. The influence of launch azimuth variations</pre>	15 15 16 16 33

LIST OF FIGURES

Figure	Title	Page
1.	Geometry Associated with Dual Time Solutions	x
2.	Various Arrival Conic Orientation Trajectory Plots	8
3.	Space-fixed Departure Velocity at a Geocentric Altitude of 400(km) That Results in Low Altitude Periselenum Arrival for Various Flight Times and Earth-Moon Positions at Arrival	11
4.	Space-fixed Arrival Velocity for Various (1) Periselenum Arrival Altitudes, (2) Trip Times, and (3) Samplings of the Earth-Moon Ephemeris at Arrival	13
5.	Unattainable Inclination Areas for Travel-Plane Transit, November-December, 1964	21
6.	Unattainable Inclination Areas for Travel-Plane Transit, March-April, 1969	22
7.	Unattainable Inclination Areas for Out-of-Plane Transit, October, 1966	27
8.	Unattainable Inclination Areas for Out-of-Plane Transit, November-December, 1964	28
9.	Survey of Arrival Inclination for Flights Having 66 hr. Trip Time Arriving on 30 November 1964, δ_{c} about -5°, with Launch Azimuth as a Para-meter	34

LIST OF TABLES

Tab le	Title	Page
1.	Arrival Characteristics of the Earth-Moon Ephemeris Sampling	6
2.	Departure and Arrival Conditions for Various Arrival Conic Orientations in November, 1964	7
3.	Departure and Arrival Conditions for Arriving at Various Periselenum Altitudes via a Fixed Arrival Path in October, 1966	9
4.	Space-fixed Arrival Velocity for Arrival at 185(km) Periselenum Altitude for Various Trip Times and Earth-Moon Ephemeris Samplings	14
5.	Departure and Arrival Conditions for Various Retrograde Arrival Conic Orientations, Fixed Flight Time of 66 hrs., and Fixed $ B $	17
6.	Departure and Arrival Conditions for Various Direct Arrival Conic Orientations, Fixed Flight Time of 66 hrs., and Fixed $ \vec{B} $	18
7.	Departure and Arrival Conditions for Trajectories Resulting in Minimum Attainable Inclinations for Travel-Plane Transit in November-December 1964, the Near Coplanar Branch of the Dual-Time Solution	23
8.	Departure and Arrival Conditions for Trajectories Resulting in Minimum Attainable Inclinations for Travel-Plane Transit in November-December 1964, the Out-of-Plane Branch of the Dual-Time Solution	24
9.	Departure and Arrival Conditions for Trajectories Resulting in Minimum Attainable Inclinations for Travel-Plane Transit in March-April 1969, the Near Coplanar Branch of the Dual-Time Solution	2 5
10.	Departure and Arrival Conditions for Trajectories Resulting in Minimum Attainable Inclinations for Travel-Plane Transit in March-April 1969, the Out-Of-Plane Branch of the Dual-Time Solution	2 6

v

Table	Title	Page
11.	Departure and Arrival Conditions for Trajectories Resulting in Minimum Attainable Inclinations for Out-of-Plane Transit in October 1966, the Low- High Peaks Branch of the Dual-Time Solution	29
12.	Departure and Arrival Conditions for Trajectories Resulting in Minimum Attainable Inclinations for Out-of-Plane Transit in October 1966, the High- Low Peaks Branch of the Dual-Time Solution	30
13.	Departure and Arrival Conditions for Trajectories Resulting in Minimum Attainable Inclinations for Out-Of-Plane Transit in November-December 1964, the Low-High Peaks Branch of the Dual-Time Solution	31
14.	Departure and Arrival Conditions for Trajectories Resulting in Minimum Attainable Inclinations for Out-of-Plane Transit in November-December 1964, the High-Low Peaks Branch of the Dual-Time	
	Solution	32

vi

SYMBOLS AND DEFINITIONS

<u>Symbol</u>	Definition
C ₃	Twice the total energy per unit mass, so called the "VIS VIVA" by some. Specifically, $C_3 = V^2 - 2 \frac{GM}{R}$, where V and R are referenced to some central body whose mass is denoted by M. The notations $C_{3\oplus}$, C_3 , and $C_{3\oplus}$ indicate that the central body is the earth, moon, and sun, respectively.
e	The eccentricity of the instantaneous two-body solution. Subscripts may be used as discussed for C3.
ⁱ M	Instantaneous inclination of the lunar travel plane relative to the true earth equator of date.
Ω _M	"The longitude of the mean ascending node of the moon's orbit measured in the ecliptic from the mean equinox of date"; see [3] for more details.
(ρ, δ, α)	Geocentric spherical coordinates of a body where
	p is the radial distance,
	δ is declination (the angle measured in the meridian containing the body from the earth's equator to the body, positive being north and negative south),
	α is right ascension (the angle measured in the equatorial plane from vernal equinox to the meridian containing the body, positive eastward).
r	Radial distance
ø'	Geocentric latitude
λ	Greenwich referenced longitude, positive eastward.
(V*, V)	Velocity magnitude measured in a space-fixed and rotating system, respectively.
(Γ, γ)	Path angle referenced to the local horizontal plane, space-fixed and rotating, respectively.
(Σ, σ)	Local azimuth angle, space-fixed and rotating, respectively.

vii

Symb	o1

Definition

h Altitude

i Inclination of a body's instantaneous plane of motion.

Right ascension of the ascending node of a body's
 instantaneous plane of motion.

SUBSCRIPTS

- ⊕, €, ⊙ Denote the central body as the earth, moon, or sun, respectively.
- N Denotes conditions of the ascending node.
- M Denotes conditions of the moon.

S Denotes "selenographic" conditions; see [3] for details.

UNUSUAL TERMS

1. <u>FLIGHT TIME</u> or <u>TRIP TIME</u> denotes the time from injection to arrival at periselenum.

2. <u>BALLISTIC TRANSIT</u> implies that travel from a geocentric parking orbit to periselenum is made with no powered plane changes. Launch time variations are used to position the parking orbit, and coast time and burning time variations are used to establish the injection into the transit plane. The final stage is controlled during burning by a technique designated by Jet Propulsion Laboratory as "Control from the Horizon."

3. <u>DUAL TIME SOLUTIONS</u> refers to the two trajectories that are possible for arriving at the moon at a <u>specified time</u>, subject to the following constraints:

a. Launch from Patrick Air Force Base at a due east azimuth.

b. Utilize a circular parking orbit.

c. Specify the TRIP TIME.

d. Require BALLISTIC TRANSIT.



х

Figure 1 illustrates the geometry of the DUAL TIME SOLUTIONS but some pertinent details are not evident from the figure. Consider the infinity of parking orbit planes subject to the above constraints (all planes passing through earth's center and passing tangent to the injection latitude circle). Upon placing the moon, considered as a point, at some position in the volume swept out by this infinity of plane, one sees that, in general, two of these planes pass through the moon. Along the extremities (circular cones) of the volume swept out there is only one plane which passes through a given point. Thus, in general, one suspects that two trajectories are available for earth to moon transit, subject to the discussed constraints.

Let us now examine the situation to see if one can actually establish the two suspected trajectories. Since arrival time and trip time are to be identical for the two solutions, injection must occur at the same time. The time interval from liftoff to parking orbit is the same in any two cases. The burning time required to achieve injection from the parking orbit is essentially the same in the two cases due to the fixed distance to the moon (same arrival time), and the fixed central travel angle (same trip time). These considerations allow the injection time equality,

$$T_{INJ} = T_{L_1} + \Delta t_{L,PO} + \Delta t_{C_1} + \Delta t_{PO,I} = T_{L_2} + \Delta t_{L,PO} + \Delta t_{C_2} + \Delta t_{PO,I},$$

to be reduced to

$$\mathbf{T}_{\mathbf{L}_{1}} + \Delta \mathbf{t}_{\mathbf{C}_{1}} = \mathbf{T}_{\mathbf{L}_{2}} + \Delta \mathbf{t}_{\mathbf{C}_{2}},$$

where T_L is liftoff time, $\triangle t_{L,PO}$ is time from liftoff to parking orbit, $\triangle t_C$ is coast time in parking orbit, and $\triangle t_{PO,I}$ is the time interval from parking orbit to injection.

Although T_{L_1} and T_{L_2} are not the same, they are fixed under the constraints, namely, that they result in two parking planes that contain the moon at arrival time. Finally then,

$$CONSTANT = T_{L_1} - T_{L_2} = \triangle t_{C_2} - \triangle t_{C_1},$$

must hold if the two solution trajectories exist. Since $\triangle t_{C_2}$ and $\triangle t_{C_1}$ must be utilized to place injection such that the central travel angle constraint is satisfied, it would be mere chance that the $(T_{L_1} - T_{L_2})$ equality were satisfied simultaneously. It should be noted, however, that theoretically one solution could be determined for arrival at the specified time. Another could be established whose arrival time would be in error by a fractional part of the period of the parking orbit. With reference to these two solutions we define and use the term "DUAL TIME SOLUTIONS."

4. <u>ARRIVAL CONIC</u> denotes the instantaneous two-body solution at arrival time with the moon as attracting body. The inclination and location of the conic is of primary interest in this report when referenced to the selenographic coordinate system. This system is discussed in [3].

5. $\overline{B} \cdot \overline{T}$ and $\overline{B} \cdot \overline{R}$ are operational scalars that are very useful in achieving various orientations of the arrival conic. A detailed discussion of these scalars is given in [7], but a brief generalized discussion is presented here.

The incoming asymptote of the selenocentric arrival conic is approximately parallel to the earth-moon line at arrival time. Denote a unit vector in the direction of the incoming asymptote as \vec{S} . The unit vector \vec{T} is constructed to lie in the EARTH-MOON travel plane normal to \vec{S} and positive toward the trailing edge of the moon. \vec{R} is also normal to \vec{S} and is given by $\vec{S} \times \vec{T}$. We see then that the plane defined by \vec{R} and \vec{T} is normal to \vec{S} . A vector \vec{B} , which is a function of the characteristics of the selenocentric arrival conic, lies in the \vec{R} \vec{T} plane and is called the "impact parameter." The magnitude of \vec{B} , $|\vec{B}|$, is related to close approach distance, R_{CA} , through the equation

$$|\bar{B}| = \sqrt{R_{CA}(2|a| + R_{CA})}$$

2

where |a| is the magnitude of the semimajor axis of the arrival conic. One can see then that by specifying the desired projections of \overline{B} onto \overline{R} and \overline{T} , $\overline{B}\cdot\overline{T}$ and $\overline{B}\cdot\overline{R}$, it is possible to survey the arrival conic orientation about \overline{S} for a given $|\overline{B}|$ or close approach distance.

GEORGE C. MARSHALL SPACE FLIGHT CENTER

MTP-AERO-62-73

EARTH-MOON TRANSIT STUDIES BASED ON EPHEMERIS DATA AND USING BEST AVAILABLE COMPUTER PROGRAM PART I: PERISELENUM CONDITIONS AS FUNCTION OF INJECTION CONDITIONS

By Byrd Tucker

SUMMARY

The objective of this report is to provide accurately determined bounds for the effects of various parameters on departure velocity, periselenum arrival velocity, and the selenocentric arrival conic orientations. The various topics usually arise as questions closely akin to those set forth in the following. Answers to the questions presented are included and are the result of this study.

- 1. How much do <u>departure velocity</u> requirements change due to variations of the arrival earth-moon ephemeris and trip time variations in the 66 hour to 90 hour range? For arriving at the moon when it is at any position, the departure velocity requirements change is bounded by:
 - a. 35(m/s) for flights of 66 hours
 - b. 22(m/s) for flights of 78 hours
 - c. 20(m/s) for flights of 90 hours.

The overall bound for all arrival ephemeris variations and all trip times in the 66 to 90 hour range is 55(m/s). These bounds are determined by projecting all injection conditions (which occurred at slightly varied altitudes) to a mean radius of 6770(km).

2. How much do <u>departure velocity</u> requirements change with different trajectory approach paths such as direct, retrograde, or polar approaches? The complete range of possible approach paths can only change the departure velocity by about 4(m/s).

3. What effect does varying the selenocentric arrival altitude have on <u>departure conditions</u>? Essentially NONE! The injection conditions,

position vector and velocity vector, are essentially invariant for arrival altitude changes in the 50(km) to 500(km) altitude range (approach path being frozen).

4. How does <u>arrival velocity</u> vary due to changes in arrival altitude?

 $\frac{\partial}{\partial}$ (ARRIVAL VELOCITY) $\frac{\partial}{\partial}$ (ARRIVAL ALTITUDE) ≈ -1 (m/s/n.m.) $\approx -.54$ (m/s/km)

5. How much does <u>arrival</u> <u>velocity</u> change for various combinations of arrival time (earth-moon positions) and trip times?

- a. The effect of all combinations of arrival times and trip times in the 66 to 90 hour range is bounded by 200(m/s).
- b. For trip time frozen at 66 hours, the varying earth-moon ephemeris effect is bounded by 105(m/s), at 78 hours the bound is 70(m/s), and at 90 hours the bound is 55(m/s).
- 6. The arrival velocity magnitude varies by about 10(m/s) for the various approach paths when arrival altitude and flight time are held constant.

In the following, inclination refers to the inclination of the arrival conic relative to the moon's equator. All the following results are for flights making no powered plane changes and having 66 hour trip time.

7. There are inclinations in the neighborhood of 0° and 180° that cannot be established for any arbitrary arrival time.

8. For retrograde flights (those arriving counter to or against the moon's motion, i.e., those having inclinations greater than 90°) the unattainable inclination area around 180° is bounded by about 7°.

9. Generally speaking, when the moon is at its maximum or minimum declination, the unattainable inclination area around 180° shrinks to less than 1°. When the moon is near zero declination, the unattainable area peaks at about 7°.

The basic trajectory data for this study were generated using a space flight program that was obtained from Jet Propulsion Laboratory. To our knowledge, this program is as accurate as any available to NASA installations.

SECTION I. INTRODUCTION

The establishment of optimum or near optimum techniques for performing various lunar missions is a current, pressing problem. Upon the introduction of optimization concepts for performing such missions, the effects of various parameters that have been considered insignificant outside the realm of optimization must be evaluated. Further, care must be exercised that simplifying assumptions and numerical inaccuracies are tolerable. Working in accordance with these views, it has been impossible to use some apparently relevant results from different works because insufficient information was available as to their accuracy.

The objective of this publication is to establish bounds for a few of the parameters of the problem, and to furnish some information for "Trade-off" considerations to serve as basis for choosing one technique rather than another.

SECTION II. CONSTRAINTS AND IMPLEMENTS OF THE STUDY

The trajectory simulations were performed on an IBM 7090 Space Flight Program which was obtained from the Jet Propulsion Laboratory. The program includes the effects of the oblate earth, sun, triaxial moon, and Jupiter. A comprehensive discussion of the program is presented in Reference 1^{*}. The various geophysical, astronomical, and operational constants required by the program are discussed in [1] and [4]. The constants used in this study are those currently in use at Jet Propulsion Laboratory, according to [1] and [4].

The numerical errors incurred by the computational procedures are well controlled. Reference 5 indicates that such error in periselenum arrival position is not more than 100 meters. Information, again from [5], on periselenum arrival velocity is vague, but indications are that the numerical error is in the seventh digit.

This study is concerned with the flight phase from a geocentric circular parking orbit to arrival at periselenum.

SECTION III. COMMENTS ON SOME CHARACTERISTICS OF THE MOON'S MOTION

References 2 and 3 present a great deal of information about the moon's motion. Reference 2 presents, primarily, graphical information. Reference 3 gives explanatory discussions and the derivation of some equations of interest.

*References will be denoted by "Reference numbers" or bracketed [] numbers in the text and refer to specific entries in the table of references in this report.

Extracting from Reference 2, the following information is restated here since it has direct influence upon some phases of this study:

1. The geocentric radial distance to the moon at its . . .

a. Apogees varies by about .4 earth radius or 2550 (km)

b. Perigees varies by about 2 earth radii or 12750 (km).

The conversion to kilometers is made assuming an earth radius to equal 6370 (km).

2. The times at which absolute perigees or "local-minimum-distance" perigees occur from a sequence, (T_1) , such that as i = 1, 2 ... n, $(T_1 = T_0 + 7^{M_0}, T_2 = T_1 + 8^{M_0}, T_3 = T_2 + 7^{M_0}, T_4 = T_3 + 8^{M_0}, ..., T_n = T_n - 1 + (8))$.

3. The graphs of lunar declination (δ_{c}) and geocentric radial distance (ρ_{c}) versus date indicate that the δ_{c} and ρ_{c} plots are ...

a. out-of-phase by about 180° in November 1964

b. out-of-phase by about 90° in October 1966

c. approximately in-phase in March 1969.

4. In March 1969, the declination of the moon takes on its maximum value, i.e., about 28.7°.

5. The ephemeris of the moon's motion relative to the earth is, for all practical purposes, periodic; the period is approximately 18.5 years.

IV. BOUNDS FOR THE EFFECT OF THE VARYING EARTH-MOON EPHEMERIS ON DEPARTURE AND ARRIVAL VELOCITIES FOR VARIOUS TRIP TIMES

1. PROCEDURE

It is desirable to know just what differences are the result of performing a lunar mission at one time rather than another. The present objective is to set forth the differences which occur in departure and arrival velocities.

The cyclic nature of the moon's motion in about each eighteen and one-half years exhibits the following characteristics:

- ρ geocentric radial distance takes on essentially all possible values each seven or eight months.
- δ declination goes through a relative maximum to minimum cycle each month but takes on an absolute maximum and minimum in about eighteen and one-half years.
- α right ascension takes on all possible values once each month.

A sampling of the earth-moon ephemeris is desired that will result in the indicated bounds on departure and arrival velocities. This sampling was taken to be the ten cases whose characteristics are set forth in Table 1. The sampling ranges over about 99.4% of all possible values for ρ , radial distance to the moon, but only the values of δ , declination of the moon, from about $\pm 24^{\circ}$ to $\pm 28.7^{\circ}$. All possible phase combinations of ρ and δ are covered by the sampling.

As one might expect, the sampling taken is adequate to determine bounds for departure and arrival velocities. The lack of coverage in the δ range is of no consequence.

Actual trajectory surveys were made for arrival at the moon in the neighborhood of our ephemeris sampling. The TRIP TIME and ARRIVAL CONIC were specified for each trajectory. This was accomplished by specifying the desired trip time, B.T, and B.R (Reference 7) quantities, and searching for the combination of launch time, coasting time, and final stage burning time that resulted in the desired quantities. TABLE 1

ARRIVAL CHARACTERISTICS OF THE EARTH-MOON EPHEMERIS SAMPLING

Moon's enced in the	Ecliptic Plane	-275.29 -275.91 -276.33	-312.14 -312.48 -312.83 -313.19
Ascending Node of Travel Plane Refer to Vernal Equinox	Earth's Equatorial Plane	12.56 12.62 12.65	8.29 8.31 8.29
Instantaneous Inclination of Moon's Travel Plane	to Earth's Equator i _M (deg)	24.56 24.61 24.61	27.28 27.30 27.33 27.34
Declination	of the Moon S _M (deg)	-23.9 (~ MIN) 24.5 (~ MAX) -5.1 (~ ZERO)	27.2 (~ MAX) -3.0 (~ ZERO) -27.0 (~ MIN) .4 (~ ZERO)
Geocentríc Radial Distance	to the Moon ρ _M (km)	404331 (~ APO) 360984 (~ PERI) 394139	380198 359253 (~ PERI) 391409 404193 (~ APO)
	Time MM, DD, YY; HH	Nov 10, 64; 08 Nov 22, 64; 05 Nov 30, 64; 03	Oct 7, 66; 07 Oct 13, 66; 18 Oct 20, 66; 08 Oct 27, 66; 04

2. RESULTS

A. Effects of Various Arrival Patterns on Velocities

How much do the velocity requirements change with a change in the orientation of the arrival conic? This question arises quite frequently in terms of the feasibility of retrograde (opposite in direction to moon's motion), direct (with the moon's motion), or polar orbits.

Four trajectories are sufficient as basis for answering this question, each trajectory having a specified approach path. Figure 2 presents a selenocentric (moon-centered) plot of the arrival portion of two of these basic trajectories. The xy plane is coincident with the true equatorial plane of date, the x-axis being in the direction of the true equinox of date. This system shall be referred to as the "Selenocentric True Ephemeris System of Date."

Table 2 lists pertinent departure and arrival conditions.

TABLE 2

DEPARTURE AND ARRIVAL CONDITIONS FOR VARIOUS ARRIVAL CONIC ORIENTATIONS IN NOVEMBER 1964

Radius r (km)	Latitude Ø' (deg)	East Longitude λ (deg)	Inertial Velocity V [*] (m/s)	Path Angle Γ (deg)	Azimuth ∑ (deg)	Arrival Path Identification	n
6792.4	15.98	333.81	10788.4	6.85	113.65	Retro - Orbital:	I
6792.1	16.22	333.26	10784.5	6.84	113.49	Direct - Orbital:	II
6792.0	15.28	335.34	10786.8	6.84	114.10	Polar - Over:	III
6792.5	16.95	331.60	10786.4	6.85	112.98	Polar - Under:	IV

Geocentric Departure Conditions

Selenographic^{*} Periselenum Arrival Conditions 66^{hr} Trip Time

Radius r _s (kma)	Latitude Ø's (deg)	Longitude λ _s (deg)	Space- Fixed Velocity V* (m/s)	Rotating Azimuth σ _g (deg)	Space- Fixed Azimuth $\Sigma_{s}(deg)$	Inclination To Earth's Equator i _⊕ (deg)	Arrival Path ID
1922.7	-3.42	190.12	2569.3	276.29	261.28	156.73	I
1897.2	7.01	87.78	2575.8	91.99	113.06	23.26	II
1910.1	53.63	147.55	2572.3	191.27	193.62	101,72	III
1909.3	-48.03	131.09	2572.8	98.96	33.16	78.33	IV

*A detailed discussion of Selenographic coordinates is given in [3].



From the data presented in Table 2, one can conclude that -

- 1. The changes in departure velocity magnitude due to various arrival paths are bounded by about 4 (m/s).
- 2. By applying the partials relationship given on page 9 to the V_s^* and r_s data of Table 2, one finds that the arrival velocity magnitude varies by about 10(m/s) for all variations in arrival conic orientations on trajectories having constant flight time and arrival altitude.
- B. VELOCITY VARIATIONS DUE TO VARYING THE ARRIVAL ALTITUDE

The basic trajectory data needed here is presented in Table 3. Three trajectories were determined to arrive at essentially the same time, along the same arrival path (RETROGRADE - ORBITAL), and all having the same trip time, 66 hours. However, in each case arrival is at a different periselenum altitude.

TABLE 3

DEPARTURE AND ARRIVAL CONDITIONS FOR ARRIVING AT VARIOUS PERISELENUM ALTITUDES VIA A FIXED ARRIVAL PATH IN OCTOBER, 1966

Radius r (km)	Latitude Ø' (deg)	East Longitude λ (deg)	Inertial Velocity V (m/s)	Path Angle Γ (deg)	Azimuth Σ (deg)	Trajectory ID
6780.5	-6.06	14.28	10767.0	6.72	117.70	ALT - 1
6780.5	-6.07	14.29	10767.0	6.72	117.70	ALT - 2
6780.4	-6.07	14.30	10767.1	6.72	117.69	ALT - 3

Geocentric Departure Conditions

Detenographic leriberenam Arrivar Obharcions, ob irib Iim	Selenographic*	Periselenum	Arrival	Conditions,	66 ^{hr}	Trip	Time
---	----------------	-------------	---------	-------------	------------------	------	------

Radius ^r s (km)	Altitude h _s (km)	Latitude \emptyset'_{s} (deg)	Longitude λ (deg)	Velocity V _s (m/s)	Azimuth σ _s (deg)	Trajec- tory ID
1865.8	127.8	9.25	177.25	2578.9	281.35	ALT - 1
1965.3	227.3	9.06	178.18	2527.1	281.49	ALT - 2
2069.7	331.7	8.87	179.12	2471.9	281.63	ALT - 3

The data of Table 3 emphasizes the fact that all arrival altitudes in the desired range of values require the same departure velocity vector. In fact the complete specification of departure position and velocity vectors is essentially invariant for all values of arrival altitude that come under present consideration, ranging from about 50 (km) to about 500 (km).

*The Selenographic coordinate system is moon-centered and rotates such that one axis is always in the general direction of the earth; see [3] for details. C. DEPARTURE AND ARRIVAL VELOCITY BEHAVIOR FOR CHANGES IN ARRIVAL EARTH-MOON EPHEMERIS AND TRIP TIME

The trajectory data of this section was generated subject to the following constraints:

- a. Launch from Patrick AFB at a due east azimuth.
- b. A parking orbit is utilized.
- c. BALLISTIC TRANSIT is used.
- d. The arrival path is always retrograde to the moon's motion and essentially in the plane of earth-moon motion, so-called the RETROGRADE ORBITAL approach.

The velocity behavior is to be examined for variations in trip time and the earth-moon ephemeris at arrival (arrival time).

1. DEPARTURE VELOCITY

First, let us recall the results already established concerning departure velocity behavior:

- The complete range of all possible arrival conic orientations causes the departure velocity to change by about 4 (m/s), Table 2.
- 2. The RETROGRADE ORBITAL approach region is the most expensive, i.e., these approaches require greater departure velocity than the other approach regions, Table 2.
- 3. Departure velocity is essentially independent of the periselenum arrival altitude in the altitude range of interest, from about 50 (km) to about 500 (km).

Figure 3 illustrates the departure velocity behavior for RETROGRADE ORBITAL approach paths (most expensive approach). One can conclude from Figure 3 that -

4. The departure velocity spread for arriving at any earthmoon ephemeris with trip times ranging from 66 hours through 90 hours is about 55 (m/s). For frozen flight times of (a) 66 hours the spread is about 35 (m/s), (b) 78 hours it is about 21 (m/s), and (c) 90 hours it is about 20 (m/s).



2. ARRIVAL VELOCITY

Figure 4 and Table 4 present the pertinent data for this discussion:

From the differences of Table 4, the effect on arrival velocity due to varying arrival periselenum altitude is seen to be about -1 (m/s) per nautical mile in altitude, i.e.,

 $\frac{\partial}{\partial}$ (ARRIVAL VELOCITY) $\frac{\partial}{\partial}$ (ARRIVAL ALTITUDE) ≈ -1 (m/s/n.m.) $\approx -.54$ (m/s/km)

Figure 4 illustrates the bounds on the effects due to variations in trip time and positions of earth-moon ephemeris. Having established the partial relationship just mentioned, the following bounds for arrival velocity at any 50 (km) to 500 (km) arrival periselenum altitude may be stated:

Arrival velocity varies by less than 200 (m/s) for any combination of arrival earth-moon ephemeris and trip times in the 66 hour to 90 hour range. For specific trip times the bounds are (a) 105 (m/s) for 66 hour trips, (b) 70 (m/s) for 78 hour trips, and (c) 55 (m/s) for 90 hour trips.



TABLE 4

						- 1-1-1			
Arrival*			SP	ACE-FIXED AKKIV	AL VELOCITY H	v (m/s)			
Date		rip Time = 66	(HRS)	Υ.	tip Time = 78	(HRS)	17	:ip Time = 90 (HRS)
MM, DD, YY	$h_{c}=140(km)$	h _s =185(km)	h _s =230(km)	h _S =140(km)	$h_{\rm S} = 185 (\rm km)$	h _s =230(km)	h _s =140(km)	h _s =185(km)	h _S =230(km)
	$h_{s} = 75(n.m)$	$h_{s} = 100(n.m)$	$h_{s} = 125(n.m)$	$h_{s} = 75(n.m)$	h _s =100(n.m)	h _S =125(n.m)	$h_{s} = 75(n.m)$	h _s =100(n.m)	h _s =125(n.m)
	0	2	VELOCITIES	FOR ARRIVAL AT	FALECTED LUN	AR APOGEES			•
11 10 64	2598	2580	2562	2502	2478	2455	24525	2425, 55	2400
10 27 66	2592	2569	2548	2496	2472	2448	2444	2420	2396
26, 69	2592	2568	2544	2491	2467	2443	2446	2421	2398
			VELOCITY FOR AR	RIVAL AT SELECT	TED LUNAR MEDI	AN DISTANCES			
11 30 64	2586	2562	1 2540	2502	2478	2455	2463	2438	2414
10 07 66	2570	2546	2523	2489	2466	2442	2451	2425	2402
10 20 66	2246	2521	2497	2473	2448	2424	2433	2408	2384
03, 18, 69	2537	2514	2492	2468	2445	2421	2439	2414 1	2390
			VELOCITIES	FOR ARRIVAL A	T SELECTED LUN	AR PERIGEES			
11 22 64	2526	2502	2480	2472	2448	2426	2450	2425	2400
10 14 66	2566	2541	2519	2506	2483	2459	2488	2464	2440
03, 12, 69	2541	2517	2494	2479	2454	2430	2447	2423	2399
			AVERAG	E VELOCITIES FC	DR ARRIVAL AT	•			
Anoves	2594	2572	2551	2496	2472	2449	2447	2422	2398
Medians	2560	2536	2513	2483	2459	2436	2447	2421	2398
Perigees	2544	2520	2498	2486	2462	2438	2462	243/	2413.
		DIFFE	RENCES IN ARRIV	AL VELOCITY DUI	E TO CHANGES I	N ARRIVAL ALTIT	UDE.		
	V100	V ₇₅ V ₁₂₅	5 - V 100	V 100 -	V ₇₅ V ₁₂₅	- V ₁₀₀	- 00T	V75 V125	- V ₁₀₀
Δυράρος	-22		-21	-27		-23	-25		-26
Medians	-24		-23	2/		-23 -24	-2(-27
Perigees	77-		77-						

*See Table 1 for the characteristics of the Earth-Moon Ephemeris sampling.

SECTION V. BOUNDS FOR THE ATTAINABLE ARRIVAL CONIC ORIENTATIONS

For this discussion, the arrival conic orientation is taken relative to the moon's equator. More specifically, the orientation shall be specified by the inclination relative to the moon's equator, is, and the selenographic longitude of the ascending node, $\Omega_{\rm NS}$.

The establishment of bounds for the achievable arrival conic orientations subject to a given set of constraints is the principle objective of this section. At the same time some interesting characteristics of the arrival conic behavior will be mentioned.

1. PROCEDURE

The basic approach has been to survey the behavior of the arrival conic orientation subject to the constraints listed at the beginning of section IV-C, page 10, of this report. Two other arrival constraints are imposed for these results:

- 1. Trip time is required to be 66 hours.
- 2. Arrival altitude is held in the 100 (km) to 200 (km) range.

Operationally the described procedure is accomplished by specifying position and velocity vectors at the parking orbit initiation which satisfy the launch constraints, and searching for the launch time, coast time, and final stage burning time combination which results in the desired arrival constraints. The arrival constraints are formulated in terms of $\vec{B} \cdot \vec{T}$, $\vec{B} \cdot \vec{R}$, and flight time, T_{F} . The magnitude of the B vector, $|\vec{B}|$, controls arrival altitude and $\vec{B} \cdot \vec{T}$ and $\vec{B} \cdot \vec{R}$ combinations result in various conic orientations for a given magnitude of the miss vector, i.e., $|\vec{B}|$.

It should be recalled that there are TWO SOLUTIONS IN TIME (generally speaking) for arriving at the moon when it is in the proximity of some specified earth-moon position. During this phase of the study it became apparent that the two solutions behaved somewhat differently; hence, both branches of the "DUAL-TIME SOLUTION" are presented.

The three months represented in the EARTH-MOON EPHEMERIS SAMPLING whose characteristic data are presented in Table 2 are used as samplings for this phase of the study also.

2. RESULTS

The behavior of the departure and arrival conditions, as a survey of $\vec{B} \cdot \vec{T}$ and $\vec{B} \cdot \vec{R}$ combinations is made (for a given \vec{B} magnitude), is quite interesting. A tabulation of these data is presented in Tables 5 and 6. The data of Table 5 result from retrograde approach flights with polar approaches at the extremes of the survey. Table 6 data are from direct approach flights, the survey being terminated short of the polar extremes.

One can observe from the i_s data of Tables 5 and 6 that arrival inclinations from about 174° to 180° (Table 5) as well as from about 0° to 18° (Table 6) are not attainable for that particular class of trajectories. Immediately questions begin coming to mind as to the reasons for the existence of such "DEAD INCLINATION AREAS," a term that shall be used to denote the unattainable areas, and the influence that various parameters have on their existence and behavior. This report does not deal exhaustively with these questions but does present some helpful results. The results are empirical in nature and no attempt is made to present any analytic evaluation of the problems.

A. The influence of the Varying Earth-Moon Ephemeris At Arrival

Four distinct sets of trajectories have been run, and, in view of the results to be presented, it is convenient to describe the sets as follows:

- a. Each set consists of trajectories resulting in the minimum attainable i_s for both branches of the DUAL-TIME SOLUTION as the arrival time is stepped through a specified era.
- b. In three of the four sets launch is from Patrick AFB at a due east azimuth resulting in a BALLISTIC TRANSIT plane inclined at about 28.3° to the earth's equator. In the other set, a fictitious launch site is assumed such that a due east launch results in a BALLISTIC TRANSIT plane inclined at about 24.4° to the earth's equator. This manipulation was done to produce two sets having the BALLISTIC TRANSIT plane near coplanar with the moon's travel plane.

TABLE 5

.

.

DEPARTURE AND ARRIVAL CONDITIONS FOR VARIOUS RETROGRADE ARRIVAL CONIC ORTENTATIONS

					_					A		
	V* m∕s	V*s ≣∕s	10785.3 2609.3	10786.4 2603.8	10786.6 2604.9	10786.8 2602.9	10786.8 2602.8	10786.7 2603.2	10786.7 2603.5	10786.4 2602.7	10786.0 2604.8	10784.8 2609.9
	Σ Deg	σ _s Deg	65.943 177.653	66.110 237.190	66.207 252.899	66.351 271.693	66.365 273.564	66.400 278.250	66.420 281.120	66.490 293.945	66.534 308.836	66.515 358.018
SNULTAIN	г Deg	i⊕ (Deg)	6.938 110.993	6.942 151.877	6.943 166.018	6.943 158.092	6.943 155.682	6.943 149.370	6.943 145.420	6.942 128.211	6.941 110.74	6.937 69.017
TYN OTNO	<u>ک</u> ب	hs km	407.19 37.78	407.51 51.35	407.65 50.38	407.84 54.74	407.86 55.03	407.89 54.07	407.91 53.34	407.96 54.20	407.97	407.81 36.56
	} Deg	$\lambda_{\rm s}_{\rm Deg}$	200.839 141.072	201.423 181.770	201.757 188.457	202.245 191.313	202.293 191.220	202.410 190.658	202.477 190.100	202.712 186.003	202.860 178.433	202.798 144.250
ITS, AND F	ø' Deg	Ø's Deg	15.359 53.530	15.626 38.623	15.779 26.587	15.999 7.184	16.021 5.103	16.074 076	16.104 -3.186	16.209 -15.913	16.275 -27.223	16.247 -41.396
TIME OF 66 ^t	о <mark>у</mark> Deg	ΩNs Deg	15.839 -37.040	15.544 -42.304	15.250 -47.037	14.706 -91.985	14.645 -113.781	14.492 -169.870	14.401 174.311	14.025 154.312	13.706 148.826	13.331 142.939
ED FLIGHT	i Deg	i Deg	28.294 88.605	28.293 131.044	28.293 148.729	28.293 172.620	28.293 173.778	28.293 171.750	28.293 168.438	28.293 151.511	28.293 133.841	28.293 91.487
FIX	Burn Time Sec	B•R (km)	366.98 -4081	367 . 09 -3000	367.12 -1999	367.14 -200	367.14 0	367.14 499	367.14 799	367.12 2000	367 . 09 3000	366.98 4081
	Coast Time Sec	B.T (km)	3840.94 0	3850.64 -2769	3856,23 -3555	3864.39 -4075	3865.21 -4081	3867.17 -4049	3868.30 -4001	3872.26 -3560	3874.77 -2767	3873.89 1
	Launch Time M, DD, HH, MIN, SEC	Arrival Time M, DD, HH, MIN, SEC	1, 27, 07, 57, 55.81 1, 30, 0 3, 17, 38.69	1, 27, 07, 56, 45.30 1, 30, 03, 16, 26.25	1, 27, 07, 55, 35.04 1, 30, 03, 16, 32.36	$\begin{bmatrix} 1, & 27, & 07, & 53, & 24.89 \\ 1, & 30, & 03, & 13, & 21.55 \end{bmatrix}$	$\begin{bmatrix} 1, & 27, & 07, & 53, & 10.& 27 \\ 1, & 30, & 03, & 13, & 07.80 \end{bmatrix}$	$\begin{bmatrix} 1, & 27, & 07, & 52, & 33.75 \\ 1, & 30, & 03, & 12, & 55.61 \end{bmatrix}$	1, 27, 07, 52, 11.81 1, 20, 03, 13, 01.60	1, 27, 07, 50, 41.91 1, 30, 03, 10, 47.85	l, 27, 07, 49, 25.64 l, 30, 03, 09, 31.89	l, 27, 07, 47, 55.96 l, 30, 03, 08, 22.95
	21	~										

9	
BLE	
ΕA	

DEPARTURE AND ARRIVAL CONDITIONS FOR VARIOUS DIRECT ARRIVAL CONIC ORIENTATIONS FIXED FLIGHT TIME OF 66^{hrs} , and fixed $|\vec{B}|$

			Concession of the local division of the loca		
v*	Vs*	10785.5	10785.4	10785.4	10785.6
m/s	m/s	2571.9	2572.2	2571.5	2570.8
Σ	σs	118.17	118.18	118.20	118.21
Deg	Deg	114.46	101.17	82.42	73.21
л	i t	6.785	6.785	6.7855	6.786
Deg	(Deg)	54.39	40.38	18.73	17.70
ᆑᄫ	kn	405.97	406.01	406.13	406.22
	k	154.89	154.20	156.26	158.43
≻	As	8.702	8.494	8.004	7.798
Deg	Deg	88.76	88.13	92.34	97.36
ø'	Ø	-2.885	-2.765	-2.506	-2.364
Deg	Deg	30.52	18.806	-2.685	-13.35
ON	Ω _{Ns}	225.97	226.08	226.46	226.73
Deg	Deg	343.51	4.772	99.69	118.84
i	is	28.30	28.30	28.30	28.30
Deg	Deg	31.42	18.92	20.14	32.94
Burn Time	B•R (km)	367.07	367.065	367.08	367.10
Sec		-1999.76	-999.79	1000.26	1999.61
Coast Time	B•T (km)	746.23	742.45	734.23	729.71
Sec		3535.53	3936.49	3936.52	3535.59
Time	I Time	55, 10.23	55, 37.55	57, 07.82	07, 36.46
MTN SEC	MIN, SEC	22, 58.04	23, 13.39	24, 44.21	26, 30.95
Launch DD HH	, DD, HH,	, 27, 21, , 30, 16,	, 27, 21, , 30, 16,	, 27, 21,	, 27, 22, , 30, 16,
Š	ξ	==	11	==	==

1 21, 55, 10, 2**3** 1 16, 22, 58, 54 1 1, 55, 38, 55 16, 23, 13, 39 16, 24, 44, 11 16, 24, 30, 15 16, 26, 30, 15 •

.

..**.**

Transit Plane Inclination, i⊕	Moon's Travel Plane Inclination, i _{⊕M}	Arrival Time Era	Set Identification
2 4. 4°	2 4.5°	Nov-Dec, 1964	Travel-Plane Transit (1)
28.3°	28.7°	Mar-Apr, 1969	Travel-Plane Transit (4)
28.3°	27.3°	Oct, 1966	Out-of-Plane Transit (1.0)
28.3°	24.5°	Nov-Dec, 1964	Out-of-Plane Transit (3.8)

c. The four sets are characterized as follows:

Figures 5 and 6 and Tables 7 through 10 present the data for the <u>TRAVEL-PLANE TRANSIT CASES</u>. Some results may be pointed out quite readily from Figures 5 and 6:

- The DUAL-TIME SOLUTION separates into a high minimum inclination branch (peaks at about 13° to 14°) and a low minimum inclination branch (peaks at about 7°). However, one should observe that the high branch does on occasion drop to a lower declination than the so-called low branch.
- 2. Inclinations of near zero are attainable when the δ_{c} at arrival is near maximum or minimum. For arrival δ_{c} around zero, the minimum inclinations are in the peak regions; i.e., around 7° is the minimum that can be obtained.

In Tables 7-14, the data designated as $\triangle \alpha_{\Phi_N}$ represents the deviation of right ascension of the ascending node of the vehicle's transit conic (at injection) from the right ascension of the moon's travel plane at that time, i.e., $\triangle \alpha_{\Phi_N} = \alpha_{\Phi_N} - \alpha_{\Phi_M}$. From this then one can conclude that:

3. The branch having low peaks is a near coplanar solution whereas the branch having high peaks would be considered an out-of-plane solution.

Figures 7 and 8 and Tables 11 through 14 present the results for the two <u>OUT-OF-PLANE TRANSIT CASES</u>. Figures 7 and 8 and Tables 11 through 14 show that for these cases:

> 4. The DUAL-TIME SOLUTION does not separate (as in the TRAVEL-PLANE TRANSIT CASES) into a high and low inclination branch. Rather each branch has a high peak and a low peak, the peaks being in the 7° and 14° neighborhood.

In these cases as was pointed out for the two previous cases:

5. Inclinations near zero are attainable when the δ_{c} at arrival is near maximum or minimum. For arrival δ_{c} in the neighborhood of zero, the minimum inclinations are in the peak regions.



;



TABLE 7

14	_		_		_		_	_	_			_	_	_		-		-	_	_			_	-
			ы	(deg)	104.90	108.63	113.28	114.35	110.98	107.37	89.40	81.64	77.32	72.13	68.54	66.39	65.56	65.94	70.04	73.59	83.07	94.20	107.28	112.64
ON 964	TIONS		8	(deg)	141.56	153.37	175.34	198.03	222.67	236.36	283.41	299.71	315.99	330.93	344.93	358.07	10.59	22.76	47.05	59.52	85.41	111.80	149.36	171.39
X SOLUTI	LE CONDI	CENTRIC	Q	(deg)	13.13	12.82	12.66	12.60	12.54	12.50	11.97	9.13	13.95	13.06	12.84	12.75	12.71	12.68	12.61	12.56	12.36	11.61	13.49	12.99
CO-PLANAF RVEY: No	DEPARTUI	GEOC	ACCEN	(deg)	0.5	0.2	0.1	0	-0.1	-0.1	-0.6	-3.5	1.4	0.5	0.2	0.2	0.1	0.1	0	0	-0.2	-1.0	0.9	0.4
D: NEAR (IME OF SU			Ø'	(deg)	19.59	16.11	7.71	-2.47	-12.86	-17.49	-24.43	-23.04	-21.07	-16.96	-12.02	-6.58	-0.96	4.55	14.42	18.38	23.49	24.09	17.56	9.50
нн			7.	(deg)	190.19	188.84	185.61	181.86	178.00	176.72	176.04	177.08	178.54	180.63	182.85	185.28	187.44	189.32	192.49	193.30	193.87	193.13	190.00	187.05
			V. I	(m/s)	2573.32	2574.43	2567.96	2547.67	2545.55	2534.13	2511.61	2507.35	2509.34	2503.24	2504.46	2504.50	2514.72	2529.29	2533.73	2545.64	2557.87	2565.10	2574.44	2575.51
			1.	(deg)	1.12	0.27	2.83	5.01	6.43	6.77	5.65	4.72	2.86	1.21	0.59	2.36	3.95	5.23	6.69	6.86	6.11	4.24	0.12	2.51
.4° .5°		OCENTRIC	<u>م</u> -	(deg)	270.76	269.75	267.99	266.40	265.47	265.41	266.07	266.72	267.97	269.11	270.47	271.67	272.65	273.58	274.79	274.79	274.31	273.17	270.09	268.12
$1_{PO} \approx 24$ $1_M \approx 24$	TIONS	SELEN	0'5	(deg)	0.81	-0.11	-1.99	-3.49	-4.57	-4.97	-4.06	-3.40	-2.01	-0.81	0.36	1.66	2.92	3.82	4.67	4.91	4.33	2.82	0.07	-1.66
	VAL CONDI		h.	(kn)	185.07	185.17	191.36	208.97	180.53	185.50	185.69	184.56	174.80	184.51	184.43	191.38	182.26	167.67	189.23	181.23	184.13	190.43	188 [°] .39	184.60
ΤΛΥΤΑΔΑ	ARRI			(WM)	77	t 42	3 07	3 06	3 04	3 04	3 02	2 51	60 8	3 05	3 05	3 04	3 03	3 03	3 01	3 00	2 58	2 53	2 58	1 22
			Tfr	(DD, HI	10 10	11 0	13 0	15 0.	17 0:	18 0	21 0	22 0	23 0.	24 0	25 0	26 0	27 0	28 0	30 0	010	03 0	0 20	08 0	10 0
5.5		ITION (EQ. T. D)	9	(ikm)	404,536	402,477	395,144	383,985	371,933	366,766	359,762	360,820	363,433	367,176	371.680	376,535	381,413	386,061	394,113	397,414	402,542	405,619	405,188	400,539
M ≈ - 275.5			Jac No	(deg)	-24.08	-22.52	-16.67	-7.45	3.73	9.46	22.68	24.39	24.37	22.67	19.57	15.44	10.62	5.43	-5.11	-10.05	-18.36	-23.48	-23.28	-18.16
5		LUNAR PO	į	(deg)	294.65	307.46	331.63	355.94	20.77	33.93	78.46	94.63	111.13	126.86	141.72	155.55	168.47	180.67	203.90	215.41	239.07	264.09	302.92	327.02

ω	
671	
Э	
m	
<	
ы	

 $i_{po} \approx 24.4^{\circ}$

ID: OUT-OF-PLANE SOLUTION

	- ≈ ^M C	275.5					i _M ≈	24.6°		-	TIME OF SU	RVEY: N	ov-Dec 19	64	
					ARRIVAL	CONDITI	ONS					DEPART	URE COND	IT IONS	
LUNAR PC) NOITIS(EQ, I, D)				SEL	ENOCENTR	IC				υ	EOCENTRIC		
QM Mo	SM (dec)	₩ (maj)	Time (DD. HR.	(WW)	hs لالعا	Ø's (deg) [.]	σ <mark>s</mark> (deg)	i (deg)	V _S (m/s)	λ _s (deg)	ِ ه' (deg)	∆Con (deg)	Q⊕N (deg)	α (deg)	Σ · (deg)
295.59	-24.00	404,427	10 06	29	192.88	-0.49	269.62	0,62	2571.06	189.95	23.94	28.5	41.08	143.26	95.01
309.31	-22.20	402,075	11 08	12	185.06	-2.54	267.55	3.53	2580.24	188.19	24.42	56.1	68.67	156.44	89.07
335.89	-15.27	393,406	13 11	29	198.32	-6.10	264.20	8.41	2580.69	184.43	21.26	109.1	121.72	180.57	77.64
1.82	-4.87	381,021	15 14	41	185.79	-8.31	261.67	11.74	2583.41	180.44	12.92	161.0	173.60	203.90	69.05
28.90	7.33	368,590	17 18	63	183.94	-9.51	260.66	13.30	2565.99	177.57	0.82	215.6	228.15	229.96	65,55
43.63	13.28	363,837	18 19	54	183.97	-9.25	260.81	13.01	2551.30	176.73	-5.82	245.4	258.02	245.08	66.20
94.42	24.38	360,796	22 02	32	180.31	-3.21	266.02	5.11	2509.78	177.04	-22.36	-8.4	4.22	299.37	79.88
111.99	24.32	363,608	23 04	26	184.90	-0.88	269.08	1.28	2505.08	178.56	-23.88	21.9	34.45	317.38	84.69
129.09	22.29	367,798	24 06	36	184.13	2.00	271.99	2.82	2510.59	180.60	-24.36	56.6	69.15	334.38	91.97
144.97	18.70	372,772	25 08	34	272.05	18.14	274.42	6.24	2470.63	183.86	-22.98	88.1	100.68	349.63	98.54
159.57	14.03	378,031	26 10	22	183.61	6.20	276.40	8.90	2531.54	185.57	-20.15	117.0	129.58	3.40	104.14
173.10	8.71	383,188	27 12	01	183.16	7.75	277.68	10.90	2542.60	188.01	-16.23	143.8	156.40	16.21	108.54
185.87	3.09	387,988	28 13	35	184.77	8.72	278.62	12.24	2551.23	190.16	-11.57	169.2	181.79	28.53	111.70
210.41	-7.95	396,045	30 16	36	183.55	9.53	278.95	13.05	2564.94	193.23	-1.09	218.2	230.84	53.24	114.44
248.52	-20.77	403,981	03 21	21	185.01	6.46	276.47	9.13	2569.23	194.08	14.15	295.1	307.72	94.04	110.15
304.41	-23.07	405,015	08 05	46	184.53	-1.78	268.19	2.54	2580.39	189.45	24.39	45.7	58.32	151.95	91.50

TABLE 9

õ			ы. М	(deg)	80.22	89.48	96.12	106.59	117.75	117.34	114.96	111.21	106.21	100.21	93.51	83.40	71.84	67.40	64.36	61.71	63.83	71.53	77.60	84.92	93.14	117.27
April 196	IS		б	(deg)	68,59	84.04	99.71	130.93	170.17	194.96	207.52	220.45	233.85	247.66	261.67	275.55	314.78	326.31	337.43	359.19	22.04	48.12	62.82	78.49	94.61	166.15
NLUTION March -	COND IT ION	TRIC	N O	(deg)	359.61	358.94	356.71	3.85	1.01	0.58	0.41	0.21	359.97	359.63	359.10	357.92	3.64	2.11	1.49	0.87	0.51	60.0	359.79	359.27	357.97	1.03
PLANAR S(SURVEY:	EPARTURE	GEOCEN	∆0¢N	(deg)	-0.7	-1.4	-3.6	3.5	0.7	0.3	0.1	-0.1	-0.3	±0.7	-1.2	-2.4	3.3	1.7	1.2	0.6	0.2	-0.2	-0.5	-1.0	-2.3	0.7
TIME OF	D		,ø	(deg)	26.66	28.18	27.65	23.22	5.78	-7,62	-13.79	-19.17	-23.49	-26.51	-28.07	-28.06	-22.05	-17.47	-12.38	-0.90	11.18	21.80	25.61	27.85	28.11	7.87
			λ_{s}	(děg)	180.36	179.95	180.14	180.79	183.84	186.59	188.08	189.44	190.74	191.82	192.77	193.31	192.43	191.43	190.07	186.25	182.85	180.05	179.33	179.11	179.33	184.57
			Va	(m/s)	2531.69	2535.50	2524.01	2532.95	2521.09	2517.65	2516.96	2523.18	2528.55	2537.32	2540.80	2548.92	2571.94	2572.68	2570.27	2580.42	2557.20	2544.17	2534.37	2524.88	2519.77	2546.16
		NTRIC	1s	(m/s)	0.23	1.28	2.62	5.76	6.85	5,70	4.57	3.17	1.59	0.07	1.61	3.02	6.47	6.88	6.99	6.42	4.90	2.39	0.93	0.64	2.13	6.84
≈ 28.3 ≈ 28.7	NS	SELENOCE	α _s .	(deg)	270.18	269.00	268.15	266.16	265.19	265.84	266.67	267.73	268.77	269.98	271.18	272.13	274.73	274.70	274.88	274.77	273.27	271.70	270.55	269.53	268.53	264.85
1 1 1 M	CONDITIO		ø's	(değ)	0*16	-0.80	-1.85	-4.30	-4.87	-3.89	-3.15	-2.21	-1.02	-0.09	1.11	2.13	4.42	5.02	5.01	4.30	3.65	1.68	0.75	-0.44	-1.53	-4.53
	ARRIVAL		hs	(ikm)	186.64	170.57	185.34	158.21	175.35	185.85	192.26	187.90	187.74	183.31	190.75	189.82	180.45	183.71	188.60	156.30	176.06	172.65	178.35	185.17	185.80	127.96
			Time	(DD, HR, MM)	08 19 52	09 19 50	10 19 41	12 20 07	15 18 24	17 18 22	18 18 21	19 18 19	20 18 18	21 18 16	22 18 13	23 18 08	26 18 27	27 18 20	28 18 17	30 18 13	01 18 10	03 18 07	04 18 06	05 18 04	06 17 59	11 16 37
59.4		γ, Τ, D)	M	(km)	373,915	372,133	370,776	369,413	372,004	377,745	381,691	386,083	390,621	394,966	398,780	401,757	403,683	401,773	398,733	390,245	380,769	373,048	370,466	368,866	368,216	374,709
Ω ₄ ≈ -3.	-	SITION (E	Mg	(deg)	-20.52	-24.79	-27.62	-27.88	-16.05	-3.51	2.99	9.21	14.91	19.86	23.85	26.72	27.64	25.36	21.92	12.18	-0.08	-12.89	-18.66	-23.47	-26.88	-17.89.
		LUNAR PO.	₹	(deg)	223.43	237.81	253.06	285.46	328.68	353.91	5.80	17.56	29.42	41.57	54.12	67.08	107.46	120.48	133.10	157.14	180.49	205.05	218.43	232.81	248.14	324.17

2
TABLE

	П	- 1		Π	N	2	4	4	m	7	8	2	2	H.	2	2	4	9		5	6	2	5	0	6	
1969			ы П П	(deg)	116.4	112.8	106.4	94.4	77.5	66.3	61.8	61.8	63.2	65.9	70.0	85.1	92.7	99.8	106.2	115.2	118.2	117.2	114.2	108.7	29.9	
N ch-April	NS		σ	(deg)	61.44	78.19	97.61	133.21	163.72	189.36	214.51	227.85	241.96	256.88	272.46	317.13	330.25	342.17	353.31	15.42	40.57	55.38	71.99	91.48	159.52	
EY: Mar	COND IT IO	ENTRIC	α _{en}	(deg)	261.59	293.08	330.93	33.80	100.84	157.10	208.35	233.85	260.05	287.40	316.44	36.78	66.06	93.36	119.41	169.72	221.91	250.58	281.91	318.90	91.12	
OF-PLANE OF SURV	PARTURE	GEOC	∆0'eN	(deg)	261.3	292.8	330.6	33.5	100.5	156.8	208.0	233.5	259.7	287.1	316.1	36.5	65.8	93.0	119.1	167.4	221.6	250.3	281.6	318.6	90.8	
-TUO	DE		,ø	(deg)	10.50	17.11	23.33	27.94	25.58	16.03	3.31	-3.22	-9.49 ⁹	-15.28	-20.48	-27.88	-28.15	-26.63	-23.50	-13.14	0.72	8.03	15.03	21.60	26.56	
			λs ́	(deg)	181.31	18'0'. 7 0'"	180.02	181.09	183.73	186.95	189.93	191.17	192.19	192.94	193.38	192.40	191.26	189.77	188.08	184.64	181.42	181.80	179.87	179.49	184.57	
			Vs	(m/s)	2558.46	2541.48	2543.39	2521.86	2541.18	2557.52	2558.45	2557.15	2555.80	2555.14	2555.36	2572.53	2582.56	2590.73	2594.64	2594.67	2586.94	2493.98	2544.23	2532.81	2534.94	-
			is	(m/s)	6.98	3.87	0.50	8.17	13.26	13.82	11.21	9.04	6.40	3.37	0.24	8.72	10.87	12.23	12.92	12.78	10.25	8.09	5.22	1.11	12.74	
с.		ENTRIC	σs	(deg)	274.84	272.46	269.71	264.20	260.77	260.41	262.03	263.58	265.53	267.78	269.87	276.28	277.63	278.66	279.23	278.48	277.27	276.13	273.68	270.90	260.92	
t _{po} ≈ 28 t u ≈ 28	LT IONS	SELENOC	Ø's	(deg)	5.03	2.98	-0.40	-5.76	-9.56	10.01-	-7.91	-6.38	-4.59	-2.53	0.20	90°9	7.77	8.67	9.08	09*6	7.25	5.29	3.71	0.64	-8.98	
	IVAL COND		hs	(km)	181.78	184.41	153.88	185.28	182.52	179.50	184.73	185.29	184.84	184.10	184.96	186.23	184.15	183.13	185.15	182.31	161.99	320.90	182.05	171.50	184.39	
Ω _M ≈ -359.4 3	ARR		le le	(WW)	2 13	10	70	8	2 12	40	50	0 24	01	5 43	31	32	21	02	. 39	45	57	4	41	31	48	
	•		TI	(DD, HI	08 1:	09 17	101	12 2:	15 0:		19 06	20 1(21 1:	22 1	23 1	26 2(27 22	29 00	30 01	010	03 07	04 0	05 11	06 1	10 2	
		. Т. D)	٣	(FB)	374,575	372,516	370,854	369,403	370,815	375,918	384,310	389,131	393,872	398,119	401,481	403,566	401,337	397,857	393,434	383,354	374,427	371,257	369,197	368,242	373,119	
	Ы	SITION (EC	Μg	(deg)	-18.91	-23.90	-27.48	-27.73	-19.74	-6.95	6.80	13.11	18.66	23.18	26.47	27.49	24.86	20.93	15.92	3.51	-10.25	-16.74	-22.31	-26.61	-21.42	
		LUNAR PO	α _M	(deg)	219.04	234.32	252.00	286.71	319.43	347.48	12.90	25.49	38.37	51.73	65.65	108.61	122.62	136.07	148.98	173.93	199.63	213.65	228.88	246.53	314.54	





		¹ po 1	≈ 28.3 M ≈ 27.3				, A d d d
	AKKIVAI	SELE	NOCENTRIC				700
пе	"u	Ø's	σ _s	is	Vs	$\lambda_{\rm s}$	J .Ø

UNAR PC

 $\alpha_{\rm M}^{\rm o}$

30.69

;- ≈ ₩ %	312.5				1po 1	≈ 28.3 m ≈ 27.3					-MOLI	HIGH I I OF SURVI	EY: Octob	er 1966
				ARRIVAI	CONDIT	IONS			1	DEP/	ARTURE CO	NDITIONS		
SITION	(EQ. T, D)				SELE	NOCENTRIC					GEOCENTI	LIC		
2 ,	8	Ĩ	пе	, h	Ø's	σs	is	Vs	\ ∖s	Ø	∆0¢nN	α	σ	ы
(deg)	(km)	, (la)	HR, M	M) (km)	(deg)	(děg)	(deg)	(m/s)	(deg)	(deg)	(deg)	(deg)	(deg)	(deg)
11.13	401,455	01	21 35	8 183.61	-8.10	261.44	11.77	2603.55	189.19	-0.56	226.1	234.40	233.35	61.71
20.86	395,028	04	00 40	0 185.90	-6.10	264.22	8.36	2583.78	185.88	-12.11	275.2	283.53	260.05	64.24
24.42	390,785	05	02 15	9 184.95	-4.06	265.97	5.72	2572.18	183.93	-17.14	301.8	310.08	275.10	67.16
26.65	385,929	90	03 56	5 181.45	-1.83	268.04	2.68	2562.60	181.90	-20.88	327.7	336.03	290.86	70.49
27.26	380,690	07	05 06	5 182.43	0.03	270.04	0.05	2553.18	180.03	-21.90	346.4	354.65	306.30	71.65
26.18	375,378	08	05 33	3 181.74	1.45	271.34	1.97	2546.00	178.42	-19.56	353.7	2.03	320.69	69.16
23.44	370,234	60	05 43	3 182.74	2.37	272.48	3.43	2538.05	177.11	-15.22	356.5	4.76	334.40	65.87
13.71	361,913	11	05 50	0 184.20	4.08	273.87	5.62	2522.99	175.60	-3.31	358.8	7.05	0.89	61.88
0.47	358,901	13	05 55	5 187.61	4.60	274.64	6.53	2509.40	176.21	10.17	0.1	8.36	27.83	63.45
-18.48	367,414	16	06 0	3 187.54	3.27	273.30	4.65	2501.28	181.33	25.48	2.3	10.56	72.91	77.30
-25.84	379,090	18	06 1{	8 186.04	0.78	271.00	1.26	2507.50	186.28	28.27	6.4	14.68	105.00	90.15
-26.99	391,416	20	07 52	3 189.11	-2.91	267.07	4.13	2523.98	190.82	28.14	31.8	40.11	135.99	92.78

100.46

115.87

69.97 55492

84.97

160.04 187.36 228.59

131.04

TABLE 11

٩.

29

62.05 66.24

270.33

302.11

293.8

-15.82

185.06

242.0 195.6

-4.60

7.27

.

13.06 10.98 6.56

180.61 180.55

403,240

-7.88 3.56 14.70 23.51

352.76

38.78 65.52

15.20

262.20

264.99

184.66

01

391,665 398,222

13.25

217.63 241.68

203.93 250.27

160.00

17.71

76.56 67.57 62.57

175.12 196.39

114.50

106.2 151.7

25.11

194.20 193.76 191.66 188.62

2577.19 2599.58 2608.97 2598.92 2574.27

11.50

261.97 260.55 260.68

-8.26 -9.32 -9.20 -7.76 -4.25

181.77 184.86

30 18 58 49 02 8

12 15 17 20

23 25 27 29

403,683 405,549

-18.04

329.22 288.05

257.92

TABLE 12

			Σ (deg)	111.98	103.10	91.93	87.26	86.55	98.24	111.08	117.69	114.68	111.05	108.37	109.19	116.90	119.57	109.46	99.34
ber 1966	SN		α (deg)	226.97	251.86	279.41	293.89	308.93	339.03	6.44	34.09	82.25	100.90	117.79	132.85	168.88	190.26	234.80	260.92
EY: Octo	CONDITIO	CENTRIC	Cen (deg)	9.12	10.45	13.48	18.11	31.63	86.63	145.80	202.68	290.47	321.59	346.10	358.92	6.24	7.54	9.46	10.97
-LOW, II OF SURVI	EPARTURE	CEO	∆0 _{©N} (deg)	0.8	2.2	5.2	9.8	23.3	78.3	137.5	194.4	282.2	313.3	337.8	350.6	357.9	359.2	1.2	2.7
HIGH TIME	D		ه' (deg)	-18.28	-25.28	-28.21	-28.14	-28.07	-27.14	-19.32	-6.08	14.28	19.33	21.88	21.18	9.12	-1.46	-20.94	-26,81
			λ _s (deg)	189.86	186.61	183.18	181.39	179.62	176.67	176.00	178.15	184.08	186.52	188.80	190.87	194.40	194.38	189.31	185.95
			Vs (m/s)	2576.28	2573.68	2563.19	2558.77	2552.10	2550.48	2555.45	2542.66	2518.37	2513.50	2514.37	2522.60	2552.61	2558.00	2574.93	2567.71
			h _s (deg)	5.75	3.93	1.28	0.45	2.87	6.17	13.42	14.67	9**6	5.61	1.86	0.94	5.38	6.58	5.34	3.18
		OCENTRIC	σs (deg)	265.81	267.09	269.16	270.32	272.15	276.46	279.56	280.36	276.78	273.93	271.29	269.40	266.28	265.23	266.23	267.82
≈ 28.3 ₩ ≈ 27.3	IONS	SELEN	β_{s}^{l} (deg)	-3.95	-2.63	-0.97	0.32	1.90	6.52	9**6	10.45	6.65	4.00	1.34	-0.72	-3.88	-4.54	-3.78	-2.32
i po	AL CONDIT		hs (km)	185.49	181.84	185.26	182.92	185.21	185.28	184.28	196.40	185.40	184.18	186.43	185.18	183.52	203.42	183.59	184.94
	ARRIV		Time (DD, HR, MM)	01 06 05	03 06 08	05 06 18	06 06 35	07 07 25	09 10 51	11 14 32	13 18 02	16 23 30	18 02 58	19 04 30	20 05 18	23 04 11	25 04 15	29 04 18	31 04 22
12.5		Q. T. D)	₹Ĵ	402,886	397,674	390,069	385,397	380,190	369,190	360,893	359,253	371,341	378,227	384,808	390,827	402,901	405,546	400,063	394,312
Ω <mark>a</mark> r≈ -31		I) NOLLIS	б _М (deg)	7.75	17.65	24.86	26.79	27.23	22.66	11.49	-3.03	-21.81	-25.53	-27.17	-27.09	-19.47	-10.26	11.22	20.57
		LUNAR PO	αM (deg)	23.54	46.39	72.24	86.57	101.92	134.23	165.07	194.15	239.05	255.87	271.58	286.52	325.14	347.80	30.87	54.81

13	
TABLE	

				-	-		-		_		_	_	_	-					_							_
			ы	(deg)	113.72	115.03	116.51	117.69	119.37	114.76	107.02	101.92	97.11	94.31	95.36	98.98	103.91	108.62	112.53	115.43	118.20	119.49	113.31	114.47	115.98	117.31
: 1964	LONS		σ	(deg)	138.60	150.95	162.73	174.19	197.14	221.99	250.83	266.98	283.95	301.29	318.41	334.60	349.39	2.91	15.57	27.77	52.28	65.12	120.71	146.75	158.70	170.12
I Nov-Dec	IRE CONDIC	SEOCENTRI	a. M	(deg)	350.52	357.72	2.36	5.59	10.18	14.08	18.98	22.82	29.10	40.42	59.32	83.83	109.88	135.28	159.50	182.71	227.66	250.06	334.09	355.83	1.16	4.74
OW-HIGH, F SURVEY:	DEPARTI		Δ0 _{0N}	(deĝ)	337.9	345.1	349.8	353.0	357.4	1.8	6.4	10.2	16.5	27.8	46.7	71.2	97.3	122.7	146.9	170.1	215.1	237.5	321.5	343.2	348.6	352.1
ID: L TIME O			ø،	(deg)	15.88	13.63	10.24	6.07	-3.73	-14.14	-22.93	-25.83	-27.43	-27.96	-27.83	-26.92	-24.87	-21.68	-17.58	-12.84	-2.48	2.66	16.49	14.06	11.62	7.72
			λa	(děg)	190.51	189.13	187,62	185.82	181.96	178.21	176.09	176.07	176.00	176.77	178.58	180.71	183.05	185.57	188.00	190.12	193.17	194.00	192.98	190.35	188.88	187.33
			Vs	(m/s)	2574.12	2573.70	2566.11	2561.26	2543.38	2532.38	2508.96	2487.66	2506.89	2516.51	2505.68	2510.88	2526.26	2537.27	2547.40	2556.89	2567.69	2572.38	2557.93	2571.42	2571.47	2566.52
			1.	(deg)	2.81	0,98	0.64	2.07	4.40	5.80	5.91	5.30	4.10	2.10	0.76	3.97	6.93	9.37	11.25	12.55	13.36	12.91	5.59	1.50	0.21	1.77
28.3° 24.6°		OCENTRIC	σs	(deg)	271.97	270.72	269.56	268.50	266.88	265.94	265.90	266.17	267.16	268.47	270.47	272.77	274.96	276.71	277.91	278.80	279.46	278.84	274.21	271.13	269.83	268.92
° 1 ₩ ₩ ₩	TIONS	SELEN	Ø's	(deg)	2.01	0.67	-0.46	-1.43	-3.10	-4.14	-4.26	-3.66	-2.96	-1.43	0.60	2.85	4.84	6.55	8.03	8.98	9.47	9.44	3.67	0.98	-0.12	-1.41
	VAL COND		hs	<u>(</u>]	I85.33	187.78	201.21	205.31	218.02	206.63	218.66	246.23	196.48	171.35	193.06	194.02	182.44	181.84	182.49	182.04	186.09	183.29	217.82	195.58	195.78	203.15
	ARRI		Time	(DD. HR. MM)	10 01 52	11 02 18	12 02 35	13 02 46	15 03 02	17 03 15	19 03 33	20 03 47	21 04 11	22 04 53	23 06 04	24 07 37	25 09 14	26 10 48	27 12 18	28 13 44	30 16 30	01 17 52	05 23 04	08 00 24	09 00 43	10 00 55
5°		T. D)	₹	(km)	.04,703	02,738	99,548	95,217	84.003	71,892	62.741	60,365	59,775	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	163.837	167.979	172,905	121	83,242	188,013	196,029	199.213	06,198	05,335	489	00,602
Ω_M ≈ -275.	:	ITION (EQ.	PM M3	(deg)	-24.20 4	-22.72 4	-20.20 3	-16.73 3	-7.47 3	3.78 3	14.92 3	19.49 3	22.80 3	24.46 3	24.24 3	22.18 3	18.59 3	13.94 3	8.65 3	3.06 3	-7.93 3	-12.89 3	-24.43 4	-23.45 4	-21.31 4	-18.23 4
		LUNAR POS	αM	(deg)	293.10	306.18	318.96	331.44	355.90	20.86	48.18	63.23	79.25	96.03	113.09	129.73	145.36	159.81	173.24	185.94	210.36	222.62	274.96	301.56	314.37	326.80

	-	_			+				-	-	-+				_			-		-+	-+	-+			_		
			L	د (deg)	00.00	52.03	82.34	77.86	65.38	61.79	63.43	65 . 67	67.42	67.22	65.41	63.43	62.10		91./0	62.30	66.37	73.68	87.50	86.83	77.67	75.16	
c 1964	SNC		Ĭ	ر (deg)		144.20	156.93	169.02	203.72	229.54	260.91	278.64	296.68	313.83	329.57	344.00	357.40	2	10.11	22.41	46.88	72.40	126.32	139.69	164.89	176.53	
LL : Nov-De	CONDITION	DCENTRIC		(deg)		63.10	83.28	105.37	175.22	225.16	280.26	308.26	332.55	349.03	358.17	3.31	6.62	;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;	9°04	11.03	14.62	18.77	41.59	56.38	16.96	119.26	
SURVEY	DEPARTURI	GE(∆0⊜N (deg)		50.5	70.7	92.8	162.6	212.6	267.7	295.7	321.0	336.4	345.6	350.6	354.0		356.4	358.4	2.0	6.2	29.0	43.8	84.3	106.7	
TIME OF				ø' (deg)		27.98	27.30	25.73	14.41	2.35	-10.11	-14.89	-17.50	-17.23	-14.44	-10.10	-4 03		0.57	6.06	16.03	23.42	28.17	28.10	26.50	24.35	
				λs (deg)		189.75	187.94	186.46	180.34	177.55	176.47	176.69	177.42	178.78	180.76	182.87	195 27	17.001	187.61	189.54	191.16	194.09	192.18	190.76	187.53	185.73	
				Vs (m/s)		2568.79	2585.61	2570.14	2589.05	2571.92	2540.31	2521.45	2510.99	2507.48	2502 01	2508-60	20.00	00.0002	2506.27	2511.98	2607.84	2531.08	2558.61	2574.17	2590.00	2595.27	
				is (deg)		2.07	4.48	6.78	12.04	13.65	12.47	10.44	7.73	5.04	2 63	97 0	2 C	7.72	3.22	4.58	6.07	5.93	0.98	1.23	6.01	8.16	
28.3 24.6°		ENTRIC		σs (deg)		268.59	266.87	265.18	261.41	260.37	261.28	262.66	264.45	266.32	768 13	260.15		2/1.0/	272.30	273.23	274.31	274.20	270.70	269.12	265.68	264.15	
1 _{po} ∎t ∎t	TONS	SELENOC		Øs (deg)		-1.51	-3.20	-4.77	-8.47	-9.72	-8.95	-7.44	-5.38	-3.43	10/1	+0° -1-		1.09	2.26	3.24	4.27	4.18	0.69	-0.87	-4.18	-5.69	
	AL CONDIT			hs (hs)		205.45	183.00	222.96	183.07	181.57	183.58	189.58	187.28	182.14	100	100.001	1// 1/2	187.53	199.07	191.53	54.46	224.96	215.49	194.53	184.48	182.29	
	ARRIV			me R, MM)		7 57	9 12	0 34	4 52	7 56	1 21	3 07	0 38	1 40		2 14	2	2 45	2 54	3 01	3 13	2 22	2 20	77 50	8 15	99 37	- ; ,
				Ti (DD, H		10	11 0	12	15 1	17 1	19 2	20	22 0	23		24 5 7	3	26 C	27 0	28 (000	5	90	20			, ,
. 5.		1 (U T C		₹Ĵ	, , ,	404,331	401,957	398.240	380,976	368,613	360,825	359.747	360,654	363 235	2236202	367,026	371,574	376,472	381.382	386 055	394 143	1 273 773	400 27/	400,214	200,000	300 303	1,,
0. ≈ -77	M.	CTTTON / B	7 107 170	δM (deg)		-23.93	-22.11	-19.16	-4.83	7.31	18.38	20.01	24 31	10 VC	74.44	22.75	19.65	15.50	10.66	1/1 5	-5 15	17 11	70.76	10. 12	37 00	-16 01	T 72*0T-
		TIMIAD DO		um (deg)	10	296.37	309.84	323.10	1.91	28.84	50 15	75 86	03 19	27.021	110.11	126.31	141.40	155.38	168.39	190.66	00.00	00. 100	20 020	2/0.0/	20 010	01 100	1 01.166

TABLE 14

32

B. THE INFLUENCE OF LAUNCH AZIMUTH VARIATIONS

Consider Figure 9 as basis for drawing the conclusion that launch azimuth variations have a negligible influence upon the minimum attainable inclinations. In a sense this variation had been studied previously under the OUT-OF-PLANE TRANSIT CASES, in which it was found that the day-to-day minima inclinations did not change significantly (less than 1°).



•
7

APPROVAL

MTP-AERO-62-73

EARTH-MOON TRANSIT STUDIES BASED ON EPHEMERIS DATA AND USING BEST AVAILABLE COMPUTER PROGRAM

PART I: PERISELENUM CONDITIONS AS FUNCTION OF INJECTION CONDITIONS

BYRD TUCKER

The information in this report has been reviewed for security classification. Review of any information concerning Department of Defense or Atomic Energy Commission programs has been made by the MSFC Security Classification Officer. This report, in its entirety, has been determined to be UNCLASSIFIED.

R F focker

R. F. HOELKER Chief, Future Projects Branch

Mumle

E. D. GEISSLER Director, Aeroballistics Division

REFERENCES

- 1. Holdridge, D. B., "Space Trajectories Program for the IBM 7090 Computer," JPL Technical Report No. 32-223, March 2, 1962.
- Davey, G. L., "A Practical Reference for Choosing Launch Dates for Lunar Missions for the Period from 1962 to 1971 Where the Declination, Radial Distance, and Phases of the Moon are Important Factors," Technical Internal Correspondence, Ref. 2253.2/27, Hughes Aircraft Company, 22 December 1961.
- 3. Kalensher, B. E., "Selenographic Coordinates," JPL Technical Report No. 32-41, February 24, 1961.
- 4. Clarke, Victor C., Jr., "Constants and Related Data Used in Trajectory Calculations at the Jet Propulsion Laboratory," JPL Technical Report No. 32-273, May 1, 1962.
- Peabody, P. R., and Holdbridge, D. B., "Computational Errors in Precise Trajectory Calculation," JPL Technical Memo No. 372-23, November 25, 1961.
- Battin, Richard H., "The Determination of Round-Trip Planetary Reconnaissance Trajectories," Journal of the Aero/Space Sciences, Vol. 26, No. 9, September, 1959.
- Kizner, W., "A Method of Describing Miss Distances for Lunar and Interplanetary Trajectories," Ballistic Missiles and Space Technology, Vol. III, 1961.

DISTRIBUTION

្វរ

۹ ۲

M-MS-	IP	M-COM	P Schulz-Arenstorff
M-FPO		DI •	Jenarz menseorri
Mr	Koelle	M-AST	P
Mr	Ruppe	Mr	Digesu
Mr	Williams	FIL •	Digesu
111 •	WIII Idnio	M_DD	
M-AFR	n	Dr	Stuhlinger
Dr	<u>C</u> eissler	Dr. Mr	Heller
Dr.	Hoelker	Mr	Bucher
Mr	Dahm	111 •	bucher
Mr	Linsley	M_D\$.	F
Mr	Wilson	Mr Mr	Swanson
Mr	Horp	rii •	Swallson
Dr	Adams	M-CP	
Mr.	Baker	Mr Mr	deFries (15)
Mr	Golmon	TIL .	defiles (15)
Mr	Hart	M-MS-1	(8)
Mr	Reed	<u></u>	
Mr	Vaughan	M-MS-1	ГР
Dr	Speer	11 110 1	
Mr	Lindherg	M-PAT	
Mr	Kurtz	<u>11 1 111</u>	
Mr	Nul 12 Miner	M-HMF.	-P
Mr	Callaway	<u> 11 11111</u>	<u> </u>
Mr	Tean	M-MS-H	4
Mr	Teacue	<u>11-110-1</u>	<u>1</u>
Mr	Schmieder		
Mr	Brand		
Mr	Ijelo		
Mr	Schuaniger		
Mr	Linch		
Mr	Hill		
Mr.	Davidson		
Dr.	Sperling		
Mr.	Tucker (10)		
Mr.	Thomae		
Mr.	Dearman		
Mr.	Telfer		
Mre	. Chandler		
Mr	McNair (5)		
LIT .			

,