

NATIONAL AERONAUTICS AND SPACE ADMINISTRATION

LM RENDEZVOUS PROCEDURES

D MISSION

FINAL

REVISION A

JAN 31, 1969



MANNED SPACECRAFT CENTER  
HOUSTON, TEXAS

N70-34680

(ACCESSION NUMBER)

06

(THRU)

TMX 64363

(PAGES)

31

(CODE)

31

(CATEGORY)

Reproduced by the  
CLEARINGHOUSE  
for Federal Scientific & Technical  
Information Springfield Va. 22151

RENDEZVOUS PROCEDURES

D MISSION

AS-504/CSM-104/LM-3

January 31, 1969

PREPARED BY:

Stephen P. Grega

Stephen P. Grega  
Orbital Procedures Section

Milton C. Contella

Milton C. Contella  
Chief, Orbital Procedures Section

APPROVED BY:

Paul C. Kramer

Paul C. Kramer  
Chief, Flight Procedures Branch

James W. Bilodeau

James W. Bilodeau  
Assistant Chief for Crew Integration  
Flight Crew Support Division

Warren J. North

Warren J. North  
Chief, Flight Crew Support Division

Donald K. Slayton

Donald K. Slayton  
Chairman, Crew Procedures Control Board

TABLE OF CONTENTS

	<u>Page</u>
1.0 Purpose . . . . .	1-1
2.0 Major Events . . . . .	2-1
2.1 Undocking Maneuver . . . . .	2-2
2.2 RCS Separation Maneuver . . . . .	2-3
2.3 Phasing Maneuver . . . . .	2-4
2.4 TPI Targeting . . . . .	2-6
2.5 IMU Alignment and Close Approach . . . . .	2-7
2.6 Insertion Maneuver . . . . .	2-8
2.7 CSI Maneuver . . . . .	2-9
2.8 CDH Maneuver . . . . .	2-10
2.9 TPI Maneuver . . . . .	2-11
2.10 Midcourse Corrections . . . . .	2-12
2.11 Braking . . . . .	2-13
3.0 Nominal Mission Procedures . . . . .	3-1
4.0 Abort Procedures . . . . .	4-1
5.0 Backup Charts . . . . .	5-1
6.0 References . . . . .	6-1

D MISSION  
RENDEZVOUS PROCEDURES  
LM ACTIVE

1.0 Purpose

This document contains the primary procedures for the LM-3 active rendezvous with CSM 104 spacecraft, in accordance with Detailed Test Objective P20.27, defined in the Mission Requirements SPD8-R-005, Revision 1, dated November 6, 1968.


The purpose of the Rendezvous Procedures Document is to provide a single source of procedures information for use in flight planning, crew training, and preparation of onboard data.

This is a control document, subject to review by all elements of the Apollo Program, and approval by the Procedures Configuration Control Board.

2.0      Major Events

The LM3/CSM104 rendezvous occurs in the "fifth period of activities" ( 87 hrs to 10<sup>1</sup> hrs G.E.T.). The procedures in this period will be divided into segments around major activities, and discussed separately in the paragraphs of Section 2.0.

Figure 2-1 shows the LM attitude time history and the locations in time and position of the 50 major events of the nominal mission.




**FIGURE 2-1**

**"D" MISSION RENDEZVOUS PROFILE**  
**(CSM-CENTERED RELATIVE MOTION)**

## LM MAJOR EVENTS

1	92+41	UNDOCKING	26	96+04	AGS TARG
2	92+44	I20 YAW RT, 90 PITCH UP	27	96+15	AGS UPDA
3	92+50	LM INSPECTION (360 YAW)	28	96+22	STAGE
4	93+06	RCS SEPARATION (CSM ACTIVE)	29	96+22	CSI THRU
5	93+07	AGS UPDATE AND ALIGN (R47)	30	96+29	CDH TARG
6	93+08	R/R CHECKOUT	31	96+30-96+54	R/R NAVIG
7	93+15	EXT ΔV FOR DPS PHASING (P30)	32	96+57	AGS UPDA
8	93+18	IMU REFSMMAT ALIGN(P52)XCOAS CALIBRATION)	33	97+06	CDH THRU
9	93+39	AGS UPDATE AND ALIG (R47)	34	97+13	TPI TARG
10	93+47	LR SPUR TEST (V78)	35	97+14-97+48	R/R NAVIG
11	93+50	DPS PHASING (P40 AND AGS CONTROL)	36	97+50	AGS UPDA
12	93+58	TPI <sub>o</sub> TARGETTING (P34)	37	97+85	CALCULATI
13	94+00-94+15	R/R NAVIGATION (P20,12 MARKS)	38	97+89	TPI THRU
14	94+16	LR SELF TEST	39	98+04	MCCI TAR
15	94+28	TPI <sub>o</sub> TARGETTING (P34)	40	98+02-98+06	R/R NAVIG
16	94+30-94+48	R/R NAVIGATION (P20,15 MARKS)	41	98+08	CALCULAT
17	94+51	GO, NO GO FOR INSERTION	42	98+08	MCCI THR
18	94+52	IMU REFSMMAT ALIGN(P52)	43	98+11	MCC2 TAR
19	95+20	MONITOR CLOSE APPROACH	44	98+12-98+18	R/R NAVIG
20	95+22	EXT ΔV FOR DPS INSERTION (P30)	45	98+20	CALCULAT
21	95+34	AGS UPDATE AND ALIGN (R47)	46	98+21	MCC2 THR
22	95+36	LR SPUR TEST (V78)	47	98+30	BRAKING
23	95+42	DPS INSERTION (P40 AND AGS CONTROL)	48	98+35	STATION
24	95+51	CSI TARGETTING (P32)	49	98+47	R/R OFF
25	95+50-96+12	R/R NAVIGATION (P20, 18 MARKS)	50		DOCK

**FOLDOUT FRAME**





**FIGURE 2-1**  
**MISSION RENDEZVOUS PROFILE**  
**(CSM-CENTERED RELATIVE MOTION)**

## LM MAJOR EVENTS

-41	UNDOCKING	26	96+04	AGS TARGETING
-44	I2O YAW RT, 90 PITCH UP	27	94+15-	AGS UPDATE AND ALIGN (R47)
-50	LM INSPECTION (360 YAW)	28	96+22	STAGE
-06	RCS SEPARATION (CSM ACTIVE)	29	96+22	CSI THRUSTING (P41)(APS INTERCONNECT)
-07	AGS UPDATE AND ALIGN (R47)	30	96+29	CDH TARGETING (P33)
-08	R/R CHECKOUT	31	96+30-96+54	R/R NAVIGATION (P20,20 MARKS)
-15	EXT AV FOR DPS PHASING (P30)	32	96+57	AGS UPDATE AND ALIGN (R47)
-18	IMU REFSMMAT ALIGN(P52)(COAS CALIBRATION)	33	97+06	CDH THRUSTING (P42)
-39	AGS UPDATE AND ALIGN (R47)	34	97+13	TPI TARGETING (P34)
-47	LR SPUR TEST (V78)	35	97+14-97+46	R/R NAVIGATION(P20,26 MARKS)
-50	DPS PHASING (P40 AND AGS CONTROL)	36	97+50	AGS UPDATE AND ALIGN(R47)
-58	TPI <sub>0</sub> TARGETING (P34)	37	97+55	CALCULATE BU SOLUTION (TPI)
-94+12	R/R NAVIGATION (P20,12 MARKS)	38	97+59	TPI THRUSTING (P41)
+16	LR SELF TEST	39	98+04	MCCI TARGETING (P35)
+28	TPI <sub>0</sub> TARGETING (P34)	40	98+02-98+08	R/R NAVIGATION (P20, 4 MARKS)
-94+48	R/R NAVIGATION (P20,15 MARKS)	41	98+08	CALCULATE BU SOLUTION (MCCI)
+51	GO, NO GO FOR INSERTION	42	98+08	MCCI THRUSTING (P41)
+52	IMU REFSMMAT ALIGN(P52)	43	98+11	MCC2 TARGETING (P35)
+20	MONITOR CLOSE APPROACH	44	98+12-98+18	R/R NAVIGATION (P20, 6 MARKS)
+22	EXT AV FOR DPS INSERTION (P30)	45	98+20	CALCULATE BU SOLUTION (MCC2)
+34	AGS UPDATE AND ALIGN (R47)	46	98+21	MCC2 THRUSTING (P41)
+35	LR SPUR TEST (V78)	47	98+30	BRAKING (P47)
+42	DPS INSERTION (P40 AND AGS CONTROL)	48	98+38	STATION KEEPING
+ 8	CSI TARGETING (P32)	49	98+47	R/R OFF
-96+12	R/R NAVIGATION (P20,18 MARKS)	50		DOCK

FOLDOUT FRAME 3



FOLDOUT FRAME 3

1      Undocking Maneuver

By 89:50 hrs G.E.T. both crewmen have entered the LM, powered up the PGNS, IMU, and AGS, and closed the hatch in preparation for the undocking. At about 91:10 over Artigua the PGNS state vector is updated. The first rendezvous related activity begins with the docked IMU align which has been preceded by a ground uplink of the REFSMMAT into the LM Guidance Computer (LGC). The docked align is accomplished without using Program 51 and 52 procedure by manually setting the REFSMMAT flag and commanding a Verb 42 to fine align. The ICDU angles used in Verb 42 are computed from the CSM's Noun 20 and the docking ring index angle with an equation similar to that given in the AOH Vol II Section 4.9. The Rendezvous Radar antenna restraint device is released and the radar self test routine executed. Meanwhile, the CSM has begun a maneuver to the undocking attitude. LM procedures up to this point are included in the crew checklist. Undocking occurs at 92:41 with the CSM backing away to about 50 feet (giving clearance for LM maneuvers), while maintaining an inertial attitude. At this time the LM will yaw right 120 degrees and pitch up 180 degrees in order for the CSM to photograph the descent engine bell, then pitch down 90 degrees under AGS control to position the LM plus Z-axis toward the CSM.

2.2 RCS Separation Maneuver

The LM is placed in AGS attitude hold (pitch, roll) and a yaw rate of approximately 1 degree/second is commanded with AGS minimum impulses. This yaw rate is held for 360 degrees, so that the CSM can visually inspect all legs of the LM landing gear and descent engine bell. When the LM plus Z-axis is again pointed at the CSM, the yaw rate is stopped and the LM enters PGNS attitude hold and begins station keeping. The attitudes of both vehicles during the inspection have been established to provide illumination of the LM surface from reflected sunlight.

At 93:05:45 the CSM performs a 5 feet/second radially downward burn to allow safe separation from the LM during IMU alignment prior to the phasing burn. The LM crew accomplishes Target Delta V (Verb 84) to update the LGC with the maneuver just accomplished by the CSM.

Phasing Maneuver

Rendezvous radar acquisition using Verb 41 Noun 72 (lock-on option) is checked by manually maneuvering to point the LM plus Z-axis at the CSM and designating the antenna to the plus Z-axis. After determining that the radar is locked on the main lobe, the tape meter is calibrated using rendezvous radar self test (Verb 62). After lock-on is accomplished and radar operation verified, the radar antenna is positioned clear of the AOT field of view and turned off. While awaiting sunset, External Delta V (Program 30) is loaded with the parameters of the phasing burn and the event timer is set counting down to this maneuver.

A REFSMMAT alignment (Program 52) is performed just prior to sunset using the center forward detent position. Manual star selection is used with automatic vehicle maneuvering. Before terminating Program 52, the COAS is calibrated for future use. The rendezvous radar is turned on and an AGS state vector update and AGS alignment is accomplished followed by an AGS external Delta V targeting.

The landing radar (LR) is activated and placed in the proper configuration for a LR spurious test (Routine 77). This test is started with a Verb 78 prior to descent propulsion system (DPS) thrusting and terminated by a Verb 79 after the DPS thrusting.

The sequence of the phasing burn is started with selection of Program 40. This program will be used to monitor the maneuver which is executed under AGS control. LM guidance is switched to AGS control at about 3 minutes prior to ignition, after insuring that the ATT CONT switches are in PULSE. Configuring the ATT CONT switches in PULSE prior to switching GUID CONT from PGNS to AGS assures that unexpected high maneuver rates are not commanded by the AGS. AGS attitude error signals are displayed on the FDAO needles when the MODE CONT switch is placed to AUTO and are nulled with AGS pulses. When these errors are nulled, the ATT CONT switches are placed to MODE CONT which enables AGS auto steering. The ABORT button is depressed, manual ullage is initiated, and the burn is executed under AGS control. Upon thrust termination, the PGNS residuals are nulled with RCS thrusting.

TPI<sub>o</sub> Targeting

When range has opened to 19,000 feet, rendezvous radar tracking with LGC updating is initiated. Program 34 (TPI) is called and targeted for a possible abort from the equi-period. The program is recycled to compute a solution for resetting the event timer. The AGS is targeted for the PGNS computed TPI time based on the LGC elevation angle option. There are few Guidance and Navigation tasks during the next several minutes except for maintaining the LM plus Z-axis coarsely aligned with the CSM using radar error needles or the COAS. This time will be spent making systems checks and accomplishing test objectives.

Final computation of TPI<sub>o</sub> is accomplished 14 minutes prior to ignition. The TPI<sub>o</sub> solution is evaluated and the onboard GO, NO GO decision is made about 94:51.

2.5      L.U Alignment and Close Approach to CSM

If the insertion maneuver is to be executed, the rendezvous radar antenna is driven from the AOT field of view and is turned off so that it will not drift back into the field of view. A REFSMMAT alignment (Program 52) is then accomplished between 94:50 and 95:08. After completion of the alignment, the rendezvous radar is turned on and an automatic radar lock on is performed in preparation for monitoring the close approach to the CSM (about 2.8rm). The inertial angular rate of the line of sight to the CSM is also monitored to insure that the trajectory is not intercepting.

6      Insertion Maneuver

When the radar indicates the range is increasing, PGNS External Delta V (Program 30) is loaded with the parameters of the insertion burn and the event timer is set counting down. The AGS is updated, aligned, and targeted in external delta V prior to the maneuver.

DPS Thrusting (Program 40) is called and the auto maneuver under PGNS control to the burn attitude is enabled. This burn is executed under automatic PGNS control with AGS monitoring.

2.7      CSI Maneuver

At about 95:49, CSI targeting is accomplished using Program 32 and AGS. Some iteration on the CDH apsis (1st or 2nd) may be required to obtain a solution from both PGNS and AGS. Prestaging checks are begun at about CSI -5 minutes to insure readiness to stage just prior to CSI. Radar updating is terminated 14 minutes prior to CSI and the final solution computed. This solution is recorded and transmitted to the ground and CSM. A CSI chart solution is calculated to validate the "G" mission procedures. The AGS is updated, aligned, and targeted in external delta V with the CSI solution to be burned. An automatic maneuver to the thrusting attitude is done under PGNS control (Program 41) and last minute prestaging systems checks are accomplished. The descent stage is jettisoned at ignition. RCS thrusting is started on time, and ascent fuel is used through the interconnect system to supplement RCS fuel usage.

.8

CDH Maneuver

Program 33 is selected after the CSI burn and the AGS absolute time of CDH is loaded from the PGNS. The LGC is updated with radar marks as in other prethrust sequences, and a solution is computed. A CDH chart solution is calculated 7 minutes prior to TIG. The AGS is updated, aligned, and targeted in external delta V with the CDH solution to be burned. An automatic maneuver to the thrust attitude is performed, and CDH thrusting is done with the Ascent Propulsion System (APS) using Program 42.

2.9 TPI Maneuver

Radar tracking is initiated after the CDH maneuver and updating of the LGC continued. Terminal Phase targeting is done in Program 34, and in the AGS. Radar updates are entered into the AGS, taking marks approximately every three minutes. Both systems are targeted to have a node occur at intercept. Backup measurements are made at the appropriate times. The AGS is aligned, updated, and retargeted in external delta V mode with the solution to be used for TPI. The TPI maneuver is accomplished in attitude hold, using RCS thrusting along the plus Z-axis with the thrust direction established with the COAS.

.10 Midcourse Corrections (MCC)

The midcourse program (Program 35) is assumed to have ATIGINC =3 minutes. (ATIGINC is the constant that determines time between selecting final computation cycle and the midcourse maneuver time).

MCC 1

Program 35 is entered immediately after TPI, and radar track reinitiated. Backup measurements are made and MCC chart solutions obtained.

MCC 1 is made to occur at TPI plus 10 minutes in the PGNS by proceeding from display "Verb 16 Noun 45" at TPI plus 7 minutes. The backup solution is valid for TPI plus 10 minutes.

If MCC 1 is to be executed, Program 41 is selected to burn the components with RCS. No maneuver to a "preferred" thrust attitude will be made. (LM plus Z-axis will remain pointed at the CSM after TPI until docking.)

MCC 2

MCC 2 occurs at TPI plus 22 minutes by keying STBY at TPI plus 19 minutes. A backup chart solution is obtained at TPI plus 20 minutes. The maneuver is executed as MCC 1.

2.11 Braking

In preparation for braking, the DAP is checked to verify narrow deadband is selected. Program 20 is terminated at 18,000 ft but the radar is kept in AUTO TRACK to provide radar range and range rate displayed on the tape meter. Average "G" is turned on prior to braking, and attitude hold is selected. The braking schedule is followed as contained in section 3.

3.0      Nominal Mission Procedures

The procedures included in this section do not specify which crewmember, Commander or LM Pilot, performs each listed task. These need not be specified since the following basic rules define which crewmember performs each task. These rules are:

COMMANDER (CDR):

1. All attitude changes, whether manual or automatic, will be accomplished by the CDR.
2. The operation of the DSKY during thrust programs (P40, P41, P42, P47) will be done by the CDR. Actual manipulation of the Translation Thrust Control Assembly (TTCA) need not be always done by the CDR, but in most cases will be.
3. Operation of the rendezvous and landing radar will be done by the CDR.
4. The CDR will operate all other systems accessible to only his crew station.

M PILOT (LMP) TASKS:

- .. AGS operation.
- 2. DSKY operation will be done by the LMP except when keyboard entries affect the control of spacecraft attitude or thrusting.
- 3. Backup data logging and chart calculations.
- 4. All logging of maneuver solutions and systems performance.
- 5. The LMP will operate all other systems accessible to only his crew station.

These general rules are guidelines only, and may be deviated from by the LM crew if they develop more efficient Task assignments.

The abbreviations used herein are consistant with those in the AOH. However, in order to condense and simplify the procedures so that they are representative of onboard data, a number of additional shorthand conventions have been used. To allow the unfamiliar reader to understand the procedures contained in this section, the following explanations are included:

1. AGS - A single asterisk is employed to denote those procedures involving operations to be performed on the DEDA. The three number group following an asterisk specifies DEDA address. An "R" following the address group indicates the address is to be read out. A five digit group behind the "R" indicates a nominal or expected display. If the three number address group is followed by a + or - sign, a data load is indicated. When a single digit follows the +, addition of 4 zeros behind this digit is assumed. Once used, these conventions are easily handled and save considerable space.

2. PGNS - The verb-noun addresses in the PGNS are indicated to the left of the procedures column. An "F" is used to indicate a flashing display, or absence of an "F" a static display. To the right of the verb-noun, on the same line, are the contents of the three data registers. If numeric quantities appear, the DSKY should be correspondingly made to agree by executing a V21, V22, or V23 and performing a data load. The procedure of blanking and loading registers is not included since it is repeated often and is highly familiar to the crews.

EXAMPLE: F 06 33 94:39:46 TIG DPS SEP

Expanded, this means; Load flashing verb 06 noun 33 with the quantity 94 hours, 39 minutes and 46 seconds; the time of ignition of the descent engine separation maneuver.

Procedurally, this is done by keying verb 25 enter, loading +00094 in register 1, +00039 in register 2, and +04500 in register 3.

If numeric quantities do not follow the verb-noun, it is indicated that a computed or information quantity is being displayed via the DSKY. If nominal values are listed for possible comparison, they appear in parentheses.

EXAMPLE: F 06 42 HA HP ΔV

Expanded, this means; Flashing verb 06 noun 42 has computed height of apogee in register 1, height of perigee in register 2, and velocity to be gained in register 3.

TIME - The numbers in the left hand column preceded by a + or - indicate "event timer" time referenced to an event.

Minus indicates event timer counting down to a future event.

Periodically, this same column contains the nominal mission ground elapsed times (G.E.T.) in parentheses. Asterisks following the event time indicate a time critical event which should be accomplished to the nearest second.

ASSUMPTIONS

- 1 TRANSFER COMPLETE
- 2 SYSTEMS CHECKS COMPLETE
- 3 PGNS ACTIVATED
- 4 AGS BN AND SELF TESTED
- 5 RCS PRESSURIZATION AND TEST FIRING COMPLETE
- 6 RNDZ RDR SELF TEST COMPLETE.
- 7 DAP LOAD (01002)
- 8 IMU ALLIGNED
- 9 LGC IN P08
- 10 V76E (PGNS PULSE)

(92:41)

WHEN CLEAR OF CSM  
 GUID CNT-AGS  
 DEFLECT ACA BUT OF DETENT  
 ATT CNT-MODE CNT(3)  
 YAW RIGHT 120DEG (RATE CMD)  
 PITCH UP 180 DEG (2 DEG/SEC  
 (CSM PHOT0 OF DPS BELL)  
 PITCH DN 90 DEG (2 DEG/SEC)  
 (CSM IN FWD WINDSW)

(92:49)

ATT CNT(YAW)=PULSE  
 YAW 360 DEG FOR INSPECTION  
 (APPROX 1 DEG/SEC)

GUID CNT-AGS  
 MODE SEL-LDG RADAR  
 RNG/ALT MN-RNG/RNGRT  
 RATE ERR MN-RNDZ RDR(CDR)  
 ATTITUDE MN-PGNS(CDR)  
 RATE ERR MN-CMPTR(LMP)  
 ATTITUDE MN-AGS(LMP)  
 SHFT/TRUN=+50  
 X-POINTER-HI MULT  
 RADAR TEST SW-BFF  
 ENG GMBL-ENABLE  
 ENG ARM-BFF  
 X-TRANSL-2JETS  
 BAL CPL-BN  
 DEADBAND-MIN  
 ATT CNT-PULSE(3)  
 MODE CNT-ATT HOLD  
 THRBT/JET-JET  
 IMU-BN  
 R/R MODE-LGC  
 TTCA/TRANSL(CDR)-ENABLE  
 ACA/4JET(CDR)-ENABLE  
 TTCA/TRANSL(LMP)-ENABLE  
 ACA/4JET(LMP)-ENABLE

1.

AS-504/CSM-104/LM-3

PREPARED BY FPRB/CF24

WHEN CLEAR OF CSM  
 GUID CNT-AGS

ATT CNT(YAW)=MODE CNT  
 KEY V77E (WHEN YAW=0)  
 GUID CNT-AGS  
 LM ACTIVE STA KEEP UNTIL  
 AFTER CSM RCS SEP.  
 GUID CNT-PGNS

-7

KEY V83E  
 F 06 54 R,RDGT,THETA  
 \*304R THETA  
 SET GRDEAL  
 PRB  
 DSKY BLANKS

\*\*\*\*\* MINI-FOOTBALL \*\*\*\*\*

KEY V84E (TGT AV)  
 F 06 84 0AVX 0AVY +0005.0AVZ  
 PRB  
 F 06 33 93:05:45 TIG RCS SEPARATION

2.

1/31/69

TGT AV'S CONFIRMED BY CSM  
PRO (TGT AV IN CSM SV)  
KEY V80E  
KEY V76E (PGNS PULSE)  
B0RESIGHT ON CSM WITH CBA

(93:07) KEY V47E (AGS UPDATE)  
F 06 16 GET OF AGS O TIME  
\*414+1 UPDATE AGS  
PRA

\* 414R (00000 COMPLETE)

F 30 16 DBMNLINK COMPLETE PRO

(WAIT 32 SECONDS)  
\*400+3 AGS ALIGN

DSKY BLANKS

KEY V63E  
(PGNS MODE 2 ERR NEEDLES)

CB AC BUS A RNDZ RDR-CLOSE  
(WAIT 30 SECONDS)  
CB PGNS RNDZ RDR-CLOSE

K/R CHECKOUT  
B0RESIGHT 0N CSM WITH CBAS.  
TEST MONITOR RNDZ RDR=AGC  
SHFT/TRUN=+5  
R/R M8DE=LGC  
\*507+0

KEY V41N72E (R/R DESIGNATE)  
F 21 73 +00000TRUN +0000CSHET

1

ANS-50/4/CSM-104/LM-3

PREPARED BY EPPR/CE 24

B69 / 31 / 1

16 72 MONITOR SHIFT/TRUN ANGLES (+00000TRUN +00000SHFT) VERIFY DSKY WITH FDIA KEY REL	KEY V83E VERIFY R/R LOCKON GOOD READ R,RDGT,THETA PRO
-49	F 06 E4

F 04	06	KEY V62E PRB	00004 00001
F 16	72	+XXX•XX *XXX•XX PRB	
F 16	78	XXXXX•XR XXXXX•XR DOT VERIFY TAPE METER WITH DSKY	
		KEY V34E (TERMINATE)	
		(MANUALLY BREAK LOCK) R/R MODE=SLEW	
		SLEW RATE SW=LB (SLEW DOWN 30 DEG.) R/R MODE=LGC	
F 21	73	KEY V41N72E (R/R DESIGNATE) PRB	
F 04	06	+000.00TRUN -077.00SHFT 00006 00002	
41		(COARSE ALIGN VERB)	
		KEY V16N72E	
16	72	M8N16R SHFT/TRUN ANGLES (000.00TRUN +283.00SHFT) VERIFY DSKY WITH FDAI	

CB AC BUS A RNDZ RDR=OPEN

\*\*\*\*\* PHASING \*\*\*\*\*  
MANEUVER WITH RCS PULSES  
F 54 71 AND MARK 1ST STAR  
PRB

KEY V44E  
KEY V37E30E (EXT AV)  
F 06 33 93:50:04 TIG DPS PHASING  
PRB  
F 06 82 DAVX OAVY -0085.0AVZ  
PRB  
F 06 42 HA HP AV  
PRB  
F 16 45 0 TFI MGA  
-36 SET ET TO DPS PHASING  
PRB  
F 37 BB  
(93:18) KEY S2E (ALIGN)  
F 04 06 00001 00003 (REFSMMAT)  
PRB  
F 50 25 00015 SELECT STAR 1  
CB AT LAMP-CLOSED  
ENTR  
-34 F 01 70 002DE LOAD STAR 1  
PRB  
F 50 18 FDAI ANGLES (R60)  
M8DE C9NT-AUTB  
PRB (AUTB MAN)  
06 18  
F 50 19 FDAI ANGLES TRIM MANEUVER  
PRB (TRIM NOT REQD)  
F 01 71 002DE  
PRB

F 01 70 002DE LOAD 2ND STAR  
PRB  
F 50 18 FDAI ANGLES  
M8DE C9NT-AUTB  
PRB (AUTB MAN)  
06 18  
F 50 19 FDAI ANGLES TRIM MANEUVER  
PRB (TRIM NOT REQD)  
-27 F 01 71 002DE  
PRB  
M8DE C9NT-ATT HOLD  
MANEUVER WITH PGNS PULSES  
F 54 71 AND MARK 2ND STAR  
PRB (MARKS COMPLETE)  
F 06 05 ANGLE DIFFERENCE  
PRB  
F 06 93 GYR6 TORQUE ANGLES (XX.XXX)  
PRB  
\*\*\*\*\* BEYOND THIS POINT  
ACCOMPLISH COAS CALIBRATION  
IN TO THE EXTENT POSSIBLE  
BY TIG MINUS 14.  
\*\*\*\*\*  
F 50 25 CC014  
PRB (COAS CALIBRATION)  
F 50 25 00015 SELECT STAR 1  
ENTR

5.  
6.

AS-504/CSM-104/LM-3

PREPARED BY FPRB/CF24

1/31/69

PRB  
 F 50 18 FDAI ANGLES (R60)  
 MODE CNT-AUTB  
 PKB (AUTO MANEUVER)  
 06 18  
 F 50 19 FDAI ANGLES TRIM MANEUVER  
 PRB (TRIM NOT REQD)

\*18 F 01 71 005DE  
 OBSERVE STAR IN CBAS, WHEN  
 ATTITUDE ERRORS ARE ZERO  
 MARK AZ-EL ANGLE ON CBAS  
 DIAGRAM.  
 -7

PRB  
 F 06 87 AZ-EL CALIB ANGLES  
 PRB  
 KEY V34E (TERMINATE)

\*14 CB A9T LAMP=OPEN  
 KEY V37E00E

KEY V47E (AGS UPDATE)  
 F 06 16 GET 9F AGS 0 TIME  
 \*414+1 UPDATE AGS  
 PRB  
 \*414R (00000 COMPLETE)

F 50 16 DOWNLINK COMPLETE  
 PRB  
 (WAIT 32 SECONDS)  
 \*400+3 AGS ALIGN  
 \*411+0 DPS ENG SELECT  
 \*400+1 GUIDANCE STEERING

(93:36) CB AC BUS A RNDZ RDR-CLOSE  
 (WAIT 30 SECONDS)

F U4 J0 UUUUJ UUUUJ  
 PRB  
 F 06 18 FDAI ANGLES  
 PRB  
 F 50 18 FDAI ANGLES  
 PRB  
 F 06 18 FDAI ANGLES  
 PRB  
 F 50 19 FDAI ANGLES TRIM MANEUVER  
 PRB

CB PGNS LR-CLOSE  
 R/R MODE-SLEW  
 NB TRK LT-BN  
 KEY V76 (PGNS PULSE)  
 MODE CNT-ATT HOLD  
 BORESIGHT BN CSM WITH CBAS.  
 (PGNS PULSE MODE)  
 SLEW RADAR NEEDLES TB (0.0)  
 MAX SIGNAL STRENGTH.  
 R/R MODE-AUTO TRACK  
 NB TRK LT-BUT  
 RATE ERR M9N-LDG RDR/CMPTR

(93:46)  
 KEY V37E40E (DPS THRUSTING)  
 F 50 18 FDAI ANGLES  
 MODE CNT-ATT HOLD  
 ENTR (MANUAL MANEUVER)

F 50 19 FDAI ANGLES TRIM MANEUVER  
 -3  
 KEY V06N86E (AV'S LV)  
 L8AD AGS EXT AV  
 \*410+5 EXT AV  
 \*450+00001AVX 451+0AVY  
 \*452+00085AVZ LOAD  
 SOLUTION IN AGS.

8.

1/31/69

PREPARED BY FPRB/CF24

7.

AS-504/CSM-104/LM-3

1/31/69

COMPLETE.  
KEY RELEASE  
KEY V78E (LR SPUR TEST)

THR<sub>T</sub>/JETS(CDR)-THR<sub>T</sub>  
THR<sub>T</sub>(CDR)-SET MIN THRUST  
ENG GMBL-0FF  
THR CNT SW-MAN  
MAN THR<sub>T</sub>-CDR  
X-TRANSL-2JETS  
ENG ARM-DES  
ATT CNT-PULSE(3)  
MODE CNT-AUTO  
GUID CNT-AGS

KEY V77E (ATT HOLD)  
PRB (BYPASS TRIM)  
F 50 25 00203 (AUTO THR<sub>T</sub> REQUEST)  
ENTR (AUT<sub>G</sub> NOT DESIRED)  
06 40 TF1 VG AV<sub>M</sub>  
\*500R00085\* AVX

DEADBAND-MIN (CBNFIRM)  
(WHEN ERRORS ARE 0.)  
TRIM AGS ERRORS TO 0.  
ATT CNT-MODE CNT(3)

•:35 DSKY BLANKS

START ET COUNTING UP AT 0  
-:08 COMMAND +X TRANSLATION  
WITH TTCA.  
F 99 40 REQUEST ENG ON  
ENG GMBL-ENABLE

0(93:50:04) ABORT-DEPRESS (ENG 0N)  
ENTR (BYPASS PGNS ENG 0N)  
F 16 40 TFC VG AV<sub>M</sub>  
MONITOR THRUST INDICATOR

9.

AS-504/CSM-104/LM-3

PREPARED BY FPRB/CF24

(AFTER 15 SEC ENG 0N)

CAUTION: BE PREPARED TO DEPRESS ENG  
STOP IN EVENT LATE CUTOFF.\*

MODE CNT-ATT HLD  
ABORT-RESET  
ENG ARM-0FF  
PRB

F 16 85 AV'S-BODY  
NULL AV'S WITH RCS  
\*500R 502R (COPY)  
GUID CNT-PGNS  
KEY V76E  
RATE ERR M0N-RNDZ RADAR  
PRB

F 37 08 KEY V79E (TERMINATE SPUR)  
KEY 00E

CB PGNS LR-BOPEN

\*\*\*\*\* TP10 TP10 TP10 \*\*\*\*\*

\*\*\*\*\*  
IF PGNS FAILURE OCCURS  
BETWEEN 93:50 AND 94:45,  
SEE APPENDIX 1 FOR ABRT  
\*\*\*\*\*

R/R MODE- GC  
KEY V95E (NG UPDATE)  
KEY V37E20E (R>19,000FT)  
F 50 18 FDAI ANGLES  
ENTR (MANUAL MANEUVER)

10.

1/31/69

KEY V80E (UPDATE LM SV)  
F 05 09 00525 (POSSIBLE ALARM)  
PRB  
F 06 05 ATTHETA B B(AFTER ALARM)  
PRB (ACCEPT ANGLE DATA)

(93:58) KEY V37E34E (TPIC)

F 06 37 95:00:00 TIG OF TPI@  
PRB

F 06 55 B +027.50 +130.0C  
PRB

F 16 45 MKS TFI -00001  
PRB

(94:03) WHEN MARKS = 5, RECYCLE.  
+15(APPRBX) KEY V32E RECYCLE

F 06 37 TIG OF TPI

F 06 58 HP AVTPI AVTPF (COPY)  
PRB

+18 F 06 59 MARKS RESUME  
PRB

F 16 45 MKS TFI -00001  
PRB

\*410+3 TPI SEARCH

\*311-332.50 AT TRANS

\*313+050.00 AT TPI

\*410+4 (WHEN TFI = 50.00)  
\*303R THETA AT TPI(027.50)

\*267R AV TPI (COMPARE PGNS)

\*371R AV TOTAL  
PRB (FINAL C8 P CYCLE)

F 06 37 TIG OF TPI  
PRB

+26 TRANSMIT TIG OF TPI TO CSM  
FOR LOADING IN P34.

11.

AS-504/CSM-104/LM-3

PREPARED BY FPRB/CF24

F 06 81 AV'S-LV (COPY)  
PRB  
F 06 59 AV'S-LDS (COPY)  
PRB  
F 16 45 MKS TFI MGA

SET ET COUNTING DOWN

F 06 37 95:00:00 TIG OF TPI@  
PRB

F 37 88

SET W-MATRIX T0 1 MR.

KEY V24NQ1E

KEY 2002E

KEY 1014E

KEY 1014E

KEY V04NC1E

KEY 2002E

VERIFY R1, R2=01014

KEY V37E00E (P00)

KEY V62E

F 04 06 00004 00001

PRB

F 16 72 +XXX.XX +XXX.XX

PRB

F 16 78 XXXXX.XR XXXXX.XRD6T

VERIFY TAPE METER WITH DSKY

KEY V37E00E

DSKY BLANKS

(94:16) PERFORM LR SELF TEST

CB PGNS LR-CLOSE

RNG/ALT M8N=ALT/ALT RT

12.

1/31/69

NAVAN TEST SW-DES  
 LDG ANT SW-DES  
 X-POINTERS (READ)  
 • VZA = +200FPS (PEGGED UP)  
 • VYA = +200FPS (PEGGED RT)  
 ALT/ALT RATE METER (READ)  
 • ALT = 8263FT (NOM)  
 LDG ANT SW-HAVER  
 ALT/ALT RATE METER (READ)  
 • ALT = 87981FT  
 • ALT RT = 449FPS  
 SET RADAR TEST MONITOR TO:  
 • ALT XMTR = 3.5V  
 • VEL XMTR = 3.78V

F 04 06 KEY V62E  
 PRB  
 F 16 66 08280FT ANT POS(00001)  
 F 16 67 VXA=00247, VYA=+00929,  
 VZA=+00665FPS  
 KEY V37E00E  
 LDG ANT SW-AUTO  
 KEY V61E  
 (WAIT 24 SECONDS)  
 KEY V62E  
 PRB  
 F 16 66 08280FT ANT POS(00002)  
 KEY V37E00E  
 LDG ANT SW-DES  
 (WAIT 10 SECONDS)  
 LDG ANT SW-AUTO  
 RADAR TEST SW-OFF  
 (94:25)

KEY V37E20E  
 F 50 18 FDAO ANGLES  
 ENTR (MANUAL MANEUVER)  
 F 50 19 FDAO ANGLES TRIM MANEUVER  
 PRB (TRIM NOT REQUIRED)  
 DSKY BLANKS  
 VERIFY R/R LOCKON GOOD  
 (94:28) KEY V37E34E (TPIO FINAL)  
 F 06 37 95:00:00 TIG OF TPI  
 PRB  
 F 06 55 B+027.50 E +130.00  
 PRB  
 F 16 45 MKS TFI -00001  
 KEY V76E (PGNS PULSE)  
 MODE CONT-ATT HOLD  
 RECEIVE GO FROM GROUND  
 WHEN MARKS = 4, RECYCLE.  
 KEY V93E (REINIT W MATRIX)  
 KEY V32E RECYCLE  
 F 06 37 TIG OF TPI (COPY)  
 PRB  
 F 06 58 HP AVTPI AVTPF (COPY)  
 PRB  
 F 06 59 AVIS-L0S (COPY)  
 PRB  
 F 16 45 MKS TFI -00001  
 \*26 SET ET COUNTING DOWN  
 WHEN MARKS = 6, RECYCLE.  
 -20(APPROX) KEY V32E RECYCLE  
 F 06 37 TIG OF TPI (COPY)  
 PRB  
 F 06 58 HP AVTPI AVTPF (COPY)  
 PRB  
 F 06 59 AVIS-L0S (COPY)

13.

AS-504/CSM-104/LH-3

PREPARED BY FPRB/CF24

1/31/69

\*410+3 TPI SEARCH ROUTINE  
 \*311+032.50 AT TRANS  
 \*313+C16.00 TFI TPI  
 \*410+4 (WHEN ET=-16)  
 \*303R THETA AT TPI  
 \*267R AV TPI (COMPARE PGNS)  
 \*371R AV TOTAL  
 COPY GND TPI SOLUTION

-14 PRB (FINAL COMP CYCLE)  
 F 06 37 TIG TPI  
 TRANSMIT TIG OF TPI TO CSM  
 FOR LOADING IN P34.  
 PRB  
 F 06 58 HP AVTPI AVTPF  
 PRB  
 F 06 81 AV'S-LV

PRB  
 F 06 59 AV'S-LOS  
 PRB  
 F 16 45 MKS TFI MGA

-10 RESET ET (IF REQD)  
 PRB  
 F 37 BB

(94:51) KEY 00E (POO)  
 ON BOARD GO,NO GO

F 06 16 KEY V47E (AGS UPDATE)  
 GET OF AGS O TIME  
 \*A14+1 UPDATE AGS  
 PRB

-9 KEY V41N72E (R/R DESIGNATE)  
 F 21 73 +000.00TRUN -077.00SHFT  
 F 04 06 00006 00002 CONTINUOUS  
 PRB  
 41 (COARSE ALIGN VERBI  
 KEY V16N72E  
 16 72 MONITOR SHFT/TRUN ANGLES  
 (000.00TRUN +283.00SHFT)

CB PGNS RNDZ RDR=OPEN  
 CB AC BUS A RNDZ RDR=OPEN

(94:52) KEY V37E52E (ALIGN)  
 F 04 06 00001 00003 (REFSMMAT)  
 PRB  
 F 50 25 00015 SELECT STAR 1  
 CB AOT LAMP=CLOSED  
 ENTR

-7 F 01 70 002DE LOAD STAR 1  
 PRB  
 F 50 18 FDAI ANGLES  
 MODE CONT=AUTO

15.

16.

AS-504/CSM-104/LM-3 PREPARED BY FPRB/CF24

1/31/69

\*400+3 AUG ALIUN

\*\*\*\*\*  
 IF ABORTING FOR A RADAR OR  
 A NON G+N FAILURE,  
 SEE APPENDIX 2 FOR ABORT  
 \*\*\*\*\*

06 18 PRB (AUTO MANEUVER)  
F 50 19 FDAI ANGLES TRIM MANEUVER  
PRB (TRIM NOT RECD)

F 01 71 002DE  
PRB  
MODE CONT-ATT HOLD  
MANEUVER WITH RCS PULSES  
F 54 71 AND MARK 1ST STAR  
PRB

-2 F 01 70 002DE LOAD 2ND STAR  
PRB  
F 50 18 FDAI ANGLES  
MODE CNT-AUTO  
PRB (AUTO MANEUVER)  
06 18 F 50 19 FDAI ANGLES TRIM MANEUVER  
PRB (TRIM NOT RECD)

F 01 71 002DE  
PRB  
MODE CONT-ATT HOLD  
MANEUVER WITH PGNS PULSES  
F 54 71 AND MARK 2ND STAR  
PRB  
F 06 05 ANGLE DIFFERENCE  
PRB  
F 06 93 GYR8 TORQUE ANGLES  
PRB

-57 F 50 25 00014  
\*\*\*\*\*  
IF TIME PERMITS CHECK  
ALIGNMENT WITH THIRD STAR  
\*\*\*\*\*

06 18 ENTR (NO CHECK)  
CB A&T LAMP OPEN  
F 37 BB

(94:56) F 01 71 002DE  
PRB  
KEY V47E (AGS UPDATE)  
F 06 16 GET OFF AGS O TIME  
\*414+1 UPDATE AGS  
PRB  
\*414R (00000 COMPLETE)  
F 50 16 D8WNLINK (COMPLETE)  
PRB  
(WAIT 32 SECONDS)  
\*400+3 AGS ALIGN  
\*\*\*\*\*  
INSERTION \*\*\*\*\*

CB AC BUS A RNDZ RDR=CLOSE  
(WAIT 30 SECONDS)  
CB PGNS RNDZ RDR=CLOSE

(95:09) F 50 18 FDAI ANGLES  
MODE CNT-AUTO  
PRB (AUTO MANEUVER)  
06 18 F 50 19 FDAI ANGLES TRIM MANEUVER  
PRB (TRIM NOT REQUIRED)  
MODE CNT-ATT HOLD  
DSKY BLANKS  
VERIFY R/R LOCKON GOOD  
KEY V80E (UPDATE LM SV)  
(95:20) MONITOR RANGE ON TAPE METER  
WHEN RANGE < 19,000FT  
KEY V95E INHIBIT SV UPDATE

17.

18.

AS-504/CSM-104/LM-3

PREPARED BY FPRB/CF24

1/31/69

F 06 33 KEY V37E30E (EXT AV)  
PR0  
F 06 82 +0039.9AVX 0AVY CAVZ  
PR0  
F 06 42 HA HP AV  
PR0  
F 16 45 MKS TFI MGA

-18 RESET ET COUNTING DOWN  
WHEN MARKS = 6, PROCEED.  
PR0  
F 37 88

-8 KEY 00E (POO)  
KEY V47E (AGS UPDATE)  
F 06 16 GET OF AGS O TIME  
\*+14+1 UPDATE AGS  
PR0  
\*+14R (100000 COMPLETE)  
F 50 16 DOWNLINK COMPLETE  
PR0  
(WAIT 32 SECONDS)  
\*400+3 AGS ALIGN  
\*411R 00000 (CONFIRM)  
\*400+1 GUIDANCE STEERING

-7 CB PGNS LR-CLOSE

(95:35) KEY V77E (ATT HOLD)  
KEY V37E40E  
MODE CNT-AUTO

19.

AS-504/CSM-104/LM-3

PREPARED BY FPRB/CF24

KEY VUONDAOT (AV'S LV)  
LOAD AGS EXT AV  
\*+10+5 EXT AV  
\*450+00040AVX 451+04VY  
\*452+0AVZ  
SOLUTION IN AGS.  
KEY RELEASE  
KEY V78E (LR SPUR TEST)

THRBT/JETS(CDR)-THRBT  
THRBT(CDR)-SET MIN THRUST  
THR CNT S<sub>W</sub>-MAN  
MAN THRBT-CDR  
X-TRANSL-2JETS  
ENG ARM-DES

\*4 F 50 19 FDAI ANGLES TRIM MANEUVER  
PRB (TRIM NOT REQD)  
\*407+0 WHEN MANEUVER IS  
COMPLETE.  
F 50 25 00203 (AUT0 THRBT REQUEST)  
ENTR (AUT0 NOT DESIRED)  
-3 06 40 TFI VG AVM  
\*COMPARE AGS ATT ERRORS  
\*500R+000040. AVX  
\*:35 DSKY BLANKS  
\*:8 MNIT0R ULLAGE  
F 99 40 REQUEST ENG ON  
ENG GMBL-ENABLE  
0(95:41:48) PR0 FOR ENG ON ENABLE  
06 40 TFC VG AVM  
MNIT0R THRUST INDICATOR

CAUTION: BE PREPARED TO DEPRESS ENG  
STOP IN EVENT LATE CUTOFF.

20.

1/31/69

F 16 40 TFC VG AVH  
ENG ARM-OFF  
PRB  
F 16 85 AVIS-BODY  
NULL AVIS WITH RCS  
THRBT/JETS(CDR)-JETS  
KEY V79E (TERMINATE SPUR)  
PRB

F 37 BB

\*\*\*\*\* CSI CSI CSI \*\*\*\*\*  
CB PGNS LR=OPEN

\*\*\*\*\*  
IF PGNS FAILURE OCCURS  
BEYOND THIS POINT,  
SEE APPENDIX 3 FOR ABORT

IF A RADAR FAILURE OCCURS,  
LM TARGETS CSI AND CDH  
WITH P30 AND EXECUTES  
BURNS AS PER NORMAL PRB-  
CEDURES, CSM IS ACTIVE  
FOR TPI AND TPF.  
\*\*\*\*\*

KEY V95E (NO UPDATE)  
KEY V37E20E  
F 50 18 FDAO ANGLES  
MODE C0NT-AUT0  
PRB (AUT0 MANEUVER)

F 50 19 FDAO ANGLES TRIM MANEUVER

DSKY BLANKS  
VERIFY R/R LOCKON GOOD  
KEY V80E (UPDATE LM SV)

(95:51) F 06 30 KEY V37E32E  
PRB

FIRST APSIDAL XING.  
F 06 55 +00001 N +027.50 E  
PRB

F 06 37 98:02:21 TIG OF TPI  
(WITH 3 MIN TIME BIAS)  
PRB

F 16 45 MKS TFI -00001

\*34 SET ET COUNTING DOWN

KEY V76E (PGNS PULSE)  
M0DE C0NT-ATT HLD  
COPY RD8T FROM TAPE METER  
FOR BU'S

WHEN MARKS = 4, RECYCLE  
KEY V93E (REINIT w MATRIX)

KEY V32E (RECYCLE)  
F 06 50 4H AT-CSI/CDH AT-CDH/TPI  
PRB

F 06 81 AVIS-LV(CSI) (C8FY)  
PRB

F 06 82 AVIS-LV(CDH) (C8PY)  
PRB

F 16 45 MKS TFI -00001  
NOTE: MANUAL ITERATION FOR FINDING  
THE PROPER APSIDAL XING MAY BE REQD  
WHEN MARKS = 4, RECYCLE.

21.

AS-504/CSM-104/LM-3

PREPARED BY FPRB/CF24

22.

1/31/69

PRB  
 F 06 82 AVIS-LV(CDH) (COMPARE)  
 PRB  
 F 16 45 MKS TFI -00001  
 WHEN RANGE IS > 50.8 NM.  
 KEY V37E00E (P00)  
 KEY V62E  
 F 04 06 00004 00001  
 PRB  
 F 16 72 +XXX.XX +XXX.XX  
 PRB  
 F 16 78 XXXXX.XR XXXXX.XR06T  
 VERIFY TAPE METER WITH DSKY  
 KEY V37E00E  
 KEY V37E20E  
 F 50 18 FDAI ANGLES  
 MODE CNT-AUTO  
 PRB (AUTO MANEUVER)  
 06 18  
 F 50 19 FDAI ANGLES TRIM MANEUVER  
 PRB (TRIM NOT REQUIRED)  
 DSKY BLANKS  
 VERIFY R/R LOCKIN GOOD  
 KEY V37E32E  
 F 06 30 96:22:00 TIG 8F CSI  
 PRB  
 FIRST APSIDAL XING.  
 F 06 55 +00001 N +027.50 E  
 PRB  
 F 06 37 98:02:21 TIG 8F TPI  
 (WITH 3 MIN TIME BIAS)  
 PRB  
 F 16 45 MKS TFI -00001

(96:04) \*277+479.3 AGS TPI TIME  
 \*605+10250 TPI ANGLE CODE  
 \*\*416+0 1ST APSIDAL  
 \*\*417+1  
 \*\*410+1 CSI ROUTINE  
 \*\*457R CHECK < 2FPS  
 \*\*463R ALT RATE (COPY)  
 \*\*313R TFI CSI  
 COMPARE 313 WITH E.T.  
 \*456R AVCSI COPY  
 \*371R AVCDH COPY  
 \*276R ABS TIME CDH(0426.5)  
 \*\*411+0 RCS ENGINE  
 \*450R AVX 452R AVZ  
 KEY V48E (DAP LOAD)  
 F 01 46 DAP CONFIGURATION (020002)  
 PRB  
 F 06 47 LM WT CSM WT  
 KEY V34E (TERMINATE)  
 F 16 45 MKS TFI -00001  
 -14 PRB (FINAL COMP CYCLE)  
 F 06 50 AH AT=CSI/CDH AT=CDH/TPI  
 PRB  
 F 06 81 AVIS-LV(CSI) (COPY)  
 -12 KEY V90E  
 F 06 16 LOAD CSI TIME  
 PRB  
 F 06 90 Y,YDBT,PSI  
 (COPY YDBT AT CSI)  
 PRB

23.

AS-504/CSM-104/LM-3

PREPARED BY FPRB/CF24

1/31/69

24.

2 FPS, LOAD •YDGT IN R2.  
•10+ COPY RANGE AND RDGT FROM  
TAPEMETER FOR BU'S

\*450, 451, 452\*LOAD THE  
COMPONENTS OF SOLUTION  
TO BE EXECUTED.  
KEY RELEASE

F 06 82 AVIS-LV(CDH) (CBPY)  
PRB

F 16 45 MKS TFI MGA  
PRB

F 37 BB KEY OOE (POO)

PERFORM PRESTAGE CHECKS.  
COMPARE AGS AND PGNS  
CBOARD SOLUTION WITH GND  
TRANSIT TGT AV'S TO CSM  
AND SYNC COUNTDOWN.

(96:15) KEY V47E (AGS UPDATE)  
F 06 16 GET OF AGS 0.  
\*414+1 UPDATE AGS SV

PRB  
\*414R (10000 COMPLETE)  
PRB  
(WAIT 32 SECONDS)

\*400+3 AGS ALIGN  
\*400+1 GUIDANCE STEERING

KEY V77E (ATT HOLD)

KEY V37E41E  
F 50 18 FDI ANGLES  
MODE CONT-AUTO  
PRB (AUTO MANEUVER)

06 18

KEY V06N86E (AV'S LV)  
LOAD AGS EXT AV

25.

AS=504/CSM=104/LM=3

\*3 F 50 19 BYPASS TRIM  
PRB (TRIM NOT RECD)

\*407+0 WHEN MANEUVER IS  
COMPLETE.  
ED: MASTER ARM=ON  
THRBT/JET(CDR)=JET  
X=TRANSL=4JETS

\*2  
16 85 AV'S-BODY  
\*COMPARE AGS ATT ERRORS  
\*500R AVX (COMPARE)

\*35 DSKY BLANKS

F 16 85

\*0 STAGE SW-FIRE  
ED: MASTER ARM SW=OFF  
NOMINAL (37°8AVX)  
(96:22:00) BURN +X WITH TTCA

ASC FEED 2-BOPEN (SYS A-B)  
CHECK ASC FUEL AND BXID  
FLAGS OPEN. (SYS A-B)  
MAIN SV (SYS A AND B)-CLOSE  
MAIN SV (SYS A AND B)-OPEN  
(BEFORE THRUST TERMINATION)  
ASC FEED 2-CLOSE (SYS A-B)  
(BEFORE THRUST TERMINATION)  
NULL REMAINING AV'S  
\*500R AVX 501RAVY 502RAVZ  
PRB

F 37 BB

26.

PREPARED BY FPRB/CF24

1/31/69

(96:26) KEY V37E20E  
 F 50 18 FD1 ANGLES  
 MODE CNT-AUTO  
 PR0 (AUTO MANEUVER)

06 18 KEY V76E (PGNS PULSE)  
 MODE CNT-ATT HOLD

F 50 19 FD1 ANGLES TRIM MANEUVER  
 PR0 (TRIM NOT REQUIRED)  
 DSKY BLANKS  
 VERIFY R/R LOCKON GOOD  
 KEY V80E (UPDATE LM SV)

(96:29)

\*54 F 06 31 KEY V37E33E (CDH)  
 TIG 9F CDH (97:06:28)  
 KEY V25E  
 (ADD 1 MIN 45 SEC BIAS)  
 PR0 MKS TFI -00001

F 16 45 MKS TFI -00001

-37 SET ET T0 TFI CDH  
 WHEN MARKS = 4, RECYCLE  
 KEY V93E (REINIT W MATRIX)  
 V32E RECYCLE

-35(APPROX) F 06 50 AHCDH ATCDH/TPI ATTPI/TPI  
 PR0  
 F 06 81 AVCDH-LV (COPY)  
 PR0  
 F 16 45 MKS TFI -00001

(96:30)

-35(APPROX) F 06 50 AHCDH ATCDH/TPI ATTPI/TPI  
 PR0  
 F 06 81 AVCDH-LV (COPY)  
 PR0  
 F 16 45 MKS TFI -00001

\*410+2 CDH ROUTINE  
 \*276+ABS TIG CDH (426.5)  
 (PG'S COMPUTED TIG CDH)  
 \*267R AV CDH (COPY)

FOR BU'S  
 \*18\* COPY RD0T FROM TAPE METER  
 FOR BU'S

\*14 F 06 50 PR0 (FINAL COMP CYCLE)  
 AHCDH ATCDH ATTPI/TPI  
 PR0  
 F 06 81 AV-S-LV (COPY)

-12 F 06 16 KEY V90E  
 LOAD CDH TIME  
 PR0  
 F 06 90 Y-YD0T,PSI  
 (COPY Y AND YD0T AT CDH)  
 PR0  
 F 16 45 MKS TFI -00001

!IF YD0T FROM V90 WAS > THAN  
 2 FPS, LOAD \*YD0T IN R2.

PR0  
 F 16 45 MKS TFI MGA  
 PR0  
 F 37 BB KEY OOE (POO)

C0BRO SOLUTION WITH GND  
 TRANSMIT TGT AV'S TO CSM  
 AND SYNC COUNTDOWN.

(96:57) KEY V47E (AGS UPDATE)  
 F 06 16 GET OF AGS 0  
 \*414+1 UPDATE AGS  
 PR0  
 \*414R (00000 COMPLETE)

27.

28.

AS-504/CSM-104/LM-3

PREPARED BY FPRB/CF24

1/31/69

F 50 16 DOWNLINK COMPLETE

PRB

(WAIT 32 SECONDS)

\*400+3 AGS ALIGN

\*400+1 GUIDANCE STEERING

\*411+1 APS THRUST

NOMINAL (37.9AVX)

PRB (FOR ENG ON)

06 40 TFC VG AVM

F 16 40 TFC VG AVM

ENG ARM=0FF

NULL REMAINING AV'S

\*500RAVX 501RAVY 502RAVZ

PRB

F 16 85 PRB

F 37 BB

KEY V83E (R, RDST, THETA)

SET 9RDEAL

PRB

COPY RDST FROM TAPE METER  
FOR BUS

(97:01) KEY V77E (ATT HLD)  
KEY V37E42E (APS THRUSTING)

F 50 18 FDAT ANGLES

MODE CNT=AUTS

PRB (AUTO MANEUVER)

06 18

KEY V06N86E (AV'S LV)  
LOAD AGS EXT AV  
\*410+5 EXT AV  
\*45C, \*451, \*452-Load THE  
COMPONENTS OF SOLUTION  
TO BE EXECUTED.

KEY RELEASE

-3 F 50 19 FDAT ANGLES TRIM MANEUVER  
PRB (TRIM NOT REQD)  
\*407+0 WHEN MANEUVER IS  
COMPLETE.  
\*COMPARE AGS ATT ERRORS  
\*500R AVX (COMPARE)  
06 40 TFI VG AVM

DSKY BLANKS

ENG ARM=ASC  
005 F 99 40 REQUEST ENG ON

29.

AS-504/CSM-104/LM-3

PREPARED BY FPRB/CF24

1/31/69

\*\*\*\*\*  
IF A RADAR FAILURE HAS  
OCCURRED, MAINTAIN Z-AXIS  
POINTING AT CSM WITH  
PULSE MODE, COMPUTE A  
NORMAL TO LOS SOLUTION AT  
TPI AND MIDCOURSES WITH  
BACK-UP CHARTS.  
\*\*\*\*\*

KEY V95E (IN0 UPDATE)  
KEY V37E20E  
KEY V37E20E  
F 50 18 FDAT ANGLES  
MODE CNT=AUTB  
PRB (AUTB MANEUVER)  
06 18 FDAT ANGLES TRIM MANEUVER  
PRB (TRIM NOT REQUIRED)  
DSKY BLANKS  
VERIFY R/R LOCKON GOOD  
KEY V80E (UPDATE LM SV)

30.

F 06 55 8 +027.50 E +130.00  
PRB  
F 16 45 MKS TPI -000001

KEY V76E (PGNS PULSE)  
MODE CANT-ATT HOLD

(97:18) WHEN MARKS = 4, RECYCLE.

KEY V93E (REINIT W MATRIX)  
KEY V32E RECYCLE  
F 06 37 TIG 9F TPI (C8PY)  
PRB

F 06 58 HP AVTPI AVTPF (C8PY)

F 06 59 AVIS-L9S (C8PY)

F 16 45 MKS TPI -000001  
PRB

-38 SET ET COUNTING DOWN

\*415+1 316+R  
\*415+1 316+R

(97:18) WHEN MARKS = 6, RECYCLE.

KEY V32E RECYCLE  
F 06 37 TIG 6F TPI (C8PY)  
PRB

F 06 58 HP AVTPI AVTPF (C8PY)

F 06 59 AVIS-L9S (C8PY)

F 16 45 MKS TPI -000001  
PRB

\*404+0 405+0 406+0  
\*411+1 RCS THRUST  
\*415+1 316+R

-32

31.

AS-504/CSM-104/LM-3

PREPARED BY FPRB/CF24

1/31/69

\*415+1 316+R  
\*267R AV TPI (COMPARE PGNS)  
\*371R AV TOTAL

COPY GND TPI SOLUTION

WHEN MARKS = 12, RECYCLE.

\*27(APPRBX) KEY V32E (RECYCLE)  
F 06 37 TIG 6F TPI (C8PY)  
PRB

F 06 58 HP AVTPI AVTPF (C8PY)

F 06 59 AVIS-L9S (C8PY)

F 16 45 MKS TPI -000001  
PRB

\*26 \*415+1 316+R  
\*23 \*415+1 316+R  
\*20 \*415+1 316+R  
\*17 \*415+1 316+R

\*313+016.C0 TFI TPI  
\*410+4 (WHEN ET = 16)

\*303R THETA AT TPI (C8PY)  
\*267R AV TPI (COMPARE PGNS)  
\*371R AV TOTAL (C8PY)

PRB (FINAL COMP CYCLE)

-11 F 06 37 TIG TPI  
TRANSMIT TIG OF TPI TO CSM  
FOR LOADING IN P34.

F 06 58 HP AVTPI AVTPF (C8PY)

F 06 81 AVIS-L9S (C8PY)  
PRB

32.

-3 KEY V06N86E (AV'S LV)  
 LOAD AGS EXT AV  
 \*410+5 EXT AV  
 \*450, 451, 452=LOAD  
 COMPONENTS OF SOLUTION  
 TO BE EXECUTED.  
 KEY RELEASE

-2 F 50 19 FDAI ANGLES TRIM MANEUVER  
 PRB (TRIM NOT REQD)  
 \*407+0 WHEN MANEUVER IS  
 COMPLETE.  
 16 85 AV'S BODY  
 \*500R AVX (COMPARE)  
 \*;35 DSKY BLANKS

F 50 16 GET AGS 0 TIME  
 \*414+1 UPDATE AGS  
 PRB  
 \*414R (00000 COMPLETE)  
 PRB  
 (WAIT 32 SECONDS)  
 \*400+3 AGS ALIGN

-0:00 SET ET COUNTING UP  
 NULL REMAINING AV'S  
 \*500RAVX 501RAVY 502RAVZ  
 PRB

F 37 BB KEY OOE (P00)  
 KEY V93E  
 (REINITIALIZE W MATRIX)

\*\*\*\*\* 1ST MC CORRECTION \*\*\*\*\*

KEY V37E20E  
 F 50 18 FDAI ANGLES  
 ENTR (MANUAL MANEUVER)  
 F 50 19 FDAI ANGLES TRIM MANEUVER  
 PRB (TRIM NOT REQUIRED)

33.

AS=504/CSM=104/LH=3

PREPARED BY FPRB/CF24

1/31/69

\*9 RESET ET (IF REQD)

PRB

KEY OOE (P00)

(97:50) KEY V47E (AGS UPDATE)  
 F 06 16 GET 9F AGS 0 TIME  
 \*414+1 UPDATE AGS  
 PRB

F 50 16 DWNLINK COMPLETE  
 PRB  
 \*304R TGT LOS ANGLE  
 \*400+3 AGS ALIGN

-8\* \*304R COPY TGT LOS ANGLE  
 COPY CSM SOLUTION FOR TPI  
 COMPARE ONBOARD SOLUTIONS  
 TRANSMIT TO CSM AND GND  
 SOLUTION TO BE BURNED  
 SYNC COUNTDOWN WITH CSM  
 \*304R COPY TGT LOS ANGLE  
 COPY R,RD8T FROM TAPE METER  
 FOR BU'S.

(97:55) CALCULATE BU SOLUTION

KEY V77E  
 KEY 41E  
 F 50 18 FDAI ANGLES  
 MODE CONT-ATT HOLD  
 ENTR (MANUAL MANEUVER)

AS=504/CSM=104/LH=3

PREPARED BY FPRB/CF24

1/31/69

(98:04) KEY V37E35E  
F 16 45 MKS TFI =000001

\*5\* \*304R COPY TGT LOS ANGLE  
\*404+0 405+0 406+C  
PRB (C0MP MC F0R TPI +10)

+7 F 06 81 AV'S-LV (C0PY)  
PRB  
F 06 59 AV'S-LOS

\*8\* \*304R COPY THETA,R,RDST

(98:09) COMPUTE BU MC CORRECTION

PRB  
F 16 45 MKS TFI MGA  
PRB  
F 37 BB

IF 1ST MC SMALL, SKIP  
P41 AND RECALL P35.

+9 KEY 41E  
F 5C 18 FDAI ANGLES  
ENTR (MANUAL MANEUVER)  
F 50 19 BYPASS TRIM  
PRB (TRIM NOT REQD)  
16 85 AV'S-BODY  
COMPARE PGNS AND BU'S  
KEY V77E

+9:25 DSKY BLANKS  
+10 F 16 85 NULL AV'S WITH RCS  
KEY V76E  
PRB

35.

AS=504/CSM=104/LM=3

PREPARED BY FPRB/CF24

+11 F 16 45 MKS TFI =000001  
WHEN MARKS = 1, KEY V93E.  
(REINITIALIZE W MATRIX)

+17\* \*304R COPY TGT LOS ANGLE  
\*404+0 405+0 406+0  
PRB (C0MP MC F0R TPI +22)  
PRB

F 06 81 AV'S-LV (C0PY)  
PRB  
F 06 59 AV'S-LOS  
PRB  
F 16 45 MKS TFI MGA  
PRB  
F 37 BB

+20\* \*304R COPY THETA,R,RDST

(98:20) COMPUTE BU MC CORRECTION

KEY 41E  
F 50 18 FDAI ANGLES  
ENTR (MANUAL MANEUVER)  
F 50 19 BYPASS TRIM  
PRB (TRIM NOT REQD)  
16 85 AV'S-BODY  
COMPARE PGNS AND BU'S  
KEY V77E  
+21:25 DSKY BLANKS

+22 F 16 85 NULL AV'S WITH RCS  
KEY V76E

36.

1/31/69

PR6

F 37 BB KEY 00E (P00)

KEY V37E47E (AVERAGE G)  
BLANK FOR 1 MIN  
F 16 83 AVIS

F 04 06 KEY V62E  
00004 00001  
PR6

F 16 72 +XXX.XX +XXX.XX  
PR6

F 16 78 XXXXX.XR XXXXX.XRD9T  
VERIFY TAPE METER WITH DSKY

(98:30) KEY V77E (AT H0:D)  
BRAKING: 30FPS = 6000FT  
20FPS = 3000FT  
10FPS = 1500FT  
5FPS = 500FT

RENDÉZVÉBUS

DCK

37.

AS-504/CSM-104/LM-3

PREPARED BY FPRB/CF24

38.

1/31/69

4.0      Abort Procedures

Three specific abort procedures are defined in this document in addition to the abort provisions inherent in the Nominal Mission Procedures. Reference is made to these in the Nominal Mission Procedures as Appendices 1, 2, and 3. Appendix 1 contains the PGNS failure abort procedures for TPI<sub>o</sub> through TPF. Appendix 2 defines the complete Guidance and Navigation (G&N) procedures for executing TPI<sub>o</sub> through TPF when aborting for failures other than G&N. Appendix 3 contains procedures for completing the remainder of the mission following a PGNS malfunction after the insertion maneuver.

PHASING.

\*30 \*415+1 316+R  
\*27 \*415+1 316+R  
\*24 \*415+1 316+R  
\*23 \*303R (MONITOR LOS ANGLE)  
\*21 \*415+1 316+R  
\*18 \*415+1 316+R  
\*-15 \*415+1 316+R 503•RD0T  
\*303R (+027•50)

(IF TPI ANGLE HAS CHANGED)  
(RETARGET AGS)  
\*410+3 TPI SEARCH  
\*313+013•CO TFI TPI  
\*303R LOS IN 13 MIN  
\*410+4 (WHEN 303R=+027•50)  
\*267R AV TPI (+00022•)  
\*371RAV TOTAL (+00050•)  
COPY AGS SOLUTION THEN,  
LOAD GROUND SOLUTION IN  
EXTERNAL DELTA V

-13  
\*8\*  
-5\*

ATT CNT-PULSE(3)  
\*400+2 RADAR ACQUISITION  
M0DE CNT-AUTO  
PULSE TO NULL AGS ERRORS  
POINT Z-AXIS IN DIRECTION  
SF CSM.  
M0DE CANT-ATT HLD  
ATT C9NT-M0DE C9NT(3)  
SLOW R/R ANT TG C.O SN FDAL  
VERIFY MAX SIGNAL STRENGTH  
R/R M0DE=AUT9 TRACK  
NA TRK LT-BFF  
COMPARE R/R ERR NEEDLES  
WITH CBAS, IF CSM VISIBLE.  
ATT C9NT-PULSE(3)

\*\*\*\*\* TPIIC TPIIC TPI0 \*\*\*\*\*

\*410+3 TPI SEARCH ROUTINE  
\*311+032•50 AT TRANS  
\*313+040•00 TFI TPI  
\*303R LOS ANGLE IN 40 MIN  
\*410+4 (WHEN 303R=+027•50)  
\*313R TFI TPI

-3  
\*3 SET ET COUNTING DOWN  
-39 \*415+1 316+R  
-36 \*415+1 316+R

\*\*\*\*\*

\*3

COPY R AND RD0T FROM TAPE  
METER FOR BU'S

CALCULATE BU SOLUTION  
\*404+0 405+0 406+0  
(IF BU'S BURNED, MONITOR AV  
APPLIED WITH 470 471 472)

M0DE C9NT-AUTO  
\*400+2 Z-AXIS GUIDANCE  
\*507+ STEERING  
PULSE TO NULL AGS ERRORS  
ATT C9NT-M0DE C9NT(3)

40.

AS=504/CSM=104/LM=3

PREPARED BY FPRB/CF24

1/31/69

SET ET COUNTING UP AT 0

\*\*\*\*\* 1ST MC CORRECTION \*\*\*\*\*

MODE CONT-ATT HOLD (WHEN  
\*502 IS LESS THAN +15)  
NULL REMAINING AV'S  
\*500RAVX 501RAVY 502RAVZ  
ATT CNT-PULSE(3)

\*304R COPY TGT LOS ANGLE

\*304R COPY THETA,R,RDOT

CALCULATE BU MC CORRECTION

\*404+C 405+0 4C6+C  
(IF BU'S BURNED, MONITOR AV  
APPLIED WITH 47C 471 472)  
\*400+0 ATT HOLD

\*\*\*\*\* 2ND MC CORRECTION \*\*\*\*\*

+10 ATT CNT-MODE CNT(3)  
NULL AV'S WITH RCS  
\*500RAVX 501RAVY 502RAVZ  
ATT CNT(3)-PULSE

\*304R COPY TGT LOS ANGLE

\*304R COPY THETA,R,RDOT

41.

AS=504/CSM=104/LM=3

PREPARED BY FPRB/CF24

+22

ATT CNT-MODE CNT(3)  
NULL AV'S WITH RCS  
ATT CNT-PULSE(3)

\*404+0 405+0 406+0  
MONITOR BRAKING AV VIA 470,  
471, AND 472.

BRAKING:

30FPS=6000FT  
20FPS=3000FT  
10FPS=1500FT  
5FPS= 500FT

RENDIEZVOUS

DOCK

42.

1/31/69

APPENDIX C FOR ALBKI

PERFORM PRESTAGE CHECKS

\*\*\*\*\* TPIO TPIO TPIO \*\*\*\*\*

\*\*\*\*\*  
IF A RADAR FAILURE OCCURS  
BEYOND THIS POINT,  
MAINTAIN Z-AXIS POINTING  
AT CSM WITH PULSE MODE,  
COMPUTE A NORMAL TO LOS  
SOLUTION AT TPI AND  
MIDCOURSES WITH BACK-JP  
CHARTS.  
\*\*\*\*\*

\*304R COPY TGT LOS ANGLE

COPY CSM SOLUTION FOR TPI  
COMPARE ONBOARD SOLUTIONS  
TRANSMIT TO CSM AND GND  
SOLUTION TO BE BURNED.  
SYNC COUNTDOWN WITH CSM

\*304R COPY TGT LOS ANGLE

COPY R AND RDGT FROM TAPE  
METER FOR BU'S

CALCULATE BU SOLUTION

KEY V37E41E (RCS THRUSTING)  
KEY V77E  
MODE CNT-MATT HOLD  
ENTR (MANUAL MANEUVER)

\*3

KEY V06N8GE (AV'S LV)  
LOAD AGS EXT AV  
\*410+5 EXT AV  
\*450, 451, 452=LOAD  
COMPONENTS OF SOLUTION  
TO BE EXECUTED.  
KEY RELEASE

F 50 19 BYPASS TRIM  
PRB (TRIM NOT REQD)  
\*407+0 WHEN MANEUVER IS  
COMPLETE.

\*2 ED: MASTER ARM SW=ON  
16 85 AVIS-BODY  
\*500R AVX (COMPARE)  
\*:35 DSKY BLANKS

STAGE SW=FIRE  
ED: MASTER ARM SW=OFF

\*0 F 16 85  
(94:59) BURN +Z WITH TTCA  
+0:00 SET ET COUNTING UP

VULL REMAINING AVIS  
\*500RAVX 501RAVY 502RAVZ  
PRB

F 37 BB  
KEY OOE (P8E)  
KEY V93E  
(REINITIALIZE W MATRIX)  
\*\*\*\*\* 1ST MC CORRECTION \*\*\*\*\*

43.

AS=504/CSM=104/LM=3

PREPARED BY FPRB/CF24

1/31/69

F 50 19 BYPASS TRIM  
DISKY BLANKS PRB (TRIM NOT REQUIRED)  
VERIFY R/R LOCKEN GOOD

F 37 BB  
PRB

KEY V37E35E  
F 16 45 MKS TFI -00001

\*5\* \*304R COPY TGT LOS ANGLE

\*404+0 405+0 406+C  
PRB (COMP MC FOR TPI +10)

F 06 81 AV'S-LV (CPY)

PRB  
F 06 59 AV'S-LOS

\*304R COPY THETA,R,RD8.

COMPUTE BU MC CORRECTION

PRB  
F 16 45 MKS TFI MGA  
PRB

F 37 BB

IF 1ST MC SMALL, SKIP  
F41 AND RECALL P35.

KEY 41E  
F 50 18 FDAI ANGLES  
ENTR (MANUAL MANEUVER)  
F 50 19 BYPASS TRIM  
PRB (TRIM NOT REQD)  
16 85 AV'S-BODY  
COMPARE PGNS AND BU'S  
KEY V77E

45.

AS-504/CSM-104/LM-3

PREPARED BY FPRB/CF24

\*\*\*\*\* 2ND MC CORRECTION \*\*\*\*\*

+11 KEY 35E  
MKS TFI -00001

\*404+0 405+0 406+C  
WHEN MARKS = 1, KEY V93E.  
(REINITIALIZE W MATRIX)

\*304R COPY TGT LOS ANGLE

\*404+0 405+0 406+C  
PRB (COMP MC FOR TPI +22)

\*304R COPY THETA,R,RD8.

COMPUTE BU MC CORRECTION

PRB  
F 06 81 AV'S-LV (CPY)

PRB  
F 06 59 AV'S-LOS

\*304R COPY THETA,R,RD8

COMPUTE BU MC CORRECTION

KEY 41E  
F 50 18 FDAI ANGLES  
ENTR (MANUAL MANEUVER)  
F 50 19 BYPASS TRIM  
PRB (TRIM NOT REQD)

16 85 AV'S-BODY  
COMPARE PGNS AND BU'S  
KEY V77E

46.

1/31/69

\*21:25 DSKY BLANKS

\*22 F 16 85 NULL AV C WITH RCS  
KEY V76E  
PRB

F 37 BB KEY OOE (P00)

KEY V37E47E (AVERAGE G)  
BLANK FOR 1 MIN  
F 16 83 AVIS

F 04 06 KEY V62E  
00004 00001  
PRB  
F 16 72 XXXXX+XXX+XXX+XX  
PRB  
F 16 78 XXXXX.XR XXXXX.XRD8T  
VERIFY TAPE METER WITH DSKY

KEY V77E (ATT HOLD)  
BRAKING: 30FPS = 6000FT  
20FPS = 3000FT  
10FPS = 1500FT  
5FPS = 500FT

RENDIEZVBUS

DCK

AS-504/CSM-104/LM-3

PREPARED BY FPRB/CF24

1/31/69

47.

48.

(95:44)

CB AC BUS A RNDZ RDR=CLOSE  
(WAIT 30 SECONDS)  
CB PGNS RNDZ RDR=CLOSE

- ATT CNT•PULSE(3)  
R/R MODE•SLEW  
\*507+0 \*30\* \*456R AVCSI COPY  
\*400+2 RADAR ACQUISITION  
RATE ERR MON=CMPTRL(MP)  
PULSE TO NULL AGS ERRORS  
PAINT Z-AXIS IN DIRECTION  
OF CSM.  
DEADBAND-MIN  
MODE CNT•ATT HOLD  
ATT CNT•MODE CNT(3)  
RATE ERR MON=RNDZ RDR(CDR)  
SLEW R/R ANT TO C.O ON FDAI  
VERIFY MAX SIGNAL STRENGTH  
R/R MODE=AUTO TRACK  
NG TRK LT=OFF  
COMPARE R/R ERR NEEDLES  
WITH CGAS, IF CSM VISIBLE.  
DEADBAND-MAX
- \*\*\*\*\* CSI CSI CSI \*\*\*\*\*
- \*275+382.0 AGS CSI TIME  
\*277+479.3 AGS TPI TIME  
\*605+10250 TPI ANGLE CODE  
\*416+0.1ST APSIDAL  
\*417+1 \*2 \*410+1 CSI RBTINE
- \*\*400+1 GUIDANCE STEERING  
PULSE TO NULL AGS ERRORS  
DEADBAND-MIN  
TRIM AGS ERRORS  
ATT CNT•MODE CNT(3)  
\*407+0 WHEN MANEUVER IS  
COMPLETE.  
\*500RAVX
- ED: MASTER ARM=ON
- 50.

AS=504/CSM=104/LM=3

PREPARED BY FPRB/CF24

1/31/69

ED: MASTER ARM=0FF

SET ET COUNTING UP AT 0.

\*0(96:22) BURN +X WITH TTCA  
ASC FEED 2•OPEN(SYS A-B)  
CHECK ASC FUEL AND OXID  
FLAGS OPEN. (SYS A-B)  
MAIN S0V (SYS A-B)=CLOSE  
MAIN S0V (SYS A-B)=OPEN.  
(BEFORE THRUST TERMINATION)  
ASC FEED 2•CLOSE (SYS A-B)  
(BEFORE THRUST TERMINATION)  
NULL REMAINING AV'S  
\*500R4VX 501R4VY 502R4VZ

\*\*\*\*\* CDH CDH CDH \*\*\*\*\*

ATT CNT•PULSE(3)  
\*400+2 RADAR ACQUISITION  
PULSE TO NULL AGS ERRORS  
POINT Z•AXIS IN DIRECTION  
OF CSM.  
MODE CNT•ATT HOLD  
ATT CNT•MODE CNT(3)  
SLEW R/R ANT TO C•O 9N FDA!  
VERIFY MAX SIGNAL STRENGTH  
R/R MODE=AUTO TRACK  
NB TRK LT•OFF  
DEADBAND•MAX

\*410+2 CDH ROUTINE  
\*276+0426+5 ABS TIME CDH  
\*313R TFI CDH  
\*411+1 APS SELECT

\*37 SET ET T0 TFI CDH

51.

AS=504/CSM=104/LM=3

PREPARED BY FPRB/CF24

\*3/UKAV LUN

COPY GROUND SOLUTION

\*29\* COPY RDAT FROM TAPE METER  
FOR BU'S

\*18\* COPY RDAT FROM TAPE METER  
FOR BU'S  
\*263R4VY CDH 8PV COPY  
\*450R4VX 452R4VZ COPY

COPY RDAT FROM TAPE METER  
FOR BU'S

CALCULATE BU CDH  
COMPARE SOLUTIONS

\*410+5 EXT AV  
\*450, 451, 452•LOAD  
GROUND SOLUTION FOR CDH.  
\*5 ATT CNT•PULSE(3)  
\*400+1 GUIDANCE STEERING  
MODE CNT=AUTO  
PULSE TB NULL AGS ERRORS  
DEADBAND-MIN  
TRIM ERRORS  
ATT CNT•MODE CNT(3)  
\*407+0 WHEN MANEUVER IS  
COMPLETE.  
\*500R4VX

\*4 MONITOR ULLAGE  
\*0(97:06:28) ABORT STAGE•DEPRESS

SET ET COUNTING UP AT 0.

52.

1/31/69

PREPARED BY FPRB/CF24

**ABORT STAGE•RESET**

1/31/

PREPARED BY FPRB/CF24

MODE C0NT-A/H WHEN 502<<5  
NULL REMAINING AV'S  
\*500R4VX 501R4VY 502R4VZ

\*22

\*\*\*\*\* 1ST MC CORRECTION \*\*\*\*\*

ATT C0NT-PULSE(3)

\*304R COPY TGT LOS ANGLE

\*304R COPY THETA,R,ROBT

CALCULATE BU MC CORRECTION

\*404+0 405+0 406+C  
(IF BU'S BURNED, MONITOR AV  
APPLIED WITH 47C 471 472)

\*10

\*400+0 ATT HBLD  
ATT C0NT-M0DE C0NT(3)  
NULL AV'S WITH RCS  
\*500R4VX 501R4VY 502R4VZ

ATT C0NT-PULSE(3)

\*\*\*\*\* 2ND MC CORRECTION \*\*\*\*\*

\*17\* \*304R COPY TGT LOS ANGLE

\*20\* \*304R COPY THETA,R,ROBT

CALCULATE BU MC CORRECTION

\*404+0 405+0 406+C  
(IF BU'S BURNED, MONITOR AV  
APPLIED WITH 470 471 472)

55.

AS-504-CSM-104/LM-3

PREPARED BY FPRB/CF24

1/31/69

ATT C0NT-M0DE C0NT(3)  
NULL AV'S WITH RCS  
ATT C0NT-PULSE(3)

\*404+0 405+0 406+C  
MONITOR BRAKING AV VIA 470,  
471, AND 472.

BRAKING:

30FPS=6000FT  
20FPS=3000FT  
10FPS=1500FT  
5FPS= 500FT

RENDEZVOUS

D0CK

56.

## 5.0 Backup Charts

Backup chart solutions are calculated at CSI, CDH, TPI, MCC 1 and MCC 2. At CSI and CDH the charts are exercised as a validation of the F and G mission rendezvous procedures. At TPI and the midcourses they are second in priority to the LM PNGS solutions.

### 5.1 CSI Chart

The CSI chart solution is based on a Maclaurin's expansion of four variables for the delta V at CSI (range rate at 30, 20, and 10 minutes prior to CSI and range 10 minutes prior to CSI). The coefficients are determined by the simultaneous solution of several expansions, each representing a dispersed trajectory prior to CSI.

### 5.2 CDH Chart

The CDH chart solution utilizes the sinusoidal time history of range rate variations from coellipticity and relative velocity errors from coellipticity. Range rate data for the CDH chart are taken 29, 18, and 7 minutes prior to CDH.

5.3 TPI and MCC Charts

The TPI charts solve for the relative position and velocity at TPI resolved into normal and along the line-of-sight (LOS) coordinates. The measured relative state is differenced with the required state conditions for intercept in 130 degrees of orbit travel. Information required for the TPI charts is the elevation of the LOS from local horizontal ( $\theta$ ) at eight and five minutes prior to TPI, plus range and range rate five minutes prior to TPI. In a similar manner the midcourse charts maintain the time of TPF consistent with the TPI maneuver. Data are taken for the midcourses five and eight minutes after TPI for MCC 1 and 17 and 20 minutes after TPI for MCC 2. The same measurement sequence as used at TPI is used for both midcourse corrections.

CSI  
BACK-UP TABLE  
(NEXT PAGE)




## CSI BACK-UP TABLE: MISSION C

	$\dot{R}_{30}$	$F_{30}$	$\dot{R}_{20}$	$F_{20}$	$R_{10}$	$F_{10}$	$G_{10}$
120.	-100.4		120.	144.4	120.	-79.1	68.
121.	-101.3		121.	145.6	121.	-79.8	69.
122.	-102.1		122.	146.9	122.	-80.4	70.
123.	-103.0		123.	148.1	123.	-81.1	71.
124.	-103.8		124.	149.3	124.	-81.8	72.
125.	-104.6		125.	150.5	125.	-82.4	73.
126.	-105.5		126.	151.7	126.	-83.1	74.
127.	-106.3		127.	152.9	127.	-83.7	75.
128.	-107.1		128.	154.1	128.	-84.4	76.
129.	-108.0		129.	155.3	129.	-85.1	77.
130.	-108.8		130.	156.5	130.	-85.7	78.
131.	-109.7		131.	157.7	131.	-86.4	79.
132.	-110.5		132.	158.9	132.	-87.0	80.
133.	-111.3		133.	160.1	133.	-87.7	81.
134.	-112.2		134.	161.3	134.	-88.4	82.
135.	-113.0		135.	162.5	135.	-89.0	83.
136.	-113.8		136.	163.7	136.	-89.7	84.
137.	-114.7		137.	164.9	137.	-90.3	85.
138.	-115.5		138.	166.1	138.	-91.0	86.
139.	-116.3		139.	167.3	139.	-91.7	87.

(NOM)

$\dot{R}_{28}$	(113.5)	$\dot{R}_{30}$	-(113.2)	$\dot{R}_{30}$	-(113.2)
$\dot{R}_{32}$	(112.8)	$\dot{R}_{10}$	(116.2)	$R_{10}$	(-76.6)
$R_{10}$			(62.2)	$G_{10}$	(- 5.0)
				$F_{30} + F_{10} + G_{10}$	(-176.4)
$\dot{R}_{20}$			(114.7)	$F_{20}$	(138.3)
				$\Delta V_{CSi}$	(-38.1)


**B MISSION CDR CHART**  
1-21-69



"D." MISSION


130. TRANSFER  
10-3-68

# TPI<sub>0</sub> FIRST OPPORTUNITY ONLY



"D" MISSION

LM-120 CSM-130  
130 DEGREE TRANSFER  
9-17-68



LM-120 CSM-120  
130 DEGREE TRANSFER  
9-17-68

WISDOM

**FIRST MIDCOURSE CORRECTION**

**DEGREE TRANSFER**, -17-68

$R_{REQ}$  — 97.4       $R_8$  — 12.90       $R_8$  — 97.4

$\Theta_5$  — 34.86       $\Delta R$  — 0.0

$\Delta\theta$  — 5.38

**PNGS GND CHARTS**

$\gamma_A$  —       $\gamma_L$  —       $\gamma_U$  —

**CORRECTION**

**JET X**

**JET Z**

**UP**      **DOWN**

**AVN**

**R REQ**


**GND**

**DEGREE TRANSFER**

**Δθ**


LM-120 CSM-130  
130 DEGREE TRANSFER  
9-17-68


SECOND MIDCOURSE CORRECTION



1/22/69

LM FOOTBALL REFERENCE TRAJECTORY





6.0 References

- 6.1 SPD 8-R-005, Revision 1, Mission Requirements, D Type Mission, LM Operations, dated November 6, 1968.
- 6.2 Apollo Mission D (AS-504/CSM-104/LM-3) Spacecraft Operational Trajectory, Mission Profile, Volume 1, dated December 2, 1968.
- 6.3 Guidance System Operations Plan, Sundance, Volume II, MIT R-557, dated July 1968.
- 6.4 Apollo Operations Handbook, Lunar Module, LMA790-3-LM3, Volume 2, Operational Procedures, dated August 15, 1968.
- 6.5 Apollo 9 Preliminary Flight Plan, Flight Crew Support Division, dated December 11, 1968.
- 6.6 S-PA-8M-036, Apollo Mission Techniques Mission D Rendezvous, Volume 1, dated December 20, 1968.
- 6.7 Apollo 9 Flight Mission Rules (AS-504/104/LM-3), Flight Control Division, dated December 15, 1968.