AC ELECTRONICS DIVISION, GENERAL MOTORS

Milwaukee, Wisconsin 53201

FOR APOLLO 7 MISSION: Bruce McCristal Quality Court

Dave Hudgens (Houston) Sheraton King's Inn Tom Nedwek

MASSACHUSETTS INSTITUTE OF TECHNOLOGY

Sheraton Cape Colony 783-2252

Quality Court 783-9431

RAYTHEON CORPORATION

AIR		<u>Cape Area (305)</u>	Houston (713
	National	784-0230	228-843
	Eastern	773-1270	224-621
		636-3144	
	American		222-987
	Continental		223-102
GROU	JND		
	Avis		643-0673
	Hertz	783-7771	
	National	783-7007	649-555
	Limousine	783-7800	488-153
		783-7200	

MOTELS


Cape Kennedy Hilton 783-0361	Holiday Inn 488-1518
Carriage House 783-9430	Nassau Bay Motor Inn. 488-3402
Holiday Inn 783-2771	Ramada Inn 488-2216
Howard Johnson 883-9481	Sheraton King's Inn 488-0220
Ramada Inn 783-9441	~



UPRATED SATURN I

LAUNCH ESCAPE SYSTEM COMMAND MODULE **REACTION CONTROL SYSTEM SERVICE MODULE** SERVICE PROPULSION SYSTEM 22,000 LBS THRUST LUNAR MODULE ADAPTER **INSTRUMENT UNIT** SATURN IVB 200,000 LBS THRUST SATURN STAGE I 1,600,000 LBS THRUST

GUIDANCE, NAVIGATION, AND CONTROL SYSTEM



THE APOLLO GUIDANCE AND NAVIGATION SYSTEM IS COMPOSED OF THREE BASIC SUBSYSTEMS: INERTIAL, OPTICAL, AND COMPUTER.

- 1. The inertial auidance subsystem is composed of inertial measurement unit (IMU) and associated equipment. This subsystem performs three major functions: (A) Measures changes in spacecraft attitude; (B) Measures spacecraft velocity due to thrust; and (C) Assists in generating steering signals.
- The optical navigation subsystem is composed of a space sextant and a scanning telescope. Sightings on celestial bodies and landmarks on the moon and earth are used by the computer subsystem to determine the spacecraft's position and velocity and to align the inertial reference within the IMU.
- 3. The command module computer (CMC) profices five major functions: (A) Calculates steering signals and engine discretes necessary to keep the spacecraft on the required trajectory; (B) Positions the stable member in the IMU to a coordinate system defined by precise optical measurements; (C) Positions the optical unit to celestial objects; (D) Conducts limited malfunction isolation of the G&N system by monitoring the level and rate of system signals; and (E) Supplies pertinent spacecraft condition information to the display and control panel.

APOLLO 7











MISSION DESCRIPTION

1. MANNED

BACKUP Stafford

Shirra Eisele

PRIME

Young

Cunningham

- 2. Earth Orbit 164 Revolutions
- 3. Planned Duration 10 Days, 20 Hours, 9 Minutes
- 4. Booster Updated Saturn 1B
- 5. Spacecraft CSM-101
- 6. Block II G&N System No. 204

G&N TEST OBJECTIVES

- 1. Inertial Measurement Unit (IMU) orientation determination
- 2. IMU in flight alignment
- 3. Guidance Navigation Control System velocity control
- 4. Guidance Navigation Control System attitude control
- 5. Guidance Navigation Control System entry monitoring
- 6. Sextant tracking
- 7. G&N/Manual thrust vector control takeover
- 8. Orbital Navigation/Landmark Tracking
- 9. Midcourse navigation
- 10. G&N system performance through all phases

GENERAL OBJECTIVES

Apollo 7 is the first manned Apollo mission and is intended to demonstrate the capability of the spacecraft, crew, and support facilities to conduct an open ended, earth orbital mission of up to 11 days duration. The mission will also qualify the heat shield, environment control system radiator performance and verify proper deployment of the spacecraft lunar module adapter panels. Other activities will include transposition, simulated docking and active rendezvous with the SIV B booster.

PHASE 1

PRE-RENDEZVOUS ORBITAL ACTIVITIES

- 1. CSM/SIVB separation over Hawaii during Revolution 2.
- 2. Simulated docking maneuver over Hawaii during Revolution 2.
- Phasing maneuver over Antiqua during Revolution 3 to set up conditions for rendezvous planned for second day.

PHASE 2

RENDEZVOUS

Begins about 26 hours into the mission and normally will require three hours and 30 minutes to complete.

- Service propulsion system (SPS) Burn 1 Corrective maneuver to begin the CSM 60 miles ahead and 30 miles above the SIVB.
- Second SPS Burn Coelliptic maneuver to begin the CSM 10 miles behind and 8 miles below the SIVB.
- Terminal Phase initiation TPI using the reaction control system RCS to begin the CSM ½ mile ahead and 1 mile below the SIVB.
- 4. Terminal Phase Finalization When the CSM is about one nautical mile from the SIVB the crew will begin braking the spacecraft, making optical corrections until the CSM is about 100 feet from the SIVB. Station keeping will last about 20 minutes as the CSM and SIVB pass over Hawaii.

PHASE 3

POST-RENDEZVOUS CSM MANEUVERS

After the CSM leaves the vicinity of the SIVB, several SPS tests are planned. The table below contains information on the purpose of the burns.

SPS-3	Burn Duration 9.0 seconds	To adjust spacecraft orbit and establish deorbit capability
SPS-4	.5 seconds	Guidance and navigation control
SPS-5	57.0 seconds	Propellent utilization and gauging
SPS-6	.5 seconds	Guidance and navigation minimum impulse test
SPS-7	19.6 seconds	To adjust perigee altitude prior to the deorbit burn
SPS-8	9.8 seconds	Deorbit burn to assure crew and spacecraft reentry

