Massachusetts Institute of Technology C. S. Draper Laboratory Cambridge, Massachusetts

Luminary Project Memo No. 19

TO:

Distribution

FROM:

R. A. Larson 241

DATE:

January 26, 1971

SUBJECT:

Hardware dependent constants used in the Luminary program

Action requested by: 23A, 23B, 23C, 23T

Date requested by: February 2, 1971

The attached list contains selected hardware dependent constants which are being used in the Luminary Program. The "Old" values are those used in Luminary; the "New" ones are taken from the Spacecraft Operational Data Book (SODB). We have been requested by the MSC to review these values in light of performance degradation or limitations of capability to determine if any of the fixed memory constants should be changed.

Distribution:

- G. Levine
- A. Klumpp
- M. Hamilton
- B. McCoy
- L. Berman
- T. Edelbaum
- P. Weissman
- G. Silver

		trn	CINARY	lie M	. SOUB
Annamental			actiques.	The True	
NA PROPERTY AND ADDRESS OF THE PERTY ADDRE	Mass	Properties			1
and the second				OLD	NEW
9		Maximum descent weight:	16,70		16697 Kg
	ETER	Minimum descent weight:	5050 6052		19943.3Mg
N	EISSMAN	Minimum ascent weight:	2200	400	70-84 .3 Kg 22-00-0 Kg 20-06-6 Kg
- College Constants		Minimum CSW weight:	4906	K9 ->	4596.6
and the same of th	RCS	jets			
		Thrust 2 jet: .	200 1	lb	2
na and an		Thrust 4 jet:	400		1 Same
-	Desce	ent engine	7		
		,	9817.	5 Ha	
-	. 00)	Thrust: Nass flow rate:	0 6	ko/sec	9790 16
V	LUMI?	Exhaust velocity:	2965	88 M/3cc	14.681 kg/sec 2987 m/sec
4	LUM.	Throttle scaling:		3 19/9:4.	
odgeniesion.	1	Throttle lag:	0.08	Sec	Same
An earthmy digests		10% DPS engine thrust:	1050		1376 16 (13%)
***********					(3.4 10 (13%)
***************************************	ABCEL	nt engine		The state of the s	ing the state of t
	-121	Thrust:	350011	2 · · · · · · · · · · · · · · · · · · ·	3476.8 16
1	ARRY	Mass flow rate: Exhaust velocity:	6-135	F3/600	S.ASS Made
	BERMAN	materials servered, according	3030	WASE &	3048.42 M/SCC
E	BEK, I	a 1-second maneuver for a unit mass vehicle:	140.19	Ra-halea	
		Minimum impalse:	31.139	ng-m/cs	140.12 kg-m/cs
	15	Slope of minimum impulse curv	6 1.55	69 K9-M/C8	2.094 40 4/02
6	EORG IN				3-1763
5	EUR6 THU	Turn on delay:	90 60	C	100 Seconds
		OPTICE			1-4 3C C 0M@ 2
		am occultation cone			
	ing paramay y	1/2 angle:	60 des	b	Same

Landing Radar

Lower limit IR data:

Maximum re-positioning delay: | | Seconds