

	3
DATA TELY GOV- ITSO- ITED. HON:3 IS IN TION. SELL	1000251 IL
	C. VENDOR SUPPLIED INFORMATION: THE FOLLOWING DATA AND INFOR- MATION IS TO BE SUPPLIED WITH EACH SHIPMENT. ALL INFORMA- TICN SUPPLIED WILL REFERENCE THE UNIT PART NUMBER, APPLICABLE PURCHASE ORDER NUMBER, QUANTITY AND DATE OF SHIP MENT, AND THE APPLICABLE DATE CODES OR DIFFUSION LOT CODES.
DANCE WITH STANDARDS PRESCRIBED	(1) A CERTIFICATE OF COMPLIANCE COVERING LEAD MATERIAL REQUIREMENTS OF PARAGRAPH 3.C. (3).
REMENTS OF NHL-S-19500 EXCEPT AS, HIREMENTS SPECIFIED HEREIN.	(2) A CERTIFICATE OF COMPLIANCE COVERING THE REQUIREMENTS OF ND 1015404.
THE QUALITY ASSURANCE PROVISIONS	(3) THE NOMINAL LEAD DIMENSIONS AS REQUIRED BY PARAGRAPH 2.E.
ARKED IN ACCORDANCE WITH TURER'S IDENTIFICATION, DATE DE, KEYING STRIPE, "(COLOR OPTIONAL, 321. THE BACK OF THE PACKAGE MAY BE OT NUMBER.	(4) THE PRESEAL INSPECTION DATA REQUIRED BY PARAGRAPH 4.C. (5) THE SUBGROUP 1 AND 3 TEST DATA REQUIRED BY TABLE II. A SUMMARY OF TEST RESULTS OF SUBGROUPS 1&3, INCLUDING THE NUMBER OF UNITS TESTED & NUMBER OF FAILURES FOUND, SHALL BE SUBMITTED WITH EACH SHIPMENT LOT. FAELE IN SHALL BE MENDED
ALL BE IN ACCORDANCE WITH	D. SELECTION OF UNITS FOR TEST: UP OF UNITS WELCE CONSTITUTE A DEC (1) THE SAMPLE USED FOR TABLE IT SHALL BE RANDOMLY SELECTED FROM THE I I GROUP OF UNITS WHICH CONSTITUTE A SHIPMENT LOT.

(1) MARKING OF SHIPPING CONTAINERS SHALL CONFORM TO THE MARKING OF UNIT AND INTERMEDIATE PACKAGES AND THE

DRAWING, MUST MEET THE REQUIREMENTS OF ND 1002248, WHEN PROCESSED AS SPECIFIED IN ND 1002248, PERFORMED AT THE BUYERS PLANT.LOTS OR SUBLOTS REJECTED BY THE CRITERIA OF PARA.4.3 OF ND

ASSEMBLED FROM DIFFUSION SUB-LOTS AND DATE CODES WHICH ARE SHIPPED AT ONE TIME WHICH HAVE BEEN FABRICATED IN A SINGLE CONTINUOUS PRODUCTION RUN USING LIKE MATERIAL'S WHICH ARE CONTROLLED USING A CONTROLLED PROCESS. NO PROCESS CHANGES DEFINED AS CRITICAL BY ND 1015404 NEGOTIATION MAY BE CHANGED DURING THE FABRICATION OF A SHIPMENT LOT. MAXIMUM NUMBER OF UNITS SHIPPED IN A LOT SHALL BE 5,000. A MAXIMUM OF 100 DIFFUSION SUB-LOTS MAY BE USED TO ASSEMBLE ONE SHIPMENT LOT. A SHIPMENT LOT MAY INCLUDE MORE THAN

(2) A DIFFUSION SUB-LOT IS DEFINED AS A GROUP OF PARTS FABRICATED FROM MATERIALS WHICH WERE PROCESSED THROUGH DIFFUSION MASKING, ETCHING AND METALLIZATION AT ONE TIME (A SINGLE BATCH), THIS SUB-LOT IDENTIFICATION MUST BE MAINTAINED THROUGH SUBSEQUENT STABES OF ASSEMBLY AND TEST. A DIFFUSION SUB-LOT SHALL BE


(3) DATE CODE LOT I'S DEFINED AS THOSE UNITS SEALED DURING

(1) THE TESTS AS DEFINED IN TABLES 1 & 11 SHALL BE PERFORMED BY THE QUALITY CONTROL DEPARTMENT OF THE VENDOR. (2) UNLESS OTHERWISE SPECIFIED HEREIN ALL ELECTRICAL TESTS MUST BE REFERENCED TO AN AMBIENT TEMPERATURE OF PLUS

(3) THE PRE-SEAL TEST PER TABLE I SHALL BE PERFORMED AFTER THE FINAL PRODUCTION INTERNAL VISUAL INSPECTION AND

PROCURE ONLY FROM APPROVED SOURCES LISTED IN ND 1002034 FOR THIS DRAWING.

	•		
	• •		
		• •	•
5 e		* *	
		• •	•
	• • •	• • •	. • •




F	1006321

SHALL BE RANDOMLY SELECTED FROM THE ENTIRE (2) A SHIPMENT LOT MAY BE RESUBMITTED FOR TABLE 11 SUBGROUP 1&3, THE REQUIREMENT OF MIL-S-19500C GROUP 1&3 FOR LOT RESUBMITTAL SHALL APPLY WITH THE TIGHTENED INSPECTION FOR THE CHARACTERISTICS

		REVISIONS
SYM	ZONE	DESCRIPTION
D		REDRAWN AND REVISED PER TORRI
Ε		REVISED PER TDRR 20877
F		REVISED PER TDRR 27100

(D) REPLACES REV(C)WITH CHANGES

••										
	QTY REQD	PART OR IDENTIFYING NO	MATERIAL OR NOTES							
					LIS	TOF	MATERIA	ALS		
SS OTHERWISE SPECIFIED NSIONS ARE IN INCHES CITOR VALUES ARE IN #f	IN	MIT STRUMENTATION CAMBRIDGE, MASS.		MANNED						
STOR VALUES ARE IN OHMS RANCES ON TIONS DECIMALS ANGLES ± ± HOT SCALE THIS DRAWING RIAL	CHECI APPRO	N A. Mong KED A. Mart OVED A Marta OVED Ellon Chall	27 MAYC 6-2-65 1 Jun 63 2 June 65	र • DU						
•	APPRO MIT APPRO	Winnen	2 July				SIZE C	-		
	MSC		DATE	SC	ALE NO	NE				
e e e e e e e e e e e e e e e e e e e	2			· . · ·						



NOTICE - WHEN GOVERNMENT DRAWINGS, SPECIFICATIONS, OR OTHER DATA ARE USED FOR ANY PURPOSE OTHER THAN IN CONNECTION WITH A DEFINITELY RELATED GOVERNMENT PROCUREMENT OPERATION, THE UNITED STATES GOV- ERNMENT THEREBY INCURS NO RESPONSIBILITY NOR ANY OBLIGATION WHATSO- EVER; AND THE FACT THAT THE GOVERNMENT MAY HAVE FORMULATED, FURNISHED, OR IN ANY WAY SUPPLIED THE SAID DRAWINGS, SPECIFICATIONS OR OTHER DATA IS NOT TO BE REGARDED BY IMPLICATION OR OTHERWISE AS IN ANY MANNER LICENSING THE HOLDER OR ANY OTHER PERSON OR CORPORATION. OR CONVEYING ANY RIGHTS OR PERMISSION TO MANUFACTURE, USE, OR SELL ANY PATENTED INVENTION THAT MAY IN ANY WAY BE RELATED THERETO.
D 2. E. LEAD DIMENSIONS: THE PARTS SUP MUST BE UNIFORM WITH RESPECT TO THICKNESS SHALL BE WITHIN ± 0.00 VALUE TO BE SPECIFIED BY THE VER
BE WITHIN ± 0.001 INCHES OF A NO SUPPLIED. THE NOMINAL VALUES FO BE SUPPLIED WITH THE APPLICABLE 3. DESIGN:
A. ABSOLUTE MAXIMUM RATINGS AT 25° (1) VOLTAGE TO PIN 10: PLUS 10 PIN 5.
(2) VOLTAGE APPLIED TO ANY INP VOLTS WITH RESPECT TO PIN (3) THERMAL RESISTANCE, JUNCTI
(4) THERMAL RESISTANCE, JUNCTION WATT. B. TEMPERATURE:
(1) TEMPERATURE RANGE, JUNCTION +125°C. (2) TEMPERATURE RANGE, JUNCTION (3) TEMPERATURE, SOLDERING LEAR
C. CONSTRUCTION: (1) SEMICONDUCTOR: SILICON, N (2) ENCLOSURE: A HERMETICALLY ISOLATED FROM POWER OR GRO
WHICH MEET THE REQUIREMENT 2.E. (3) LEADS: LEAD MATERIAL SHALL BE IN
PS 1015402 WITH THE FOLLOW GOLD PLATE SHALL BE A MINI 200 MICRO INCHES. THE NIC SHALL BE OPTIONAL BUT IF U 100 MICRO INCHES, AND PARA CERTIFICATE OF COMPLIANCE
ACCOMPANY EACH LOT SHIPPED 4. TEST METHODS: (REF. MIL-STD-750 WI
A. AVERAGE PROPAGATION DELAY (T _p): PERFORMED ON EACH INPUT USING T FIGURE 2 MADE UP OF ACCEPTABLE VOLTAGE 4V ± 10% DURING TEST AL GROUNDED.
A second and the seco

IPPLIED IN ANY SHIPMENT LOT O LEAD DIMENSIONS. THE LEAD 0005 INCHES OF A NOMINAL ENDOR. THE LEAD WIDTH SHALL NOMINAL VALUE ALSO TO BE FOR EACH SHIPPING LOT WILL E SHIPMENT.

• •

-C AMBIENT: 10.0 VOLTS WITH RESPECT TO

IPUT PIN PLUS OR MINUS 4 5. ION-CASE. (OJC): 200°C/WATT. TION-AMBIENT. (0JA): 500°C/

ION, OPERATING: -55°C TO

ION, STORAGE: -65°C TO +150°C. EADS: +250°C (1 MINUTE MAX).

NPN.

Y SEALED PACKAGE ELECTRICALLY ROUND, THE DIMENSIONS OF NTS OF FIGURE 1 AND PARAGRAPH


ACCORDANCE WITH NASA DOCUMENT DWING EXCEPTIONS:

NIMUM OF 100 AND A MAXIMUM OF ICKEL STRIKE UNDER THE GOLD USED SHALL BE A MAXIMUM OF RAGRAPH 3.4.2 SHALL NOT APPLY. FOR LEAD MATERIAL SHALL **V**.

WITH EXCEPTIONS NOTED BELOW).

): MEASUREMENTS SHALL BE TEST CIRCUIT SPECIFIED IN E UNITS WHERE $T_p = (T_1 + T_2)/2$. All unused bases shall be

-



•

006321 E

		REVISION
SYM	ZONE	DESCRIPTION
D.		REDRAWN AND REVISED PER TORR
Ε		REVISED PER TDRR 2087
F	:	REVISED PER TDRR 27100

•

٠

💓 🤹 - -


•

• •

. . . .

-		 	•				
	\bigcirc	REPLAC	ES	RE	/(C)W	17
	QTY REQD	PART OR IDENTIFYING NO		MATERIAL OR NOTES		•	
				LIS	ST OF M	ATERI	ALS
ESS OTHERWISE SPECIFIED ENSIONS ARE IN INCHES ACITOR VALUES ARE IN #f	IN:	MIT STRUMENTATION CAMBRIDGE, MASS.	MANNED				
ISTOR VALUES ARE IN OHMS ERANCES ON CTIONS DECIMALS ANGLES	DRAW CHEC	KED a. Mars	27 MM6 : 6-2-65				
± ± NOT SCALE THIS DRAWING		OVED Ellen C. Hall		(F SPECIFICAT			
SEE NOTE	APPRO MIT	WEDWKunn	zfadi	CODE IDEI		SIZE C	
• •	APPRO MSC	WED Al Khie	6-2-61 DATE	SCALE NC			
· · · · · · · · · · · · · · · · · · ·	2			an a	 		

and the same



	MARKING FLAKING CERAMIC AT THE OVER 50 IN OR 0 KINKS A WITHIN THE SPE MAY BE TO PHYS LEADS 0 C. PRESEA SHALL SPECIF COVERING THAT F THE NU	4 AND MECHANICAL EXTENDS SHALL BE LEGIBLE. SHALL BE LEGIBLE. SHALL HAVE NO SEAL GLASS, CERAMIC OR SO OF THE SEAL WIDTH ON THE SEAL INTERFACT AND NICKS AND SHALL LEAD SPECIFICATIONS ECIFIED LEAD MATERIAL CUT FROM THE LEAD POSICAL EXAMINATION. OR PACKAGE SEAL AREA L VISUAL INSPECTION: DE PERFORMED USING TO THE DIFFUSION SUBLE IED IN TABLE I. DAT NG THE NUMBER OF SUB AILED FROM EACH SUB- MBER OF TIMES EACH S	THE CASE FINISH ING OR HOLES. THE IMPAIRING CRACKS. OLDER SEAL SHALL N NO FOREIGN MATT E. LEADS SHALL BE MAINTAIN A UNIFORM THE UNITS SHALL REQUIREMENT. LE REFORM AND SHALL N NO BODY PAINT SHALL THE PRESEAL VISU HE REJECTION CRITE OT SHALL BE UTILIZ A SHALL ACCOMPANY -LOTS TESTED, THE LOT, THE CAUSE OF	SHALL HAVE NO GLASS OR RE-ENTRANCE DT EXTEND TO ER SHALL BE FREE FROM THICKNESS COMPLY WITH AD SECTION (A DT BE SUBJECT BE ON THE AL INSPECTION RIA OF ND 100 ED FOR SAMPLI EACH SHIPMENT NUMBER OF UNI FAILURE, AND
	TEST. P TEST VISUAL INTERNAL INSPECTION	TABLE I RE SEAL VISUAL INSPE TEST CONDITIONS SEE NOTE 2.C.(4) AND 4.C.	ECTION DIFFUSION SUB-LOT LTPD* = 7 MAX ACC NO. = 1	
	INTERPRET DRAY	wing in accordance with 4) BY MIL-D-70327

創 二回 およ (新聞) あく

1. A.

14-14

ing a chuige

L EXAMINATION UNDER 10X AND 80X MAGNIFICATION:

HE CASE FINISH SHALL HAVE NO OR HOLES. THE GLASS OR PAIRING CRACKS. RE-ENTRANCE ER SEAL SHALL NOT EXTEND TO NO FOREIGN MATTER SHALL BE LEADS SHALL BE FREE FROM NTAIN A UNIFORM THICKNESS THE UNITS SHALL COMPLY WITH EQUIREMENT. LEAD SECTION (A) ORM AND SHALL NOT BE SUBJECTED BODY PAINT SHALL BE ON THE


THE PRESEAL VISUAL INSPECTION REJECTION CRITERIA OF ND 1002257 SHALL BE UTILIZED FOR SAMPLING SHALL ACCOMPANY EACH SHIPMENT ITS TESTED, THE NUMBER OF UNITS , THE CAUSE OF FAILURE, AND LOT WAS RESUBMITTED TO TABLE I



SYMMETRICAL ABOUT & WITHIN .010 AND & OF LEADS TO BE SYMMETRICAL WITHIN .005 OF & OF PIN 1.2 OF LEADS TO BE MEASURED WITHIN .030 OF PACKAGE BODY. SEE PARAGRAPH 2.E.

-----.275 MAX OUTSIDE **P** • 1 .190 MAX OUTSIDE 1 • • • 2 • • • 2 TYP


USED ON





same and the

NEXT ASSY

APPLICATION







		- APPROVAL P A Hanley 1 Jun 63	
	DO NOT SCALE DRAWING	APPROVAL Eldon C. Hell 2Jun 65	עע איז
MATERIAL		APPROVAL	SPECIFICATI
		NASA APPROVAL () & Rhie	CODE IDENT NO. SIZE
		MIT APPROVAL	80230 C
		MIT APPROVAL N Rug 2 mels	SCALE NONE WT
		2 / 11 0	

	fear, a		- 					· · · · · · · · · · · · · · · · · · ·				en a general présidents la composition de la composition				i de ser ser de second de secondades a secondades de secondades de secondades	n a far de la companya de la company Service de la companya de la company Service de la companya de la company Service de la companya de la company Service de la companya de la companya de la comp	
Ţ		NOTICE - WHEN COVERNMENT DRAWINGS, SPECIFICA ARE USED FOR ANY PURPOSE OTHER THAN IN CONNECT RELATED GOVERNMENT PROCUREMENT OPERATION, TH ERNMENT THEREBY INCURS NO RESPONSIBILITY NOR AN EVER; AND THE FACT THAT THE GOVERNMENT MA FURNISHED, OR IN ANY WAY SUPPLIED THE SAID DRAY OR OTHER DATA IS NOT TO BE REGARDED BY IMPLICATION ANY MANNER LIGENSING THE HOLDER OR ANY OTHER PE OR CONVEYING ANY RIGHTS OR PERMISSION TO MANUF	TION WITH A DEFIN HE UNITED STATES IT OBLIGATION WH IT HAVE FORMUL WINGS, SPECIFICA ON OR OTHERWISE IRSON OR CORPOR	ATED. AS IN ATION.			3					J I	22900	2)]				PER TORR 198
	D	ANY PATENTED INVENTION THAT MAY IN ANY WAY BE				TABLE	E II E INSPECTION	*		•	•	•	• •			بطؤل ببرابك النفات تسمي ويعوده ومضرب ببري	PER TORI	R 20877 R 27100
. .		TEST * * *	SYMBOL	······································	·		NDITIONS **			"L'IM MEN		UNETS	LOT] .		n an	
		SUBGROUP 1 VISUAL AND MECHANICAL EXAMINATION		METHOD 2071 SEE PARA	GRAPH (4. B				*			1	•LTPD = = 1 IMAX ACE.	-		•		
		SUBGROUP 2 BASE CURRENT BASE CURRENT BASE CURRENT	IB IB		PIN 3.7 +1800±10mV +870±2mV +1800±10mV	ον	PIN 4.8 +1800±10mV +1800±10mV +870±2mV		PIN: 0 +4±.01V +4±.01V +4±.01V		1·52 1·52 1·52	UA UA UA	T 100% TEST REQUIRED			•. •		•
		OUTPUT VOLT PIN 1.9 OUTPUT VOLT PIN 1.9 OUTPUT VOLT PIN 1.9	V0 V0 V0	+770±2mV OPEN OPEN	OPEN +770±2mV OPEN	OV OV OV	OPEN OPEN +770±2m∀		+4±.01V +4±.01V +4±.01V		300 300 300	Vm Vm Vm			•			
	C	SAT VOLT PIN 1.9 SAT VOLT PIN 1.9 SAT VOLT PIN 1.9 OUTPUT CURRENT PIN 1.9	V _S V _S V _S	+870±2mV OPEN OPEN +500±2mV	OPEN +870±2mV OPEN +500±2mV	OV OV OV	OPEN OPEN +870±2mV +500±2mV	+870±2m¥	+4±.01V +4±.01V +4±.01V +4±.01V	760		wV wV wV		· ·			•	• •
		COLLECTOR-EMITTER THRESHOLD CURRENT SUBGROUP 3 COLLECT CUTOFF CURRENT	ICEX	+500±2mV	+500±2mV OPEN	0V	+500±2mV OPEN	+1.00±.01V	OPEN		15 100	WA National WA	+LTPD = 5					• •
		EMITTER CUTOFF CURRENT COLLECT CUTOFF CURRENT COLLECT CUTOFF CURRENT INTERFACE TEST	EBO B B 1	07 07 07 870±2mV	OV OV OV OPEN	+4±.1V OPEN OV		OPEN +8±.1V 5KΩ TO +10V	OPEN OPEN		100 100 100 400		(COMBINED) MAX. ACC.				•	
		INTERFACE TEST	B2	OPEN	870±2mV	OV	OPEN	5KA TO +10	OPEN		400	m۷		n, an a mar againg de fa d i fad i 1				•
•		INTERFACE TEST	B3	OPEN	OPEN .	07-	870±2m¥	-5KΩ TO +10	OPEN .		400	. m V		•				,
		COLLECTOR EMITTER SUSTAINING VOLTAGE AVERAGE PROPAGATION DELAY		IC = 5 MA SEE PARA	التعريب والاست والتقاد وبالكالي ويورق وأراد بالتي وبالن		المجمع بزيابي أزارك نعكا استحصدا كالمتحد الكريف			.5	24	VOLTS	+LTPD = 7					
		COLLECTOR RESISTANCE	RL	BETWEEN PI	NS 10 AND 1.	9			na u ar dan manga fan	2.7		Kohms	MAX. ACC. +LTPD = 10	<u>NO. = 1</u> D				
	B	D.C. CURRENT GAIN	hFE		$T CURRENT = V_{CE} = 0.5V$		SISTORS	•			200		MAX. ACC. +LTPD = 7 MAX. ACC.				,	
		 LTPD PER MIL-S-195 SAMPLE SIZE USED I CORRESPOND TO THE MEASUREMENTS TO BI MEASUREMENTS TO BI SAMPLING TEXTRONIX SAMPLING 	BY THE BU Max Acc E Made On G Probe P	YER AND VEND NUMBER SPECT GATE 1 AND 6032 WITH 50	FIED IN MIL- GATE 2. X ATTENUATOR	S-19500C				•	· · ·			D F	PLA	SES	REV((C) WIT
`				•			•	· ·	18	•	,	,	** *	OTY REQD	PART OR IDENTIFYING NO		ATERIAL R NOTES	NC MATERIALS
		•					•				ENSIONS ACITOR	HERWISE S S ARE IN II VALUES AF	NCHES RE IN #f	С	MIT UMENTATION AMBRIDGE, MASS.			MANNED SE
	A		·	4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4						TOLI FRAC ± DO	ERANCE: CTIONS	S ON	ALS ANGLES ±	APPROVED		1 June 65	SPE	DUAL (FL)
			•	👾 ಕೆ ಮೇಶಕ				NEXT ASSY APPLICAT	USED ON				-	APPROVED MIT APPROVED MSC	WRyten Wyski	6-2-65	CODE IDENT NO 8023C	C
		4		•			3	•			•.		· •	2	₹			
-		na n	Maran Maran San Ang San	ອີງດີນີ້ນັ້ນ. ເຊິ່ງ ເຊິ່ງເປັນ ອີດ ຊີ່ມີເຫັດແຫ່ນແບບເຊິ່ງເຫັດເອັດໃຫ້ ເດັ່ງ ອີດສາຍ	n norman an a	a start and a s	2 - Marina and Anna an				·	an an an Arge r at a	an a			e and the state of the st	U norther and gamma • Arrowski and gamma • Arrowski and gamma	t in the second s

1200

· • • - 8

.

۱ -

