

NOTICE - WHEN GOVERNMENT DRAWINGS, SPECIFICATIONS, OR OTHER DATA ARE USED FOR ANY PURPOSE OTHER THAN IN CONNECTION WITH A DEFINITELY RELATED GOVERNMENT PROCUREMENT OPERATION, THE UNITED STATES GOVERNMENT THEREBY INCURS NO RESPONSIBILITY FOR ANY OBLIGATION WHATSOEVER, AND THE FACT THAT THE GOVERNMENT MAY HAVE FORMULATED, FURNISHED, OR IN ANY WAY SUPPLIED THE SAID DRAWINGS, SPECIFICATIONS OR OTHER DATA IS NOT TO BE REGARDED BY IMPLICATION OR OTHERWISE AS IN ANY MANNER LICENSING THE HOLDER OR ANY OTHER PERSON OR CORPORATION, OR CONFERRING ANY RIGHTS OR PERMISSION TO MANUFACTURE, USE, OR SELL ANY PATENTED INVENTION THAT MAY IN ANY WAY BE RELATED THERETO.

NOTES:

1. GENERAL REQUIREMENTS:

- INTERPRET DRAWING IN ACCORDANCE WITH STANDARDS PRESCRIBED BY MIL-D-70327.
- SUPPLIER SHALL CONFORM TO THE QUALITY ASSURANCE PROVISIONS CONTAINED IN ND 1015404, CLASS 2.
- UNITS SHALL BE CAPABLE OF MEETING THE QUALIFICATION REQUIREMENTS AS LISTED IN TABLE III WITH REFERENCES TO MIL-T-23648 AND ND 1002057. ANY UNIT WILL BE CONSIDERED A FAILURE IF ITS

ZERO-POWER RESISTANCE CHANGES BY MORE THAN 1.0% AS A RESULT OF HAVING BEEN SUBJECTED TO ANY OF THE ENVIRONMENTAL TESTS SPECIFIED.

- MARKING: UNIT PACKAGES SHALL BE PERMANENTLY AND LEGIBLY MARKED, PER MIL-STD-129, WITH THE MANUFACTURER'S NAME AND/OR SYMBOL, LOT CODE OR SERIAL NUMBER, DATE OF MANUFACTURE, AND THE NASA PART NUMBER (DRAWING NUMBER, REVISION LETTER, AND DASH NUMBER).

2. ACCEPTANCE AND INSPECTION REQUIREMENTS (100%)

A. MECHANICAL REQUIREMENTS:

- LEAD MATERIAL: NICKEL (GRADE A) PER ND PS 1015400.
- PROTECTIVE VARNISH: MOISTURE AND FUNGUS PROOF VARNISH PER MIL-V-173.
- MATERIAL AND FINISH CERTIFICATION: LEAD MATERIAL AND RESISTOR MOISTURE PROOF VARNISH COMPLIANCE SHALL BE CERTIFIED WITH EACH SHIPMENT.

B. ELECTRICAL CHARACTERISTICS (AT $25^{\circ} \pm 0.1^{\circ}\text{C}$):

- ZERO-POWER RESISTANCE VALUE: TABLE I VALUE $\pm 1\%$.

3. DESIGN REQUIREMENTS:

- DISSIPATION CONSTANT: SEE TABLE I FOR THE AMOUNT OF POWER WHICH WILL RAISE THE THERMISTOR ONE DEGREE CENTIGRADE ABOVE AMBIENT.
- TIME CONSTANT: SEE TABLE I FOR THE TIME REQUIRED FOR THE THERMISTOR TO REACH 63% OF THE TEMPERATURE CHANGE FOR A CERTAIN CHANGE IN AMBIENT TEMPERATURE. THE THERMISTOR WILL REACH 98% OF TEMPERATURE CHANGE IN APPROX 5 TIMES THE CONSTANT LISTED.

- STORAGE LIFE: 1 YEAR MINIMUM AT ROOM TEMPERATURE AND HUMIDITY WHEN STORED IN UNOPENED CONTAINERS.
- CONSTRUCTION: RESISTIVE WAFER MATERIAL WITH LEADS SOLDERED IN PLACE.
- ENVIRONMENTAL: CAPABLE OF OPERATION OVER THE AMBIENT TEMPERATURE RANGE OF -55°C TO $+105^{\circ}\text{C}$.

4. SPECIAL CONDITIONING:

- TEMPERATURE CYCLING: RESISTORS SHALL BE TESTED PER MIL-STD-202, METHOD 102, CONDITION C EXCEPT TEMPERATURE EXTREMES OF -55°C AND $+105^{\circ}\text{C}$. RESISTANCE, ONE HOUR AFTER TESTING, SHALL NOT VARY MORE THAN $\pm 1\%$ FROM THE INITIAL MEASUREMENT. THERE SHALL BE NO MECHANICAL DAMAGE.
- BURN-IN: RESISTORS SHALL BE BURNED IN NON-OPERATING AT 50°C FOR 100 HOURS. RESISTANCE, ONE HOUR AFTER TESTING SHALL NOT VARY MORE THAN $\pm 1\%$ FROM THE INITIAL MEASUREMENT. THERE SHALL BE NO MECHANICAL DAMAGE.

PROCURE ONLY FROM APPROVED SOURCES LISTED IN ND 1002034 FOR THIS DRAWING.

E 2129001

REVISIONS 03038			
SYM	DESCRIPTION	DATE	APPROVAL
-	INITIAL RELEASE, CLASS A PER TDRR 03038	11/16/63	WKE
A	REVISED PER TDRR 06243	1-18-64	WKE
B	REVISED PER TDRR 08861	6/2/64	WKE
C	REVISED PER TDRR 12767	4/21/65	WKE
D	REVISED PER TDRR 19731	8/15/65	WKE
E	REVISED PER TDRR 24692	12/11/65	WKE


SPECIAL CONDITIONING (CONT'D)

- FOLLOWING BURN-IN. THE ZERO-POWER RESISTANCE OF EACH UNIT SHALL BE MEASURED AT THREE(3) TEMPERATURES;

$0^{\circ} \pm 0.1^{\circ}\text{C}$, $25^{\circ} \pm 0.1^{\circ}\text{C}$, AND $50^{\circ} \pm 0.1^{\circ}\text{C}$. THE RESISTANCE MEASURED AT THESE TEMPERATURES SHALL BE SUPPLIED FOR EACH UNIT. A CERTIFICATE OF COMPLIANCE TO THE REQUIREMENTS OF PARA. 4A AND 4B ABOVE SHALL ALSO BE SUPPLIED WITH EACH LOT SHIPPED.

5. VENDOR SUPPLIED INFORMATION:

- THE FOLLOWING DATA AND INFORMATION TO BE SUPPLIED WITH EACH SHIPMENT UNLESS OTHERWISE SPECIFIED. ALL DATA SUPPLIED WILL REFERENCE THE UNIT PART NUMBER, APPLICABLE DASH NUMBER, AND APPLICABLE PURCHASE ORDER NUMBER.
 - A CERTIFICATE OF COMPLIANCE COVERING REQUIREMENTS OF PARA 2.A(3) AND 4.C. OF THIS SPECIFICATION AND PARA 3.3.3 OF ND1015404.
 - TEST DATA AS REQUIRED BY PARA 4.C OF THIS SPECIFICATION.



UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES	
TOLERANCES ON	
FRACTIONS	DECIMALS ANGLES
\pm	\pm \pm
DO NOT SCALE THIS DRAWING	
MATERIAL	
SEE NOTES	
HEAT TREATMENT	
FINAL FINISH	
NEXT ASSY	USED ON
APPLICATION	

QTY REQD	PART OR IDENTIFYING NO.	NOMENCLATURE OR DESCRIPTION	FIND NO.
LIST OF MATERIALS			
MIT INSTRUMENTATION LAB CAMBRIDGE, MASS. DWS. NO. 0 CONTRACT		MANNED SPACECRAFT CENTER HOUSTON, TEXAS	
DRAWN <i>Ray Wheeler</i> DATE <i>Aug 63</i> CHECKED <i>J. Ruggan</i> DATE <i>10/1/63</i> APPROVAL <i>By G. M. S. 10/1/63</i> APPROVAL <i>By C. M. 9/24/63</i>		RESISTOR, TEMPERATURE SENSITIVE, WAFER SPECIFICATION CONTROL DRAWING	
NASA APPROVAL <i>By M. L. 7/1/63</i> MIT APPROVAL <i>W. R. 10/1/63</i>		CODE IDENT NO. 80230 SIZE C	NASA DRAWING NO. 1006712
SCALE NONE		WT	SHEET 1 OF 2

NOTICE - WHEN GOVERNMENT DRAWINGS, SPECIFICATIONS, OR OTHER DATA ARE USED FOR ANY PURPOSE OTHER THAN IN CONNECTION WITH A DEFINITELY RELATED GOVERNMENT PROCUREMENT OPERATION, THE UNITED STATES GOVERNMENT THEREBY INCURS NO RESPONSIBILITY FOR ANY OBLIGATION WHATSOEVER, AND THE FACT THAT THE GOVERNMENT MAY HAVE FORMULATED, FURNISHED, OR IN ANY WAY SUPPLIED THE SAID DRAWINGS, SPECIFICATIONS OR OTHER DATA IS NOT TO BE REGARDED BY IMPLICATION OR OTHERWISE AS IN ANY MANNER LICENSING THE HOLDER OR ANY OTHER PERSON OR CORPORATION, OR CONVEYING ANY RIGHTS OR PERMISSION TO MANUFACTURE, USE, OR SELL ANY PATENTED INVENTION THAT MAY IN ANY WAY BE RELATED THERETO.

TABLE I

DASH NO.	ZERO-POWER RESISTANCE IN OHMS			DISSIPATION CONSTANT MW/°C MIN	TIME CONSTANT SECONDS MIN	DIMENSIONS			
	+25±0.1°C	0±0.1°C	+50±0.1°C			A	B	C	D NOM
-1	500±1%	1,635±3%	179.7±3%	2.25	5.25	.19 .11	.19 .11	.021 .019	.10
-2	1,000±1%	3,274±3%	359.5±3%	1.95	3.75	.13 .07	.13 .07	.021 .019	.10
-3	5,000±1%	17,700±3%	1,630±3%	3.225	8.95	.28 .18	.28 .18	.021 .019	.20

TABLE II

EXAMINATION OR TEST	REQUIREMENT PARAGRAPHS
GENERAL QUALIFICATION REQUIREMENTS	PARA. 3.2 THROUGH 3.9.2 OF ND - 1002057
GROUP I (ALL SAMPLES) VISUAL & MECHANICAL ZERO-POWER RESISTANCE	PARA 4.2.1 OF ND -1002057 PARA 4.5.2 OF MIL-T-23648 EXCEPT MEASURE AT 25°C, +50°C & 0°C
DISSIPATION CONSTANT THERMAL TIME CONSTANT MAXIMUM POWER RATING	PARA 4.5.4 OF MIL-T-23648 PARA 4.5.5 OF MIL-T-23648 PARA 3.3.7 OF MIL-T-23648 EXCEPT MEASURE POWER THAT PRODUCES TEMPERATURE RISE OF +80°C
GROUP II (1/3 OF SAMPLES) CHARACTERISTICS TEMPERATURE CYCLING THERMAL STABILITY LOW TEMPERATURE STORAGE TERMINAL STRENGTH	PARA 4.5.8 OF MIL-T-23648 (EXCEPT USE TEST CONDITION A OF MIL-STD-202) PARA 4.5.6 OF MIL-T-23648 EXCEPT TEMPERATURE IN PARA 4.5.6.2 WILL BE +105 ± 2°C PARA 4.5.7 OF MIL-T-23648 EXCEPT LOW TEMPERATURE WILL BE -55 ± 3°C PARA 4.5.10 OF MIL-T-23648
GROUP III (1/3 OF SAMPLES) VIBRATION SHOCK MOISTURE RESISTANCE	PARA 4.2.11 OF ND 1002057 (SEE NOTE 1) PARA 4.2.12 OF ND 1002057 (SEE NOTE 1) PARA 4.5.13 OF MIL-T-23648 (SEE NOTE 2)
GROUP IV (1/3 OF SAMPLES) LOAD LIFE LEAD COMPOSITION	PARA 4.5.15 OF MIL-T-23648 EXCEPT INITIAL RESISTANCE MAY BE MEASURED PRIOR TO START OF LIFE. MAX OPERATING TEMPERATURE IS +105°C PARA 4.2.16 OF ND 1002057

NOTE 1

THE AMOUNT OF POWER TO BE APPLIED WILL BE THAT NECESSARY TO RAISE THE THERMISTOR TEMPERATURE TO APPROX. +65°C UNDER NORMAL FREE AIR CONDITIONS. ZERO-POWER RESISTANCE WILL BE MEASURED BEFORE AND AFTER TEST PER PARA. 4.5.2. OF MIL-T-23648.

NOTE 2

INDICATED STEPS (a), (d), AND (f) REPLACED BY (1), (4), AND (7) RESPECTIVELY.

E 1006712

REVISIONS 03038			
SYM	DESCRIPTION	DATE	APPROVAL
-	INITIAL RELEASE CLASS A PER TDRR 03038	10/26/63	WPK
A	REVISED PER TDRR 06243	2-18-64	WPK
B	REVISED PER TDRR 08861	6/2/64	WPK
C	REVISED PER TDRR 12767	4/21/65	WPK
D	REVISED PER TDRR 19731	6/15/65	WPK
E	REVISED PER TDRR 24692	12/4/65	WPK

3.49

QTY REQD	PART OR IDENTIFYING NO.	NOMENCLATURE OR DESCRIPTION	FIND NO.
LIST OF MATERIALS			
MIT INSTRUMENTATION LAB CAMBRIDGE, MASS.		MANNED SPACECRAFT CENTER HOUSTON, TEXAS	
DRAWN <i>Ray W. Hale</i> DATE <i>15 Aug 63</i> CHECKED <i>S. Ruggen</i> DATE <i>14 Sep 63</i> APPROVAL <i>A. Y. G. MAYO</i> DATE <i>9/1/63</i> APPROVAL <i>E. R. Hale</i> DATE <i>9/24/63</i>		RESISTOR, TEMPERATURE SENSITIVE, WAFER SPECIFICATION CONTROL DRAWING	
NASA APPROVAL <i>W. J. Hale</i> DATE <i>9/1/63</i> MIT APPROVAL <i>W. J. Hale</i> DATE <i>10/1/63</i>		CODE IDENT NO. 80230 SCALE NONE	SIZE C WT SHEET 2 OF 2

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES ON FRACTIONS DECIMALS ANGLES ± ± ± DO NOT SCALE THIS DRAWING MATERIAL HEAT TREATMENT FINAL FINISH NEXT ASSY USED ON APPLICATION
--