

NOTICE - WHEN GOVERNMENT DRAWINGS, SPECIFICATIONS, OR OTHER DATA ARE USED FOR ANY PURPOSE OTHER THAN IN CONNECTION WITH A DEFINITELY RELATED GOVERNMENT PROCUREMENT OPERATION, THE UNITED STATES GOVERNMENT THEREBY INCURS NO RESPONSIBILITY FOR ANY OBLIGATIONS WHATSOEVER, AND THE FACT THAT THE GOVERNMENT MAY HAVE FORMULATED, FURNISHED, OR IN ANY WAY SUPPLIED THE SAID DRAWINGS, SPECIFICATIONS OR OTHER DATA IS NOT TO BE REGARDED BY IMPLICATION OR OTHERWISE AS IN ANY MANNER LICENSING THE HOLDER OR ANY OTHER PERSON OR CORPORATION, OR CONFIRMING ANY RIGHTS OR PERMISSION TO MANUFACTURE, USE, OR SELL ANY PATENTED INVENTION THAT MAY IN ANY WAY BE RELATED THERETO.

1006751

REVISIONS			
SYM	DESCRIPTION	DATE	APPROVAL
C	REPLACES REV B WITH CHANGE PER TDRR 00513		WLD
D	REVISED PER TDRR 01274	5-15-63	WLD

NOTES:


1. REQUIREMENTS:

- A. ENCAPSULATION: GLASS. UNITS SHALL BE HERMETICALLY SEALED.
- B. LEAD MATERIAL SHALL BE IRON-NICKEL ALLOY, COPPER CLAD, GOLD PLATED IN ACCORDANCE WITH NDPS 1015401. A CERTIFICATE OF COMPLIANCE WITH THIS REQUIREMENT SHALL ACCOMPANY EACH SHIPMENT.
- C. SHALL WITHSTAND A THERMAL SHOCK OF 300°C FROM 0°C WITHIN 30 SECONDS AND BE RETURNED TO ROOM AMBIENT WITHOUT AFFECTING OPERATING CHARACTERISTICS AS SPECIFIED HEREIN, IN ADDITION TO THE REQUIREMENTS OF ND 1002000.
- D. SUPPLIER SHALL CONFORM TO THE QUALITY ASSURANCE PROVISIONS OF ND1015404 SECTION II.
- E. UNITS SHALL BE 100 PERCENT INSPECTED FOR COMPLIANCE WITH THE REQUIREMENTS IN TABLE I UNLESS OTHERWISE SPECIFIED.
- F. TRANSIENT RESPONSE: USING A TECHTRONIX TYPE S PLUG-IN UNIT AND $I_F = 5$ MILLIAMPERES AND $I_R = 100$ MICROAMPERES, THE MEASURED TIME MUST BE LESS THAN .5 MICROSECOND. THE SLOPE OF THAT PORTION OF THE DISCHARGE CURVE CORRESPONDING TO LINEAR CAPACITANCE SHALL BE GREATER THAN .5 VOLTS AND .2 MICROSECOND.
- G. LEAD TESTS: EACH LEAD SHALL BE CAPABLE OF WITHSTANDING THE FOLLOWING TESTS:
 - (1) LEAD BEND TEST: WITH THE COMPONENT BODY HELD IN A VERTICAL POSITION AND A ONE POUND WEIGHT SUSPENDED IN AN AXIAL DIRECTION FROM THE LEAD UNDER TEST, 2 CYCLES OF BENDS SHALL BE ACCOMPLISHED. ONE CYCLE OF BENDS SHALL CONSIST OF MOVING THE BODY OF THE UNIT IN THE SAME PLANE THROUGH 90 DEGREES IN ONE DIRECTION THEN BACK 180 DEGREES IN THE OPPOSITE DIRECTION AND BACK 90 DEGREES TO THE ORIGINAL POSITION. NO MECHANICAL DAMAGE OR LACK OF PERFORMANCE SHALL BE EVIDENCED AFTER THE TEST.
 - (2) LEAD PULL TEST: EACH LEAD SHALL WITHSTAND AN AXIAL PULL OF 4 POUNDS MINIMUM. NO MECHANICAL DAMAGE OR LACK OF PERFORMANCE SHALL BE EVIDENCED AFTER THE TEST.
- H. EACH DIODE SHALL BE MICROSCOPICALLY INSPECTED, BEFORE PAINTING, UNDER 10X MAGNIFICATION, FOR FOREIGN PARTICLES, TIPPED DICE, INCOMPLETE SEALING, AND REDUCTION OF LEAD DIAMETER AT POINT OF FUSING.
- I. PREPARATION FOR DELIVERY: IN ACCORDANCE WITH MIL-S-19491 LEVEL C PRESERVATION AND PACKAGING AND LEVEL C PACKING. MARKING OF UNIT PACKAGES AND EXTERIOR SHIPPING CONTAINERS SHALL INCLUDE THE NASA DRAWING NUMBER AND REVISION LETTER.

2. INTERPRET DRAWING IN ACCORDANCE WITH STANDARDS PRESCRIBED BY MIL-D-70327.

FOR INFORMATION ONLY

CLASS B RELEASE TDR No. 00165 DATE 12-12-62



Ⓢ REPLACES REV B WITH CHANGE

D	—
C	—
REV — A	REV —
SHEET 1	SHEET 2
REVISION STATUS OF SHEETS	

MASTER

QTY REQD	PART OR IDENTIFYING NO.	NOMENCLATURE OR DESCRIPTION	FIND NO.
LIST OF MATERIALS			
MIT INSTRUMENTATION LAB CAMBRIDGE, MASS		MANNED SPACECRAFT CENTER HOUSTON, TEXAS	
DRAWN <i>Ray Wheeler</i> DATE 2/9/62 CHECKED <i>E. C. Hall</i> 27 Nov 62 APPROVAL <i>E. C. Hall</i> 11 Dec 62		SEMICONDUCTOR DEVICE, DIODE	
APPROVAL		SPECIFICATION CONTROL DRAWING	
NASA APPROVAL <i>W. J. R. Pliner</i> 12-12-62		CODE IDENT NO.	NASA DRAWING NO.
MIT APPROVAL <i>W. J. R. Pliner</i> 12/12/62		SIZE C	1006751
SCALE NONE		WT	SHEET 1 OF 2

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES	
TOLERANCES ON	
FRACTIONS	DECIMALS ANGLES
±	± ±
DO NOT SCALE THIS DRAWING	
MATERIAL	
SEE NOTE 1	
HEAT TREATMENT	
NONE	
FINAL FINISH	
NONE	
NEXT ASSY	USED ON
APPLICATION	

PROCURE ONLY FROM APPROVED SOURCES LISTED ON ND1002034 FOR THIS DRAWING

