

NOTICE - WHEN GOVERNMENT DRAWINGS, SPECIFICATIONS, OR OTHER DATA ARE USED FOR ANY PURPOSE OTHER THAN IN CONNECTION WITH A DEFINITELY RELATED GOVERNMENT PROCUREMENT OPERATION, THE UNITED STATES GOVERNMENT THEREBY INCURS NO RESPONSIBILITY FOR ANY OBLIGATION WHATSOEVER, AND THE FACT THAT THE GOVERNMENT MAY HAVE FORMULATED, FURNISHED, OR IN ANY WAY SUPPLIED THE SAID DRAWINGS, SPECIFICATIONS OR OTHER DATA IS NOT TO BE REGARDED BY IMPLICATION OR OTHERWISE AS IN ANY MANNER LICENSING THE HOLDER OR ANY OTHER PERSON OR CORPORATION, OR CONFESSING ANY RIGHTS OR PERMISSION TO MANUFACTURE, USE, OR SELL ANY PATENTED INVENTION THAT MAY IN ANY WAY BE RELATED THERETO.

H 6929001		REVISIONS	
SYM	DESCRIPTION	DATE	APPROVAL
H	REPLACES REV G WITH CHANGES AND UPGRADED TO CLASS A RELEASE PER TDRR 02923	8/2/63	[Signature]

REQUIREMENTS:

1. GENERAL:

- A. INTERPRET DRAWING IN ACCORDANCE WITH STANDARDS PRESCRIBED BY MIL-D-70327.
- B. UNITS SHALL MEET THE REQUIREMENTS OF MIL-S-19500 WITH THE MODIFICATIONS AND ADDITIONS SPECIFIED HEREIN.
- C. THE SUPPLIER SHALL CONFORM TO THE QUALITY ASSURANCE PROVISIONS AS CONTAINED IN ND 1015404, CLASS 2.
- D. UNITS SHALL BE CAPABLE OF MEETING THE QUALIFICATION REQUIREMENTS AS CONTAINED IN ND 1002048 UNLESS MODIFIED OR AMENDED BY SECTION 2 OF THIS DRAWING.
- E. PACKAGING AND PACKING: UNIT PACKAGING AND PACKING SHALL BE IN ACCORDANCE WITH MIL-S-19491, LEVEL A IN BOTH INSTANCES.


2. ACCEPTANCE AND INSPECTION:

- A. LOT: A LOT IS DEFINED AS A GROUP OF PARTS IN A SINGLE PROCUREMENT SELECTED FROM A SINGLE CONTINUOUS PRODUCTION RUN USING LIKE MATERIALS WHICH ARE CONTROLLED USING A PROCESS WHICH IS THE SAME FROM THE BEGINNING TO THE END OF THE RUN.
- B. INSPECTION CONDITIONS: UNLESS OTHERWISE SPECIFIED HEREIN ALL INSPECTIONS SHALL BE MADE AT AN AMBIENT TEMPERATURE OF PLUS 25 DEGREES CENTIGRADE PLUS OR MINUS 3 DEGREES CENTIGRADE.
- C. ELECTRICAL: 100% TESTING
 - (1) UNITS SHALL BE SUBJECT TO THE ELECTRICAL TESTS SPECIFIED IN ND 1002017.

D. MECHANICAL: (REFERENCE MIL-STD-750 AS MODIFIED HEREIN)

- (1) LEAD FATIGUE (DESTRUCTIVE): LEADS SHALL BE CAPABLE OF WITHSTANDING THE FOLLOWING LEAD BEND TEST. THE UNIT SHALL BE HELD IN A VERTICAL POSITION WITH A ONE-POUND WEIGHT SUSPENDED FROM THE LEAD UNDER TEST. TWO CYCLES OF BENDING SHALL BE PERFORMED, A CYCLE CONSISTING OF MOVING THE BODY OF THE UNIT, WHILE IN THE SAME PLANE, 90 DEGREES FROM THE VERTICAL IN ONE DIRECTION, THEN 180 DEGREES IN THE OPPOSITE DIRECTION AND BACK 90 DEGREES TO THE ORIGINAL POSITION. NO MECHANICAL DAMAGE SHALL BE EVIDENCED AFTER THE TEST. A SAMPLE OF 3 UNITS PER LOT SHALL BE TESTED.
- (2) LEAD TENSION: EACH LEAD SHALL BE CAPABLE OF WITHSTANDING AN AXIAL PULL OF 4 POUNDS MINIMUM FOR 30 SECONDS. NO MECHANICAL DAMAGE SHALL BE EVIDENCED AFTER THE TEST. A SAMPLE OF 3 UNITS PER LOT SHALL BE TESTED.
- (3) THE ABOVE MECHANICAL TEST TO BE PERFORMED ON ELECTRICAL REJECTS.

- (3) SEAL TEST: THE UNITS SHALL BE SUBJECT TO A HELIUM OR RADIFLO LEAK DETECTION TEST WITH A SENSITIVITY OF AT LEAST 1×10^{-6} CUBIC CENTIMETERS PER ATMOSPHERE PER SECOND. A LEAKAGE RATE OF THIS VALUE OR GREATER SHALL CONSTITUTE A FAILURE. THIS TEST SHALL BE PERFORMED ON A 100-PERCENT-OF-A-LOT BASIS.
- (4) VISUAL AND MECHANICAL EXAMINATION: MARKING SHALL BE LEGIBLE, THE CASE FINISH SHALL HAVE NO PITS, FLAKING OR CHIPPING, LEADS SHALL BE FREE FROM KINKS AND NICKS AND SHALL COMPLY WITH THE SPECIFIED LEAD MATERIAL REQUIREMENT. GLASS IN HEADER SHALL HAVE NO CRACKS, CHIPS OR BUBBLES. THIS TEST SHALL BE PERFORMED ON A 100-PERCENT-OF-A-LOT BASIS. THIS TEST PERFORMED UNDER 10X MAGNIFICATION



* SEE PAR 3.3.2

FIGURE 1

(H) REPLACES REV G WITH CHANGES


PROCURE ONLY FROM APPROVED SOURCES LISTED IN ND 1002034 FOR THIS DRAWING.

MASTER

H	H
SHEET 1	SHEET 2
REVISION STATUS OF SHEETS	

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES	MIT INSTRUMENTATION LAB	MANNED SPACECRAFT CENTER
TOLERANCES ON FRACTIONS DECIMALS ANGLES	CAMBRIDGE, MASS.	HOUSTON, TEXAS
DO NOT SCALE THIS DRAWING MATERIAL	CONTRACT	SEMICONDUCTOR DEVICE, INTEGRATED SENSE AMPLIFIER
SEE NOTES	DRAWN [Signature]	SPECIFICATION CONTROL DRAWING
HEAT TREATMENT	CHECKED [Signature]	NASA DRAWING NO. 1006769
FINAL FINISH	APPROVAL [Signature]	SCALE NONE WT
NEXT ASSY USED ON APPLICATION	MIT APPROVAL [Signature]	SHEET 1 OF 2

QTY REQD	PART OR IDENTIFYING NO.	NOMENCLATURE OR DESCRIPTION	FIND NO.
LIST OF MATERIALS			
MIT INSTRUMENTATION LAB		MANNED SPACECRAFT CENTER	
CAMBRIDGE, MASS.		HOUSTON, TEXAS	
DRAWN [Signature]		SEMICONDUCTOR DEVICE, INTEGRATED SENSE AMPLIFIER	
CHECKED [Signature]		SPECIFICATION CONTROL DRAWING	
APPROVAL [Signature]		NASA DRAWING NO. 1006769	
HEAT TREATMENT		CODE IDENT NO. C	SCALE NONE WT
FINAL FINISH		SHEET 1 OF 2	
NXT ASSY USED ON APPLICATION		MIT APPROVAL [Signature]	



NOTICE - WHEN GOVERNMENT DRAWINGS, SPECIFICATIONS, OR OTHER DATA ARE USED FOR ANY PURPOSE OTHER THAN IN CONNECTION WITH A DEFINITELY RELATED GOVERNMENT PROCUREMENT OPERATION, THE UNITED STATES GOVERNMENT THEREBY INCURS NO RESPONSIBILITY FOR ANY OBLIGATION WHATSOEVER, AND THE FACT THAT THE GOVERNMENT MAY HAVE FORMULATED, FURNISHED, OR IN ANY WAY SUPPLIED THE SAID DRAWINGS, SPECIFICATIONS OR OTHER DATA IS NOT TO BE REGARDED BY IMPLICATION OR OTHERWISE AS IN ANY MANNER LICENSING THE HOLDER OR ANY OTHER PERSON OR CORPORATION, OR CONVEYING ANY RIGHTS OR PERMISSION TO MANUFACTURE, USE, OR SELL ANY PATENTED INVENTION THAT MAY IN ANY WAY BE RELATED THERETO.

H 6929001

REVISIONS			
SYM	DESCRIPTION	DATE	APPROVAL
H	THIS SHEET ADDED AND UPGRADED TO CLASS A RELEASE PER TDRR 02823	9/28/63	JW

REQUIREMENTS (CONTINUED):

3. DESIGN:

A. MECHANICAL REQUIREMENTS:

- (1) LEAD MATERIAL SHALL BE IRON-NICKEL-COBALT ALLOY (KOVAR) IN ACCORDANCE WITH NASA DOCUMENT PS 1015402 EXCEPT LEAD DIAMETER SHALL BE AS FOLLOWS: THE LEAD DIAMETER IN THE ZONE BETWEEN .050 AND .250 FROM THE BASE SEAT SHALL BE .016 PLUS .003 MINUS .000, IN THE ZONE BETWEEN .250 AND 1.5 FROM THE BASE SEAT SHALL BE .021 MAXIMUM, AND OF THE REMAINDER OF THE LEAD SHALL BE UNCONTROLLED. A CERTIFICATE OF COMPLIANCE WITH THE LEAD MATERIAL REQUIREMENT SHALL ACCOMPANY EACH SHIPMENT.
- (2) MARKING:
 - (a) UNITS SHALL BE MARKED IN ACCORDANCE WITH MIL-STD-130 WITH THE MANUFACTURER'S IDENTIFICATION, DATE CODE, SERIAL NUMBER AND THE NUMBER 769. PLUS THE REVISION LETTER
 - (b) INTERIOR AND EXTERIOR SHIPPING CONTAINERS SHALL BE MARKED IN ACCORDANCE WITH MIL-STD-129 WITH THE MANUFACTURER'S NAME, LOT OR SERIAL NUMBER, DATE OF MANUFACTURE OR CODING AND THE NASA DRAWING NUMBER AND REVISION LETTER. A TAG MARKED WITH THE FOREGOING INFORMATION SHALL BE INCLUDED IN EACH CONTAINER.
- (3) ENCLOSURE: METAL CASE WITH GLASS HEADER, HERMETICALLY SEALED (REFERENCE JEDEC TO-5 CASE).
- (4) SEMICONDUCTOR MATERIAL: SILICON, NPN, DIFFUSED OXIDE PASSIVATED SURFACE.
- (5) INTERCONNECTIONS: THE DIFFUSED TRANSISTORS AND RESISTORS SHALL BE INTERCONNECTED AS SHOWN IN FIGURE 1.

THE TRANSISTORS SHALL BE SEPARATED FROM EACH OTHER AND FROM RESISTORS BY DIFFUSED ISOLATION REGIONS.

B. ELECTRICAL CHARACTERISTICS:

- (1) THE ELECTRICAL CHARACTERISTICS SHALL BE AS SPECIFIED IN SENSE AMPLIFIER ACCEPTANCE TEST PROCEDURE ND 1002017.
- (2) THE EQUIVALENT CIRCUIT IS SHOWN IN FIG. 1. THE RESISTOR VALUES SHALL BE $\pm 30\%$. RESISTOR R_3 AND R_4 SHALL BE GREATER THAN 20 OHMS.

C. ABSOLUTE MAXIMUM RATINGS:

- (1) POWER DISSIPATION: 75 MILLIWATTS MAXIMUM WHILE OPERATING IN THE TEST CIRCUIT OF ND 1002017.
- (2) STORAGE TEMPERATURE: MINUS 65 DEGREES CENTIGRADE TO PLUS 200 DEGREES CENTIGRADE.
- (3) OPERATING TEMPERATURE: MINUS 20 DEGREES CENTIGRADE TO PLUS 125 DEGREES CENTIGRADE.
- (4) THERMAL IMPEDANCE, JUNCTION TO CASE: .087 DEGREE CENTIGRADE PER MILLIWATT.
- (5) VOLTAGES: +20 VOLTS BETWEEN PIN 10 AND PIN 3.

4. SPECIAL CONDITIONS:

- A. HIGH TEMPERATURE STORAGE: ALL UNITS SHALL BE STORED FOR 250 HOURS AT 150 DEGREES CENTIGRADE MIN

Ⓜ THIS SHEET ADDED

QTY REQD	PART OR IDENTIFYING NO.	NOMENCLATURE OR DESCRIPTION	FIND NO.
LIST OF MATERIALS			
MIT INSTRUMENTATION LAB CAMBRIDGE, MASS.		MANNED SPACECRAFT CENTER HOUSTON, TEXAS	
DRAWN <i>C. G. G. DATE 15 Aug 63</i>		SEMICONDUCTOR DEVICE, INTEGRATED SENSE AMPLIFIER SPECIFICATION CONTROL DRAWING	
CHECKED <i>J. R. G. DATE 17 Aug 63</i>			
APPROVAL <i>E. D. G. DATE 27 Aug 63</i>			
HEAT TREATMENT		NASA APPROVAL <i>J. B. B. DATE 27 Aug 63</i>	CODE IDENT NO. SIZE C
NEXT ASSY USED ON		MIT APPROVAL <i>L. H. H. DATE 27 Aug 63</i>	NASA DRAWING NO. 1006769
APPLICATION		FINAL FINISH	SCALE NONE WT SHEET 2 OF 2

