†090101 ARE USED FOR ANY PURPOSE OTHER THAN IN CONNECTION WITH A DEFINITELY DESCRIPTION DATE APPROVAL RELATED GOVERNMENT PROCUREMENT OPERATION THE UNITED STATES GOVERN RESISTANCE MENT THEREBY INCURS NO RESPONSIBILITY NOR ANY OBLIGATION WHATSOEVER INITIAL RELEASE CLASS A AND THE FACT THAT THE GOVERNMENT MAY HAVE FORMULATED. FURNISHED OR NASA IN ANY WAY SUPPLIED THE SAID DRAWINGS. SPECIFICATIONS OR OTHER DATA IS OHMS PER TDRR 02559 NOT TO BE REGARDED BY IMPLICATION OR OTHERWISE AS IN ANY MANNER RESISTANCE (A) LICENSING THE HOLDER OR ANY OTHER PERSON OR CORPORATION. OR CONVEY-PART NUMBER ING ARY RIGHTS OR PERMISSION TO MANUFACTURE, USE, OR SELL ANY PATENTED INVENTION THAT MAY IN ANY WAY BE RELATED THERETO PART NUMBER OHMS, NOMINAL NOMINAL REVISED PER TDRR 80053 WK 20760 REQUIREMENTS: B REVISED PER TDRR 06773 GENERAL: REVISED PER TDRR 07/04 A. UNITS SHALL BE CAPABLE OF MEETING THE REQUIREMENTS OF SPECIFI-REVISED PER TORR 07314 CATION MIL-R-26 FOR INSULATED TYPE: EXCEPT AS SPECIFIED REVISED PER TORR 10810 7/1/4 WK HEREIN. REVISED PER TDRR 10925 660 UNITS SHALL BE CAPABLE OF MEETING THE QUALIFICATION REQUIRE-MENTS SPECIFIED IN ND 1002057 UNLESS MODIFIED OR AMENDED BY THE DESIGN REQUIREMENTS SECTION OF THIS DRAWING. 690 C. SUPPLIER SHALL CONFORM TO THE QUALITY ASSURANCE PROVISIONS SPECIFIED IN ND 1015404, CLASS 2. 710 D. INTERPRET DRAWING SYMBOLS, ABBREVIATIONS AND REFERENCE DESIGNATIONS IN ACCORDANCE WITH GOVERNMENT STANDARDS PRESCRIBED IN MIL-D-70327. 720 E. PACKAGING: UNITS SHALL BE PACKAGED IN ACCORDANCE WITH ND 1002129. 3300 INSPECTION AND ACCEPTANCE A. ELECTRICAL REQUIREMENTS: (1) RESISTANCE VALUE: PER TABLE (2) RESISTANCE TOLERANCE: ± 1% B. MECHANICAL REQUIREMENTS: (1) LEADS: IRON NICKEL ALLOY COPPER CLAD GOLD PLATED PER NASA 1000 SPECIFICATION PS 1015401. A CERTIFICATE OF COMPLIANCE OF LEAD MATERIAL SHALL ACCOMPANY EACH LOT SHIPPED. B. THE COMPLETE PART NUMBER IS THIS DRAWING (2) MARKING: , MARK UNITS PER" ND1002019 WITH MANUFACTURER'S NUMBER PLUS THE APPLICABLE DASH NUMBER. NAME AND/OR SYMBOL. NASA PART NUMBER, AND REVISION LET-TER, DATE CODE MANUFACTURER'S PART NUMBER MAY APPEAR ON THE PART OR PACKAGE. MARKING OF UNIT PACKAGES AND EXTERIOR SHIPPING CONTAINERS SHALL INCLUDE NASA PART NUMBER AND REVISION DERATING CHART LETTER .. PER MIL-STD-129. % RATED DESIGN REQUIREMENTS: A. PER MIL-R-26 EXCEPT AS MODIFIED BY THIS DRAWING. B. POWER RATING: 1 WATT AT +25°C, DERATED PER CHART. c. TEMPERATURE COEFFICIENT: ± 30 PPM/°C UP TO +275°C. · 019 D. EACH LEAD SHALL BE CAPABLE OF WITHSTANDING TWO (2) BENDS UNDER A TWO (2) POUND VERTICAL PULL (LEADS VERTICAL WITH RESPECT 100 150 200 250 300 350 TO UNIT BODY). TWO (2) BENDS SHALL BE ACCOMPLISHED BY MOVING THE BODY OF THE UNIT, WHILE IN THE SAME PLANE, THROUGH 90° IN ONE DIRECTION, THEN BACK 180° TO THE OPPO-AMBIENT TEMP. OC SITE DIRECTION, THEN BACK 90° TO THE ORIGINAL POSITION. NO MECHANICAL DAMAGE OR LACK OF PERFORMANCE SHALL BE EVI-DENCED AFTER THE TEST. E. MECHANICAL STRENGTH: PER MIL-R-26 EXCEPT 5 LB. MAX LOAD SPECIAL CONDITIONING BY SUPPLIER: A. BURN-IN: UNITS SHALL BE BURNED-IN FOR JOO HRS AT 25°C AND RATED WATTAGE 1-1/2 HRS ON, 1/2 HR OFF, UNITS THAT EXCEED NOMENCLATURE OR PART OR DESCRIPTION IDENTIFYING NO. THE INITIAL TOLERANCE OR CHANGE MORE THAN .5% SHALL BE LIST OF MATERIALS REJECTED. UNLESS OTHERWISE SPECIFIED MANNED SPACECRAFT CENTER INSTRUMENTATION LA DIMENSIONS ARE IN INCHES CAMBRIDGE MASS NAS HOUSTON, TEXAS TOLERANCES ON FRACTIONS DECIMALS PROCURE ONLY FROM APPROVED SOURCES LISTED IN CHECKED House 27 JULY 63 RESISTOR, FIXED, WIREWOUND ND 1002034 FOR THIS DRAWING. APPROVAVA & test 8/3/6 DO NOT SCALE THIS DRAWING 1 WATT MATERIAL SPECIFICATION CONTROL DRAWING APPROVA SEE NOTES HEAT TREATMENT NASA APPROVAL W) Raine CODE IDENT NO. SIZE NASA DRAWING NO. NONE 1010604 NEXT ASSY USED ON FINAL FINISH NONE **APPLICATION** INCHES

PHOTOGRAPHIC SCALE ONLY