THE basic principle of Surface Vessel recognition as with aircraft is familiarity with the *total form* of the object observed. The true character of a ship is not determined by a single feature or features but by the familiarity we may have with the total mass of the hull and superstructure, when viewed from great distances.


As in aircraft recognition, the salient recognition characteristics are shown in their simplest form by silhouettes. If this silhouette is further simplified into its basic masses, we obtain a silhouette where the minor details have disappeared, leaving only the real recognition features. It should be noted, however, that in one important respect ship silhouettes differ from those of aircraft. With planes, all three views are of nearly equal importance for correct identification, but in ship recognition, the use of the beam, or side view silhouette, is by far the most important. If the beam silhouette is thoroughly known, the ship can be recognized from either the surface or the air. This can be proven by examining any group of aerial views of ships.

Preceding each group of vessels of each nation represented in this manual is a chart of these simplified silhouettes representing a vessel of each class. These are arranged at the same scale for ease of comparison with each other and with other ships in the same class in other navies. Large instructional charts of these simplified silhouettes are being prepared and will be distributed in the near future. The present manual will serve as a text book in recognition courses inasmuch as it will have material, readily available, within a single cover, on all ships on the present operational list.

Sets of scale models of surface craft are available on request for supplementary instruction from the Bureau of Aeronautics for the Navy, and from the A. A. F. Training Aids Division, New York City, for the Army Air Forces. These are useful for detail examination and for various forms of realistic display on surfaces simulating water under varying light conditions, such as study of fleet maneuvers. The models are particularly valuable since they may be displayed at any angle and may be viewed from above to illustrate views of ships or groups of ships.

Motion pictures are available for a limited number of subjects and serve further to assist in recognition training.

Training in recognition of surface craft follows the same general pattern as in aircraft recognition. The principal value of the flash meter as a teaching device is that it forces the student to grasp total form as opposed to detail. It has already been indicated that this recognition of total mass is as essential for surface craft as for aircraft. Therefore, exposures of slides should be as brief as is consistent with the progress of the group being taught. While, in general, exposures will probably be at the one or one-half second rate, successful work on surface craft images has been reported at speeds up to 1/16 of a second.



NOTE: Terms later defined in the text of this section have been omitted in the following list.

ABAFT \_\_ behind; toward stern from.

ABEAM\_ at right angles to the keel.

AMIDSHIPS\_\_ the middle portion of a vessel.

ARMOR\_\_ steel plating designed to defeat shells,

bombs, or underwater explosion.

ARMOR BELT\_\_ band of armor extending along a ship's sides above and below water-line.

ATHWART \_\_ across; from side to side; transversly.

BEAM \_\_ extreme width of ship.

BILGE... curved part of ship's hull where sides and flat bottom meet.

BLISTER. \_ a bulge built into a ship's side as a protection against torpedoes.

 $BOOM.\_$  a free-swinging spar used to secure boats or to handle cargo, boats or aircraft.

 $\mathsf{BREAK}_{--}$  the point at which upper decks are discontinued.

BRIDGE\_\_ raised forward platform from which ship is conned and navigated.

BULKHEAD. \_ transverse or longitudinal partitions subdividing the interior of a ship.

BULWARKS\_\_ light plating or wooden extension of ship's sides above upper deck.

CASEMATE.\_ armored gun mount built into the sides or superstructure of a ship.

CLASS... vessels of the same type built to a common basic design.

COMBINED OPERATIONS.\_ joint operations conducted by nonhomogeneous forces or forces of different services and/or nationalities.

COMPANIONWAY - hatchway providing access from one deck to another.

COMPARTMENTATION\_ subdivision of a ship's hull by means of transverse and/or longitudinal bulkheads.

CONNING TOWER\_\_ armored ship control station. In submarines, the main deck structure.

COUNTER\_\_ side of a vessel's quarter.

COWL\_\_ a smoke baffle located on top of a funnel; opening of a ventilator.

DAMAGE CONTROL\_\_ comprehensive term for all means of mitigating or offsetting effects of damage aboard ship.

DEPTH CHARGE\_\_ explosive device projected or dropped from air or surface craft; detonated at predetermined depths by a hydrostatic mechanism.

DISPLACEMENT.. the weight of water displaced by a ship.

FANTAIL\_\_ after section of the main deck.

FORE\_\_ That part of a ship lying between bow and midship section.

FORE AND AFT\_\_ lengthwise of a ship.

FORECASTLE\_ deck; a forward upper deck extending to bow.

FREEBOARD... height of a ship's sides from waterline to a weather deck.

FLYING BRIDGE... a light self-supporting structure extending from side of ship's bridge.

GUN HOUSE\_\_ a lightly protected, rotating mount for guns of lesser calibre.

GUN SHIELD. any protection for gun crews which does not completely enclose mount.

GUNWALE\_\_ upper edge of a vessel's or boat's side. HALYARDS\_\_ light lines used in hoisting signals, flags, etc.

HATCH \_\_ opening in a deck.

HAWSE PIPES\_\_ tubes leading anchor chains from deck down and forward through bow plating.
HELM\_\_ the mechanism for operating the ship's rudder.

HULL\_ main body of a vessel exclusive of elements of superstructure.

ISLAND\_ a free-standing section of a ship's superstructure. On aircraft carriers, the ship's superstructure.

KEEL\_\_ center line strength member running fore and aft along the bottom of a ship.

KNOT... a unit of speed, equalling one nautical mile (6,080.20 feet) per hour.

LIST\_\_ transverse inclination of a vessel.

MAIN BATTERY\_\_ the heaviest calibre gun armament carried by a naval vessel.

MAIN DECK\_\_ a ship's highest continuous deck.
MINE\_\_ a device containing high explosive charge,
free-floating or anchored at fixed depth, or resting on bottom: detonated by contact, or by electrical or magnetic impulse.

MULTIPLE MAST\_\_ an exposed mast having one or more supporting elements.

PEAK (fore and aff)\_\_ compartment at the extreme bow or stern of vessel below decks—usually a tank.
PORT\_\_ left hand side of a vessel when looking towards bow; an opening.

QUARTER\_ that portion of a vessel's side near the stern.

QUARTER DECK.\_ part of upper deck reserved for officers; also the deck near the stern.

RADIO DIRECTION FINDER\_ device for determining direction of source of radio impulses.

RAKE\_\_ fore and aft inclination from vertical.

RANGEFINDER\_\_ optical instrument for determining distance to a target or other object.

RECIPROCATING ENGINE\_\_ a steam actuated piston engine as distinguished from a turbine.

RIGGING\_\_ collective term for ropes and chains employed to support masts, yards, and booms of vessel.

SECONDARY BATTERY... the gun armament next in calibre to main battery.

SHEER.\_ longitudinal upward or downward curvature of deck or gunwale.

SHEER LINE\_ line formed by intersection of deck and sides of a ship.

SPLINTER SCREEN\_ light armor shields for protection of crew.

STACK... exposed uptake from ship's boilers; funnel.

STARBOARD\_\_ the right hand side of a vessel when looking towards bow.

STEM\_\_ extreme forward line of bow.

STERN POST\_\_ the main vertical post in the stern frame upon which the rudder is hung.

SUPERSTRUCTURE\_ any structure built above a ship's hull.

TASK FORCE\_ a naval force organized to carry out a specific mission.

TURRET\_\_ a rotating mount enclosed by armor for guns of large calibre.

TWIN TURRET\_\_ a turret housing two guns.

TYPE\_\_ all vessels built or converted for the same purpose.

WELL\_ a lateral opening in a ship's hull or superstructure.

#### ATTRIBUTES OF FIGHTING SHIPS


A ship, to be classed as a fighting ship, must be capable of inflicting damage and of sustaining or avoiding damage. She must possess sufficient speed and maneuverability to execute her mission and the capacity to proceed independently to a scene of action. The type of a warship is determined by the degree to which each of these qualities has been stressed in her design.

#### ARMAMENT


Capacity to "dish it out" is a primary attribute of fighting ships. Ships may be designed to inflict damage by shells from their guns, torpedoes from their tubes, bombs from aircraft they may carry, or by depth charges or mines. Battleships and cruisers are essentially gun ships,

#### **PROTECTION**

A fighting ship must also be able to "take it." A ship may be designed to absorb punishment, to mitigate its effect, or to avoid it. She may be provided with armor: heavy steel plate around vital parts to defeat shells, bombs, and torpedoes. Her hull will be subdivided into separate spaces, or provided with bulges or blisters, to confine the effects of flooding and explosion. This is called compartmentation. Damage control systems consisting of provisions for counterflooding, fire fighting, etc., are developed in varying degree in all types. Speed and



although they carry other weapons. Carriers, minelayers, and torpedo boats are designed for special attack functions, with guns provided largely for defense, while destroyers and submarines are dual armament ships, using either guns or torpedoes. Larger types carry secondary batteries, primarily intended for defense against destroyers or submarines. or, if "dual purpose," for protection from attack from the air.




maneuverability in themselves constitute factors of protection in smaller types in which armament and protection have been sacrificed for these qualities, while submarines depend for protection largely on their ability to make themselves invisible by submerging.

#### MOBILITY

Most fighting ships are propelled by highpressure steam boilers and geared turbine engines, although Diesel or reciprocating engines are sometimes used in smaller types. Diesels are used in submarines when operating on the surface, electric storage battery motors when submerged.

Since a large proportion of total displacement and space is allotted to armament and protection in the design of battleships, these ships do not attain the high speeds of many smaller combat




units. Carriers are designed for speed, with corresponding sacrifice of armor. Cruisers' speed will range from 30 knots, which will permit a heavy cruiser to operate with the fleet and outrun most battleships, to speeds of over 40 knots in lighter types. Speed is essential to a destroyer's functions and new types are capable of attaining or bettering that of any cruiser.

#### SEA KEEPING

Without the capacity to reach a scene of operations, execute a mission, and return to a base, even the fastest and most powerful fighting ship would be of little value.

To bring an enemy to action is the battleship's primary function, and these ships must carry crews and provisions necessary to take them into battle with enough shells and fuel and food aboard to permit them to fight and return. Since cruisers are often required to perform independent missions at great distances, sea keeping capacity is a vital consideration in their design. Carriers must also be designed to accommodate provision for extended operations and fuel for their aircraft. Destroyers, as they



often operate with battle fleets or in convoy, must also carry provisions for such work, subject to limitations of size, while submarines are required to remain in enemy waters for extended periods. It will, therefore, be seen that sea keeping is a very important factor in the design of all more important types of fighting ships.


The bulky hull of the battleship (above) reflects capacity to accommodate provision for sea repair and for storage of immense quantities of fuel, water, food, ships stores, and lubricating oil, while the proportions of destroyer hulls indicate limitations in sea-keeping capacity inherent in their type.

# GERMAN NAVAL VESSELS






# SIMPLIFIED SILHOUETTES



DIVISION OF NAVAL INTELLIGENCE—IDENTIFICATION AND CHARACTERISTICS SECTION—JULY, 1942






SHIP BEYOND THE HORIZON


LENGTH 766' OA-741'-6" WL BEAM 98'-5" DRAFT 24'-7" (MEAN)

DISPLACEMENT











KNOTS	RPM
	350
	300
301/4	275
	250
****	245
27	240
	220
23	200
18	160
	150
121/2	120
*****	80

28 KTS




DIVISION OF NAVAL INTELLIGENCE—IDENTIFICATION AND CHARACTERISTICS SECTION—AUGUST, 1942



LENGTH 817' OA—792'—4" WL BEAM 118'-1" DRAFT 33'-9" (MAX.)

DISPLACEMENT 41,500 TONS (STANDARD)

DENSITY OF FIRE



# MAIN BATTERY 30° 0° 30° 4 8 4 140° 180° 140°

ARM	AMENT	MAX. ELEV.	RANGE
8-15" 12-5".9 16-4".1	TWIN TURRET TWIN TURRET TWIN A.A. SHIELD	40-45° 45° 70° (SLANT)	41,500 YD. 27,000 YD. 17,000 YD. YD.
	SMALLER A.A. RPEDO TUBES (TRIPLES) INE SCOUTS 2 CATAPUL		
		**	

PROTECTION  BELT—13" MAIN 5.7" UPPER TURRETS—13.8" FACE PLATES 7.9" SIDES 6" CROWNS CONNING TOWER 12.6" BARBETTES 13.8"	
SECONDARIES 2" (MAX.) ON TURRETS AND BARBETTES DECKS—2" MAIN DECK 4.75"—3.2" THIRD DECK THICKEST OVER VITALS	

- 1		
KN	ots	R.P.M.
		300
		275
		250
		245
	31	240
	30	220
		200
		160
		150
		120
		80
DES.	SPD.	DES, H.P.
301/4	KTS	150,000




TIRPITZ—BB4

BEGUN-OCTOBER 24, 1936. COMPLETED-NOVEMBER 10, 1940

SISTER SHIP-BISMARCK-SUNK MAY 27, 1941

DIVISION OF NAVAL INTELLIGENCE—IDENTIFICATION AND CHARACTERISTICS SECTION—AUGUST, 1942

ONI 204 RESTRICTED



ONI 204 RESTRICTED CONDENSED AND PRINTED FOR FM 30-50, NAVAER 00-80V-57

GRAF ZEPPELIN-CV1
DIVISION OF NAVAL INTELLIGENCE—IDENTIFICATION AND CHARACTERISTICS SECTION—SEPTEMBER, 1942

#### HEIGHT OF OBSERVER




HORIZON BEYOND THE SHIP

LENGTH-820' WL 850' OA (EST)

BEAM -88'-7"

DRAFT -18'-4"

SHIP BEYOND THE HORIZON



#### ARMAMENT

16-5"9 10-4"1

18-1"46 AA 4-0.79 AA

AIRCRAFT-40 (OFFICIAL)

#### **PROTECTION**

BELT-2-1/3" CASEMATES FOR 5."9 GUNS

#### PROPULSION

HP -110,000 SPEED-32 KNOTS




IT IS KNOWN THAT CERTAIN SUPERSTRUCTURAL FEATURES, INCLUDING AA BATTERY DISPOSITION, VARY FROM THESE DRAWINGS, WHICH ARE BELIEVED SUBSTANTIALLY CORRECT FOR HULL PROPORTION AND GENERAL OUTLINE. DETAILS OF PROFILES, AIR VIEWS AND TARGET ANGLES AWAIT BETTER RECONNAIS-SANCE PHOTOGRAPHS.




BEGUN—DECEMBER 1, 1936
DATA ON GERMAN CARRIERS IS LACKING IN SEVERAL IMPORTANT DETAILS, INCLUDING COMPLETION DATE OF GRAF ZEPPELIN.

ONI 204



R.A.F., 1941 🗸

DECEMBER 8, 1938 ♠




#### ONI 204 RESTRICTED CONDENSED AND PRINTED FOR FM 30-50, NAVAER 00-80V-57

### ADMIRAL HIPPER—CA1 DIVISION OF NAVAL INTELLIGENCE—IDENTIFICATION AND CHARACTERISTICS SECTION—JULY, 1942








HORIZON BEYOND THE SHIP


SHIP BEYOND THE HORIZON



DISPLACEMENT 10,000 TONS (STANDARD)



#### DENSITY OF FIRE MAIN BATTERY



#### ARMAMENT


MAX. ELEV.

RANGE

8-8" TWIN TURRETS 12-4.1 (D.P.)


70° (SLANT) 17,000 YD.

12 (PLUS) A.A. 12-21" TORPEDO TUBES (TRIPLES) 1 CATAPULT, 3 SEAPLANE SCOUTS



#### **PROTECTION**

BELT-4" (ESTIMATED) TURRETS CONNING TOWER-2" RANGEFINDERS-2" DECKS-THIRD DECK-31/4"





OTS	RPM
***********	420
	400
	350
***************************************	300
1	275
	250
	245
	240
	220
-	200
	160
********	150
	100
	80

DES. SPD DES. HP 32 KTS 95,000

BEGUN-JAN. 18, 1935 COMPLETED-APR. 29, 1939 SISTER SHIPS-EUGEN, SEYDLITZ, EX-LÜTZOW (SOLD TO RUSSIA) BLÜCHER (SUNK APRIL 9, 1940)

ONI 204








R.A.F. JAN. 26, 1941

ONI 204 RESTRICTED CONDENSED AND PRINTED FOR FM 30-50, NAVAER 00-80V-57 105

DIVISION OF NAVAL INTELLIGENCE—IDENTIFICATION AND CHARACTERISTICS SECTION—SEPTEMBER, 1942






LENGTH-609'-3" OA-596'-2" WL

BEAM —68'-3" DRAFT —23'-3" (MAXIMUM)

16'-5" (MEAN)

DISPLACEMENT 10,000 TONS (STANDARD)





MAX. ELEV.	RANGE
40°	36;000 YD.
30-40°	27,000 YD.
85°	
DRUPLE)	
	40° 30–40°

PROTECT	TON		
BELT— TURRETS—	4" WITH 11/2" IN 4" BASES 51/2" FACES	TERNALLY	
CONNING TOWE	2-3" SIDES R—5" 2" ROOF	DECKS—1½"—2½ 3" OVER	Z"
UNDERWATER P	ROTECTION VERY C	OMPLETE 3 OVER	VITALO
		*	
TIRE			

KNOTS	R.P.M.
	420
	400
	350
	300
	275
	250
	245
	240
	220
25	200
20	160
	150
15	120
10	80
ES. SPD	. DES. H.P.
28 KTS.	54,000

0

BEGUN—MAY 2, 1929. COMPLETED—JAN. 4, 1933 SISTER SHIPS: ADMIRAL SCHEER—CA7 ADMIRAL GRAF SPEE—SUNK DECEMBER 17, 1939


ONI 204 RESTRICTED





1937

1939-40




#### ONI 204 RESTRICTED CONDENSED AND PRINTED FOR FM 30-50, NAVAER 00-80V-57

#### ADMIRAL SCHEER-CA 7

DIVISION OF NAVAL INTELLIGENCE—IDENTIFICATION AND CHARACTERISTICS SECTION—SEPTEMBER, 1942




HEIGHT OF OBSERVER




HORIZON BEYOND THE SHIP

SHIP BEYOND THE HORIZON


LENGTH-617' 8" OA-596' 2" WL BEAM -71' 1"



DENSITY OF FIRE MAIN BATTERY



ARMAMENT MAX. ELEV. RANGE 6-11" (50) TRIPLE TURRETS 40° 36,100 YD. 8-5."9 (50) TWIN 30-40° 27,000 YD. 6-4".1 AA TWIN 85° 8-1,46 AA TWIN TORPEDOES 8-21" AIRCRAFT-2 FLOAT PLANES, 1 CATAPULT



BELT—4" AMIDSHIPS TAPERING TO 2" FORWARD AND AFT TURRETS—7" FACE PLATE—2" SIDES—5" TO 3" TOP BARBETTES—4"
CONNING TOWER—5" WITH 3" TOP DECKS—1" MAIN DECK; 11/2" SECOND DECK, 3" OVER VITALS UNDERWATER PROTECTION VERY COMPLETE;

**PROTECTION** 


EXTERNAL BULGES

KNOTS	R.P.M.
	420
	400
	350
	300
	275
	250
	245
	240
	220
	200
20	160
20	150
15	120
10	00

DES SPD DES HP 28 KTS 54,000




ONI 204










R.A.F.—APRIL 30, 1942



1941

DIVISION OF NAVAL INTELLIGENCE—IDENTIFICATION AND CHARACTERISTICS SECTION—AUGUST, 1942






LENGTH 5081/2' OA-4933/4' WL BEAM 47' DRAFT 171/2' DISPLACEMENT

DENSITY OF FIRE MAIN BATTERY 30° 7° 0° 7° 30°

5,400 TONS



#### ARMAMENT

8-5.9 SINGLE SHIELDS 3-3"5 A.A.

4-M.G.

4-19",7 TORPEDO TUBES

MAX. ELEV.


RANGE

18,750 YD.

#### **PROTECTION**

BELT—2" AMIDSHIPS, TAPERING TO 11/2" AT ENDS TURRETS—NONE, WEATHER SHIELDS ONLY CONNING TOWER—4" SECONDARY BATTERY—3" TO 4" VERT, SIDES 2" GUN HOUSES

DECKS-1"




CNOTS	R.P.M.
Page 14	420
	400
	300
	275
	245
*****	240
****	200
	150
	120
****	00

DES. SPD DES. HP 29 KTS 46,500







R.A.F. 1941

FEBRUARY 8, 1936

DIVISION OF NAVAL INTELLIGENCE—IDENTIFICATION AND CHARACTERISTICS SECTION—AUGUST, 1942



SHIP BEYOND THE HORIZON

15

LENGTH 570'-10" OA-554'-5" WL

BEAM 49'-10"

HEIGHT OF OBSERVER 105

90

75

60

45

30

DRAFT 17'-8" (FULL LOAD)


HORIZON BEYOND THE SHIP



DISPLACEMENT 6,000 TONS (STANDARD)


DENSITY OF FIRE MAIN BATTERY 10° 9° 19° 130° 130°

ARMA	MENT	MAX. ELEV.	RANGE
9-5.9	TRIPLE TURRETS	40°	27,000 YD.
6-3.5	TWIN A.A. SHIELDS	80°	
18 (PLUS)	SMALLER A.A.		
12-21"	TORPEDO TUBES (TRI	PLES)	
1 CATAPU	LT, 2 SEAPLANE SCOU	TS	




	TO	EC.	$\Gamma \cap \Gamma$	A.I.
PP	(())		1 1 ( ) 1	NI.

BELT-2" TAPERING TO 11/2" AT ENDS TURRETS-11/2" FACE PLATES, 11/4" SIDES, 3/4" BACK WALL BARBETTES-CONNING TOWER-3"-4" DECKS-2" (MAX.) POOR UNDERWATER PROTECTION




KNOTS	R.P.M.
	420
	400
	350
	300
	275
	250
	240
	220
	200
	160
	150
	120
	80


DES. SPD DES. HP 32 KTS 65,000















RANGE

20,000 YD.



DENSITY OF FIRE



MAX. ELEV.

50°

80°

ARMAMENT

9-5'9 TRIPLE TURRETS

6-3"5 H.A. TWIN TURRETS

8-14.6 A.A. TWIN TURRETS 12-21" TORPEDO TUBES (TRIPLE)


PROTECTION BELT—4" BEHIND BULGE
TURRETS—1½" FACE PLATES—1¼" SIDES—¾" BACK WALL BARBETTES—
F.C. TOWER—4" SECONDARY BATTERY— DECKS—34" TO 1½"
1 1

KNOTS	RPM
32	400
29	350
	300
22	250
20	245
	200
131/2	150


DE0 000	DEC UD
DES. SPD	DES. HP
32 KTS	TURBINE
	60,000
	DIESEL
	12,000


















LENGTH 603' OA-557' 9" WL BEAM 54' DRAFT 14'-3" (MEAN)

DISPLACEMENT 6,000 TONS (STANDARD)





DENSITY OF FIRE



PROTECTION	
BELT-13/4" AMIDSHIP	
TURRETS— 11/2" FACE PLATES 11/4" SIDE PLATES 3/4" REAR WALL	
BARBETTES— F.C. TOWER—4"	
DECKS— 34" TO 11/2" UNDER WATER PROTECTION VERY COMPLETE	
-	

MATERIAL SERVICES	
KNOTS	R.P.M.
	420
	400
****	350
	300
	275
	250
	225
	200
	175
	150
	125
-	100
DES. SPD 32 KTS.	DES. HP 72,000






#### ONI 204 RESTRICTED CONDENSED AND PRINTED FOR FM 30-50, NAVAER 00-80V-57

#### MAASZ CLASS-DD4-16

DIVISION OF NAVAL INTELLIGENCE—IDENTIFICATION AND CHARACTERISTICS SECTION—SEPTEMBER, 1942





LENGTH-381'OA-374' WL BEAM -37'-1"

DRAFT -9'-2" (MEAN)



DISPLACEMENT 1,625 TONS (STANDARD)

#### ARMAMENT

MAY CARRY MINES

5-5" GUN SHIELDS 4-1"46 AA 2-0.78 AA 8-21" TORPEDO TUBES (QUADRUPLE)



#### **PROPULSION**

BOILERS— H.P. WATER TUBE DESIGNED H.P.- 50,000 DESIGNED SPEED-36 KTS.

KNOTS	R.P.M.
35	420
201	400
263/	350
	275
23	250
	240
	220
19	160
14	150
	120
	80

SHIP BEYOND THE HORIZON


MAASZ CLASS—DD4-16

DIVISION OF NAVAL INTELLIGENCE—IDENTIFICATION AND CHARACTERISTICS SECTION—SEPTEMBER, 1942

SISTER SHIPS
RICHARD BEITZEN
PAUL JACOBI
THEODOR RIEDEL
HERMANN SCHOEMANN—DD7 1935

PAUL JACOBI
THEODOR RIEDEL
HERMANN S


RESTRICTED




LEBERECHT MAASZ J

PAUL JACOBI—1939 ↑













## "NARVIK" CLASS—DD 23-43 DIVISION OF NAVAL INTELLIGENCE—IDENTIFICATION AND CHARACTERISTICS SECTION—AUGUST, 1942

BEGUN—1939. COMPLETED—1940 NAMES AND NUMBERS UNREPORTED; "NARVIK" IS TEMPORARY CLASS DES-IGNATION DERIVED FROM A "NARVIK FLOTILLA" COMPRISED OF THESE BOATS. SISTER SHIPS—Z-23 (BRUNO HEINEMAN) Z-24-43

ONI 204 RESTRICTED






PHOTOS-1941

ONI 204 RESTRICTED CONDENSED AND PRINTED FOR FM 30-50, NAVAER 00-80V-57 MÖEWE CLASS SIMILAR WOLF CLASS—TB 7-12
DIVISION OF NAVAL INTELLIGENCE—IDENTIFICATION AND CHARACTERISTICS SECTION—SEPTEMBER, 1942 HEIGHT OF OBSERVER 90 90 75 60 60 45 45 30 30 15 HORIZON BEYOND THE SHIP SHIP BEYOND THE HORIZON LENGTH 304' OA-292' WL BEAM 28'-3" DRAFT 8'-8" (MAXIMUM) DISPLACEMENT 800 TONS (STANDARD)



ARMAMENT MAX. ELEV. RANGE
3-4\*1 DP SHIELDS 70°
2-1\*18 AA
6-21\* TORPEDO TUBES (TRIPLE)



#### PROPULSION


BOILERS— 3 SCHULTZ-THORNYCROFT
"MARINE" TYPE
FUEL— OIL 338 TONS
DESIGNED H.P.— 25,000

DESIGNED H.P.— 25,000
DESIGNED SPEED—34 KNOTS
ENDURANCE— 2,200 AT 20 KTS


B. I	0-	-	-	~
IVI			-	
I VI		ы		

BUILT AS A "DESTROYER" UNDER TERMS OF VERSAILLES TREATY. UNSATISFACTORY FOR DESTROYER WORK. REPORTED TO HAVE BOW RUDDER.

KINOLO	List sivis
******	420
*******	400
	350
	300
	275
	250
	245
	240
	220
	200
	160
	150
	120
	80 ]



ONI 204 RESTRICTED CONDENSED AND PRINTED FOR FM 30-50, NAVAER 00-80V-57 T1 CLASS-TB 13-42 DIVISION OF NAVAL INTELLIGENCE-IDENTIFICATION AND CHARACTERISTICS SECTION-AUGUST, 1943 HEIGHT OF OBSERVER 60 60 30 30 15 HORIZON BEYOND THE SHIP SHIP BEYOND THE HORIZON LENGTH-279'8" OA-267'1" WL BEAM -28'3" DRAFT -6'3" (MEAN) DISPLACEMENT 600 TONS (STANDARD) ARMAMENT **PROPULSION** NOTES MAX. RANGE 1-4"1 (SHIELDED) GEARED TURBINES **EMPLOYMENT** .460 .440 1-1,46 HIGH PRESSURE WATER TUBE -SCREENING MAJOR SURFACE UNITS .420 5-AAMG BOILERS -"STIFFENING" COASTAL CONVOY .400 6-21' TORPEDO TUBES H.P.-22,000 380 ESCORTS AND PATROL FLOTILLAS DESIGNED SPEED-36 KNOTS -COVER AM AND AIRCRAFT RESCUE 340 VESSELS .320 .300 DANGEROUS OPPONENTS AT LOW VISI-.280 260 BILITY BECAUSE OF LOW SILHOUETTE 240 AND HEAVY TORPEDO BATTERY 160



# ITALIAN NAVAL VESSELS



