

to create a diffusion between the nickel and the iron substrate; with an additional layer of natural nickel-graphite then electrolytically plated on the top side of the strip of the nickel plated steel strip; with the nickel-graphite, nickel plated material sufficiently ductile and adherent to the substrate to permit forming without cracking, flaking, peeling, or any other evidence of separation; having a coating thickness: top side: nickel-graphite, tin-nickel layer  $\geq 1.0$  micrometers; nickel-graphite layer  $\geq 0.5$  micrometers; bottom side: nickel layer  $\geq 1.0$  micrometers; (c) diffusion annealed nickel-graphite plated products, which are cold-rolled or tin mill black plate base metal conforming to the chemical requirements based on AISI 1006; having the bottom side of the base metal first electrolytically plated with natural nickel, and the top side of the strip then plated with a nickel-graphite composition; with the strip then annealed to create a diffusion of the nickel-graphite and the iron substrate on the bottom side; with the nickel-graphite and nickel plated material sufficiently ductile and adherent to the substrate to permit forming without cracking, flaking, peeling, or any other evidence of separation; having coating thickness: top side: nickel-graphite layer  $\geq 1.0$  micrometers; bottom side: nickel layer  $\geq 1.0$  micrometers; (d) nickel-phosphorous plated diffusion annealed nickel plated carbon product, having a natural composition mixture of nickel and phosphorus electrolytically plated to the top side of a diffusion annealed nickel plated steel strip with a cold rolled or tin mill black plate base metal conforming to the chemical requirements based on AISI 1006; with both sides of the base metal initially electrolytically plated with natural nickel, and the material then annealed to create a diffusion of the nickel and iron substrate; another layer of the natural nickel-phosphorous then electrolytically plated on the top side of the nickel plated steel strip; with the nickel-phosphorous, nickel plated material sufficiently ductile and adherent to the substrate to permit forming without cracking, flaking, peeling or any other evidence of separation; having a coating thickness: top side: nickel-phosphorous, nickel layer  $\geq 1.0$  micrometers; nickel-phosphorous layer  $\geq 0.1$  micrometers; bottom side: nickel layer  $\geq 1.0$  micrometers; (e) diffusion annealed, tin-nickel plated products, electrolytically plated with natural nickel to the top side of a diffusion annealed tin-nickel plated cold rolled or tin mill black plate

base metal conforming to the chemical requirements based on AISI 1006; with both sides of the cold rolled strip initially electrolytically plated with natural nickel, with the top side of the nickel plated strip electrolytically plated with tin and then annealed to create a diffusion between the nickel and tin layers in which a nickel-tin alloy is created, and an additional layer of natural nickel then electrolytically plated on the top side of the strip of the nickel-tin alloy; sufficiently ductile and adherent to the substrate to permit forming without cracking, flaking, peeling or any other evidence of separation; having coating thickness: top side: nickel-tin-nickel combination layer  $\geq 1.0$  micrometers; tin layer only  $\geq 0.05$  micrometers; bottom side: nickel layer  $\geq 1.0$  micrometers; and (f) tin mill products for battery containers, tin and nickel plated on a cold rolled or tin mill black plate base metal conforming to chemical requirements based on AISI 1006; having both sides of the cold rolled substrate electrolytically plated with natural nickel; then annealed to create a diffusion of the nickel and iron substrate; then an additional layer of natural tin electrolytically plated on the top side; and again annealed to create a diffusion of the tin and nickel alloys; with the tin-nickel, nickel plated material sufficiently ductile and adherent to the substrate to permit forming without cracking, flaking, peeling or any other evidence of separation; having a coating thickness: top side: nickel-tin layer  $\geq 1$  micrometer; tin layer alone  $\geq 0.05$  micrometers; bottom side: nickel layer  $\geq 1.0$  micrometer.

Also excluded from this order are products meeting the following specifications: (1) Widths ranging from 10 millimeters (0.394 inches) through 100 millimeters (3.94 inches); (2) thicknesses, including coatings, ranging from 0.11 millimeters (0.004 inches) through 0.60 millimeters (0.024 inches); and (3) a coating that is from 0.003 millimeters (0.00012 inches) through 0.005 millimeters (0.000196 inches) in thickness and that is comprised of either two evenly applied layers, the first layer consisting of 99% zinc, 0.5% cobalt, and 0.5% molybdenum, followed by a layer consisting of phosphate, or three evenly applied layers, the first layer consisting of 99% zinc, 0.5% cobalt, and 0.5% molybdenum followed by a layer consisting of phosphate, and finally a layer consisting of silicate.

### Initiation of Changed Circumstances Antidumping Duty Administrative Review, and Intent To Revoke Order in Part

Pursuant to sections 751(d)(1) and 782(h)(2) of the Act, the Department may revoke an antidumping or countervailing duty order, in whole or in part, based on a review under section 751(b) of the Act (*i.e.*, a changed circumstances review) where the Department determines that "producers accounting for substantially all of the production of that domestic like product have expressed a lack of interest in issuance of an order." See section 782(h)(2) of the Act. See *e.g.*, *Certain Cold-Rolled Carbon Steel Flat Products From the Netherlands: Initiation and Preliminary Results of Changed Circumstances Review*, 66 FR 57415, 57416 (November 15, 2001).

Furthermore, 19 CFR 351.222(g)(1) provides that the Department will conduct a changed circumstances administrative review under 19 CFR 351.216, and may revoke an order (in whole or in part), if it determines that producers accounting for substantially all of the production of the domestic like product to which the order pertains have expressed a lack of interest in the relief provided by the order, in whole or in part, or if other changed circumstances sufficient to warrant revocation exist. In addition, in the event that the Department concludes that expedited action is warranted, 19 CFR 351.221(c)(3)(ii) permits the Department to combine the notices of initiation and preliminary results.

In accordance with sections 751(d)(1) and 782(h)(2) of the Act, and 19 CFR 351.216 and 351.222(g), based on affirmative statements by domestic producers of the like product, Bethlehem Steel Corporation, National Steel Corporation, and United States Steel Corporation ("Domestic Producers"), no further interest exists in continuing the order with respect to certain corrosion-resistant carbon steel flat products meeting the following specifications: (1) Flat-rolled products (provided for in HTSUS subheading 7210.49.00), other than of high-strength steel, known as "ASE Iron Flash" and either: (A) Having a base layer of zinc-based zinc-iron alloy applied by hot-dipping and a surface layer of iron-zinc alloy applied by electrolytic process, the weight of the coating and plating not over 40 percent by weight of zinc; or (B) two-layer-coated corrosion-resistant steel with a coating composed of (a) a base coating layer of zinc-based zinc-iron alloy by hot-dip galvanizing process, and (b) a surface coating layer