

TABLE 5 TO SUBPART DDDD.—PERFORMANCE TESTING AND INITIAL COMPLIANCE DEMONSTRATIONS FOR THE COMPLIANCE OPTIONS AND OPERATING REQUIREMENTS—Continued

For each . . .	For the following compliance options and operating requirements . . .	You have demonstrated initial compliance if . . .
(7) Process unit listed in Table 1B of this subpart controlled by routing exhaust to a combustion unit with heat input capacity greater than or equal to 44 megawatts.	Compliance options in Table 1B of this subpart or the emissions averaging compliance option in § 63.2240(c).	You submit with your Notification of Compliance Status documentation showing that your combustion unit has a heat input capacity greater than or equal to 44 megawatts and that the process exhausts controlled enter into the flame zone.

TABLE 6 TO SUBPART DDDD.—INITIAL COMPLIANCE DEMONSTRATIONS FOR WORK PRACTICE REQUIREMENTS

For each. . .	For the following work practice requirements. . .	You have demonstrated initial compliance if. . .
(1) Dry rotary dryer	Process furnish with an inlet moisture content less than or equal to 30 percent (by weight, dry basis) AND operate with an inlet dryer temperature of less than or equal to 600°F.	You meet the work practice requirement AND you submit a signed statement with the Notification of Compliance Status that the dryer meets the criteria of a “dry rotary dryer” AND you have a record of the inlet moisture content and inlet dryer temperature (as required in § 63.2263).
(2) Hardwood veneer dryer	Process less than 30 volume percent softwood species.	You meet the work practice requirement AND you submit a signed statement with the Notification of Compliance Status that the dryer meets the criteria of a “hardwood veneer dryer” AND you have a record of the percentage of softwoods processed in the dryer (as required in § 63.2264).
(3) Softwood veneer dryer	Minimize fugitive emissions from the dryer doors and the green end.	You meet the work practice requirement AND you submit with the Notification of Compliance Status a copy of your plan for minimizing fugitive emissions from the veneer dryer heated zones (as required in § 63.2265).
(4) Veneer redryers	Process veneer with an inlet moisture content of less than or equal to 25 percent (by weight, dry basis).	You meet the work practice requirement AND you submit a signed statement with the Notification of Compliance Status that the dryer operates only as a redryer AND you have a record of the veneer inlet moisture content of the veneer processed in the redryer (as required in § 63.2266).

TABLE 7 TO SUBPART DDDD.—CONTINUOUS COMPLIANCE WITH THE COMPLIANCE OPTIONS AND OPERATING REQUIREMENTS

For . . .	For the following compliance options and operating requirements . . .	You must demonstrate continuous compliance by . . .
(1) Each process unit listed in Tables 1A and 1B of this subpart or used in calculation of emissions averaging credits under § 63.2240(c).	Compliance options in Tables 1A and 1B of this subpart or the emissions averaging compliance option in § 63.2240(c) and the operating requirements in Table 2 of this subpart based on monitoring of operating parameters.	Collecting and recording the operating parameter monitoring system data listed in Table 2 of this subpart for the process unit according to § 63.2268(a)–(e); AND reducing the operating parameter monitoring system data to the specified average in units of the applicable requirement according to calculations in § 63.2268(a); AND maintaining the average operating parameter at or above the maximum, at or below the minimum, or within the range (whichever applies) established according to § 63.2262.
(2) Each process unit listed in Tables 1A and 1B of this subpart or used in calculation of emissions averaging credits under § 63.2240(c).	Compliance options in Tables 1A and 1B of this subpart or the emissions averaging compliance option in § 63.2240(c) and the operating requirements in Table 2 of this subpart based on THC CEMS data.	Collecting and recording the THC monitoring data listed in Table 2 of this subpart for the process unit according to § 63.2268(g); AND reducing the CEMS data to 3-hour block averages according to calculations in § 63.2268(g); AND maintaining the 3-hour block average THC concentration in the exhaust gases less than or equal to the THC concentration established according to § 63.2262.