

TABLE 10 TO SUBPART DDDD.—APPLICABILITY OF GENERAL PROVISIONS TO SUBPART DDDD—Continued

| Citation                         | Subject                                     | Brief description   | Applies to subpart DDDD |
|----------------------------------|---|---|-------------------------|
| § 63.10(b)(2)(vii)–(ix) .....    | Records .....                               | Measurements to demonstrate compliance with compliance options and operating requirements; performance test, performance evaluation, and visible emission observation results; measurements to determine conditions of performance tests and performance evaluations. | Yes.                    |
| § 63.10(b)(2)(xii) .....         | Records .....                               | Records when under waiver .....   | Yes.                    |
| § 63.10(b)(2)(xiii) .....        | Records .....                               | Records when using alternative to relative accuracy test.   | Yes.                    |
| § 63.10(b)(2)(xiv) .....         | Records .....                               | All documentation supporting initial notification and notification of compliance status.  | Yes.                    |
| § 63.10(b) (3) .....             | Records .....                               | Applicability Determinations .....  | Yes.                    |
| § 63.10(c)(1)–(6),(9)–(15) ..... | Records .....                               | Additional Records for CMS .....  | Yes.                    |
| § 63.10(c)(7)–(8) .....          | Records .....                               | Records of excess emissions and parameter monitoring exceedances for CMS.   | No.                     |
| § 63.10(d)(1) .....              | General Reporting Requirements ...          | Requirement to report .....   | Yes.                    |
| § 63.10(d)(2) .....              | Report of Performance Test Results.         | When to submit to Federal or State authority .....  | Yes.                    |
| § 63.10(d)(3) .....              | Reporting Opacity or VE Observations.       | What to report and when .....   | NA.                     |
| § 63.10(d)(4) .....              | Progress Reports .....                      | Must submit progress reports on schedule if under compliance.   | Yes.                    |
| § 63.10(d)(5) .....              | Startup, Shutdown, and Malfunction Reports. | Contents and submission .....   | Yes.                    |
| § 63.10(e)(1)–(2) .....          | Additional CMS Reports .....                | Must report results for each CEM Reports on a unit; written copy of performance evaluation; 3 copies of COMS performance evaluation.  | Yes.                    |
| § 63.10(e)(3) .....              | Reports .....                               | Excess Emission Reports .....   | No.                     |
| § 63.10(e)(4) .....              | Reporting COMS data .....                   | Must submit COMS data with performance test data  | NA.                     |
| § 63.10(f) .....                 | Waiver for Recordkeeping/Reporting.         | Procedures for Administrator to waive .....   | Yes.                    |
| § 63.11 .....                    | Flares .....                                | Requirements for flares .....   | NA.                     |
| § 63.12 .....                    | Delegation .....                            | State authority to enforce standards .....  | Yes.                    |
| § 63.13 .....                    | Addresses .....                             | Addresses where reports, notifications, and requests are send.  | Yes.                    |
| § 63.14 .....                    | Incorporation by Reference .....            | Test methods incorporated by reference .....  | Yes.                    |
| § 63.15 .....                    | Availability of Information .....           | Public and confidential information .....   | Yes.                    |

**Appendix A to Subpart DDDD—  
Alternative Procedure To Determine  
Capture Efficiency From A Hot Press  
Enclosure in the Plywood and  
Composite Wood Products Industry  
Using Sulfur Hexafluoride Tracer Gas**

**1.0 Scope and Application**

This procedure has been developed specifically for the proposed rule for the plywood and composite wood products

industry and is used to determine the capture efficiency of a partial hot press enclosure in that industry. This procedure is applicable for the determination of capture efficiency for press enclosures that are not considered to be permanent total enclosures (PTEs) as defined in EPA Method 204 and is proposed as an alternative to the construction of temporary total enclosures (TTEs). Sulfur hexafluoride (SF<sub>6</sub>) is used as a tracer gas (other tracer gases may be used if approved by the

Administrator). This gas is not indigenous to the ambient atmosphere and is nonreactive.

This procedure uses infrared spectrometry (IR) as the analytical technique. When the infrared spectrometer used is a Fourier-Transform Infrared spectrometer (FTIR), an alternate instrument calibration procedure may be used; the alternate calibration procedure is the calibration transfer standard (CTS) procedure of EPA Method 320. Other analytical techniques which are capable of