

in this investigation, the hearing will tentatively be held two days after the deadline for submission of the rebuttal briefs, at the U.S. Department of Commerce, 14th Street and Constitution Avenue, NW, Washington, DC 20230. Parties should confirm by telephone the time, date, and place of the hearing 48 hours before the scheduled time. Interested parties who wish to request a hearing, or to participate if one is requested, must submit a written request within 10 days of the publication of this notice. Requests should specify the number of participants and provide a list of the issues to be discussed. Oral presentations will be limited to issues raised in the briefs. See 19 CFR 351.310.

We will make our final determination no later than 135 days after the date of publication of this preliminary determination, pursuant to section 735(a)(1) of the Act.

This determination is published pursuant to sections 733(f) and 777(i) of the Act.

Dated: March 14, 2003.

Joseph A. Spetrini,

Acting Assistant Secretary for Import Administration.

[FR Doc. 03-6736 Filed 3-19-03; 8:45 am]

BILLING CODE 3510-05-P

DEPARTMENT OF COMMERCE

International Trade Administration

[A-201-822]

Notice of Amended Final Results of Antidumping Duty Administrative Review: Stainless Steel Sheet and Strip in Coils From Mexico

AGENCY: Import Administration, International Trade Administration, Department of Commerce.

ACTION: Notice of amended final results of antidumping duty administrative review of stainless steel sheet and strip from Mexico.

EFFECTIVE DATE: March 20, 2003.

SUMMARY: On February 11, 2003, the Department of Commerce (the Department) published in the **Federal Register** its notice of final results of the antidumping duty administrative review of stainless steel sheet and strip in coils from Mexico for the period July 1, 2000 through June 30, 2001. See *Stainless Steel Sheet and Strip in Coils from Mexico; Final Results of Antidumping Duty Administrative Review*, 68 FR 6889 (February 11, 2003). We are amending our final determination to correct ministerial errors alleged by respondent and petitioners.

FOR FURTHER INFORMATION CONTACT: Deborah Scott or Robert James, AD/CVD Enforcement, Group III, Import Administration, International Trade Administration, U.S. Department of Commerce, 14th Street and Constitution Avenue, NW., Washington, DC 20230, telephone: (202) 482-2657 or (202) 482-0649, respectively.

SUPPLEMENTARY INFORMATION:

Scope of the Review

For purposes of this administrative review, the products covered are certain stainless steel sheet and strip in coils. Stainless steel is an alloy steel containing, by weight, 1.2 percent or less of carbon and 10.5 percent or more of chromium, with or without other elements. The subject sheet and strip is a flat-rolled product in coils that is greater than 9.5 mm in width and less than 4.75 mm in thickness, and that is annealed or otherwise heat treated and pickled or otherwise descaled. The subject sheet and strip may also be further processed (e.g., cold-rolled, polished, aluminized, coated, etc.) provided that it maintains the specific dimensions of sheet and strip following such processing.

The merchandise subject to this order is classified in the Harmonized Tariff Schedule of the United States (HTS) at subheadings: 7219.13.00.31, 7219.13.00.51, 7219.13.00.71, 7219.13.00.81, 7219.14.00.30, 7219.14.00.65, 7219.14.00.90, 7219.32.00.05, 7219.32.00.20, 7219.32.00.25, 7219.32.00.35, 7219.32.00.36, 7219.32.00.38, 7219.32.00.42, 7219.32.00.44, 7219.33.00.05, 7219.33.00.20, 7219.33.00.25, 7219.33.00.35, 7219.33.00.36, 7219.33.00.38, 7219.33.00.42, 7219.33.00.44, 7219.34.00.05, 7219.34.00.20, 7219.34.00.25, 7219.34.00.30, 7219.34.00.35, 7219.35.00.05, 7219.35.00.15, 7219.35.00.30, 7219.35.00.35, 7219.90.00.10, 7219.90.00.20, 7219.90.00.25, 7219.90.00.60, 7219.90.00.80, 7220.12.10.00, 7220.12.50.00, 7220.20.10.10, 7220.20.10.15, 7220.20.10.60, 7220.20.10.80, 7220.20.60.05, 7220.20.60.10, 7220.20.60.15, 7220.20.60.60, 7220.20.60.80, 7220.20.70.05, 7220.20.70.10, 7220.20.70.15, 7220.20.70.60, 7220.20.70.80, 7220.20.80.00, 7220.20.90.30, 7220.20.90.60, 7220.90.00.10, 7220.90.00.15, 7220.90.00.60, and 7220.90.00.80. Although the HTS subheadings are provided for convenience and Customs purposes, the Department's written description of the

merchandise under review is dispositive.

Excluded from the scope of this order are the following: (1) Sheet and strip that is not annealed or otherwise heat treated and pickled or otherwise heat descaled; (2) sheet and strip that is cut to length; (3) plate (*i.e.*, flat-rolled stainless steel products of a thickness of 4.75 mm or more); (4) flat wire (*i.e.*, cold-rolled sections, with a prepared edge, rectangular in shape, of a width of not more than 9.5 mm); and (5) razor blade steel. Razor blade steel is a flat-rolled product of stainless steel, not further worked than cold-rolled (cold-reduced), in coils, of a width of not more than 23 mm and a thickness of 0.266 mm or less, containing, by weight, 12.5 to 14.5 percent chromium, and certified at the time of entry to be used in the manufacture of razor blades. See Chapter 72 of the HTSUS, "Additional U.S. Note" 1(d).

In response to comments by interested parties the Department has determined that certain specialty stainless steel products are also excluded from the scope of this order. These excluded products are described below.

Flapper valve steel is defined as stainless steel strip in coils containing, by weight, between 0.37 and 0.43 percent carbon, between 1.15 and 1.35 percent molybdenum, and between 0.20 and 0.80 percent manganese. This steel also contains, by weight, phosphorus of 0.025 percent or less, silicon of between 0.20 and 0.50 percent, and sulfur of 0.020 percent or less. The product is manufactured by means of vacuum arc remelting, with inclusion controls for sulphide of no more than 0.04 percent and for oxide of no more than 0.05 percent. Flapper valve steel has a tensile strength of between 210 and 300 ksi, yield strength of between 170 and 270 ksi, plus or minus 8 ksi, and a hardness (Hv) of between 460 and 590. Flapper valve steel is most commonly used to produce specialty flapper valves for compressors.

Also excluded is a product referred to as suspension foil, a specialty steel product used in the manufacture of suspension assemblies for computer disk drives. Suspension foil is described as 302/304 grade or 202 grade stainless steel of a thickness between 14 and 127 microns, with a thickness tolerance of plus-or-minus 2.01 microns, and surface glossiness of 200 to 700 percent Gs. Suspension foil must be supplied in coil widths of not more than 407 mm, and with a mass of 225 kg or less. Roll marks may only be visible on one side, with no scratches of measurable depth. The material must exhibit residual stresses