

- (i) thickness at least 0.8 mm but not greater than 1.0 mm; yield strength at least 590 N/mm² but not greater than 730 N/mm²; and elongation at least 13 percent but not greater than 20 percent;
 - (ii) thickness at least 1.0 mm but not greater than 1.2 mm; yield strength at least 580 N/mm² but not greater than 730 N/mm²; and elongation at least 14 percent but not greater than 21 percent;
 - (iii) thickness at least 1.2 mm but not greater than 1.6 mm; yield strength at least 580 N/mm² but not greater than 730 N/mm²; and elongation at least 14 percent but not greater than 22 percent; or
 - (iv) thickness at least 1.6 mm but not greater than 2.3 mm; yield strength at least 580 N/mm² but not greater than 730 N/mm²; and elongation at least 14 percent;
- (ccxlii) cold-rolled flat-rolled steel products, designated as A-694, the foregoing with thickness 1.0 mm or more but not over 2.3 mm; having the following chemical composition (percent by weight): carbon not over 0.09, silicon not over 1.0, manganese not over 3.00, phosphorus not over 0.012 and sulfur not over 0.005; tensile strength 980 N/mm² or more but not over 1080 N/mm²; yield strength 800 N/mm² or more but not over 980 N/mm²; elongation 6 percent or more but not over 14 percent; stretch flangeability at least 70 percent;
- (ccxliii) cold-rolled flat-rolled steel products, designated as A-694, the foregoing having the following chemical composition (percent by weight): carbon not over 0.10, silicon not over 0.80, manganese not over 2.5, phosphorus not over 0.015 and sulfur not over 0.010; tensile strength at least 780 N/mm²; meeting one of the following sets of properties:
- (i) thickness at least 0.6 mm but not greater than 0.8 mm; yield strength at least 420 N/mm² but not greater than 645 N/mm²; and elongation at least 14 percent but not greater than 25 percent;
 - (ii) thickness at least 0.8 mm but not greater than 1.0 mm; yield strength at least 410 N/mm² but not greater than 635 N/mm²; and elongation at least 15 percent but not greater than 26 percent;
 - (iii) thickness at least 1.0 mm but not greater than 1.2 mm; yield strength at least 400 N/mm² but not greater than 625 N/mm²; and elongation at least 16 percent but not greater than 27 percent;
 - (iv) thickness at least 1.2 mm but not greater than 1.6 mm; yield strength at least 400 N/mm² but not greater than 625 N/mm²; and elongation at least 17 percent but not greater than 28 percent; or
 - (v) thickness at least 1.6 mm but not greater than 2.3 mm; yield strength at least 400 N/mm² but not greater than 625 N/mm²; and elongation at least 18 percent;
- (ccxliv) cold-rolled flat-rolled steel products, designated as A-694, the foregoing having the following chemical composition (percent by weight): carbon not over 0.16, silicon not over 0.80, manganese not over 2.60, phosphorus not over 0.012 and sulfur not over 0.010; tensile strength at least 1180 N/mm²; meeting one of the following sets of properties:
- (i) thickness at least 0.8 mm but not greater than 1.0 mm; yield strength at least 835 N/mm² but not greater than 1,225 N/mm² and elongation at least 5 percent but not greater than 10 percent;
 - (ii) thickness at least 1.0 mm but not greater than 1.2 mm; yield strength at least 825 N/mm² but not greater than 1,215 N/mm²; and elongation at least 5 percent but not greater than 17 percent;
 - (iii) thickness at least 1.2 mm but not greater than 1.6 mm; yield strength at least 825 N/mm² but not greater than 1,215 N/mm²; and elongation at least 7 percent but not greater than 18 percent; or
 - (iv) thickness at least 1.6 mm but not greater than 2.3 mm; yield strength at least 825 N/mm² but not greater than 1,215 N/mm²; and elongation at least 8 percent;
- (ccxlv) bright finish cold-rolled saw steel products, designated as A-711, the foregoing flat-rolled; thickness not over 4.0 mm; width not over 710 mm; having the following chemical composition (percent by weight): carbon 0.70 to 0.80, silicon 0.25 to 0.50, manganese 0.60 to 0.80, phosphorus not over 0.035, sulfur not over 0.035 and chromium 0.30 to 0.45; through-hardened to 40 to 50 HRC with a tolerance of +/- 2HRC; thickness tolerance of +/- 0.03 mm; surface finish bright finish free from pits, cracks or seams; smooth edges; cross bow (per mm of width) not greater than 0.0015 mm;
- (ccxlvii) bright finish cold-rolled flat-rolled chrome-vanadium saw steel, designated as A-711, the foregoing with thickness not over 4.0 mm, width not over 710 mm; having the following chemical composition (percent by weight): carbon 0.75 to