

- (i) 30 to 40 percent polytetrafluoroethylene and 60 to 70 percent lead oxide, with the lead oxide being dispersed throughout the polytetrafluoroethylene in a scale-like arrangement;
 - (ii) 50 to 60 percent polytetrafluoroethylene, 5 to 10 percent fluorinated ethylene propylene, with the balance a tin-lead alloy dispersed in globular form throughout the polytetrafluoroethylene and fluorinated ethylene propylene;
 - (iii) 70 to 80 percent polytetrafluoroethylene, 8 percent fluorinated ethylene propylene, with the balance consisting of a tin-oxide alloy dispersed in globular form throughout the polytetrafluoroethylene and fluorinated ethylene propylene and a polyester resin dispersed in fiber form;
 - (iv) 95 to 99.5 percent polyacetal with a balance of titanium dioxide;
 - (v) 70 to 80 percent polytetrafluoroethylene, 8 to 10 percent fluorinated ethylene propylene, with the balance consisting of a tin oxide alloy dispersed in globular form throughout the polytetrafluoroethylene and fluorinated ethylene propylene and carbon dispersed in fiber form; or
 - (vi) 80 to 90 percent polytetrafluoroethylene, with the balance carbon fibers dispersed throughout the polytetrafluoroethylene;
- (cclxxxiii) flat-rolled products, designated as A-688, the foregoing coated with zinc-aluminum alloy, such alloy consisting of 95 percent zinc and 5 percent aluminum by weight; sometimes referred to as (but not limited to) products known as "Ragal Galfan"; width of 1,220 mm or more;
- (cclxxxiv) flat-rolled coated SAE 1009 steel in coils, designated as A-695, meeting one of the following characteristics (compositions by weight):
- (i) thickness not less than 0.915 mm but not over 0.965 mm, width not less than 19.75 mm or more but not over 20.35 mm; with a two-layer coating; the first layer consisting of tin 9 to 11 percent, lead 9 to 11 percent, zinc less than 1 percent, other materials (other than copper) not over 1 percent and balance copper; the second layer consisting of lead 45 to 55 percent, molybdenum disulfide (MoS_2) 3 to 5 percent, other materials not over 2 percent, balance polytetrafluoroethylene (PTFE);
 - (ii) thickness not less than 0.915 mm or more but not over 0.965 mm; width not less than 18.65 mm or more but not over 19.25 mm; with a two-layer coating; the first layer consisting of tin 9 to 11 percent, lead 9 to 11 percent, zinc less than 1 percent, other materials (other than copper) not over 1 percent, balance copper; the second layer consisting of lead 33 to 37 percent, aromatic polyester 13 to 17 percent, other materials (other than polytetrafluoroethylene (PTFE)) less than 2 percent, balance PTFE;
 - (iii) thickness not less than 0.920 mm or more but not over 0.970 mm; width not less than 21.35 mm or more but not over 21.95 mm; with a two-layer coating; the first layer consisting of tin 9 to 11 percent, lead 9 to 11 percent, zinc less than 1 percent, other materials (other than copper) not over 1 percent, balance copper; the second layer consisting of lead 33 to 37 percent, aromatic polyester 13 to 17 percent, other materials (other than PTFE) less than 2 percent, balance PTFE;
 - (iv) thickness not less than 1.80 mm or more but not over 1.85 mm, width not less than 14.7 mm or more but not over 15.3 mm; with a lining consisting of tin 2.5 to 4.5 percent, lead 21.0 to 25.0 percent, zinc less than 3 percent, iron less than 0.35 percent, other materials (other than copper) less than 1 percent, balance copper;
 - (v) thickness 1.59 mm or more but not over 1.64 mm; width 14.5 mm or more but not over 15.1 mm; with a lining consisting of tin 2.3 to 4.2 percent, lead 20 to 25 percent, iron 1.5 to 4.5 percent, phosphorus 0.2 to 2.0 percent, other materials (other than copper) less than 1 percent, with a balance copper;
 - (vi) thickness not less than 1.75 mm or more but not over 1.8 mm; width not less than 18.0 mm or more but not over 18.6 mm; with a lining consisting of tin 2.3 to 4.2 percent, lead 20 to 25 percent, iron 1.5 to 4.5 percent, phosphorus 0.2 to 2.0 percent, other materials (other than copper) less than 1 percent, with a balance copper;