

TABLE 1 TO SUBPART DDDDD OF PART 63—EMISSION LIMITS—Continued

For . . .	You must meet these emission limits . . .
5. Each new or reconstructed industrial, commercial, or institutional boiler or process heater in the small solid fuel subcategory.	a. Emissions of particulate matter must not exceed 0.026 lb per MMBtu of heat input; or b. Emissions of total selected metals must not exceed 0.0001 lb per MMBtu of heat input. c. Emissions of hydrogen chloride must not exceed 0.02 lb per MMBtu of heat input. d. Emissions of mercury must not exceed 0.000003 lb per MMBtu of heat input.
6. Each new or reconstructed industrial, commercial, or institutional boiler or process heater in the small liquid fuel subcategory.	a. Emissions of particulate matter must not exceed 0.03 lb per MMBtu of heat input. b. emissions of hydrogen chloride must not exceed 0.0009 lb per MMBtu of heat input.
7. Each existing industrial, commercial, or institutional boiler or process heater in the large solid fuel subcategory..	a. Emissions of particulate matter must not exceed 0.07 lb per MMBtu of heat input; or b. Emissions of total selected metals must not exceed 0.001 lb per MMBtu of heat input. c. Emissions of hydrogen chloride must not exceed 0.09 lb per MMBtu of heat input. d. Emissions of mercury must not exceed 0.000007 lb per MMBtu of heat input.
8. Each existing industrial, commercial, or institutional boiler or process heater in the limited use solid fuel subcategory.	a. Emissions of particulate matter must not exceed 0.21 lb per MMBtu of heat input; or b. Emissions of total selected metals must not exceed 0.001 lb per MMBtu of heat input.

As stated in § 63.7500, you must comply with the applicable operating limits:

TABLE 2.A TO SUBPART DDDDD OF PART 63—OPERATING LIMITS FOR BOILERS AND PROCESS HEATERS IN THE LARGE, LIMITED USE, OR SMALL SOLID FUEL SUBCATEGORIES

For...	That is controlled with...	You must meet these operating limits...
1. Each new or reconstructed industrial, commercial, or institutional boiler or process heater in the large solid fuel subcategory, the limited use solid fuel subcategory, or the small solid fuel subcategory.	<p>a. An add-on control other than a wet scrubber or a dry scrubber</p> <p>b. A fabric filter either alone or in combination with an add-on control other than a wet scrubber or a dry scrubber.</p>	<p>i. Maintain opacity to less than or equal to the operating level established during the performance test according to the provisions in § 63.7530(c) that demonstrated compliance with the emission limits for particulate matter and mercury or the opacity level established during the performance test according to the provisions in § 63.7530(c) that demonstrated compliance with the alternative emission limitation for total selected metals and the mercury emission limit; and</p> <p>ii. Maintain the fuel chlorine content to less than or equal to the operating level established during the performance test according to the provisions in § 63.7530(c) that demonstrated compliance with the emission limit for hydrogen chloride.</p> <p>i. Maintain the fabric filter operation such that the operating limit established for fabric filters in § 63.7530(c)(6)(v) is maintained; and</p> <p>ii. Maintain the fuel chlorine content to less than or equal to the operating level established during the performance test according to the provisions in § 63.7530(c) that demonstrated compliance with the emission limit for hydrogen chloride.</p>