

TABLE 5.A TO SUBPART DDDDD OF PART 63—INITIAL COMPLIANCE WITH EMISSION LIMITATIONS FOR PARTICULATE MATTER OR TOTAL SELECTED METALS FOR BOILERS OR PROCESS HEATERS IN LARGE, LIMITED USE, OR SMALL SOLID FUEL SUBCATEGORIES—Continued

For . . .	That is controlled with . . .	For the following emission limitation . . .	You have demonstrated initial compliance if . . .
3. Each existing industrial, or commercial, institutional boiler or process heater in the large solid fuel subcategory.	a. Either no add-on controls or an add-on control other than a wet scrubber.	i. 0.07 lb particulate matter per MMBtu heat input or 0.001 lb total selected metals per MMBtu heat input.	(1) The average emissions in units of lb particulate matter per MMBtu heat input, measured using PM emissions concentration and sections 12.2 and 12.3 of Method 19 of appendix A over the three-run performance test period, do not exceed the emission limit; or the average emissions in units of lb total selected metals per MMBtu heat input measured using total selected metals emission concentration and sections 12.2 and 12.3 of Method 19 of appendix A over the three-run performance test period, do not exceed the emission limits; and (2) You keep a record of the average site-specific opacity level for each test run over the 3-hour performance test during which particulate matter or total selected metals emissions did not exceed the emissions limit; or if the unit is controlled with a fabric filter, instead of establishing a site-specific opacity level you keep records of the installation and calibration data and the manufacturer's certification of the bag leak detection system as required in § 63.7525(i).
	b. A wet scrubber .....	i. 0.07 lb particulate matter per MMBtu heat input or 0.001 lb total selected metals per MMBtu heat input or 0.001 lb total selected metals per MMBtu heat input.	(1) The average emissions in units of lb particulate matter per MMBtu heat input, measured using PM emissions concentration and sections 12.2 and 12.3 of Method 19 of appendix A over the three-run performance test period, do not exceed the emission limit; or the average emissions in units of lb total selected metals per MMBtu heat input measured using total selected metals emission concentration and sections 12.2 and 12.3 of Method 19 of appendix A over the three-run performance test period, do not exceed the emission limit; and (2) You keep a record of the average site-specific pressure drop and liquid flow-rate of the wet scrubber for each test run over the three-run performance test during which particulate matter or total selected metals emissions did not exceed the emissions limit.