

TABLE 5.B TO SUBPART DDDDD OF PART 63—INITIAL COMPLIANCE WITH EMISSION LIMITATIONS FOR PARTICULATE MATTER FOR BOILERS OR PROCESS HEATERS IN LARGE, LIMITED USE, OR SMALL LIQUID FUEL SUBCATEGORIES—Continued

| For . . . | That is controlled with . . . | For the following emission limitation . . . | You have demonstrated initial compliance if . . . |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------|-----------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| | c. A wet scrubber in combination with a fabric filter. | i. 0.03 lb particulate matter per MMBtu heat input. | (1) The average emissions in units of lb particulate matter per MMBtu heat input, measured using PM emissions concentration and sections 12.2 and 12.3 of Method 19 of appendix A over the three-run performance test period, do not exceed the emission limit; and (2) You keep a record of the average site-specific pressure drop and liquid flow-rate of the wet scrubber for each test run over the three-run performance test during which particulate matter emissions did not exceed the emissions limit; and (3) You keep records of the installation and calibration data and the manufacturer's certification of the bag leak detection system as required in § 63.7525(i). |
| | d. A wet scrubber in combination with an electrostatic precipitator. | i. 0.03 lb particulate matter per MMBtu heat input. | (1) The average emissions in units of lb particulate matter per MMBtu heat input, measured using PM emissions concentration and sections 12.2 and 12.3 of Method 19 of appendix A over the three-run performance test period, do not exceed the emission limit; and (2) You keep a record of the average site-specific pressure drop and liquid flow-rate of the wet scrubber and the average secondary current and voltage or total power input of the electrostatic precipitator for each test run over the three-run performance test during which particulate matter emissions did not exceed the emissions limit. |
| 2. Each new or reconstructed industrial, commercial, or institutional boiler or process heater in one of the liquid fuel subcategories that burns only liquid fossil fuels other than residual oil either alone or in combination with gaseous fuels. | a. Any type of device | i. 0.03 lb particulate matter per MMBtu heat input. | (1) You submit a signed statement in the Notification of Compliance Status report required in § 63.7545(e) that indicated you burn only liquid fossil fuels other than residual oil either alone or in combination with gaseous fuels; and (2) You keep records, as required in § 63.7555, that demonstrate that you burn only liquid fossil fuels other than residual oil either alone or in combination with gaseous fuels. |

As stated in § 63.7530, you must show initial compliance with the emission limitations for affected sources according to the following: