

TABLE 5.D TO SUBPART DDDDD OF PART 63—INITIAL COMPLIANCE WITH EMISSION LIMITATIONS FOR HYDROGEN CHLORIDE FOR BOILERS OR PROCESS HEATERS IN LARGE, LIMITED USE, OR SMALL LIQUID FUEL SUBCATEGORIES—Continued

For . . .	That is controlled with . . .	For the following emission limitation . . .	You have demonstrated initial compliance if . . .
	b. A dry scrubber	i. 0.0009 lb hydrogen chloride per MMBtu heat input.	(1) The average emissions in units of lb hydrogen chloride per MMBtu heat input, measured using hydrogen chloride emissions concentration and Method 19 of appendix A over the three-run performance test period, do not exceed the emission limit; and (2) You keep a record of the average site-specific sorbent injection rate of the dry scrubber for each test run over the three-run performance test during which hydrogen chloride emissions did not exceed the emissions limit.
4. Each new or reconstructed industrial, commercial, or institutional boiler or process heater in one of the liquid fuel subcategories that burns only liquid fossil fuels other than residual oil either alone or in combination with gaseous fuels.	a. Any type of device	i. 0.0005 lb hydrogen chloride per MMBtu heat input for units in the large liquid fuel subcategory or 0.0009 lb hydrogen chloride per MMBtu heat input for units in the limited use or small liquid fuel subcategories.	(1) You submit a signed statement in the Notification of Compliance Status report required in § 63.7545(e) that indicates you burn only liquid fossil fuels other than residual oil either alone or in combination with gaseous fuels; and (2) You keep records, as required in § 63.7555, that demonstrate that you burn only liquid fossil fuels other than residual oil either alone or in combination with gaseous fuels.

As stated in § 63.7530, you must show initial compliance with the emission limitations for affected sources according to the following:

TABLE 5.E TO SUBPART DDDDD OF PART 63—INITIAL COMPLIANCE WITH EMISSION LIMITATIONS FOR MERCURY FOR BOILERS OR PROCESS HEATERS IN LARGE, LIMITED USE, OR SMALL SOLID FUEL SUBCATEGORIES

For . . .	That is controlled with . . .	For the following emission limitation . . .	You have demonstrated initial compliance if . . .
1. Each new or reconstructed industrial, commercial or institutional boiler or process heater in large solid fuel subcategory, the limited use solid fuel subcategory, or the small solid fuel subcategory.	a. Either no add-on control or an add-on control other than wet scrubber.	i. 0.000003 lb mercury per MMBtu heat input.	(1) The average emissions in units of lb mercury per MMBtu heat input, measured using mercury emissions concentration and sections 12.2 and 12.3 of Method 19 of appendix A over the three-run performance test period, do not exceed the emission limit; and (2) You keep a record of the average site-specific opacity level for each test run over the three-run performance test during which mercury emissions did not exceed the emissions limit; or if the unit is controlled with a fabric filter, instead of establishing a site-specific opacity level you keep records of the installation and calibration data and the manufacturer's certification of the bag leak detection system as required in § 63.7525(i).