

TABLE 17.2.—DATA ACCEPTANCE CRITERIA WORKSHEET—Continued

| Test No. | Temperature | | | Laminate roll out time, min | Relative humidity, % | | Resin weight, (g) | Glass con- tent, % | Resin distribution | Meets criteria Y/N |
|----------------|-------------|-----|-------|-----------------------------------|----------------------|----------------------|----------------------|-----------------------|-----------------------|-----------------------|
| | Min | Max | Delta | | Initial | Final | | | | |
| 12 | | | | | | | | | | |
| Average | | | | | | | | | | |
| Criteria | | | ± 2°F | ±10% of Av- erage | ± 15 of Av- erage | ± 15 of Av- erage | ± 10% of Avg. | ± 10% of Avg. | <1/2 inch off mat | All Y |

17.3 VSE Factor Calculation

TABLE 17.3.—CALCULATIONS WORKSHEET

| Vapor suppressed | | Non-vapor suppressed | |
|---------------------|---------------|----------------------|---------------|
| Test # | % Weight loss | Test # | % Weight loss |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| Average Weight Loss | | | |
| VSE Factor | | | |

VSE Factor = $1 - (\% \text{ Average Weight Loss}_{\text{VS}} / \% \text{ Average Weight Loss}_{\text{NVS}})$

17.4 Figures