

for barges or a commercial facility, and used solely for restricted service, such as making up or breaking up larger tows;

(2) Used solely for harbor-assist;

(3) Used solely for assistance towing as defined by 46 CFR 10.103;

(4) Used solely for response to emergency or pollution;

(5) A public vessel that is both owned, or demise chartered, and operated by the United States Government or by a government of a foreign country; and that is not engaged in commercial service;

(6) A foreign vessel engaged in innocent passage;

(7) Pushing a barge ahead, or towing a barge alongside, when the barge's coastwise or Great Lakes route is restricted (as indicated on its certificate of inspection), so the barge may operate "in fair weather only, within 20 miles of shore," or with words to that effect; or

(8) Exempted by the Captain of the Port (COTP).

(c) If you think your towing vessel should be exempt from the paragraph (b) requirements for a specified route, you should submit a written request to the appropriate COTP. The COTP will provide you with a written response granting or denying your request. The COTP will consider the extent to which unsafe conditions would result if your vessel lost propulsion because of a fire in the engine room.

(d) You must test and maintain all of the equipment required by this part in accordance with the attached nameplate or manufacturer's approved design manual.

§ 27.101 Definitions.

As used in this part—

Accommodation includes any:

- (1) Messroom.
- (2) Lounge.
- (3) Sitting area.
- (4) Recreation room.
- (5) Quarters.
- (6) Toilet space.
- (7) Shower room.
- (8) Galley.
- (9) Berthing facility.
- (10) Clothing-changing room.

Engine room means the enclosed area where any main-propulsion engine is located. It comprises all deck levels within that area.

Fixed fire-extinguishing system means a carbon-dioxide system that satisfies 46 CFR subpart 76.15 and is approved by the Commandant; a manually-operated clean-agent system that satisfies the National Fire Protection Association (NFPA) Standard 2001 (incorporated by reference in § 27.102) and is approved by the Commandant; or a manually-

operated water-mist system that satisfies NFPA Standard 750 (incorporated by reference in § 27.102) and is approved by the Commandant.

Fleeting-area means a separate location where individual barges are moored or assembled to make a tow. The barges are not in transport, but are temporarily marshaled, waiting for pickup by different vessels that will transport them to various destinations. A fleeting-area is a limited geographic area.

Harbor-assist means docking and undocking ships.

Limited geographic area means a local area of operation, usually within a single harbor or port. The local Captain of the Port (COTP) determines the definition of local geographic area for each zone.

Operating station means the principal steering station on the vessel from which the vessel is normally navigated.

Towing vessel means a commercial vessel engaged in, or intending to engage in, pulling, pushing, or hauling alongside, or any combination of pulling, pushing, or hauling alongside.

Towing vessel in inland service means a towing vessel that is not in ocean or coastal service.

Towing vessel in ocean or coastal service means a towing vessel that operates beyond the baseline of the U.S. territorial sea.

We means the United States Coast Guard.

Work space means any area on the vessel where the crew could be present while on duty and performing their assigned tasks.

You means the owner of a towing vessel, unless otherwise specified.

§ 27.102 Incorporation by reference.

(a) Certain material is incorporated by reference into this part with the approval of the Director of the Federal Register—in accordance with 5 U.S.C. 552(a) and 1 CFR part 51. To enforce any edition other than that specified in paragraph (b) of this section, the Coast Guard must publish notice of the change in the **Federal Register** and make the material available for inspection. All approved material is available at the Office of the Federal Register, 800 North Capitol Street NW., suite 700, Washington, DC 20001, and at the U.S. Coast Guard, Office of Design and Engineering Standards (G-MSE), 2100 Second Street SW., Washington, DC 20593-0001 and is available from the sources indicated in paragraph (b) of this section.

(b) The material approved for incorporation by reference in this part and the sections affected are:

American Boat and Yacht Council (ABYC), 3069 Solomons Island Road, Edgewater, MD 21037-1416.

H-25-1986—Portable Fuel Systems for Flammable Liquids ...	27.211
H-33-1989—Diesel Fuel Systems	27.211
National Fire Protection Association (NFPA), 1 Batterymarch Park, Quincy, MA 02269-9101	
NFPA 302-1989—Pleasure and Commercial Motorcraft	27.211
NFPA 750—Standard on Water Mist Fire Protection Systems, 2000 edition	27.101
NFPA 2001—Standard on Clean Agent Fire Extinguishing Systems, 2000 edition	27.101
Society of Automotive Engineers (SAE), 400 Commonwealth Drive, Warrendale, PA 15096-0001	
SAE J1475-1984—Hydraulic Hose Fitting for Marine Applications	27.211
SAE J1942-1989—Hose and Hose Assemblies for Marine Applications	27.211

Subpart B—Fire-Protection Measures for Towing Vessels

§ 27.201 What are the requirements for general alarms on towing vessels?

(a) You must ensure that your vessel is fitted with a general alarm that:

(1) Has a contact-maker at the operating station that can notify persons on board in the event of an emergency.

(2) Is capable of notifying persons in any accommodation, work space, and the engine room.

(3) Has installed, in the engine room and any other area where background noise makes a general alarm hard to hear, a supplemental flashing red light that is identified with a sign that reads:

Attention

General Alarm—When Alarm Sounds or Flashes Go to Your Station.

(4) Is tested at least once each week.

(b) You or the operator may use a public-address (PA) system or other means of alerting all persons on your towing vessel instead of a general alarm, if the system—

(1) Is capable of notifying persons in any accommodation, work space, and the engine room;

(2) Is tested at least once each week;

(3) Can be activated from the operating station; and

(4) Complies with paragraph (a)(3) of this section.

§ 27.203 What are the requirements for fire detection on towing vessels?

You must have a fire-detection system installed on your vessel to detect