

TABLE 4 TO SUBPART LLLLL TO PART 63.—INITIAL COMPLIANCE WITH EMISSION LIMITATIONS

| For— | For the following emission limitation— | You have demonstrated initial compliance if— |
|--|--|---|
| 1. Each blowing still, Group 1 asphalt loading rack, and Group 1 asphalt storage tank, at existing, new, and reconstructed asphalt processing facilities;. | <p>a. Reduce total hydrocarbon mass emissions by 95 percent or to a concentration of 20 ppmv, on a dry basis corrected to 3 percent oxygen.</p> <p>b. Route the emissions to a combustion device achieving a combustion efficiency of 99.5 percent.</p> <p>c. Route the emissions to a combustion device that does not use auxiliary fuel achieving a THC destruction efficiency of 95.8 percent.</p> <p>d. Route emissions to a boiler or process heater with a design heat input capacity of 44 MW or greater.</p> <p>e. Introduce the emissions into the flame zone of a boiler or process heater.</p> <p>f. Route emissions to a flare meeting the requirements of § 63.11(b).</p> | <p>i. The total hydrocarbon emissions, determined using the equations in § 63.8687 and the test methods and procedures in Table 3 to this subpart, over the period of the performance test are reduced by at least 95 percent by weight or to a concentration of 20 ppmv, on a dry basis corrected to 3 percent oxygen; and</p> <p>ii. You have a record of the average control device operating parameters^a over the performance test during which emissions were reduced according to 1.a.i. of this table.</p> <p>i. The combustion efficiency of the combustion device, determined using the equations in § 63.8687 and the test methods and procedures in Table 3 to this subpart, over the period of the performance test is at least 99.5 percent; and</p> <p>ii. You have a record of the average combustion zone temperature^a and carbon monoxide, carbon dioxide, and total hydrocarbon outlet concentrations over the performance test during which the combustion efficiency was at least 99.5 percent.</p> <p>i. The THC destruction efficiency of the combustion device, determined using the equations in § 63.8687 and the test methods and procedures in Table 3 to this subpart, over the period of the performance test is at least 95.8 percent; and</p> <p>ii. You have a record of the average combustion zone temperature^a and carbon monoxide, carbon dioxide, and total hydrocarbon outlet concentrations over the performance test during which the THC destruction efficiency was at least 95.8 percent.</p> <p>You have a record of the boiler or process heater design heat capacity.</p> <p>You have a record that shows the emissions are being introduced into the boiler or process heater flame zone.</p> <p>You have a record of the flare design and operating requirements.</p> |
| 2. Each coating mixer, saturator (including wet looper), coater, sealant applicator, adhesive applicator, and Group 1 asphalt storage tank at new and reconstructed asphalt roofing manufacturing lines. | <p>a. Reduce total hydrocarbon mass emissions by 95 percent or to a concentration of 20 ppmv, on a dry basis corrected to 3 percent oxygen.</p> <p>b. Route the emissions to a combustion device achieving a combustion efficiency of 99.5 percent.</p> <p>c. Route the emissions to a combustion device that does not use auxiliary fuel achieving a THC destruction efficiency of 95.8 percent.</p> <p>d. Route emissions to a boiler or process heater with a design heat input capacity of 44 MW or greater.</p> <p>e. Introduce the emissions into the flame zone of a boiler or process heater.</p> <p>f. Route emissions to a flare meeting the requirements of § 63.11(b).</p> | <p>See 1.a.i. and ii. of this table.</p> <p>See 1.b.i. and ii. of this table.</p> <p>See 1.c.i. and ii. of this table.</p> <p>See 1.d. of this table.</p> <p>See 1.e. of this table.</p> <p>See 1.f. of this table.</p> |
| 3. The total emissions from the coating mixer, saturator (including wet looper), coater, sealant applicator, and adhesive applicator at each existing asphalt roofing manufacturing line. | <p>a. Limit PM emissions to 0.04 kg/Mg (0.08 lb/ton) of asphalt shingle or mineral-surfaced roll roofing produced.</p> | <p>i. The PM emissions, determined using the equations in § 63.8687 and the test methods and procedures in Table 3 to this subpart, over the period of the performance test are no greater than the applicable emission limitation; and</p> <p>ii. You have a record of the average control device^a or process parameters over the performance test during which the particulate matter emissions were no greater than the applicable emission limitation.</p> |