

TABLE 4 TO SUBPART LLLLL TO PART 63.—INITIAL COMPLIANCE WITH EMISSION LIMITATIONS—Continued

For—	For the following emission limitation—	You have demonstrated initial compliance if—
4. Each saturator (including wet looper) and coater at an existing, new, or reconstructed asphalt roofing manufacturing line.	b. Limit PM emissions to 0.4 kg/Mg (0.8 lb/ton) of saturated felt or smooth-surfaced roll roofing produced. a. Limit visible emissions from the emissions capture system to 20 percent of any period of consecutive valid observations totaling 60 minutes. b. Limit opacity emissions to 20 percent.	See 3.a.i. and ii. of this table. The visible emissions, measured using EPA test method 22, for any period of consecutive valid observations totaling 60 minutes during the initial compliance period described in § 63.8686(b) do not exceed 20 percent. The opacity, measured using EPA test method 9, for each of the first 30 6-minute averages during the initial compliance period described in § 63.8686(b) does not exceed 20 percent.
5. Each Group 2 asphalt storage tank at existing, new, and reconstructed asphalt processing facilities and asphalt roofing manufacturing lines.	Limit exhaust gases to 0 percent opacity.	The opacity, measured using EPA test method 9, for each of the first 30 6-minute averages during the initial compliance period described in § 63.8686(b) does not exceed 0 percent.

^aIf you use a CEMS or COMS to demonstrate compliance with the emission limits, you are not required to record control device operating parameters.

TABLE 5 TO SUBPART LLLLL OF PART 63.—CONTINUOUS COMPLIANCE WITH OPERATING LIMITS ^a

For—	For the following operating limit—	You must demonstrate continuous compliance by—
1. Each non-flare combustion device. ^a	a. Maintain the 3-hour ^c average combustion zone temperature at or above the operating limit establishing during the performance test.	i. Passing the emissions through the control device; and ii. Collecting the combustion zone temperature data according to § 63.8688(b); and iii. Reducing combustion zone temperature data to 3-hour ^c averages according to calculations in Table 3 to this subpart; and iv. Maintaining the 3-hour ^c average combustion zone temperature within the level established during the performance test.
2. Each flare	Meet the operating requirements specified in § 63.11(b)..	The flare pilot light must be present at all times and the flare must be operating at all times that emissions may be vented to it.
3. Control devices used to comply with the particulate matter emission standards.	a. Maintain the 3-hour ^c average inlet gas temperature and pressure drop across device ^d at or below the operating limits established during the performance test.	i. Passing the emissions through the control device; and ii. Collecting the inlet gas temperature and pressure drop ^d data according to § 63.8688 (b) and (c); and iii. Reducing inlet gas temperature and pressure drop ^d data to 3-hour ^c averages according to calculations in Table 3 to this subpart; and iv. Maintaining the 3-hour ^c average inlet gas temperature and pressure drop ^d within the level established during the performance test.
4. Control devices other than combustion devices or devices used to comply with the particulate matter emission.	a. Maintain the monitoring parameters within the operating limits established during the performance test.	i. Passing the emissions through the devices; ii. Collecting the monitoring parameter data according to § 63.8688(d); and iii. Reducing the monitoring parameter data to 3-hour ^c averages according to calculations in Table 3 to this subpart; and iv. Maintaining the monitoring parameters within the level established during the performance test.

^aThe operating limits specified in Table 2 and the requirements specified in Table 5 are applicable if you are monitoring control device operating parameters to demonstrate continuous compliance. If you use a CEMS or COMS to demonstrate compliance with the emission limits, you are not required to record control device operating parameters. However, you must maintain emissions below the value established during the initial performance test. Data from the CEMS and COMS must be reduced as specified in § 63.9(g).

^bContinuous parameter monitoring is not required if (1) the emissions are routed to a boiler or process heater with a design heat input capacity of 44 MW or greater; or (2) the emissions are introduced into the flame zone of a boiler or process heater.

^cA 15-minute averaging period can be used as an alternative to the 3-hour averaging period for this parameter.

^dAs an alternative to monitoring the pressure drop across the control device, owners or operators using an ESP to achieve compliance with the emission limits specified in Table 1 of this subpart can monitor the voltage to the ESP. If this option is selected, the ESP voltage must be maintained at or above the operating limit established during the performance test.

TABLE 6 TO SUBPART LLLLL OF PART 63—REQUIREMENTS FOR REPORTS

You must submit—	The report must contain—	You must submit the report—
1. An initial notification	The information in § 63.9(b)	According to the requirements in § 63.9(b).
2. A notification of performance test	A written notification of the intent to conduct a performance test.	At least 60 calendar days before the performance test is scheduled to begin, as required in § 63.9(e).
3. A notification of opacity and visible emission observations.	A written notification of the intent to conduct opacity and visible emission observations.	According to the requirements in § 63.9(f).