

Congress recognized that regulating only those sources that discharge effluent directly into the nation's waters would not be sufficient to achieve the CWA's goals. Consequently, the CWA requires EPA to promulgate nationally applicable pretreatment standards that restrict pollutant discharges from facilities that discharge wastewater through sewers flowing to publicly-owned treatment works (POTWs) (section 307(b) and (c), 33 U.S.C. 1317(b) and (c)). National pretreatment standards are established for those pollutants in wastewater from indirect dischargers which pass through, interfere with, or are otherwise incompatible with POTW operations. Generally, pretreatment standards are designed to ensure that wastewater from direct and indirect industrial dischargers are subject to similar levels of treatment. In addition, POTWs are required to develop and enforce local pretreatment limits applicable to their industrial indirect dischargers to satisfy any local requirements (*see* 40 CFR 403.5).

Direct dischargers must comply with effluent limitations in National Pollutant Discharge Elimination System (NPDES) permits; indirect dischargers must comply with pretreatment standards. These limitations and standards are established by regulation for categories of industrial dischargers and are based on the degree of control that can be achieved using various levels of pollution control technology.

1. Best Practicable Control Technology Currently Available (BPT)—Section 304(b)(1) of the CWA

In the regulations, EPA defines BPT effluent limitations for conventional, toxic, and non-conventional pollutants. Section 304(a)(4) designates the following as conventional pollutants: biochemical oxygen demand (BOD₅), total suspended solids (TSS), fecal coliform, pH, and any additional pollutants defined by the Administrator as conventional. The Administrator designated oil and grease (O&G) as an additional conventional pollutant on July 30, 1979 (*see* 44 FR 44501). EPA has identified 65 pollutants and classes of pollutants as toxic pollutants, of which 126 specific substances have been designated priority toxic pollutants (*see* Appendix A to part 403, reprinted after 40 CFR 423.17). All other pollutants are considered to be non-conventional.

In specifying BPT, EPA looks at a number of factors. EPA first considers the total cost of applying the control technology in relation to the effluent reduction benefits. The Agency also

considers the age of the equipment and facilities, the processes employed and any required process changes, engineering aspects of the control technologies, non-water quality environmental impacts (including energy requirements), and such other factors as the EPA Administrator deems appropriate (CWA 304(b)(1)(B)). Traditionally, EPA establishes BPT effluent limitations based on the average of the best performances of facilities within the industry of various ages, sizes, processes or other common characteristics. Where existing performance is uniformly inadequate, BPT may reflect higher levels of control than currently in place in an industrial category if the Agency determines that the technology can be practically applied.

2. Best Conventional Pollutant Control Technology (BCT)—Section 304(b)(4) of the CWA

The 1977 amendments to the CWA required EPA to identify effluent reduction levels for conventional pollutants associated with BCT for discharges from existing industrial point sources. In addition to the other factors specified in section 304(b)(4)(B), the CWA requires that EPA establish BCT limitations after consideration of a two part "cost-reasonableness" test. EPA explained its methodology for the development of BCT limitations in July 1986 (*see* 51 FR 24974).

3. Best Available Technology Economically Achievable (BAT)—Section 304(b)(2) of the CWA

In general, BAT effluent limitations guidelines represent the best available economically achievable performance of plants in the industrial subcategory or category. The factors considered in assessing BAT include the cost of achieving BAT effluent reductions, the age of equipment and facilities involved, the process employed, potential process changes, and non-water quality environmental impacts, including energy requirements. The Agency retains considerable discretion in assigning the weight to be accorded these factors. BAT limitations may be based on effluent reductions attainable through changes in a facility's processes and operations. Where existing performance is uniformly inadequate, BAT may reflect a higher level of performance than is currently being achieved within a particular subcategory based on technology transferred from a different subcategory or category. BAT may be based upon process changes or internal controls,

even when these technologies are not common industry practice.

4. New Source Performance Standards (NSPS)—Section 306 of the CWA

NSPS reflect effluent reductions that are achievable based on the best available demonstrated control technology. New sources have the opportunity to install the best and most efficient production processes and wastewater treatment technologies. As a result, NSPS should represent the most stringent controls attainable through the application of the best available demonstrated control technology for all pollutants (*i.e.*, conventional, non-conventional, and priority pollutants). In establishing NSPS, EPA is directed to take into consideration the cost of achieving the effluent reduction and any non-water quality environmental impacts and energy requirements.

5. Pretreatment Standards for Existing Sources (PSES)—Section 307(b) of the CWA

PSES are designed to prevent the discharge of pollutants that pass through, interfere with, or are otherwise incompatible with the operation of publicly-owned treatment works (POTWs), including sludge disposal methods at POTWs. Pretreatment standards for existing sources are technology-based and are analogous to BAT effluent limitations guidelines.

The General Pretreatment Regulations, which set forth the framework for the implementation of national pretreatment standards, are found at 40 CFR 403.

6. Pretreatment Standards for New Sources (PSNS)—Section 307(c) of the CWA

Like PSES, PSNS are designed to prevent the discharges of pollutants that pass through, interfere with, or are otherwise incompatible with the operation of POTWs. PSNS are to be issued at the same time as NSPS. New indirect dischargers have the opportunity to incorporate into their plants the best available demonstrated technologies. The Agency considers the same factors in promulgating PSNS as it considers in promulgating NSPS.

B. Pollution Prevention Act

The Pollution Prevention Act of 1990 (PPA) (42 U.S.C. 13101 *et seq.*, Public Law 101-508, November 5, 1990) "declares it to be the national policy of the United States that pollution should be prevented or reduced whenever feasible; pollution that cannot be prevented should be recycled in an environmentally safe manner, whenever