

TABLE 4 TO SUBPART JJJJJ OF PART 63.—INITIAL COMPLIANCE WITH EMISSION LIMITATIONS—Continued

For each . . .	For the following emission limitation . . .	You have demonstrated initial compliance if . . .
	<p>b. HCl emissions must not exceed 0.028 kg/Mg (0.056 lb/ton) of fired product; or uncontrolled HCl emissions must be reduced by at least 85 percent; and</p> <p>c. PM emissions must not exceed 0.060 kg/Mg (0.12 lb/ton) of fired product.</p>	<p>ii. You establish and have a record of the operating limits listed in Table 2 to this subpart over the 3-hour performance test during which HF emissions did not exceed 0.029 kg/Mg (0.057 lb/ton) or uncontrolled HF emissions were reduced by at least 90 percent.</p> <p>i. The HCl emissions measured using Method 26A of 40 CFR part 60, appendix A or Method 320 of 40 CFR part 63, appendix A over the period of the initial performance test, according to the calculations in § 63.8445(g)(1), do not exceed 0.028 kg/Mg (0.056 lb/ton); or uncontrolled HCl emissions measured using Method 26A of 40 CFR part 60, appendix A or Method 320 of 40 CFR part 63, appendix A over the period of the initial performance test are reduced by at least 85 percent, according to the calculations in § 63.8445(g)(2); and</p> <p>ii. You establish and have a record of the operating limits listed in Table 2 to this subpart over the 3-hour performance test during which HCl emissions did not exceed 0.028 kg/Mg (0.056 lb/ton) or uncontrolled HCl emissions were reduced by at least 85 percent.</p> <p>i. The PM emissions measured using Method 5 of 40 CFR part 60, appendix A, over the period of the initial performance test, according to the calculations in § 63.8445(g)(1), do not exceed 0.060 kg/Mg (0.12 lb/ton); and</p> <p>ii. You establish and have a record of the operating limits listed in Table 2 to this subpart over the 3-hour performance test during which PM emissions did not exceed 0.060 kg/Mg (0.12 lb/ton).</p>

As stated in § 63.8470, you must demonstrate continuous compliance with each emission limit and operating limit that applies to you according to the following table:

TABLE 5 TO SUBPART JJJJJ OF PART 63.—CONTINUOUS COMPLIANCE WITH EMISSION LIMITS AND OPERATING LIMITS

For each . . .	For the following emission limits and operating limits . . .	You must demonstrate continuous compliance by . . .
1. Kiln equipped with a DLA	Each emission limit in Table 1 to this subpart and each operating limit in Item 1 of Table 2 to this subpart for kilns equipped with a DLA.	<p>i. Collecting the DLA pressure drop data according to § 63.8450(a); reducing the DLA pressure drop data to 3-hour block averages according to § 63.8450(a); maintaining the average pressure drop across the DLA for each 3-hour block period at or above the average pressure drop established during the performance test; and</p> <p>ii. Verifying that the limestone hopper and storage bin (located at the top of the DLA) contain adequate limestone by performing a daily visual check; and</p> <p>iii. Recording the limestone feeder setting daily to verify that the feeder setting is being maintained at or above the level established during the performance test; and</p> <p>iv. Using the same grade of limestone from the same source as was used during the performance test; maintaining records of the source and type of limestone; and</p> <p>v. Performing VE observations of the DLA stack at the frequency specified in § 63.8470(g) using Method 22 of 40 CFR part 60, appendix A; maintaining no VE from the DLA stack.</p>