

TABLE 3 TO SUBPART FFFFF OF PART 63.—CONTINUOUS COMPLIANCE WITH EMISSION AND OPACITY LIMITS—Continued
[As required in § 63.7833(a), you must demonstrate continuous compliance with the emission and opacity limits according to the following table]

For . . .	You must demonstrate continuous compliance by . . .
8. Each casthouse at a new blast furnace	<p>b. Maintaining the opacity of secondary emissions that exit any opening in the casthouse or structure housing the blast furnace at or below 20 percent (6-minute average); and</p> <p>c. Conducting subsequent performance tests at least twice during each term of your title V operating permit (at midterm and renewal).</p> <p>a. Maintaining emissions of particulate matter from a control device at or below 0.003 gr/dscf;</p> <p>b. Maintaining the opacity of secondary emissions that exit any opening in the casthouse or building housing the casthouse at or below 15 percent (6-minute average); and</p> <p>c. Conducting subsequent performance tests at least twice during each term of your title V operating permit (at midterm and renewal).</p>
9. Each BOPF at a new or existing BOPF shop ...	<p>a. Maintaining emissions of particulate matter from the primary emission control system for a BOPF with a closed hood system at or below 0.03 gr/dscf;</p> <p>b. Maintaining emissions of particulate matter from the primary emission control system for a BOPF with an open hood system at or below 0.02 gr/dscf for an existing BOPF shop or 0.01 gr/dscf for a new BOPF shop;</p> <p>c. Maintaining emissions of particulate matter from a control device applied solely to secondary emissions from a BOPF at or below 0.01 gr/dscf for an existing BOPF shop or 0.0052 gr/dscf for a new BOPF shop; and</p> <p>d. Conducting subsequent performance tests at least twice during each term of your title V operating permit (at midterm and renewal).</p>
10. Each hot metal transfer, skimming, and desulfurization operation at a new or existing BOPF shop.	<p>a. Maintaining emissions of particulate matter from a control device at or below 0.01 gr/dscf at an existing BOPF or 0.003 gr/dscf for a new BOPF; and</p> <p>b. Conducting subsequent performance tests at least twice during each term of your title V operating permit (at midterm and renewal).</p>
11. Each ladle metallurgy operation at a new or existing BOPF shop.	<p>a. Maintaining emissions of particulate matter from a control device at or below 0.01 gr/dscf at an existing BOPF shop or 0.004 gr/dscf for a new BOPF shop; and</p> <p>b. Conducting subsequent performance tests at least twice during each term of your title V operating permit (at midterm and renewal).</p>
12. Each roof monitor at an existing BOPF shop ..	<p>a. Maintaining the opacity of secondary emissions that exit any opening in the BOPF shop or other building housing the BOPF or shop operation at or below 20 percent (3-minute average); and</p> <p>b. Conducting subsequent performance tests at least twice during each term of your title V operating permit (at midterm and renewal).</p>
13. Each roof monitor at a new BOPF shop	<p>a. Maintaining the opacity (for any set of 6-minute averages) of secondary emissions that exit any opening in the BOPF shop or other building housing a bottom-blown BOPF or shop operation at or below 10 percent, except that one 6-minute period greater than 10 percent but no more than 20 percent may occur once per steel production cycle;</p> <p>b. Maintaining the opacity (for any set of 3-minute averages) of secondary emissions that exit any opening in the BOPF shop or other building housing a top-blown BOPF or shop operation at or below 10 percent, except that one 3-minute period greater than 10 percent but less than 20 percent may occur once per steel production cycle; and</p> <p>c. Conducting subsequent performance tests at least twice during each term of your title V operating permit (at midterm and renewal).</p>

TABLE 4 TO SUBPART FFFFF OF PART 63.—APPLICABILITY OF GENERAL PROVISIONS TO SUBPART FFFFF

[As required in § 63.7850, you must comply with the requirements of the NESHAP General Provisions (40 CFR part 63, subpart A) shown in the following table]

Citation	Subject	Applies to Subpart FFFFF	Explanation
§ 63.1	Applicability	Yes.	
§ 63.2	Definitions	Yes.	
§ 63.3	Units and Abbreviations	Yes.	
§ 63.4	Prohibited Activities	Yes.	
§ 63.5	Construction/Reconstruction	Yes.	
§ 63.6(a), (b), (c), (d), (e), (f), (g), (h)(2)(ii)–(h)(9).	Compliance with Standards and Maintenance Requirements.	Yes.	
§ 63.6(h)(2)(i)	Determining Compliance with Opacity and VE Standards.	No	Subpart FFFFF specifies Method 9 in appendix A to part 60 of this chapter to comply with roof monitor opacity limits.
§ 63.7(a)(1)–(2)	Applicability and Performance Test Dates.	No	Subpart FFFFF and specifies performance test applicability and dates.
§ 63.7(a)(3), (b), (c)–(h)	Performance Testing Requirements	Yes.	
§ 63.8(a)(1)–(a)(3), (b), (c)(1)–(3), (c)(4)(i)–(e), (c)(7)–(8), (f)(1)–(5), (g)(1)–(4).	Monitoring Requirements	Yes	CMS requirements in § 63.8(c)(4) (i)–(ii), (c)(5) and (6), (d), and (e) apply only to COMS for electrostatic precipitators.