

TABLE 3 TO SUBPART TTTTT OF PART 63.—INITIAL COMPLIANCE WITH EMISSIONS LIMITS—Continued

As required in 63.9916, you must demonstrate initial compliance with the emission limits according to the following table:

| For . . .   | You have demonstrated initial compliance if . . .  |
|---|--|
| 2. Each magnesium chloride storage bins scrubber stack. | <ul style="list-style-type: none"> <li>b. The average mass flow of hydrochloric acid from the control system applied to emissions from each spray dryer, determined according to the performance test procedures in § 63.9914(c), did not exceed 200 lbs/hr.</li> </ul>  |
| 3. Each melt/reactor system stack                       | <ul style="list-style-type: none"> <li>a. The average mass flow of hydrochloric acid from the control system applied to the magnesium chloride storage bins scrubber exhaust, measured according to the performance test procedure in § 63.9914, did not exceed 47.5 lbs/hr; and</li> <li>b. The average mass flow of PM<sub>10</sub> from the control system applied to the magnesium chloride storage bins scrubber exhaust, determined according to the performance test procedures in § 63.9913, did not exceed 2.7 lbs/hr.</li> </ul>   |
| 4. Each launder off-gas system stack.                   | <ul style="list-style-type: none"> <li>a. The average mass flow of PM<sub>10</sub> from the control system applied to the melt/reactor system exhaust, measured according to the performance test procedures in § 63.9913, did not exceed 13.1 lbs/hr; and</li> <li>b. The average mass flow of hydrochloric acid from the control system applied to the melt/reactor system exhaust, measured according to the performance test procedures in § 63.9914, did not exceed 7.2 lbs/hr; and</li> <li>c. The average mass flow of chlorine from the control system applied to the melt/reactor system exhaust, measured according to the performance test procedures in § 63.9914, did not exceed 100 lbs/hr.</li> <li>d. The average concentration of dioxins/furans from the control system applied to the melt/reactor system exhaust, measured according to the performance test procedures in § 63.9915, did not exceed 36 ng TEQ/dscm to 7% oxygen.</li> </ul> |

TABLE 4 TO SUBPART TTTTT OF PART 63.—CONTINUOUS COMPLIANCE WITH EMISSION LIMITS

As required in § 63.9923, you must demonstrate continuous compliance with the emission limits according to the following table:

| For . . .  | You must demonstrate continuous compliance by . . .   |
|--|---|
| 1. Each spray dryer stack .....                    | <ul style="list-style-type: none"> <li>a. Maintaining emissions of PM<sub>10</sub> at or below 100 lbs/hr; and</li> <li>b. Maintaining emissions of hydrochloric acid at or below 200 lbs/hr; and</li> <li>c. Conducting subsequent performance tests at least twice during each term of your title V operating permit (at mid-term and renewal).</li> </ul>  |
| 2. Magnesium chloride storage bins scrubber stack. | <ul style="list-style-type: none"> <li>a. Maintaining emissions of hydrochloric acid at or below 47.5 lbs/hr or 0.35 gr/dscf; and</li> <li>b. Maintaining emissions of PM<sub>10</sub> at or below 2.7 lbs/hr or 0.016 gr/dscf; and</li> <li>c. Conducting subsequent performance tests at least twice during each term of your title V operating permit (at mid-term and renewal).</li> </ul>  |
| 3. Each melt/reactor system stack                  | <ul style="list-style-type: none"> <li>a. Maintaining emissions of PM<sub>10</sub> at or below 13.1 lbs/hr; and</li> <li>b. Maintaining emissions of hydrochloric acid at or below 7.2 lbs/hr; and</li> <li>c. Maintaining emissions of chlorine at or below 100 lbs/hr; and</li> <li>d. Maintaining emissions of dioxins/furans at or below 36 ng TEQ/dscm to 7% oxygen.</li> <li>e. Conducting subsequent performance test at least twice during each term of your title V operating permit (at mid-term and renewal).</li> </ul> |
| 4. Each launder off-gas system stack.              | <ul style="list-style-type: none"> <li>a. Maintaining emissions of particulate matter at or below 37.5 lbs/hr; and</li> <li>b. Maintaining emissions of hydrochloric acid at or below 46.0 lbs/hr; and</li> <li>c. Maintaining emissions of chlorine at or below 26.0 lbs/hr; and</li> <li>d. Conducting subsequent performance tests at least twice during each term of your title V operating permit (at mid-term and renewal).</li> </ul>  |

TABLE 5 TO SUBPART TTTTT OF PART 63.—APPLICABILITY OF GENERAL PROVISIONS TO SUBPART TTTTT OF PART 63

As required in § 63.9950, you must comply with the requirements of the NESHAP General Provisions (40 CFR part 63, subpart A) shown in the following table:

| Citation   | Subject                       | Applies to Subpart TTTTT | Explanation |
|------------|-------------------------------|--------------------------|-------------|
| 63.1 ..... | Applicability .....           | Yes.                     |             |
| 63.2 ..... | Definitions .....             | Yes.                     |             |
| 63.3 ..... | Units and Abbreviations ..... | Yes.                     |             |
| 63.4 ..... | Prohibited Activities .....   | Yes.                     |             |