

Special conditions are initially applicable to the model for which they are issued. Should Raytheon Aircraft Services, Inc. apply at a later date for a supplemental type certificate to modify any other model included on Type Certificate A3EU to incorporate the same or similar novel or unusual design feature, these special conditions would also apply to the other model under the provisions of § 21.101(a)(1), Amendment 21-69, effective September 16, 1991.

Novel or Unusual Design Features

As noted earlier, the Raytheon Model HS.125 Series 700A and 700B airplanes modified by Raytheon Aircraft Services, Inc. will incorporate an EFIS that will perform critical functions. This system may be vulnerable to high-intensity radiated fields external to the airplane. The current airworthiness standards of part 25 do not contain adequate or appropriate safety standards for the protection of this equipment from the adverse effects of HIRF. Accordingly, this system is considered to be a novel or unusual design feature.

Discussion

There is no specific regulation that addresses protection requirements for

electrical and electronic systems from HIRF. Increased power levels from ground-based radio transmitters and the growing use of sensitive avionics/electronics and electrical systems to command and control airplanes have made it necessary to provide adequate protection.

To ensure that a level of safety is achieved equivalent to that intended by the regulations incorporated by reference, special conditions are needed for the Raytheon Model HS.125 Series 700A and 700B airplanes modified by Raytheon Aircraft Services, Inc. These special conditions require that new avionic/electronic and electrical systems that perform critical functions be designed and installed to preclude component damage and interruption of function due to both the direct and indirect effects of HIRF.

High-Intensity Radiated Fields (HIRF)

With the trend toward increased power levels from ground-based transmitters and the advent of space and satellite communications coupled with electronic command and control of the airplane, the immunity of critical digital avionic/electronic and electrical systems to HIRF must be established.

It is not possible to precisely define the HIRF to which the airplane will be exposed in service. There is also uncertainty concerning the effectiveness of airframe shielding for HIRF. Furthermore, coupling of electromagnetic energy to cockpit-installed equipment through the cockpit window apertures is undefined. Based on surveys and analysis of existing HIRF emitters, an adequate level of protection exists when compliance with the HIRF protection special condition is shown with either paragraph 1 or 2 below:

1. A minimum threat of 100 volts rms (root-mean-square) per meter electric field strength from 10 KHz to 18 GHz.

a. The threat must be applied to the system elements and their associated wiring harnesses without the benefit of airframe shielding.

b. Demonstration of this level of protection is established through system tests and analysis.

2. A threat external to the airframe of the field strengths indicated in the following table for the frequency ranges indicated. Both peak and average field strength components from the table are to be demonstrated.

Frequency	Field strength (volts per meter)	
	Peak	Average
10 kHz–100 kHz	50	50
100 kHz–500 kHz	50	50
500 kHz–2 MHz	50	50
2 MHz–30 MHz	100	100
30 MHz–70 MHz	50	50
70 MHz–100 MHz	50	50
100 MHz–200 MHz	100	100
200 MHz–400 MHz	100	100
400 MHz–700 MHz	700	50
700 MHz–1 GHz	700	100
1 GHz–2 GHz	2000	200
2 GHz–4 GHz	3000	200
4 GHz–6 GHz	3000	200
6 GHz–8 GHz	1000	200
8 GHz–12 GHz	3000	300
12 GHz–18 GHz	2000	200
18 GHz–40 GHz	600	200

The field strengths are expressed in terms of peak of the root-mean-square (rms) over the complete modulation period.

The threat levels identified above are the result of an FAA review of existing studies on the subject of HIRF, in light of the ongoing work of the Electromagnetic Effects Harmonization Working Group of the Aviation Rulemaking Advisory Committee.

Applicability

As discussed above, these special conditions are applicable to Raytheon

Model HS.125 Series 700A and 700B airplanes modified by Raytheon Aircraft Services, Inc. Should Raytheon Aircraft Services, Inc. apply at a later date for a supplemental type certificate to modify any other model included on Type Certificate A3EU to incorporate the same or similar novel or unusual design feature, these special conditions would apply to that model as well as under the provisions of § 21.101(a)(1),

Amendment 21-69, effective September 16, 1991.

Conclusion

This action affects only certain novel or unusual design features on the Raytheon Model HS.125 Series 700A and 700B airplanes modified by Raytheon Aircraft Services, Inc. It is not a rule of general applicability and affects only the applicant which applied