

sought, and the petitioner's argument in favor of relief.

Eastern Maine Railway; FRA Waiver Petition No. FRA-2003-15011

Eastern Maine Railway (EMRY), located in St. John, New Brunswick, Canada, seeks a permanent waiver of compliance from 49 CFR 241.7(c), *United States Locational Requirements for Dispatching of United States Rail Operations*, to allow the continuation of Canadian dispatching of that part of Mattawamkeag Subdivision located in the United States extending between Vanceboro, Maine, and Brownville Junction, Maine, approximately 99 miles, as defined in Appendix A to Part 241. This request was submitted in accordance with § 241.7(c)(3), which permits waiver of the requirements found in Part 241 that all dispatching of U.S. rail operations be conducted in the U.S. This territory was previously grandfathered in the exceptions to extraterritorial dispatching contained in FRA's Interim Final Rule (see 66 FR 63942, December 11, 2001).

In this regard, the track segment identified in the Interim Final Rule remains the same as identified above. This segment consists of a single main track dispatched from a single desk at the EMRY's Rail Traffic Control office in St. John, New Brunswick, Canada, under Canadian Rail Operating Rules (CROR), and the EMRY's Timetable and Special Instructions. The trackage is non-signaled and operated under Occupancy Control System rules. All dispatching is conducted in English. All units of measure are the same as those used in the U.S. EMRY operates approximately 2 trains a day over this segment. The train dispatchers who perform the dispatching function for the EMRY are employed by the New Brunswick Southern Railway (NBSR) and are therefore covered under the NBSR's company drug and alcohol policies and their dispatching office is under 24-hour security. The Department of Transportation of the Province of New Brunswick, Canada, is the regulatory authority which exercises safety jurisdiction over the New Brunswick Southern Railway, which provides dispatching services for the EMRY.

Based on the foregoing, EMRY seeks a permanent waiver of compliance from 49 CFR 241.7(c), *United States Locational Requirements for Dispatching of United States Rail Operations*, to allow the continuation of Canadian dispatching on that part of the Mattawamkeag Subdivision located in the United States, as described above.

Interested parties are invited to participate in this proceeding by submitting written views, data, or comments. FRA does not anticipate scheduling a public hearing in connection with the request for a waiver of certain regulatory provisions. If any interested party desires an opportunity for oral comment, he or she should notify FRA, in writing, before the end of the comment period and specify the basis for his or her request. All communications concerning these proceedings should identify the appropriate docket number (Docket Number FRA 2003-15011) and must be submitted to the DOT Docket Management Facility, Room PL-401 (Plaza level) 400 Seventh Street, SW., Washington, DC 20590. All documents in the public docket, including EMRY's detailed waiver request, are also available for inspection and copying on the Internet at the docket facility's Web site at <http://dms.dot.gov>. Communications received within 30 days of the date of this notice will be considered by FRA before final action is taken. Comments received after that date will be considered as far as practicable. All written communications concerning this proceeding are available for examination during regular business hours (9 a.m.-5 p.m.) at the above facility.

FRA wishes to inform all potential commenters that anyone is able to search the electronic form of all comments received into any of our dockets by the name of the individual submitting the comment (or signing the comment, if submitted on behalf of an association, business, labor union, etc.). You may review DOT's complete Privacy Act Statement in the Federal Register published on April 11, 2000 (Volume 65, Number 70; Pages 19477-78) or you may visit <http://dms.dot.gov>.

Issued in Washington, DC on June 11, 2003.

Grady C. Cothen, Jr.,

Deputy Associate Administrator for Safety Standards and Program Development.

[FR Doc. 03-15395 Filed 6-17-03; 8:45 am]

BILLING CODE 4910-06-P

DEPARTMENT OF TRANSPORTATION

Federal Railroad Administration

Petition for Waiver of Compliance

In accordance with part 211 of title 49 Code of Federal Regulations (CFR), notice is hereby given that the Federal Railroad Administration (FRA) received a request for a waiver of compliance with certain requirements of its safety

standards. The individual petition is described below, including the party seeking relief, the regulatory provisions involved, the nature of the relief being requested, and the petitioner's arguments in favour of relief.

National Railroad Passenger Corporation

[Docket Number FRA-2003-14444]

The National Railroad Passenger Corporation (Amtrak) has petitioned for a permanent waiver of compliance for the Acela trainsets and HHP-8 Electric locomotives from certain dimensional requirements of the *Railroad Passenger Equipment Safety Standards*, 49 CFR 238.429 and Safety Appliance Standards, 49 CFR 231.14. Amtrak requests this relief due to the unique carbody design of this new equipment and its structural frame that precludes installation of safety appliances compliant with the safety standards. Amtrak and the equipment's manufacturer have made every effort to bring the safety appliance arrangement into compliance, but find it not possible for the following items:

- Requirements of § 238.429(d)(4) & § 231.14(c)(3)(ii)—“The maximum and minimum distances from the top of the rail for vertical handrails and handholds shall be 51 inches * * *”.

Proposed alternate compliance—The current handholds are approximately 68 inches from the top of the rail. The structural integrity of the carbody side sill would be compromised by strict adherence to this dimensional requirement. Amtrak proposes an alternate solution with the installation of additional horizontal handholds on either side of the cab door, approximately 53 to 54 inches from the top of the rail. These additional handholds will provide personnel the support necessary for a safe ingress to the powercar or locomotive cab area while eliminating the danger of weakening the side sill structure. Additionally, carbody clearance constraints and strict infrastructure clearance limits dictate that the horizontal handholds have a maximum clearance of 2.0 inches.

- Requirements of § 238.429(d)(5)—“Vertical handrails and handholds shall continue to a point equal to the top edge of the control cab door.”

Relief Requested—The powercar's structural members are arranged such that they extend to a point several inches below the top of the control cab door to maximize the integrity of the upper framework. The vertical handholds are arranged to avoid interference with these structural members. Serious consideration was