

*Steel Sheet and Strip in Coils from France*, 68 FR 14948 (March 27, 2003).

#### Verification

As provided in section 782(i)(3) of the Act, we verified the information submitted by Ugine for use in our preliminary results. We used standard verification procedures, including examination of relevant accounting and production records and original source documents provided by Ugine. From June 15, 2003 through June 20, 2003, we verified sales and successorship information provided by Ugine. From June 24, 2003 through July 1, 2003, we verified constructed export price ("CEP") sales information provided by Ugine and its U.S. sales affiliates. Our verification results are outlined in the public version of the verification report and are on file in the Central Records Unit ("CRU") located in room B-099 of the main Department of Commerce Building, 14th Street and Constitution Avenue, NW., Washington, DC. See *Memorandum from Cheryl Werner and Eugene Degnan, Case Analysts through James C. Doyle, Program Manager, to the File: Verification of Sales and Successorship for Ugine S.A. in the 3rd Antidumping Duty Administrative Review of Stainless Steel Sheet and Strip in Coils from France*, dated July 31, 2003 ("Home Market Report"); *Memorandum from Cheryl Werner and Kit Rudd, Case Analysts through James C. Doyle, Program Manager, to the File: Verification of CEP Sales for Usinor Stainless USA in the 3rd Antidumping Duty Administrative Review of Stainless Steel Sheet and Strip in Coils from France*, dated July 31, 2003 ("U.S. Sales Report I"); and *Memorandum from Cheryl Werner and Kit Rudd, Case Analysts through James C. Doyle, Program Manager, to the File: Verification of CEP Sales for Hague Steel Corporation in the 3rd Antidumping Duty Administrative Review of Stainless Steel Sheet and Strip in Coils from France*, dated July 31, 2002 ("U.S. Sales Report II").

#### Period of Review

The period of review ("POR") is July 1, 2001, through June 30, 2002.

#### Scope of Review

For purposes of this administrative review, the products covered are certain stainless steel sheet and strip in coils. Stainless steel is an alloy steel containing, by weight, 1.2 percent or less of carbon and 10.5 percent or more of chromium, with or without other elements. The subject sheet and strip is a flat-rolled product in coils that is greater than 9.5 mm in width and less

than 4.75 mm in thickness, and that is annealed or otherwise heat treated and pickled or otherwise descaled. The subject sheet and strip may also be further processed (e.g., cold-rolled, polished, aluminized, coated, etc.) provided that it maintains the specific dimensions of sheet and strip following such processing.

The merchandise subject to this order is currently classifiable in the Harmonized Tariff Schedule of the United States ("HTS") at subheadings:

7219.13.0031, 7219.13.0051, 7219.13.0071, 7219.1300.81<sup>1</sup>, 7219.14.0030, 7219.14.0065, 7219.14.0090, 7219.32.0005, 7219.32.0020, 7219.32.0025, 7219.32.0035, 7219.32.0036, 7219.32.0038, 7219.32.0042, 7219.32.0044, 7219.33.0005, 7219.33.0020, 7219.33.0025, 7219.33.0035, 7219.33.0036, 7219.33.0038, 7219.33.0042, 7219.33.0044, 7219.34.0005, 7219.34.0020, 7219.34.0025, 7219.34.0030, 7219.34.0035, 7219.35.0005, 7219.35.0015, 7219.35.0030, 7219.35.0035, 7219.90.0010, 7219.90.0020, 7219.90.0025, 7219.90.0060, 7219.90.0080, 7220.12.1000, 7220.12.5000, 7220.20.1010, 7220.20.1015, 7220.20.1060, 7220.20.1080, 7220.20.6005, 7220.20.6010, 7220.20.6015, 7220.20.6060, 7220.20.6080, 7220.20.7005, 7220.20.7010, 7220.20.7015, 7220.20.7060, 7220.20.7080, 7220.20.8000, 7220.20.9030, 7220.20.9060, 7220.90.0010, 7220.90.0015, 7220.90.0060, and 7220.90.0080.

Although the HTS subheadings are provided for convenience and Customs purposes, the Department's written description of the merchandise under review is dispositive.

Excluded from the review of this order are the following: (1) Sheet and strip that is not annealed or otherwise heat treated and pickled or otherwise descaled, (2) sheet and strip that is cut to length, (3) plate (i.e., flat-rolled stainless steel products of a thickness of 4.75 mm or more), (4) flat wire (i.e., cold-rolled sections, with a prepared edge, rectangular in shape, of a width of not more than 9.5 mm), and (5) razor blade steel. Razor blade steel is a flat-rolled product of stainless steel, not further worked than cold-rolled (cold-reduced), in coils, of a width of not more than 23 mm and a thickness of

0.266 mm or less, containing, by weight, 12.5 to 14.5 percent chromium, and certified at the time of entry to be used in the manufacture of razor blades. See Chapter 72 of the HTS, "Additional U.S. Note" 1(d).

Flapper valve steel is also excluded from the scope of the order. This product is defined as stainless steel strip in coils containing, by weight, between 0.37 and 0.43 percent carbon, between 1.15 and 1.35 percent molybdenum, and between 0.20 and 0.80 percent manganese. This steel also contains, by weight, phosphorus of 1.025 percent or less, silicon of between 0.20 and 0.50 percent, and sulfur of 1.020 percent or less. The product is manufactured by means of vacuum arc remelting, with inclusion controls for sulphide of not more than 0.04 percent and for oxide of no more than 0.05 percent. Flapper valve steel has a tensile strength of between 210 and 300 ksi, yield strength of between 170 and 270 ksi, plus or minus 8 ksi, and a hardness (Hv) of between 460 and 590. Flapper valve steel is most commonly used to produce specialty flapper valves in compressors.

Also excluded is a product referred to as suspension foil, a specialty steel product used in the manufacture of suspension assemblies for computer disk drives. Suspension foil is described as 302/304 grade or 202 grade stainless steel of a thickness between 14 and 127 microns, with a thickness tolerance of plus-or-minus 2.01 microns, and surface glossiness of 200 to 700 percent Gs. Suspension foil must be supplied in coil widths of not more than 407 mm, and with a mass of 225 kg or less. Roll marks may only be visible on one side, with not scratches of measurable depth. The material must exhibit residual stresses of 2 mm maximum deflection, and flatness of 1.6 mm over 685 mm length.

Certain stainless steel foil for automotive catalytic converters is also excluded from the scope of this order. This stainless steel strip in coils is a specialty foil with a thickness of between 20 and 110 microns used to produce a metallic substrate with a honeycomb structure for use in automotive catalytic converters. The steel contains, by weight, carbon of no more than 0.030 percent, silicon of no more than 1.0 percent, manganese of no more than 1.0 percent, chromium of between 19 and 22 percent, aluminum of no less than 5.0 percent, phosphorus of no more than 0.045 percent, sulfur of no more than 0.03 percent, lanthanum of less than 0.002 or greater than 0.05 percent, and total rare earth elements of more than 0.06 percent, with the balance iron.

<sup>1</sup> Due to changes to the HTS numbers in 2001, 7219.13.0030, 7219.13.0050, 7219.13.0070, and 7219.13.0080 are now 7219.13.0031, 7219.13.0051, 7219.13.0071, and 7219.13.0081, respectively.