

LEC's outside plant at or near a multiunit premises. One category of this subloop is inside wire, which is defined for purposes of this section as all loop plant owned or controlled by the incumbent LEC at a multiunit customer premises between the minimum point of entry as defined in § 68.105 of this chapter and the point of demarcation of the incumbent LEC's network as defined in § 68.3 of this chapter.

(i) *Point of technically feasible access.* A point of technically feasible access is any point in the incumbent LEC's outside plant at or near a multiunit premises where a technician can access the wire or fiber within the cable without removing a splice case to reach the wire or fiber within to access the wiring in the multiunit premises. Such points include, but are not limited to, a pole or pedestal, the network interface device, the minimum point of entry, the single point of interconnection, and the feeder/distribution interface.

(ii) *Single point of interconnection.* Upon notification by a requesting telecommunications carrier that it requests interconnection at a multiunit premises where the incumbent LEC owns, controls, or leases wiring, the incumbent LEC shall provide a single point of interconnection that is suitable for use by multiple carriers. This obligation is in addition to the incumbent LEC's obligations, under paragraph (b)(2) of this section, to provide nondiscriminatory access to a subloop for access to multiunit premises wiring, including any inside wire, at any technically feasible point. If the parties are unable to negotiate rates, terms, and conditions under which the incumbent LEC will provide this single point of interconnection, then any issues in dispute regarding this obligation shall be resolved in state proceedings under section 252 of the Act.

(3) *Other subloop provisions—(i) Technical feasibility.* If parties are unable to reach agreement through voluntary negotiations as to whether it is technically feasible, or whether sufficient space is available, to unbundle a copper subloop or subloop for access to multiunit premises wiring at the point where a telecommunications carrier requests, the incumbent LEC shall have the burden of demonstrating to the state commission, in state proceedings under section 252 of the Act, that there is not sufficient space available, or that it is not technically feasible to unbundle the subloop at the point requested.

(ii) *Best practices.* Once one state commission has determined that it is technically feasible to unbundle

subloops at a designated point, an incumbent LEC in any state shall have the burden of demonstrating to the state commission, in state proceedings under section 252 of the Act, that it is not technically feasible, or that sufficient space is not available, to unbundle its own loops at such a point.

(c) *Network interface device.* Apart from its obligation to provide the network interface device functionality as part of an unbundled loop or subloop, an incumbent LEC also shall provide nondiscriminatory access to the network interface device on an unbundled basis, in accordance with section 251(c)(3) of the Act and this part. The network interface device element is a stand-alone network element and is defined as any means of interconnection of customer premises wiring to the incumbent LEC's distribution plant, such as a cross-connect device used for that purpose. An incumbent LEC shall permit a requesting telecommunications carrier to connect its own loop facilities to on-premises wiring through the incumbent LEC's network interface device, or at any other technically feasible point.

(d) *Local circuit switching.* An incumbent LEC shall provide a requesting telecommunications carrier with nondiscriminatory access to local circuit switching, including tandem switching, on an unbundled basis, in accordance with section 251(c)(3) of the Act and this part as set forth in paragraph (d) of this section.

(1) *Definition.* Local circuit switching is defined as follows:

(i) Local circuit switching encompasses all line-side and trunk-side facilities, plus the features, functions, and capabilities of the switch. The features, functions, and capabilities of the switch shall include the basic switching function of connecting lines to lines, lines to trunks, trunks to lines, and trunks to trunks.

(ii) Local circuit switching includes all vertical features that the switch is capable of providing, including custom calling, custom local area signaling services features, and Centrex, as well as any technically feasible customized routing functions.

(2) *DSO capacity (i.e., mass market) determinations.* An incumbent LEC shall provide access to local circuit switching on an unbundled basis to a requesting telecommunications carrier serving end users using DSO capacity loops except where the state commission has found, in accordance with the conditions set forth in paragraph (d)(2) of this section, that requesting telecommunications carriers are not impaired in a particular market,

or where the state commission has found that all such impairment would be cured by implementation of transitional unbundled local circuit switching in a given market and has implemented such transitional access as set forth in paragraph (d)(2)(iii)(C) of this section.

(i) *Market definition.* A state commission shall define the markets in which it will evaluate impairment by determining the relevant geographic area to include in each market. In defining markets, a state commission shall take into consideration the locations of mass market customers actually being served (if any) by competitors, the variation in factors affecting competitors' ability to serve each group of customers, and competitors' ability to target and serve specific markets profitably and efficiently using currently available technologies. A state commission shall not define the relevant geographic area as the entire state.

(ii) *Batch cut process.* In each of the markets that the state commission defines pursuant to paragraph (d)(2)(i) of this section, the state commission shall either establish an incumbent LEC batch cut process as set forth in paragraph (d)(2)(ii)(A) of this section or issue detailed findings explaining why such a batch process is unnecessary, as set forth in paragraph (d)(2)(ii)(B) of this section. A batch cut process is defined as a process by which the incumbent LEC simultaneously migrates two or more loops from one carrier's local circuit switch to another carrier's local circuit switch, giving rise to operational and economic efficiencies not available when migrating loops from one carrier's local circuit switch to another carrier's local circuit switch on a line-by-line basis.

(A) A state commission shall establish an incumbent LEC batch cut process for use in migrating lines served by one carrier's local circuit switch to lines served by another carrier's local circuit switch in each of the markets the state commission has defined pursuant to paragraph (d)(2)(i) of this section. In establishing the incumbent LEC batch cut process:

(1) A state commission shall first determine the appropriate volume of loops that should be included in the "batch."

(2) A state commission shall adopt specific processes to be employed when performing a batch cut, taking into account the incumbent LEC's particular network design and cut over practices.

(3) A state commission shall evaluate whether the incumbent LEC is capable of migrating multiple lines served using