

estimate that it would take approximately 0.5 work hour per engine to calculate the 6th stage LPT air seal part life, and that the average labor rate is \$65 per work hour. Based on these figures, we estimate the total cost of the proposed AD to U.S. operators to be \$11,928.

Regulatory Findings

We have determined that this proposed AD would not have federalism implications under Executive Order 13132. This proposed AD would not have a substantial direct effect on the States, on the relationship between the national Government and the States, or on the distribution of power and responsibilities among the various levels of government.

For the reasons discussed above, I certify that the proposed regulation:

1. Is not a "significant regulatory action" under Executive Order 12866;
2. Is not a "significant rule" under the DOT Regulatory Policies and Procedures (44 FR 11034, February 26, 1979); and
3. Would not have a significant economic impact, positive or negative, on a substantial number of small entities under the criteria of the Regulatory Flexibility Act.

We prepared a summary of the costs to comply with this proposal and placed it in the AD Docket. You may get a copy of this summary by sending a request to us at the address listed under **ADDRESSES**. Include "AD Docket No. 2003-NE-34-AD" in your request.

List of Subjects in 14 CFR Part 39

Air transportation, Aircraft, Aviation safety, Safety.

The Proposed Amendment

Accordingly, under the authority delegated to me by the Administrator, the Federal Aviation Administration proposes to amend 14 CFR part 39 as follows:

PART 39—AIRWORTHINESS DIRECTIVES

1. The authority citation for part 39 continues to read as follows:

Authority: 49 U.S.C. 106(g), 40113, 44701.

§ 39.13 [Amended]

2. The FAA amends § 39.13 by adding the following new airworthiness directive:

Pratt & Whitney: Docket No. 2003-NE-34-AD.

Comments Due Date

(a) The Federal Aviation Administration (FAA) must receive comments on this airworthiness directive (AD) action by November 4, 2003.

Affected ADs

- (b) None.

Applicability

(c) This AD applies to Pratt & Whitney (PW) JT9D-3A, -7, -7A, -7AH, -7H, -7F, -7J, -20, and -20J turbofan engines. These engines are installed on, but not limited to, Boeing 747-100, 747-200, 747SR, 747SP, and DC10-40 series airplanes.

Unsafe Condition

(d) This proposed AD is prompted by reports of certain 6th stage low pressure turbine (LPT) air seals possibly not being life tracked due to confusion from updates to the engine manuals. Chapter 5 of Engine Manuals part numbers (P/Ns) 646028, 770407, and 770408 will be revised to show a life limit of 15,000 cycles-since-new (CSN) for 6th stage air seal P/N's 808846, 809171, 811260 and 811261. We are issuing this AD to prevent failure of the 6th stage LPT air seal which could cause LPT damage, resulting in an uncontained engine failure.

Compliance

(e) You are responsible for having the actions required by this AD performed within the compliance times specified unless the actions have already been done.

Determine Service Life

(f) For 6th stage LPT air seals, P/Ns 808846, 809171, 811260, and 811261, with an unknown number of cycles since installed, calculate the service life within 60 days after the effective date of this AD.

(1) Use Method 1 of the Accomplishment Instructions of PW Service Bulletin (SB) No. JT9D 6448, dated June 10, 2003, for when all service records are available for the specific air seal, to calculate the service life.

(2) Use Method 2 of the Accomplishment Instructions of PW SB No. JT9D 6448, dated June 10, 2003, for when any or all service records are not available for a specific air seal, to calculate the service life. If the worst-case daily utilization rate is unknown, use the fleet worst-case daily utilization rate of 2.9 cycles/day.

Removal From Service

(g) Remove 6th stage LPT air seals, P/Ns 808846, 809171, 811260, and 811261, from service at or before accumulating the CSN in the following Table 1.

TABLE 1.—PART NUMBER AND ENGINE APPLICABILITY

Part No.	Engine applicability	Life limit CSN
808846 (old)	JT9D-3A, -7, -7A, -7AH, -7H, -7F, -7J, -20, -20J	15,000
811260 (new)	JT9D-3A, -7, -7A, -7AH, -7H, -7F, -7J, -20, -20J	15,000
809171 (old)	JT9D-3A, -7, -7A, -7AH, -7H, -7F, -20	15,000
811261 (new)	JT9D-3A, -7, -7A, -7AH, -7H, -7F, -20	15,000

(h) If the service life cannot be determined as specified in paragraph (f) of this AD, remove the 6th stage LPT air seal before accumulating 2,500 cycles-in-service after the effective date of this AD.

(i) After the effective date of this AD, do not install any 6th stage LPT air seal, P/N 808846, 809171, 811260, or 811261, that exceeds 15,000 CSN, or that was removed to comply with paragraph (h) of this AD because its service life could not be determined.

Alternative Methods of Compliance

(j) The Manager, Engine Certification Office, has the authority to approve alternative methods of compliance for this

AD if requested using the procedures found in 14 CFR 39.19.

Material Incorporated by Reference

(k) You must use Pratt & Whitney Service Bulletin No. JT9D 6448, dated June 10, 2003, to perform the service life calculations required by this AD. Approval of incorporation by reference from the Office of the Federal Register is pending.

Related Information

- (l) None.

Issued in Burlington, Massachusetts, on August 28, 2003.

Jay J. Pardee,

Manager, Engine and Propeller Directorate, Aircraft Certification Service.

[FR Doc. 03-22621 Filed 9-4-03; 8:45 am]

BILLING CODE 4910-13-P