

following are not considered wastewater for the purposes of this subpart:

- (1) Stormwater from segregated sewers;
- (2) Water from fire-fighting and deluge systems, including testing of such systems;
- (3) Spills;
- (4) Water from safety showers;
- (5) Samples of a size not greater than reasonably necessary for the method of analysis that is used;

- (6) Equipment leaks;
- (7) Wastewater drips from procedures such as disconnecting hoses after cleaning lines; and
- (8) Noncontact cooling water.

*Wastewater stream* means a stream that contains only wastewater as defined in this paragraph (h).

*Work practice standard* means any design, equipment, work practice, or operational standard, or combination

thereof, that is promulgated pursuant to section 112(h) of the CAA.

#### Tables to Subpart FFFF of Part 63

As required in § 63.2455, you must meet each emission limit and work practice standard in the following table that applies to your continuous process vents:

TABLE 1 TO SUBPART FFFF OF PART 63.—EMISSION LIMITS AND WORK PRACTICE STANDARDS FOR CONTINUOUS PROCESS VENTS

For each . . .	For which . . .	Then you must . . .
1. Group 1 continuous process vent.	a. Not applicable .....	i. Reduce emissions of total organic HAP by ≥98 percent by weight or to an outlet process concentration ≤20 ppmv as organic HAP or TOC by venting emissions through a closed-vent system to any combination of control devices (except a flare); or ii. Reduce emissions of total organic HAP by venting emissions through a closed vent system to a flare; or iii. Use a recovery device to maintain the TRE above 1.9 for an existing source or above 5.0 for a new source.
2. Halogenated Group 1 continuous process vent stream.	a. You use a combustion control device to control organic HAP emissions.	i. Use a halogen reduction device after the combustion device to reduce emissions of hydrogen halide and halogen HAP by ≥99 percent by weight, or to ≤0.45 kg/hr, or to ≤20 ppmv; or ii. Use a halogen reduction device before the combustion device to reduce the halogen atom mass emission rate to ≤0.45 kg/hr or to a concentration ≤20 ppmv. Comply with the requirements in § 63.993 and the requirements referenced therein.
3. Group 2 continuous process vent at an existing source.	You use a recovery device to maintain the TRE level >1.9 but ≤5.0.	Comply with the requirements in § 63.993 and the requirements referenced therein.
4. Group 2 continuous process vent at a new source.	You use a recovery device to maintain the TRE level >5.0 but ≤8.0.	

As required in § 63.2460, you must meet each emission limit and work

practice standard in the following table that applies to your batch process vents:

TABLE 2 TO SUBPART FFFF OF PART 63. EMISSION LIMITS AND WORK PRACTICE STANDARDS FOR BATCH PROCESS VENTS

For each . . .	Then you must . . .	And you must . . .
1. Process with Group 1 batch process vents.	a. Reduce collective uncontrolled organic HAP emissions from the sum of all batch process vents within the process by ≥98 percent by weight by venting emissions from a sufficient number of the vents through a closed-vent system to any combination of control devices (except a flare); or b. Reduce collective uncontrolled organic HAP emissions from the sum of all batch process vents within the process by ≥95 percent by weight by venting emissions from a sufficient number of the vents through a closed-vent system to any combination of recovery devices; or c. For all batch process vents within the process that are not controlled by venting through a closed-vent system to a flare or to any other combination of control devices that reduce total organic HAP to an outlet concentration ≤20 ppmv as TOC or total organic HAP, reduce organic HAP emissions by venting emissions from a sufficient number of the vents through a closed-vent system to any combination of recovery devices that reduce collective emissions by ≥95 percent by weight and/or any combination of control devices that reduce collective emissions by ≥98 percent by weight.	Not applicable.  Not applicable.  Not applicable.