

available under proprietary trade names such as "Arnokrome III."²

Certain electrical resistance alloy steel is also excluded from the scope of this order. This product is defined as a non-magnetic stainless steel manufactured to American Society of Testing and Materials (ASTM) specification B344 and containing, by weight, 36 percent nickel, 18 percent chromium, and 46 percent iron, and is most notable for its resistance to high temperature corrosion. It has a melting point of 1390 degrees Celsius and displays a creep rupture limit of 4 kilograms per square millimeter at 1000 degrees Celsius. This steel is most commonly used in the production of heating ribbons for circuit breakers and industrial furnaces, and in rheostats for railway locomotives. The product is currently available under proprietary trade names such as "Gilphy 36."³

Certain martensitic precipitation-hardenable stainless steel is also excluded from the scope of this order. This high-strength, ductile stainless steel product is designated under the Unified Numbering System (UNS) as S45500-grade steel, and contains, by weight, 11 to 13 percent chromium, and 7 to 10 percent nickel. Carbon, manganese, silicon and molybdenum each comprise, by weight, 0.05 percent or less, with phosphorus and sulfur each comprising, by weight, 0.03 percent or less. This steel has copper, niobium, and titanium added to achieve aging, and will exhibit yield strengths as high as 1700 Mpa and ultimate tensile strengths as high as 1750 Mpa after aging, with elongation percentages of 3 percent or less in 50 mm. It is generally provided in thicknesses between 0.635 and 0.787 mm, and in widths of 25.4 mm. This product is most commonly used in the manufacture of television tubes and is currently available under proprietary trade names such as "Durphynox 17."⁴

Finally, three specialty stainless steels typically used in certain industrial blades and surgical and medical instruments are also excluded from the scope of this order. These include stainless steel strip in coils used in the production of textile cutting tools (e.g., carpet knives).⁵ This steel is similar to ASTM grade 440F, but containing, by weight, 0.5 to 0.7 percent of molybdenum. The steel also contains, by weight, carbon of between 1.0 and

1.1 percent, sulfur of 0.020 percent or less, and includes between 0.20 and 0.30 percent copper and between 0.20 and 0.50 percent cobalt. This steel is sold under proprietary names such as "GIN4 Mo." The second excluded stainless steel strip in coils is similar to AISI 420-J2 and contains, by weight, carbon of between 0.62 and 0.70 percent, silicon of between 0.20 and 0.50 percent, manganese of between 0.45 and 0.80 percent, phosphorus of no more than 0.025 percent and sulfur of no more than 0.020 percent. This steel has a carbide density on average of 100 carbide particles per square micron. An example of this product is "GIN5" steel. The third specialty steel has a chemical composition similar to AISI 420 F, with carbon of between 0.37 and 0.43 percent, molybdenum of between 1.15 and 1.35 percent, but lower manganese of between 0.20 and 0.80 percent, phosphorus of no more than 0.025 percent, silicon of between 0.20 and 0.50 percent, and sulfur of no more than 0.020 percent. This product is supplied with a hardness of more than Hv 500 guaranteed after customer processing, and is supplied as, for example, "GIN6."⁶

Analysis of Comments Received

All issues raised in the case and rebuttal briefs by parties to this administrative review are addressed in the "Issues and Decision Memorandum" (Decision Memorandum) from Joseph A. Spetrini, Deputy Assistant Secretary for Import Administration to Faryar Shirzad, Assistant Secretary for Import Administration, dated February 3, 2003, which is hereby adopted by this notice. A list of the issues which parties have raised and to which we have responded, all of which are in the Decision Memorandum, is attached to this notice as an appendix. Parties can find a complete discussion of all issues raised in this review and the corresponding recommendations in this public memorandum which is on file in room B-099 of the main Department of Commerce building. In addition, a complete version of the Decision Memorandum can be accessed directly on the internet at www.ia.ita.doc.gov. The paper copy and electronic version of the Decision Memorandum are identical in content.

Changes Since the Preliminary Results

Based on our analysis of comments received, we have made changes in the margin calculations. The changes are listed below:

- We have calculated average values for finish, gauge, width, hot/cold rolled, and temper for any sales missing these physical characteristics.

- We modified our calculation of interest expenses.

- We have deducted indirect selling expenses incurred in the country of manufacture from U.S. price and in our calculation of CEP profit to account for all U.S. selling expenses for TKN's affiliated U.S. reseller KHSP.

- We have also corrected certain programming and clerical errors in our preliminary results, where applicable. Any alleged programming errors with which we do not agree are discussed in the relevant sections of the Decision Memorandum, accessible in B-099 of the main Department of Commerce building and on the web at www.ia.ita.doc.gov.

Final Results of the Review

We determine the following percentage weighted-average margin exists for the period July 1, 2000 through June 30, 2001:

Manufacturer/Exporter	Weighted average margin (percentage)
TKN	4.77

Liquidation

The Department shall determine, and U.S. Customs Service (Customs) shall assess, antidumping duties on all appropriate entries. In accordance with 19 CFR 351.212(b)(1), we have calculated exporter/importer-specific assessment rates. The Department will issue appropriate assessment instructions directly to Customs within 15 days of publication of these final results of review. With respect to constructed export price sales, we divided the total dumping margins for the reviewed sales by the total entered value of those reviewed sales for each importer. We will direct Customs to assess the resulting assessment rate against the entered Customs values for the subject merchandise on each of the importer's entries under the relevant order during the POR.

Cash Deposit Requirements

The following deposit requirements will be effective upon publication of this notice of final results of administrative review for all shipments of stainless steel sheet and strip in coils from Germany entered, or withdrawn from warehouse, for consumption on or after the date of publication, as provided by section 751(a)(1) of the Tariff Act: (1) The cash deposit rate for the reviewed

² "Arnokrome III" is a trademark of the Arnold Engineering Company.

³ "Gilphy 36" is a trademark of Imphy, S.A.

⁴ "Durphynox 17" is a trademark of Imphy, S.A.

⁵ This list of uses is illustrative and provided for descriptive purposes only.

⁶ "GIN4 Mo," "GIN5" and "GIN6" are the proprietary grades of Hitachi Metals America, Ltd.