

| Table E.II.2 Assessment Requirements for Transmission Pipelines in HCAs (Re-assessment intervals are maximum allowed) | | | | | | |
|---|----------------------|--|---|----------------------|------------------------|---|
| Re-Assessment Requirements (see Note 3) | | | | | | |
| Baseline Assessment Method (see Note 3) | At or above 50% SMYS | | | At or above 30% SMYS | | Below 30% SMYS |
| | Max | Re-Assessment Interval | Assessment Method | Max | Re-Assessment Interval | Assessment Method |
| Pressure Testing | 7 | CDA | CDA | 7 | Ongoing | Preventative & Mitigative (P&M) Measures (see Table E.II.3), (see Note 2) |
| | 10 | Pressure Test or ILI or DA | Pressure Test or ILI or DA (see Note 1) | 15 (see Note 1) | Ongoing | Pressure Test or ILI or DA (see Note 1) |
| | | Repeat inspection cycle every 10 years | Repeat inspection cycle every 15 years | | 20 | Pressure Test or ILI or DA |
| | | | | | | Repeat inspection cycle every 20 years |
| In-Line Inspection | 7 | CDA | CDA | 7 | Ongoing | Preventative & Mitigative (P&M) Measures (see Table E.II.3), (see Note 2) |
| | 10 | ILI or DA or Pressure Test | ILI or DA or Pressure Test (see Note 1) | 15 (see Note 1) | Ongoing | ILI or DA or Pressure Test |
| | | Repeat inspection cycle every 10 years | Repeat inspection cycle every 15 years | | 20 | ILI or DA or Pressure Test |
| | | | | | | Repeat inspection cycle every 20 years |