# AN INTELLIGENCE SERIES

# ULTRA IN THE ATLANTIC Volume IV

# TECHNICAL INTELLIGENCE FROM ALLIED COMMUNICATIONS INTELLIGENCE

# An Edited Version of SRH-025

- German Search Receivers and Radar.
- Anti-detection Devices.
- Schnorchel.
- Armament (Torpedoes and Anti-aircraft guns).
- German-Japanese Exchange of Information.
- Fuel.
- U-boat Navigation.
- U-boat Communications and U.S. Navy Communications Intelligence.

Edited By Jeffrey K. Bray

From Aegean Park Press

# **ULTRA IN THE ATLANTIC**

**VOLUME IV** 

# **TECHNICAL INTELLIGENCE FROM ALLIED COMMUNICATIONS INTELLIGENCE**

Edited by

Jeffrey K. Bray

ISBN: 0-89412-238-X

Aegean Park Press P.O. Box 2837 Laguna Hills, CA 92654 (714) 586-8811 FAX (714) 586-8269

Manufactured in the United States of America

# **ULTRA IN THE ATLANTIC**

### **VOLUME IV**

### TECHNICAL INTELLIGENCE FROM ALLIED COMMUNICATIONS INTELLIGENCE

			page
Acknowl	ledgme	nts	v
Preface			vii
Introduc	tion		ix
List of	Abbrevi	iations	xxi
Chapter	I	German Search Receivers and Radar.	1
Chapter	II	Anti-detection Devices.	13
Chapter	III	Schnorchel.	21
Chapter	IV	Armament (Torpedoes and Anti-aircraft guns).	27
Chapter	v	German-Japanese Exchange of Information.	39
Chapter	VI	Fuel.	47
Chapter	VII	U-boat Navigation.	51
Chapter	VIII	U-boat Communications and U.S. Navy Communications Intelligence.	59

This effort was originally intended to correct the quality of the copies that are currently on file at the National Archives and Records Administration in Washington, D.C. Throughout the process of retyping and editing the manuscript many individuals contributed to the overall success and the open disclosure of the "Battle of the Atlantic History."

Specifically I would like to thank Vice Admiral John M. McConnell, Director of the National Security Agency and his outstanding staff in the Freedom of Information Office; Mr. Bernard Cavalcante and Mrs. Kathy Lloyd at the Operational Archives, Naval Historical Center; Mr. John Taylor and Mr. Barry Zerby at the Military Reference Branch, National Archive and Records Administration; Mr. Dennis Vetock at the U.S. Army Military History Institute; Mr. Grady Lewis and Mr. Irv Newman at the Naval Cryptologic Veteran's Association; Mrs. Alice Creighton at the Special Collections Division, Nimitz Library, U. S. Naval Academy; and Lt. Patrick Padgett and LN1 Steve Neal at the Staff Judge Advocate Office, Naval Security Group Command.

I would also like to thank Dr. Carl Boyd, at Old Dominion University, for his assistance and encouragement provided throughout the whole effort. The assistance provided by the many cryptologic veterans of the Second World War who have also given their time is greatly appreciated.

Every attempt has been made to correct any errors in the manuscript. The original copy was in draft form and never went into production. The intent has been made to keep the history in the same format as drafted. Several corrections are included and, in some instances, clarification is offerred to benefit the reader's understanding. Any oversights are those of the editor.

V

#### Preface

The Battle of the Atlantic series was an official internal history of the activities of Director of Naval Communications (OP-20-GI-A). The history comprised five volumes. In the original draft version appendices appeared in between individual chapters. This format can result in confusion and it interrupts the normal flow of the text. All of the appendices have been combined into a single group and comprise the contents of volume six.

Specifically, the contents of each volume is as follows:

Volume I	Allied Communication Intelligence and the Battle of the Atlantic
Volume II	U-Boat Operations
Volume III	German Naval Communication Intelligence
Volume IV	Technical Intelligence from Allied Communications Intelligence
Volume V	German Naval Grid and its Cipher
Volume VI	Appendices

Volume four of the U.S. Navy's "Battle of the Atlantic" history is a review of U-boat operations from a communications intelligence perspective. Volume four is a full disclosure edition of Special Research History-025 (SRH-025) of the Records of the National Security Agency (Record Group 457) presently held at the National Archives and Records Administration. While the actual authors have remained anonymous it is known that the draft version was proof read and annotated by, then Captain, Joseph N. Wenger.<sup>1</sup> The work was so closely guarded that even the senior officers assigned within the Atlantic Section were not aware of its development

<sup>&</sup>lt;sup>1</sup>The annotations have been verified by the editor's interview with Admiral Wenger's son, Jeffrey Wenger, on 2 January 1994. Admiral Wenger was then the head of OP-20-G.

or existence.<sup>2</sup> It is most likely the product of Lieutenant John V. Connorton who was Captain Wenger's staff historian for OP-20-G and had access to the Atlantic Section's files.

The American "Battle of the Atlantic" history is not an all encompassing document. The series was written near the end of the war. The project was started around November 1944 and was not completed until shortly after V-J Day. Since the American history was completed as the war was ending it only uses sources available at the time in the offices of the Atlantic Section. However, unknown to many, the British at GC&CS were able to accomplish a more comprehensive study. A twentyfour volume naval history of communications intelligence in the Second World War was completed following the end of the war. The British series exclusively covers the naval conflict in the Atlantic and European theaters and a good portion it was the product of several American naval officers assigned to Bletchley Park.<sup>3</sup> The British effort was able to utilize all sources. Allied and Axis, in documenting the war from the perspective of communications intelligence and as such presents a more comprehensive study.

However, the American study provides a detailed view of the struggle for the Atlantic. The problems of Allied collaboration continuously plagued the communications intelligence effort. The increasing levels of intercepted message traffic, especially following the Normandy landings, placed a heavy strain on the whole apparatus. Nevertheless, as is demonstrated, the priority of eliminating the U-boat threat with this new form of special intelligence reconciled many differences. ŏ

õ

č

õ

ŏ

ŏ

ŏ

ŏ

<sup>&</sup>lt;sup>2</sup>Editor's interviews with Willard "Van" O. Quine on 18 September 1993, Knight McMahan on 5 October 1993, and Allan Moltzen on 2 November 1993.

<sup>&</sup>lt;sup>3</sup>Editor's interview with Knight McMahan on 5 October 1993.

The conduct of the Battle of the Atlantic was unlike any previous conflict on the high seas. Risks were substantially high for both sides. The excessive loss of vessels on either side could effect the outcome. For the Allies this meant the protection of merchant shipping. For the Germans, the protection of U-boats from Allied escorts and aircraft was paramount. Both sides relied significantly upon technological advances to gain the upper hand. To achieve the advantage in this technical tug of war the need for technical intelligence was paramount. To this end, the Allies were able to obtain a variety of technical details about the enemy from intercepted communications.

Communications intelligence proved to be a source of high reliability which benefited the Allied cause. A wide variety of sources were available which provided technical details on U-boat operations, weapons, equipment, and projected innovations. These sources included, in addition to the intercepted U-boat messages, the German Naval Attaché in Tokyo, the Japanese Naval Attaché in Berlin, the Japanese Ambassador in Berlin, and several non-U-boat German naval units. Additional technical material was even obtained from a series of special radar situation reports (PSREs) issued by Uboat Command itself.<sup>1</sup> Even some forms of clandestine traffic provided insight into German naval technology. However, communications intelligence was not to be considered the sole source of technical intelligence.

Complete technical intelligence required the fusion of a variety of information from a diverse collection of sources. Communications intelligence topped the list of sources due to its extraordinary level of reliability. Captured documents were next in reliability to be followed by captured material. Intelligence obtained through the interrogation of prisoners of war (POWs) also provided corroborating technical details. In many cases, it was disclosures from POWs that assisted the intelligence officers in forming correct assumption from analyzing all the information involved.

<sup>&</sup>lt;sup>1</sup>Records of the National Security Agency, "OP-20-GI Special Studies Relating to U-boat Activities, 1943-1945," SRMN-054 (Part 1), 241-302. National Archives, Washington, D.C., Record Group 457 (hereafter cited as NSA, RG 457, with filing designations).

The rapid advances in technology experienced in the Second World War were unlike those from any period in history. The Germans had demonstrated that they were technically inclined and demonstrated this frequently with the sudden appearances of new innovations. The identification of many of these innovations involved German lexicon that were simply unknown to the Allied code breakers. For example, the word "schnorchel" was first seen in Baltic U-boat communications in December 1943.<sup>2</sup> Confusion developed as to the actual meaning of the word and what it implied.<sup>3</sup> It was only following the disclosure of the First Lieutenant of U-172 during interrogation that the Allies had a clear understanding of the meaning of the term schnorchel.

The example of schnorchel exposes the need for correlating all forms of intelligence to provide accurate analysis. The sensitivities of communications intelligence prohibited casual distribution of intercepted material. The risks of compromise were too great and therefore the communications intelligence personnel would have to evaluate all intelligence to gain a proper perspective. For the Americans this function in the Atlantic theater was accomplished by the Communications Intelligence Section (OP-20-G) of the Office of the Director of Naval Communications (OP-20). The final responsibility for this fell upon the Atlantic Section (OP-20-GI-A) of the Communications Intelligence Section.

The Atlantic Section processed and disseminated all intelligence derived from intercepted and decrypted enemy naval communications. Within two months of starting operations the Officer in Charge, Lieutenant Commander Bernard F. "Dutch" Roeder, realized that technical intelligence would require special attention. The ever increasing amount of technical details was overwhelming the watch officers. Roeder has already pulled Lieutenant Knight McMahan off the watchbill to investigate possible cipher compromises.<sup>4</sup> He was

- <sup>3</sup>NSA, RG 457, SRH-236 (part 6), 116, 138, and 185.
- <sup>4</sup>Jeffrey K. Bray, ed., Ultra in the Atlantic, 6 vols. (Laguna Hills, CA: Aegean Park Press, 1994) 3:xvii-xviii.

<sup>&</sup>lt;sup>2</sup>F. H. Hinsley et al, British Intelligence in the Second World War, 5 vols. (New York: Cambridge University Press, 1979-90) 3 (Part 1):241. This was not revealed to the Americans until 30 January 1944. See NSA, RG 457, SRH-236 (Part 6), "USN Submarine Warfare Message Reports Admiralty to COMINCH," 116. The spelling of Schnorchel has since been Anglicized as snorkel.

given the additional technical responsibility, by Roeder, of becoming the Special Research Officer.<sup>5</sup> McMahan was to make detailed studies of any new developments that were exposed by communications intelligence. The series of special reports that followed were called "Self Amazement's" or simply SA Reports.<sup>6</sup>

The Office of Naval Intelligence [ONI] (OP-16) contributed significantly to the understanding of technical details gained from communications intelligence. The Atlantic Section was on the distribution list for all Atlantic related intelligence gained from general sources. The Special Activities Section (OP-16-Z) of Naval Intelligence would be the primary source of interrogation and captured material reports. Additional information gained on other aspects of the Atlantic campaign were also documented and forwarded on to the Atlantic Section. In turn, if the Atlantic Section discovered some new aspect of which there was little information it would generate a "Spot Item" so that the Special Activities Section would be aware of the fact. This method of feed back did not compromise the ULTRA secret. For example, once schnorchel was discovered it became ONI Spot Item #213.7

The spring of 1943 had brought a change in the Battle of the Atlantic. The U-boats had been very effective at sinking Allied merchant shipping with minimal losses. However, in the first five months of 1943 U-boat Command lost 96 submarines. Grand Admiral Dönitz, Commander of U-boats (COMSUBs), realized that he could not endure the excessive loss rate. On 24 May he announced to his U-boats that he was withdrawing from operations in the North Atlantic.<sup>8</sup> He viewed this as a momentary set back and felt that once the problems experienced from enemy aircraft and radar were eliminated operations would resume.

Dönitz believed that German technological advances could counter the threat posed by aircraft and radar. In most cases,

<sup>&</sup>lt;sup>5</sup>Editor's interview with Knight McMahan on 5 October 1993. <sup>6</sup>Ibid. When McMahan was given the task he asked Roeder what he wanted to see. Roeder's reply was "just amaze me." Hence, the phase "self amazement." Roeder did not want the Atlantic Section to be caught off-guard by any other German developments like those with the cipher compromises. There was a companion series of reports more technical in nature. These "SM Reports" have not been declassified yet. <sup>7</sup>NSA, RG 457, SRH-236 (Part 6), 185. <sup>8</sup>Bray, ed., 2:67.

# Type VII U-boat Conning Tower Variants



**Tower Modification U-Flak I** 

Dönitz believed, the attacking aircraft were using radar to locate the U-boats. The development of radar search receivers were given priority to offset the threat and provide ample warning prior to attack. The first indication of a German Search Receiver (GSR) in intercepted message traffic came on 8 February 1943.<sup>9</sup> The device was referred to as Metox but it would take two months to gain any significant details. Interrogation of POWs from U-187 revealed that Metox was the name of the manufacturer in Paris and that the device was definitely a search receiver. However, it scanned a frequency range that was becoming obsolete. The Allies were then introducing a new generation of aircraft radar that the Germans were unaware of.

The Germans also made use of POW interrogation reports. A British Coastal Command aircraft crashed and the pilot told his interrogators how Allied aircraft were able to accurately locate U-boats. Remarkably, he explained that the emissions from the GSR's were detectable from the air and compromised the U-boat's position.<sup>10</sup> The Germans discovered that the GSR did in fact produce a detectable signature and a resulting panic occurred at U-boat Command. The result was a string of different generations of GSRs that failed to keep pace with Allied technological advances.

Other areas of the U-boat were also given attention to counter the aircraft threat. The most visible was the metamorphosis of the type VII U-boat conning towers. A variety of conning tower modifications were utilized to increase the anti-aircraft firepower of the U-boat. The most apparent of these was the Flak-U-boat. The Flak-U-boat had two quadruple 20mm guns mounted forward and aft of the conning tower and a single 37mm gun aft of the rear quad.<sup>11</sup> Intercepted traffic revealed that the modification required 11 to 13 weeks of yard time to complete. Once mounted, the quadruple mounts became a maintenance nightmare for their crews. Additionally, the 20mm ammunition experienced a high percentage of misfires. Due to these factors, the quadruple

<sup>&</sup>lt;sup>9</sup>NSA, RG 457, SRMN-051, "OP-20-GI Memoranda to COMINCH F-35 on German U-boat Activities, December 1942 - September 1943," 233.
<sup>10</sup>Steven W. Roskill, *The War at Sea*, 3 vols. (London: Her Majesty's Stationary Office, 1954-61) 3 (Part 1):32-33.
<sup>11</sup>NSA, RG 457, SRMN-054 (Part 1), 381.

mounts were eventually removed and used for much needed harbor defense at the U-boat bases.

The lack of success with the Flak-U-boat did not diminish the need for increased anti-aircraft defenses on U-boats. It was revealed, from intercepts, on 5 August that U-boat Command was suspending all deployments of submarines that lacked proper anti-aircraft protection.<sup>12</sup> Several variations of conning tower modifications began to materialize in the message traffic. Tower V replaced the quad gun mounts with automatic 37mm guns. The forward mount had the added benefit of a metal skirt where railings were normally located. Yet, the new skirt reduced the crew's visibility in the conning tower by sending ocean spray directly at them.<sup>13</sup> An alternative modification. Tower VI, had a similar appearance of Tower V but lacked the wind skirt. This reduced the amount of ocean spray and received more favorable reports than Tower V. The tower modifications were to be conducted at the home ports when the U-boats returned from patrol. By June 1944, the invasion of France minimized the importance of tower modifications.

The dramatic turn of events experienced by the U-boats in the spring and summer of 1943 brought out a new submarine philosophy. On 10 July 1943, Dönitz granted an interview with the Japanese Ambassador, General Oshima Hiroshi, to discuss naval topics.<sup>14</sup> During the conversation Dönitz disclosed that he was preparing to start a new phase of U-boat warfare at the end of August. Unknown to Oshima, Dönitz was preparing to field a new torpedo for the U-boat fleet. It was hoped that the new torpedo, combined with increased anti-aircraft armament and improved non-radiating GSRs, would enable the U-boats to regain the initiative.

The development of a new type of torpedo had caught the naval communications intelligence sections off guard. Prior to 2 September 1943, there had been no mention or implication of a new weapon entering fleet service. On that day, Dönitz transmitted a message to "Zaunkönig" U-boats in a special cipher setting. In the message he demanded his men to take "every opportunity to bring your sharp weapon into play."<sup>15</sup>

<sup>14</sup>Hinsley, 3 (Part 1):211.

<sup>&</sup>lt;sup>12</sup>Hinsley, 3 (Part 1):217.

<sup>13</sup>NSA, RG 457, SRMN-054 (Part 1), 386.

<sup>&</sup>lt;sup>15</sup>For the text of the whole message see Bray, ed., 1:48.

	Ba	asic Gem	nan Subn	narine Torp	edoes	
Type	Propulsion	Speed (Knots)	Max Range (Yards)	Type Exploder	Use	Path
T-I	Air	40 30	8,700 15,300	Impact or magnetic	General	Straight, visible track
T-II	Electric	30	5,400	Impact	General	Straight, trackless
T-III	Electric	30	5,400	Impact/ magnetic	General	Straight, trackless
T-IV	Electric	20	8,200	Impact	Escorts	Straight then homing
T-V	Electric	24	6,200	Impact/ magnetic	Escorts	Straight then homing
FAT-1	Air	40 30	8,700 15,300	Impact	Convoy	Pattern
FAT-II	Electric	30	5,400	Impact/ magnetic	Сопуоу	Pattern

A new U-boat group was forming in the vicinity of 48°N and 25°-30°W and this group had been addressed as Zaunkönig (Wren). It was noted that all groups named after birds had previously operated against northern convoy routes.<sup>16</sup> The American and British interpretation of the meaning of Dönitz' message differed. The British believed the message was simply a pep talk from the Admiral.<sup>17</sup> The Americans saw it as a specific implication towards a new weapon in use.<sup>18</sup> After the American viewpoint was shared with the British the difference remained. The British still held to the belief this it was a morale inspiring message. In fact, they stated "our torpedo experts have no reason to suppose acoustic or any other new type yet in use.<sup>119</sup>

<sup>&</sup>lt;sup>16</sup>NSA, RG 457, SRMN-051, 507. The group was actually named *Leuthen*. See NSA, RG 457, SRMN-037, "U-boat Intelligence Summaries (June 1943-May 1945)," 179-81.

<sup>&</sup>lt;sup>17</sup>NSA, RG 457, SRH-236 (Part 4), 193-94.

<sup>&</sup>lt;sup>18</sup>NSA, RG 457, SRH-208 (Part 2), "USN Submarine Warfare Message Reports COMINCH to Admiralty," 73.

<sup>&</sup>lt;sup>19</sup>NSA, RG 457, SRH-236 (part 4), 195-96.

The Zaunkönig issue would remain a mystery for approximately four weeks. The American estimate turned out to be correct. On 28 September a decrypted message revealed the existence of a new torpedo in use - the TVNS.<sup>20</sup> The T-V was an acoustic homing torpedo designed specifically to counter the convoy escort threat. The bird associated name was used as a new series of code words for a generation of torpedoes under development. The T-IV, for instance, was also an acoustic torpedo whose code name was Falke (Falcon). The connection between Zaunkönig and the T-V torpedo was finally confirmed by an interrogated POW in British custody.<sup>21</sup> 000

More advanced details on torpedoes were obtained from communications intelligence. Of the wide variety of sources, the most prized by the Atlantic Section was the Japanese Naval Attaché (JNA) in Berlin. His correspondence with Tokyo revealed minute details of German torpedo development. Revelations included the discovery of a high speed turbine torpedo (UTO), a wire guided torpedo, and a torpedo driven mobile influence mine. JNA reports disclosed that observed test firings of the UTO revealed that it had a speed of 47 knots. Additionally, the absence of the wake track was of a higher degree than that of the Japanese oxygen torpedo.<sup>22</sup> The continued correspondence of the JNA provided additional details on current and projected torpedo systems to the delight of the Atlantic Section.

An additional aspect of technical intelligence concerned the future of the U-boat force. A new submarine concept was formed by Dönitz and was described as "Total Underwater Warfare." The roots of which were formed by the experiences felt by the U-boat force in the first half of 1943. The mounting U-boat losses forced Dönitz to realize that the existing submarine technology was unsuited for the environment it faced. These submarines were designed to operate primarily on the surface, experienced slow speeds and poor endurance, and lacked proper sensors to detect incoming threats. The incorporation of schnorchels served as an interim solution to the realities facing the U-boats. What was needed was a

<sup>20</sup>NSA, RG-457, SRMN-051, 527. The German navy habitually used roman numerals in the designation of its equipment. <sup>21</sup>Ibid.

<sup>22</sup>NSA, RG 457, SRMN-054 (Part 2), 125-26.

revolutionary new generation of German submarines. The first clues to such a submarine came on 21 June 1944.

The new generation of German submarines had been a closely guarded secret until late June 1944. The JNA had sent a message to Tokyo, concerning German submarine development, on 28 December 1943. It was intercepted by the Allies but the cipher used was not broken until the following spring. The resulting back log of traffic had to be processed and the December messages was not decrypted until 21 June.<sup>23</sup> The JNA dispatch revealed the existence of a new class of German submarine - the type XXI. Further significance of the new type XXI came three days later. Dönitz informed COMSUBs West of his intention to decommission four type VIIc U-boats and use their crews to man the new type XXI's.<sup>24</sup> From August on, the Japanese naval delegation in Berlin supplied a wealth of information concerning the construction details of the type XXI and its coastal companion the type XXIII.25 This detailed information led the Admiralty's Naval Intelligence Division to state that the new German submarines represented "the revolution of U-boat design and construction."26

The communications systems of the U-boats also received technical scrutiny. Beginning in October 1943 the Germans began employing an "off-frequency" method of communication. The messages were transmitted on a pre-arranged frequency that was above or below a basic frequency. Messages were acknowledged on a separate frequency minimizing the exposure of the "off-frequency" to the enemy. U-boat Command believed that combining this method with short signals it would be possible to reduce exposure to enemy HF/DF. The significance of this approach was quickly acknowledged by the Americans as a beneficial approach to

<sup>&</sup>lt;sup>23</sup>NSA, RG 457, SRMN-037, 411. The British official intelligence history claims the message was decrypted on 1 May 1944. (Hinsley, 3 (Part 1):244) However, this message was not disclosed to the Americans in the daily ULTRA exchange between the two navies. In fact, the Americans brought it to the attention of the British on 25 June. The American decrypt occurred around 21 June 1944. See NSA, RG 457, SRH-208 (Part 3), 44.

<sup>&</sup>lt;sup>24</sup>NSA, RG 457, SRMN-037, 410; NSA, RG 457, SRH 236 (Part 7), 252.

<sup>&</sup>lt;sup>25</sup>A useful index of this series of messages is in NSA, RG 457, SRMN-054 (Part 1), 434-41.

<sup>&</sup>lt;sup>26</sup>Hinsley, 3 (Part 1):244-43.

communications security.<sup>27</sup> The Americans were themselves employing submarines in distant waters of the Pacific and exposed to the same communications vulnerabilities. Studies were initiated by OP-20-G which verified the security of such a system and recommended that similar methods be employed in the Pacific.<sup>28</sup> Like many German innovations, the off frequency method was a limited success. A more advance method was needed to reduce the risk of enemy communications intelligence operations.

High speed communication was believed to be the only way U-boats could escape communications interception and direction finding. The U.S. Navy had itself conducted test with high speed, or burst, communications in early summer of 1942.<sup>29</sup> It was appreciated that this form of communication had many benefits. The first indications that the Germans had developed a similar system came in late June 1944. A captured document from U-505 on U-boat communications regulations contained a citation on "Short Signal Procedure 'Kurier.'<sup>30</sup> It was noticed that the citation placed Kurier between "off-frequency" procedures and ENIGMA conversation. The former dealt with avoidance of HF/DF and the latter involved signal speed. Decrypts soon followed stating that Kurier trials would be conducted shortly and that the outcome of which was "important for the war.<sup>31</sup>

Kurier represented a new technology of communications for which the Allies were totally unprepared for. The Kurier system was an automatic transmitter that could send out at an estimated rate of 600 words per minute. German naval radio

#### <sup>27</sup>NSA, RG 457, SRMN-032, 129-30.

<sup>28</sup>Records of the Secretary of the Navy/Chief of Naval Operations (Secret/Confidential), CNO letter to Commander in Chief, Pacific Fleet, serial 0408420, dated 3 February 1944, Folder A6-2(29---), Box 1612 (A6-2(29)--A6-3(27)/QS1). National Archives, Washington, D.C., Record Group 80 (hereafter cited as SECNAV/CNO (SC), RG 80, with filing designations); SECNAV/CNO, RG 80, CNO letter to Commander in Chief, Pacific Fleet, serial 010571201, dated 7 February 1944, Folder A6-2(29---), Box 1612 (A6-2(29)--A6-3(27)/QS1).

<sup>29</sup>This "Flash" communication system was tested between radio station at Washington, D.C., San Francisco and Mare Island, California. See SECNAV/CNO (SC), RG 80, "Report on 'Flash' Communications Test," dated 4 May 1942, Folder A6-2(16)--A6-2(28), Box 288 (A6-2(14)--A6-3/EF13 (Feb 42)).

<sup>30</sup>NSA, RG 457, SRMN-054 (Part 2), 177; Hinsley, 3 (part 2):852. <sup>31</sup>Hinsley, # (Part 2):852. operators, who were considered by many as the best in the field, could send 30 words per minute at best speed.<sup>32</sup> The Kurier system represented a 2,000 percent increase in transmission speed. This would, in effect, make the Allied HF/DF network obsolete.<sup>33</sup> The transmissions were based on seven letter code groups, or multiples of seven, which would also further complicate the cryptologic effort against German naval communications. The potential of the Kurier system and its effect on Allied communications intelligence brought on British anxieties of a massive blackout.<sup>34</sup>

Kurier underwent a series of evaluation periods and demonstrated mixed results. The first evaluation period began in the middle of August 1944 with ten U-boats equipped with Kurier.<sup>35</sup> The tests were discontinued after two weeks due to transmitter flaws. A second evaluation period began in the middle of November. The British discovered during this period that they could record the burst messages on film.<sup>36</sup> It was apparent from COMSUBs' remarks that he considered the trails a success. The British discovery was muted by the fact that on 9 December the U-boats used frequency tables held on board for determining the pre-arranged settings.<sup>37</sup> The development of new receivers in April allowed the British to continue monitoring Kurier transmissions. Before Kurier could become completely operational the war in Europe was over.

Technical intelligence during the Second World War touched upon almost every area of undersea warfare. From

<sup>&</sup>lt;sup>32</sup>Editor's interview with Grady Lewis on 20 January 1994.

<sup>&</sup>lt;sup>33</sup>The Kurier signal would register on the CRT of an HF/DF set but the image would appear as a flicker of momentary blip. The problem was further compounded by the fact that the Kurier signal shifted frequencies during transmission. For an excellent technical description of the system see U.S. Navy, Division of Naval Intelligence, "Electronics Research in the German Navy: Series of Lectures Delivered by Freg. Kapt. Dr. Ing. Schlicke," 15 September 1945, lecture 8. German Naval Records, Essays (German Officers), Box T73, Operational Archives/Naval Historical Center, Washington, D.C.

<sup>&</sup>lt;sup>34</sup>Hinsley, 3 (part 2):472, 482, and 628.

<sup>&</sup>lt;sup>35</sup>NSA, RG 457, SRMN-054 (Part 2), 179.

<sup>&</sup>lt;sup>36</sup>Ibid., 188. On 24 November, the British intercept station at Scarborough recorded ten Kurier messages.

<sup>&</sup>lt;sup>37</sup>Previously, Kurier frequency deviation settings had been broadcast in normal ENIGMA traffic. This new approach left the British clueless as to the change in settings. As a result, new equipment had to be constructed that could detect frequency deviations within 200 kcs of either side of the main frequency.

the construction of submarines to the development of innovations for practical use. The contribution of communications intelligence to this effort was considerable. Communications intelligence was the only reliable source of technical information about the enemy short of capturing documents or equipment. The perspective of technical intelligence was not overly time sensitive. Decryption delays experienced did not affect technical findings as they did operational intelligence. Yet, when necessary, technical communications intelligence could provide immediate insight and aid the development of appropriate countermeasures.<sup>38</sup> Communications intelligence was a vital source in the technological theater of the Battle of the Atlantic.

<sup>&</sup>lt;sup>38</sup>A perfect example of this fact is the T-V (Zaunkönig) torpedo. The first use of the weapon was on 19 September 1943. A suitable countermeasure, the FXR, was in mass production by the end of the month. Granted, American scientists were developing a countermeasure prior to the discovery it was communications intelligence that disclosed the existence of a new weapon. Had this intelligence not been obtained, as it was, more losses would surely have been experienced until a discovery was made.

# List of Abbreviations

A/C	Aircraft
A/S	Anti-submarine
ASDIC	Underwater sound location device
BAMS	Broadcasts for Allied Merchant Ships
CBM	Cubic meter
CINCCNA	Commander in Chief, Canadian Northwest Atlantic
CINCWA	Commander in Chief, Western Approaches
CESF	Commander, Eastern Sea Frontier
CMSF	Commander, Moroccan Sea Frontier
CNO	Chief of Naval Operations
COMINCH	Commander in Chief
COMNAVEU	Commander, Naval Forces Europe
CRT	Cathode Ray Tube, television screen
CSP	Code and Signal Publication
CVE	Escort aircraft carrier
D/D	Destroyer
D/F	Direction Finding
FOIC	Flag Officer in Charge
GAF	German Air Force
GC&CS	Government Code and Cypher School
GNA	German Naval Attaché
GNAT	German Naval Acoustic Torpedo
GSR	German Search Receiver
H/F	High Frequency
JNA	Japanese Naval Attaché
KCS	Kilocycles
MCS	Megacycles
M/F	Medium Frequency
MPA	German naval D/F divisions
MPHS	German naval D/F main stations
MPNS	German naval D/F subsidiary stations
M/V	Merchant Vessel
NEMO	American code name for captured U-505
NOIC	Naval Officer in Charge

xxi

ONI	Office of Naval Intelligence
RAF	Royal Air Force
RIP	Radio Intelligence Publication
RFP	Radio Finger Printing
R/V	Rendezvous
SIS	Italian Naval Communications Intelligence Organization
SKL	German Naval High Command
SPECNAVO	Special Naval Observer
TINA	Radio Transmission Characteristics Intelligence
T-V	Zaunkönig acoustic torpedo
U/B	U-boat
VL/F	Very Low Frequency
WW	German Weather Messages

### Chapter I

German Search Receivers and Radar

\* \* \*

- 1. Summary.
- 2. Introduction to Allied radar and the first German search receiver.
- 3. The introduction of centimeter radar.
- 4. The "Magic Eye."
- 5. Measures against infra-red detection and short-timed radar.

6. The Germans take stock.

7. The radiation specter.

8. The first non-radiating receivers.

9. Discovery of the use of centimeter wavelength radar.

- 10. Schnorchel and GSR.
- 11. German U-boat radar.

#### 1. Summary.

In the German navy's fight to preserve the "invisibility" of the U-boat, it's chief enemy in direct combat through most of the war proved to be Allied airborne radar. At the beginning of the war the U-boats had been able to range far at sea, often to intercept convoys without fear of advance detection by aircraft, and to sink their prey and get away before any defensive force could be effectively brought to bear against them. The equipping of aircraft engaged in anti-submarine operations with radar began early in 1941 and gradually initiated a contest between Allied radar and German countermeasures which became very acute by 1943. Among the counter-devices upon which the Germans pinned their hopes were search receivers designed to intercept radar transmissions and thus inform U-boat's in advance when they were in danger of attack by a radar equipped aircraft.

Several different models of the GSR were developed, with varying degrees of success. The first model, though poorly constructed and primitive, served its purpose. When the Allies resorted to centimeter wavelength radar, however, the tables were turned and a long period of desperate searching for the cause of Allied successes followed. For many months the German effort to determine that cause failed completely. The first step taken was to improve the GSR models currently in use. When that failed to produce results the U-boat Command turned to investigation of the possibility that infra-red detectors were being used by the Allies.

In the summer of 1943 the German navy became obsessed with the idea that the enemy was profiting by detection of radiations from the GSR. New models were developed to eliminated radiation, this at a great loss of valuable time. It was not until September 1943, after the Germans had discovered that Allied aircraft were using centimeter radar, that U-boats were equipped with GSR capable of dealing with all wavelengths in use by the Allies. Even this search receiver was inadequate, owing to its very short warning range and the fact that it never had a permanent aerial. Since the introduction of Schnorchel early in 1944 did not eliminate the possibility of detection by radar, it was necessary to fit the Schnorchel mast with an aerial, which, however, was incapable of receiving centimeter wavelength transmission at distances more than 1,000 meters.

German radar, under development and in use concurrently with GSR, took a definite second place in the opinion of U-boat commanders. Confidence in its capabilities was expressed from time to time by Command, but fear that Allied aircraft were equipped with search receivers caused the commanders to neglect its use until the spring of 1944. Thereafter radar became more popular with the commanders and proved of value as a warning against aircraft and as an occasional aid in convoy shadowing, firing and navigation.

2. Introduction to Allied radar and the first German search receiver.

The use by Allied aircraft of the Anti-submarine Visualizer (ASV) radar, operating on meter wave lengths, was instituted early in 1941 and soon proved its value in increased sinkings of U-boats, including not only those in the vicinity of convoys, but also those in other areas. Mounting Allied successes, together with the appearance of aircraft so frequently as to eliminated the possibility that their presence was due to visual sighting, aroused the Germans to the fact that some locating devise was being used against them. They were not backward in technical matters and were quite aware of the possibilities of meter wavelength radar. Aided by the capture of an ASV Mark II (150cm) in the spring of 1942, they concluded that radar was the cause of the U-boat's troubles and set about finding a means to counteract its effect.

The answer to their problem, proved by tests in the summer 1942, rested upon the fact that transmissions of a radar set could be received by means of a simple aerial and receiver; hence a U-boat could discover the presence in its vicinity of a user of radar and submerge before it could be successfully located. A makeshift search receiver, manufactured by the firm of Metox in Paris and designated the R600, was hastily put into production and designed to cover a range of 60 to 265 centimeters, including harmonics, and probably had a maximum effective detection range of about 6 miles. Hurriedly contrived as it was, it showed the varied and serious weaknesses which might have been expected under the circumstances. Its generally poor structure, particularly its primitive aerial, resulted in frequent breakdowns; its usefulness was limited by its inability to distinguish between radar and non-radar disturbances, its inability to take a bearing and its inability to receive short transmissions. In addition, the set was a source of powerful radiations when in operation, a matter which was dismissed as of little consequence at the time, but which was later to be remembered, and exaggerated in the mind of the German technical expert to a significance out of all keeping with common sense, this at great cost to the U-boat.

Despite all its weaknesses, however, the Metox set was operationally successful for some time. It was improved in some respects as time went on, mainly in the substitution of a fixed basket aerial ("Runddipol") for the old cross type, addition of a second oscillator, and installation of a "Magic" mechanism; but it remained the only standard U-boat search receiver for more than 6 months. U-boat radio traffic for November and December 1942, the first read here, abounded in reports of "Ortung" (radar) and plainly showed the success of the German counter-device. That radar had been successfully counteracted for the moment was also shown by the general picture in the Atlantic war, for Allied shipping losses had continued high in the latter part of 1942 despite improved convoy arrangements. The U-boat still maintained its decisive advantage.

3. The introduction of centimeter radar.

In February and March 1943, a new refinement in the war of detection in the form of ASV Mark III (10cm), a set operating on centimeter wavelength, was introduced on Allied aircraft. The R600, with its 60 centimeter lower limit, was quite unable to detect transmissions on the new very short wavelengths, and the result was a gradual increase in the number of sightings of U-boats and attacks against them, accompanied by an increase in the proportion attacks carried out without prior appreciation by the U-boat that radar was being used. In his message 1631 of 30 May 1943, for instance, Kentrat (U-196) reported that he had been flown at twice during the hours of darkness by aircraft "without radar"; and in his message 1019 of 26 September, Schroeteler (U-667) reported: "So far 5 attacks at slight distance without any radar. Cruising at night is impossible, since there is no time for outmaneuvering." A more correct interpretation was recorded by Hartenstein (U-156), who reported in his 0105 of 7 March

1943: " A new kind of radar, Metox is useless. Very accurate attacks without searchlight." The deteriorating situation quite naturally became evident to the Germans before many months had passed, but they were totally unaware of the cause of it, and contrived counter-measures, most of which were aimed at the wrong objective.

4. The "Magic Eye."

The first attempt to solve the new detection problem centered about improvements to already existing search receiver sets, the Metox R600 and the Grandin, a receiver which covered the same frequencies as the former. It was first assumed that Allied radar transmissions were now producing headphone vibrations outside the range of audibility. Working on this hypothesis, a visual tuning indicator of the "Magic Eye" type was introduced into the improved Metox R600A, development mentioned in ENIGMA traffic in message 2105 of 10 March 1943. By the rarest good fortune, it happened that naval aircraft in the Mediterranean area were using supersonic modulation at the time, and the success of the "Magic Eve" in detecting these particular aircraft evidently led the German technical experts to believe, for as long a period as a couple of months, that they had solved the problem. Evidence for this appeared in message 1217 and 1304 of 23 May in which it was indirectly stated that the "Magic Eve" indicated inaudible impulse frequencies and that outfitting of U-boat's would continue. But the continued Allied successes, representing the worst situation for U-boats since the beginning of the war, could not permit continued reliance on the "Magic Eye."

5. Measures against infra-red detection and shorttimed radar.

The next line of attack taken by the technical authorities was in the field of counter-measures for infra-red detection. The suspicion that infra-red detection might be the secret of the new Allied success was based upon reports for U-boats at sea mentioning a dull red glow emanating from attacking aircraft. The German technical staff turned its attention with characteristic singleness of purpose to the discovery of a means of counteracting the suspected bogey. Infra-red detectors were carried by some U-boats for experimental purposes, but difficulties in operations of the device precluded formation of any definite conclusions from the lack of successful experiments with it, and the Germans wasted the whole summer of 1943 clinging tenaciously to their suspicion that infra-red was the cause of their troubles. U-boats were covered with a special paint calculated to absorb infra-red rays and other precautions were taken, yet sinkings by Allied aircraft continued. Simultaneous research directed toward developing means of detecting the suspected use of shorttimed radar as an anti-interception technique also produced no visible results in a decrease in U-boat sinkings.

#### 6. The Germans take stock.

After several months of failure by the Germans to find the cause of their misfortunes, it was apparent that the U-boat Command and its commanders had lost faith in their search receiver. In the Bay of Biscay U-boats began to spend the nights underwater. Preferring to take a chance on visual sighting of an enemy during daylight for the period of time necessary for ventilating and charging the batteries. In July 1943 the Director of the Naval Communications Division, German Naval War Staff, admitted in long communication concerning the search receiver service that the "invisibility" of the U-boat was gone, that the element of surprise in U-boat attacks had been eliminate by new Allied location methods which had so far proved inaccessible to interception. The Director outlined plans for overcoming the German deficiency. including increased use of radar itself by naval and coastal defense forces. Taking note of many serious mistakes made in the past, he announced extensive changes in organization and procedure aimed at strengthening radar and radar interception research and practices, and stated that the Commander in Chief of the navy had promised his special support toward attaining that end, as indeed Admiral Dönitz had promised U-boats in May.

#### 7. The radiation specter.

For some reason, the fact that search receiver radiations were capable of being detected at a distance of several miles suddenly began to plague the Germans in the summer of 1943. No new technical knowledge was concerned in their appreciation of that fact, for they had known of that possibility when the search receiver was first introduced and had discounted its importance as a threat to the U-boat. The Allies had also investigated the practicability of using search receiver radiations for homing purposes and had abandoned the idea because of the difficult operating conditions aboard aircraft. But now the Germans, still searching for the cause of Allied detection successes, fastened upon this specter as the object of their feverish activity during the next several months. Tests on the Metox receiver showed that it produced very powerful radiations, and in the middle of August use of both Metox and Grandin was prohibited because of the fear of benefit to the enemy. (PSRE 0410/15)

To make sure that the prohibition was observed, it was ordered that the U-boat commander should remove an essential part of the set, keep it under lock and key, and enter that action in the war log. (PSRE 2022/17) The Metox was replaced by a new GSR called Wanz G1 or Hagenuk, details of which were passed to OP-20-S in a memorandum of 6 October This set, designed for frequencies between 120 and 150 1943. centimeters, was originally produced for the specific purpose of detecting suspected short-timed radar transmissions, but by chance produced radiations only about one twenty-fifth as powerful as those emitted by the R600. Hence it was also an improvement over the old R600 in other ways, for scanning with the visual indicator was automatic, and only after a transmission had been picked up was manual scanning for sound reception necessary. In addition, the set had a greater range (about 30 miles for an aircraft at about 1,000 feet altitude, 60 miles at 6,500 feet), and greater sensitivity. Yet, in spite of all these improvements, especially the greatly reduced radiation, sinkings continued.

The German mind was still not convinced that radiation was not its great enemy. On 5 November 1943 messages were sent instructing U-boats not to use their Wanz G1 because freedom from radiation had not been established. (2049/5 November) Instead they were to be supplied with either Wanz G2 or Borkum search receivers. As further insurance against radiation ordinary radio programs were to be received by Uboats east of 18°W. while submerged, using VL/F.

7

#### 8. The first non-radiating receivers.

The Wanz G2 was a later version of the G1, as its name implies. Covering the same frequency range, it had the advantage of practical elimination of radiation, though at considerable cost in warning range (only about 37 miles with aircraft at 6,500 feet altitude). Another of the stop-gap devices, it was subject to frequent breakdowns, but all its imperfections were accepted in favor of the release from fear of detection through radiation. The Borkum set, designed to receive all signals in the 75 to 300 centimeter band without tuning, had been first introduced in the summer of 1943. Out side the band mentioned its sensitivity decreased, but it is possible that it gave some indication even of 10 centimeter transmissions. An emergency installation, its efficiency was considerably below that of the Wanz G2 (about one fourth, according to 0246/16 June 1944) and was used in practice chiefly when the latter was out of order. The Borkum, too, produced radiations below evaluable magnitude, so the Germans had a long last conquered their imaginary enemy. The real enemies still remained.

#### 9. Discovery of the use of centimeter wavelength radar.

In some way U-boat Command became aware by September 1943 that centimeter wavelength radar was in use against them, a discovery which should have led to the speedy solution of the radar problem. Actually the search receiver developed for use against the newly recognized threat at first defeated its own purpose because of its lack of sensitivity. The Naxos set was designed for the 3 to 12 centimeter band, in which receiving would have been difficult enough with an excellent set. The Naxos was far from excellent. It was very delicate, therefore subject to continual breakdowns. A particular weakness was the antenna, which was subject to frequent breakage because of the use of porcelain rods in its construction, and which had to be mounted each time the Uboat surfaced and taken down again before submerging. The disadvantage of this was strikingly illustrated in the case of U-625, whose commander was lost at sea because of difficulties which developed in removing the antenna in time for a crashdive to avoid an attacking aircraft. (0532/4 January 1944) The warning range of the set with its original antenna was

pitifully small, so small as to render it almost useless, but every effort was made to increase its efficiency, particularly by improvement of the antenna.

The first improvement of this nature was the introduction in early February of the Fliege, a reflector antenna giving approximate bearings and operating in the 8 to 12 centimeter range. Use of this antenna greatly increased the range of Naxos against 10-centimeter radar, making it an effective detection device. In addition the Fliege was used separately with some success for aiming anti-aircraft guns in advance of appearance of the target. Another antenna, the Mücke, was put into operational use in May 1944 as a complement to Fliege to cover wavelengths from 2 to 4 centimeters, for it had been discovered through capture of a crashed aircraft that 3-centimeter radar was in use by the Allies. Also a directional antenna, the Mücke covered approximately the same warning range as the Fliege. These two antennae were later incorporated into a single frame called "Tunis", and the Naxos set continued in use against centimeter wavelength radar until the end of the war.

On the radar question as a whole very extensive experimental work was done in the spring of 1944. In February and April, respectively. U-406 and U-473 left port fully equipped to investigate every type of Allied radar. Both boats were sunk, but others carried on constant investigation of Allied frequencies. "Feldwache," a combination of several different sets, was used for experimental searching of all wave bands from 320cm down to 5cm. A summary of results of experiences presented as a Current Order on the use of Tunis (0602/22 June 1944) indicated that the Naxos-Tunis combination would remain the chief instrument for search receiving, but that experimentation would meanwhile continue.

#### 10. Schnorchel and GSR.

While the introduction of schnorchel in 1944 proved a blessing to the U-boats, it did not eliminate entirely their susceptibility to location by radar when the schnorchel was extended, although the radar target was considerably smaller than that of the whole U-boat. It was therefore necessary to devise a means of search receiving for the schnorcheling Uboat. This was brought about by including a drum type aerial, called the schnorchel round dipole, in the Schnorchel mast. The round dipole was capable of receiving radar transmissions on meter wavelengths, but according to message 2003/10 of July 1944, it could only register Fliege range radar at the short distance of 1,000 meters. The Germans apparently believed it practically impossible for a schnorchel to be picked up by centimeter radar because of its rubber camouflage protections and considered search reception over the round dipole adequate protection from meter wavelength radar. At the end of the war they were trying to develop a permanent centimeter aerial for the schnorchel mast. That they had not succeeded was shown by a reply from Germany to Surabaya's inquiry concerning the installation of such an aerial. Berlin replied:

> "At present there is still no gear available for observing centimeter radar during Schnorchel cruise." (PPB 86, 3 April 1945)

Type XXI U-boats were to have carried such aerials.

11. German U-boat radar.

It was known from the first two months of U-boat traffic read here that at least some U-boats were fitted with radar and that its wavelength was 80cm. There was no indication that Uboats made any real use of radar. Reference in traffic were very few until the summer of 1943, when U-boat Command started a campaign to persuade U-boat captains that their own radar should be used for aircraft detection in lieu of the forbidden GSR. Among the significant developments in the radar picture, easily followed by reading of German traffic, was the continuing question of U-boat radar's merit relative to the GSR. There was great reluctance to use radar because of the fear that Allied aircraft were fitted with search receivers. Owing to the fact that GSR ranges were greater than those of radar, it was not surprising that the U-boats preferred to rely on GSR for warning against enemy aircraft, especially in view of the radiation scare of 1943.

There appeared to be a split between command on the one hand and the operating U-boats on the other as to the advisability of using the radar sets provided. This was chiefly illustrated by the periodic appearance of instructional messages from the COMSUBs emphasizing that the German radar was an effective instrument and should be used. Occasionally there was direct reprimand for failure to use radar under circumstances favorable to its use. In June 1943, for instance, there were two messages (2343/5 and 1252/25) which directed that radar should be used as much as possible, one of them stating:

> "Our own radar sets are well suited to establish the presence of airplanes independently of their use of radar, for example during surface cruise altitudes of 500 meters and more at a distance of 10 kilometers at the least. For the time being, enemy search reception of our radar is not to be presumed."

A slight shift in sentiment on the latter point was demonstrated in PSRE 0257/9 September, in which, while use of radar was still stated to be the only means for locating the enemy under certain conditions, it was pointed out that

> "it is necessary to be prepared at all times for enemy search receiving activity."

A memorandum to COMINCH sent on 22 October 1943 recorded the fact that German radar seemed destined to occupy a role secondary to GSR an opinion which was borne out by future developments. Nevertheless, COMSUBs continued to exhort his boats to use radar, and provided them with improved sets to make its use more effective. The original set supplied, the Gema, had been a cumbersome, unsatisfactory set operating on 80 centimeters. As technical development progressed, improvements were made to the Gema and a new set, the Hohentwiel, operating on 50-55 centimeters, was introduced. Both the improved Gema and the Hohentwiel represented advances both in case of operation and in increased effective range.

There were continual reports of sets out of order, however, leading to a statement by COMSUBs that failures were often due to insufficient tending and lack of training. (1840/1 April 1944) Meanwhile the effort of Command to popularize the use of radar had continued, with three separate messages devoted to the subject to February alone (2141/4, 1752/16, and 1622 ff.) There were indications in March that the reluctance of U-boat commanders had been overcome to some extent, for several instances of successful use of radar were reported. As time went on that reluctance was further broken down, with many reports of aircraft successfully detected by radar before they were able to attack. There was also increased use of radar for locating the shadowing of surface vessels. In addition, examples were recorded of U-boat's using radar as the means of aiming at both attacking aircraft (1947/16 October 1944) and surface targets (0308/15 December 1944) It was also pointed out that Hohentwiel could be successfully used as a navigation aid in hazy weather. (0018/5 December 1944)

# Chapter II

## Anti-Detection Devices

\* \* \*

1. Summary.

0

2. Introduction of "Aphrodite."

3. Radio intelligence action on the information at hand.

- 4. "Aphrodite" successes.
- 5. "Aphrodite" and the Invasion.

6. "Thetis."

7. "Bold."

# **THETIS Radar Decoy**



Assembled configuration: Two mast sections and two tube sections connected together. Storage configuration: One mast section is store inside one tube section.

#### 1. Summary.

A clear-cut illustration of the value of communications intelligence is offered by the story of "Aphrodite," a radar decoy balloon first used in the middle of 1943. The device was first mentioned on 17 April in Baltic naval traffic which was read by the British and reported by them to the Atlantic Section. With few details given in the original message and two other messages sent in June, it was possible for the Atlantic Section to inform COMINCH of the nature and description of the device before it was put into operational use. "Aphrodite" consisted of hydrogen balloon to which were attached metal strips tuned to known British and American radar frequencies. They were released to lead searchers off on a wild goose chase and thus allow a U-boat to escape detection. The device proved very successful at times, even leading, in connection with the T-V acoustic torpedo, to several sinkings of Allied craft. During the invasion, "Aphrodites" were released in large numbers to deceive searching aircraft while U-boats not provided with schnorchel surfaced for charging in the Bay of Biscay. Another device with the same object as "Aphrodite" was "Thetis," a dummy buoy to which metal dipoles were attached, designed to give the same radar reflection as U-boat. All significant details of this device were given in the message which announced its impending use in January 1944. Traffic indicated that is was used to simulate patrol lines and for protection of non-schnorchel U-boats during the invasion. "Bold," a device which produced noises and bubbles when discharged into the water, was used against vessels searching with Asdic or hydrophones.

2. Introduction of "Aphrodite."

The first mention of "Aphrodite" to come to the attention of the Atlantic Section was in a British routine report on communications matters, issued under date 1 May 1943. Speaking on a radio circuit guarded by the British, it was stated that at 0115/17 April, Communications Experiment Trial Command sent the following to the depot ship "Wilhelm Bauer" for Captain Giessler:
"Communications Equipment Trial Command tests today without result. No "Aphrodite" signals established. Propose on 17/4 first experimental series from 1300 with 'A.S.V.' aircraft due to arrive at midday. For each series have ready 2 to 3 free and 2 to 3 captive. Characteristics of U-boat: swastika flag forward, morse lamp flashes on closing."

To this the British added the following notes:

- "1. Giessler had long been connected with R.D.F.
- 2. Nothing known of 'Aphrodite.'"

Nothing more was heard of "Aphrodite" until June, when two messages on all U-boat circuits mentioned the device. One of these, 1552/12, was addressed to "boats with 'Aphrodite II'" and stated:

> "Hydrogen tanks not dangerous even if hit. At worst gases with blow off without exploding."

The other message, 1203/15, stated:

"Beginning at once the use of 'Aphrodite' according to instructions is authorized."

3. Radio intelligence action on the information at hand.

With the arrival of the June messages quoted in the preceding paragraph, a conclusion as to the nature of "Aphrodite," based entirely upon the earlier British report and a knowledge of the place occupied by Aphrodite in Greek mythology, was formulated. Thus it was that on 23 June 1943 the Atlantic Section was able to send information in a memorandum to COMINCH giving an accurate theory as to the nature and use of the device. The memorandum stated:

> "It is believed that 'Aphrodite' refers to deception equipment of submarines in combating aircraft radar. The assumption as to its working is as follows: When a surfaced submarine obtains via Metox any indication of radar, a hydrogen balloon is released by the submarine. To the balloon are attached metal strips of various lengths tuned to

known British and American radar frequencies. The submarine steams off into the wind while the balloon passes off the leeward, drawing the hunter off on a wild goose chase."

Later, incontrovertible evidence demonstrated that the above theory was in fact correct.

Of great importance was the fact that by means of communication intelligence COMINCH knew of the existence of "Aphrodite" before it was put into operational use.

## 4. "Aphrodite" successes.

In July the U-boat Command, apparently impatient because it had received no reports on the performance of "Aphrodite," directed U-boat's to make experimental use of it, since there was little possibility of tactical use, and various reports were sent in answer to that order. A possible, but not confirmed, tactical use may have occurred on 21 July, when an Allied report cited a disappearing radar contact in 15°45'N -72°50'W; but the first tactical use acknowledged by the U-boat Command was in September and October, when several successful deceptions were claimed and an obvious campaign to instill confidence in the device was carried on by the U-boat Command. It must be remembered that for the previous several months the U-boat had existed under the heavy shadow of fear of radar and almost complete inability to detect or combat it. "Aphrodite" was a hope, and in the German struggle against surprise attack for the air, was worthy of every consideration and trial. Whatever comfort it could supply to the demoralized U-boat arm was sadly needed.

Actually, after the long dearth of U-boat successes, there was some occasion for rejoicing in the reports of "Aphrodite" successes. Aside form the general feeling of satisfaction resulting from any aid to avoidance of aircraft, a few reports of extremely advantageous use in offensive action must have been very encouraging. U-68 (Lauzemis), for instance sank the Free French escorted freighter *Fort le Vaux* on 30 November 1943 "after successful use of 'Aphrodite'"; and, most striking of all, at the end of December, Petersen (U-541) used "Aphrodite" in conjunction with the very effective acoustic torpedo "Zaunkönig" to sink "three destroyers" in one attack. It is small wonder that the commandr of U-541 thought that "Aphrodite" was "first-rate," and that thereafter command urged upon all U-boats the advantage of "the skillful release of 'Aphrodite' along with the use of 'Zaunkönig.'"

From the beginning of 1944 on, reports on "Aphrodite" showed no unanimity of opinion among U-boat captains as to its effectiveness in various instances and in differing situations. The high tide of its use seemed to have passed, and it assumed the position of a rather routine, not especially exciting, countermeasure, though it was apparent that the U-boat Command considered it a successful device on the whole. One significant reference during January directed Group *Borkum* to "infest the area with numerous 'Aphrodite' to loosen up the defenses." Other references during the first months of 1944 showed that it was being used for the purpose of testing German radar sets, and that its range for deception covered not only meter length radar, but also frequencies around 10 centimeters.

5. "Aphrodite" and the Invasion.

One further episode of importance in the "Aphrodite" story occurred in connection with the difficult situation for Uboats in the Bay of Biscay during and after the Allied invasion of France. In the midst of the unprecedented danger from aircraft, U-boats caught in the danger area without schnorchel were sometimes forced to surface in order to charge their batteries and ventilate the boat. In such cases a "forest of Aphrodites" was successfully used to protect the boat from detection and attack during the period of emergency. In several messages read during June, emphasis was on the large number of "Aphrodites" being used and the difficulty of supplying replacements through the French ports, a difficulty which persisted throughout the remainder of the time the ports were in use by U-boats. As time went on, reports on use of "Aphrodite" became more and more infrequent, and by the advent of 1945 they were almost non-existent. Boats leaving port continued to carry the device, however, so it was clear that it was still considered an effective counter-measure under certain conditions, even though the addition of schnorchel had revolutionized the whole problem of U-boat attack and defense.

6. "Thetis."

Message 1642/11 January 1944 on all U-boat circuits introduced a new German anti-radar device to Allied communications intelligence, and through the usual channel to COMINCH. The translation of the message read:

> "To interfere with enemy radar activity, dummy buoys of type 'Thetis 20' will be put out in Bay of Biscay as far as bout 12°W. beginning 11 January. Description: A thin wooden upright 5 meters long, on a float. Weighted underneath with a 5-meter steel tube. Then metal dipoles on the wooden mast, can be seen only from very short distances. Effect: Buoy gives same reflection as U-boat."

In this one short message the most significant details about "Thetis" and its purpose were given. Until July 1944 messages reporting the setting out of "Thetis" buoys occurred in considerable number, with positions in the Mediterranean and in the Atlantic as far as 31°W. Thereafter the number of references in traffic decreased, with final mention in message 1641 (Gray) of 15 August to French U-boat flotillas, in which it was ordered, concerning cargoes to be carried by U-boats escaping form French ports:

> "Relegate transfer of 'Thetis' to last place. They are too unwieldy. Use space for important things such as 'Aphrodite', power cable, valves and 'Bold'."

Thus the relative unimportance of "Thetis" was finally announced.

The one significant detail not revealed in the original message about "Thetis" came to light in three almost simultaneously transmitted messages of 19 March, all directing the addressees to set out their remaining "Thetis" at 15-mile intervals, the object presumably being to simulate patrol lines. This type of mass use continued through July, including general use for protection of non-schnorchel U-boats during the invasion.



ŏ

Individual Bold Pellet

## 7. "Bold."

A counter-device less frequently mentioned in U-boat traffic than "Aphrodite" was the "Bold," a cartridge containing pellets of a chemical composition which produced noises and bubbles when discharged into the water. Their purpose was to confuse anti-submarine search by vessels using Asdic or hydrophones. The device was first mentioned in ENIGMA traffic when Bülow (U-404) requested a rendezvous with another U-boat so that he might take aboard some "Bold" (1925/28 January 1943). That COMSUBs attached importance to the device was indicated by the fact that he granted the request as well as by a more direct statement in a message on 1531/24 April. Reminding U-boat commanders of the use of "Bold" when taking evasive action, he said: "The 'Bold' technique has been used in recent times almost invariably with success." Only a limited amount of material about "Bold" appeared in ENIGMA traffic, but information at hand from all sources was correlated and presented to COMINCH in a memorandum of 30 July 1943, and was sufficient to indicate the nature and tactical possibilities of "Bold". The instructions pamphlet taken from the U-505 and translated by the Atlantic Section proved helpful in elucidating several messages sent to U-boat's during the winter of 1944-1945 concerning the more effective use of "Bold" in "Total Underwater Warfare."

# Chapter III

## Schnorchel

\* \* \*

#### 1. Summary.

- 2. The testing period: January May 1944.
- 3. Schnorchel and the Invasion.
- 4. Schnorchel and radar.
- 5. Schnorchel and radio.

### 1. Summary.

Schnorchel, an extensible trunk which allowed charging of batteries as well as diesel propulsion and U-boat ventilation while submerged, was first used by U-boats in January 1944. The first few months of use were devoted to experimentation under operational conditions. During the invasion, schnorchel was used to the limit of its capacity and allowed operation by U-boats against invasion traffic at a time when air coverage was as effective as to necessitate the recall to port of all Uboat's not equipped with schnorchel. The device was considered of such importance that its installation was designated the chief task of U-boats in port in August 1944. Although schnorchel was not immune to detection by radar, it was much less susceptible than a surfaced U-boat and permitted boats to operate close to coastal traffic concentrations with little fear of detection for weeks at a time. Unquestionably, schnorchel was the most effective counterdevice developed by the Germans in the Battle of the Atlantic. While a half-way measure in the development of a true underwater boat, schnorchel did make possible a dangerous approximation of the "Total Underwater Warfare" which the Germans were trying to perfect on blueprints and in the shipbuilding yards.

## 2. The Testing Period, January-May 1944.

That the Germans had not devoted all of their time and effort to alleviation of the radiation condition of their search receivers during the latter months of 1943 was clearly shown at the beginning of 1944, when schnorchel was first used by Uboat's operating in the Atlantic Section through various references in radio traffic. The first such reference, in January, gave no indication as to what the device might be, except that it was of a mechanical nature and had some connection with the diesel engines, but the British had seen the term in their reading of Baltic traffic and were able to supply the opinion that it was a cover-name for "an internal combustion system of propulsion which can be used by a submerged U-boat." Later information from traffic, prisoners of war, and captured documents provided extensive knowledge of the device. It was

0 

found to consist of two trunks, one for air intake, the other for diesel exhaust, encased side by side. A valve arrangement prevented entry of water, and an oil pressure system was used to raise the schnorchel from its horizontal resting position on the deck to its vertical operating position.

The first several months of 1944 were used in gaining information on the performance of schnorchel in practical use, and Command sent orders at various times requiring U-boat's to make reports on their findings in this regard. In addition, Command was apparently worried over a possible tendency of schnorchel U-boat's to feel to safe with their new protection, for several times during February and March, warnings were sent that schnorchel was not secure from location by radar. Replies to requests for information of the practical performance of schnorchel were evaluated and used as the basis for the Current Order 20, broadcast in 2200 and 2259/31 May, which indicated that several U-boat's had used schnorchel with success for submerged cruises lasting several days; that charging of batteries could be accomplished by use of schnorchel for four to five hours daily; that certain U-boat's tended to smoke up during schnorchel cruising; that schnorchel could be located by radar only at distances considerably shorter than those at which a surfaced U-boat could be located; and that it was necessary to interrupt schnorcheling approximately every twenty minutes in order to make a hydrophone sweep.

#### 3. Schnorchel and the Invasion.

The Allied invasion of France on June 6 brought the Germans not only the opportunity, but also the necessity of using schnorchel to the limit of its capacity. On June 6 in message 1150, the operational area for schnorchel U-boat's as previously ordered was changed and they were disposed about the southern coast of England and in the English Channel to interfere as much as possible with passage of traffic between England and France. More than that, within a week, U-boat's in the Bay of Biscay not fitted with schnorchel were ordered to put into port (2302/12 June), for it had become apparent that the U-boat which was forced to surface in order to charge its batteries in the Biscay area could not survive.

The relative safety of the schnorchel U-boat, on the other hand, could only lead to the conclusion that boats not already fitted should receive the equipment as soon as possible; consequently, the summer and early fall of 1944 were devoted with great energy to its installation in the hard-pressed ports of western France. For U-boats which were already fitted, the main activity during the summer was, of course, a concerted attempt to prevent the movement of Allied ships in the Channel area. Fortunately, there was little success in this effort, owing in part, perhaps, to the fact that there was still considerable hesitation in using schnorchel with the boldness later evidenced by some commanders. Aside from the directly operational objective, boats also concentrated on shortening the time required for charging batteries during schnorchel operation. The continued confidence of Command in schnorchel was evidenced in August in an order directing that completion of equipment with schnorchel should be considered the main task of U-boat's in port, and that boats without schnorchel should not leave port unless the port was directly threatened (2055/7 Gray).

## 4. Schnorchel and radar.

On the basis of accumulated experiences, message 1333/10 of September 1944, gave an estimate of the effectiveness of schnorchel as a means of avoiding radar, advising U-boat's that if the schnorchel was extended only the normal amount, one-half meter above the surface, the impression on a radar receiver would be only about 30 percent that of a fully surfaced U-boat. In addition it was claimed that schnorchel could not be located accurately enough by radar to permit good placement of bombs. Again the general satisfaction of Command was expressed in an Experience Message in the characteristic style of Admiral Dönitz, signed personally by him (1551/17 October). It stated in part:

> "the experiences of many commanders have shown that schnorchel permits cruising without great detours. The schnorchel allows the U-boat to remain in sea areas close to the coast in spite of very strong patrol and achieve successes there. . . I require the captains to make the most energetic use possible of the singular capacity offered by schnorchel and to become master of the enemy defense. Go right to the sources of enemy traffic and attack there . . ."

This note of confidence and exhortation was prevalent in communications of Command concerning schnorchel at the end of 1944, and a new Current Order giving instructions on procedure in operational areas gave considerable attention to the use of schnorchel in "Total Underwater Warfare." In addition a separate new edition of the old schnorchel Current Order went into great detail on all aspects of schnorchel operation. During this period there were scattered references to the apparently satisfactory rubber covering and anti-radar mats with which the schnorchel had been provided. A final estimate of the value of schnorchel, for from inaccurate, occurred in a weekly news summary of the German COMINCH (1831/27 January 1945), in which it was stated:

> "The war at sea has entered a completely new stage through use of the schnorchel, which makes it possible for U-boat's to remain under water for weeks at a time. The more adroit the U-boat's can become in use of schnorchel against the enemy, the greater their successes will be."

#### 5. Schnorchel and radio.

0

0

Along with the decided advantages brought by schnorchel, the operational U-boat received certain disadvantages quite apart from the question of the crew's comfort during a 70-day submerged cruise. Dampness became a problem, certainly harming the more delicate apparatus aboard. Radio gear was particularly affected. At the same time that the efficiency of standard radio equipment was being reduced, the schnorchel U-boat was trying to develop the radio communications system of the U-boat of the future, but like schnorchel itself only a half-way measure was tried. Communications experiments with the schnorchel round dipole failed to relieve the U-boat from the necessity for surfacing to transmit.

## **Chapter IV**

## Armament (Torpedoes and Anti-aircraft Guns)

\* \* \*

- 1. Summary.
- 2. Information on torpedoes available in ENIGMA traffic.
- 3. Standard torpedoes.
- 4. "Curly" torpedoes.
- 5. The electric-acoustic T-V.
- 6. Anti-aircraft armament prior to December 1943. Quadruple mounts and flak-boats.
- 7. The 37mm automatic anti-aircraft gun.

German Submarine Torpedoes



## Armament (Torpedoes and Anti-aircraft Guns)

## 1. Summary.

ULTRA sources contributed information of value not only in following technical progress in matters of armament, but in showing the potential striking power and duration of cruise of operating U-boats. In the field of torpedoes, the most important developments were the "curly" (FAT) torpedo, which increased the probability of a hit by traversing the immediate area of a convoy several times, and the "GNAT" (T-V or "Zaunkönig"), a torpedo which homed acoustically after an initial straight run. Both types met with considerable success, and the "GNAT" accounted for the sinking of many Allied destroyers before noise-makers were devised to lure it from its intended prey. Developments in anti-aircraft armament were clearly indicated in ENIGMA traffic. Armament was greatly increased on U-boats in the first months of 1943, and during that year there were concurrent experiments with 20mm quadruple mounts and 37mm automatic guns, with inclusion of both types on a special anti-aircraft U-boat. Failure of the Flak-U-boat led to reversion to the principle of greater antiaircraft protection for all boats at a cost in crash-diving speed. Outfitting with 37mm guns was undertaken on a large scale in December 1943, but the weapon never reached the effectiveness hoped for by Command.

2. Information on torpedoes available in ENIGMA traffic.

Among developments in the field of weapons which could be followed with great advantage by the reading of enemy traffic, the most important were probably concerned with the U-boats chief weapon, the torpedo, upon the development of which the technical staffs of the German navy expended considerable efforts and ingenuity. Data available from ULTRA sources included more than one type of information of value. There were, for instance, frequent reports from U-boats at sea giving the number of torpedoes of different types on hand. These reports, along with other pertinent information, were an indication of the potential striking power of the U-boat concerned, and thus aided in determining how long the boat was likely to operate before returning to port. Another type of

information furnished, especially from the reading of administrative traffic which began with the breakdown of German landlines in June 1944, concerned the problem of supply of torpedoes to U-boat bases as well as the departing Uboats. In addition there were extensive orders and reports which gave valuable clues as to the character of new types of torpedoes and torpedo parts and their effectiveness.

## 3. Standard torpedoes.

Torpedoes at the disposal of U-boat commanders were of three basic types: air, electric and electric-acoustic. The capabilities of the air and electric types were further increased by use of improved exploders<sup>1</sup> and fuzes as well as by introduction of a "curly" mechanism, which increased the probability of a hit by directing the torpedo back and forth several times over the area being traversed by a convoy or ship. The standard 21-inch air torpedo, generally carrying an impact pistol, had three settings: 44 knots to 6,500 yards, 40 knots to 8,700 yards, and 30 knots to 15,300 yards.<sup>2</sup> It make a visible track, so was usually used in night attacks. Because it required less attention than the electric torpedo, it was generally used by U-boats carrying out long patrols. The standard 21-inch electric torpedo had only one setting allowing for a speed of 30 knots to possibly 7,000 yards if the battery was pre-heated. Owing to the fact that it showed no track, it was a more popular type for general use.

4. "Curly" torpedoes.

The first FAT (Feder-Apparat-Torpedo) were introduced aboard U-boats late in 1942, as evidenced by a message to Dietrichs in January 1943 (1326/1) in which he was required to "report in detail on FAT and pistol." An order sent the middle of the same month (1902/15) gave a hint as to the nature of FAT when it cautioned U-boats that overestimation was to be preferred underestimation, since as a result of underestimation "the entire FAT falls short and the torpedo

<sup>1</sup>Exploder is the American term for the detonating mechanism of the warhead. Throughout the war the British term, pistol, was more commonly used.

<sup>2</sup>The 44 knot setting was for Schnell boats only and not used by U-boats.

changes course before reaching the target," whereas "an overestimated FAT distance utilizes at least the preliminary run of the torpedo and consequently affords the same chances of success as does the normal straight shot." A flurry of shortsignal reports during February and March giving notice of intention to attack with FAT indicated that the device was receiving adequate trial in the field, and there were several reports giving firing data for successful shots. Such reports continued to be sent throughout the course of the war.

In December 1943 (1058/28 and continuations), in a long Current Order, it was pointed out that the FAT torpedo, as well as the newer electric-acoustic T-V, was valuable for firing under the current difficult conditions which prevented U-boats from approaching their targets to favorable distances and from favorable directions. It was indicated that these torpedoes were especially suitable for "blind" firing by hydrophone data.

Meanwhile, continued experimentation had produced not only improved models of the FAT, but also a new refinement of the same principle, LUT (Lagenunabhängiger Torpedo), a torpedo which could be fired effectively in a "curly" pattern independent of the target angle from its straight run and its mean speed of advance along its "curling" direction could be pre-set at will from 5 to 19 knots. The LUT was not used extensively until the middle of 1944, when COMSUBs stated that a destroyer and two large freighters had been sunk by LUT spread shots. (2333/6 July) Most reports of the period, however, were concerned with tube runners caused by failure of the LUT adjuster to disengage, and this trouble continued at least until the beginning of November, after which little was heard of LUT.

5. The electric-acoustic T-V.

The most spectacular torpedo developed by the Germans, because of its appeal to the imagination as well as the impact of its sudden initial success, was the T-V, called the "Zaunkönig" ("Wren") by the Germans and the German Naval Acoustic Torpedo (GNAT) by the British. That COMSUBs was relying heavily upon this new torpedo to restore to the U-boat its former advantage in the Battle of the Atlantic was evidenced by a series of messages during September 1943, all sent in Offizier settings for purposes of security. The first reference (1128/2 September) called upon all U-boats equipped with Zaunkönig to make use of every opportunity to bring their "sharp weapon" into play and to act upon the principle that "offense is the best defense." Decimation of the convoy's escort was stated to be their main goal.

The great importance of secrecy with regard to the new weapon was emphasized not only by the use of Offizier settings in the first messages concerning it, but by the fact that the contents of the messages, in so far as they could be made known to the crew at all, were withheld until shortly before the beginning of the first operation. (1226/13 September) Moreover, in reports on shots with "Zaunkönig," the target angle was to be disguised by use of an additive and comments on enemy speed were to be given in code-words. It was expressly directed that details of firing and the limits of effectiveness of the torpedo should be kept secret from the crew. (1422/21 September)

Continuation of this secrecy into 1944 was demonstrated by instructions to U-boats enroute to the Far East to sink their "Zaunkönigs" and keep them absolutely secret from the Japanese.<sup>3</sup> (1024/4 April 1944) It was not until the end of May that Admiral Dönitz was ready to supply the Japanese with general information and even in June an order was given that while the Japanese at Penang were to be allowed to inspect the torpedo itself, they were under no circumstances to be permitted to see the instructions for its use. (2119/19 June) The implication even then was that the inspection was to be allowed because it could no longer be avoided. Fortunately for the Allies, all the German secrecy was to no avail, for radio intelligence had made the nature of the torpedo available even before it was actually used for the first time by Group Leuthen in mid-September 1943.

The T-V was a 21-inch torpedo which could be fired either on the surface of down to a depth of about 100 feet with a speed of about 24 knots up to 6,000 yards. The torpedo's most important attribute was its ability to home acoustically to the propeller noise of the target after an initial straight run. The immediate widespread use of the T-V can be appreciated form the fact that after the initial report of a tube runner by Mäder on 15 September (0029) there followed within ten days fifteen separate reports on the firing of T-V's. Almost half of

<sup>&</sup>lt;sup>3</sup>The Japanese Naval Attaché in Berlin had already gotten wind of the weapon.

the reports claimed indications of success, and it was significant that the successes were generally registered against escorting vessels rather than freighters. In a message of 12 October (1555) COMSUBs enthusiastically claimed further successes, including five destroyers and three freighters sunk and one destroyer probable sunk, all between the second and tenth of October. In message 1847/25 November, while admonishing U-boat commanders to utilize all opportunities for firing T-V's "has fundamentally altered the U-boat-destroyer relationship in favor of the U-boat. In this torpedo the U-boat has not only a good defense, but a strong attacking weapon as well."

0

0

The large number of sinkings which continued to be reported bore out this opinion, and the Japanese Naval Attaché in Berlin reported on 29 January 1945 (JNA #914) that the rate of hits of acoustic torpedoes since they were first put into use was 43 percent. When the French U-boat bases were evacuated in the middle of 1944, the "Zaunkönig" was so highly valued that the removal of T-V torpedoes and testing facilities from the bases was considered a paramount task. The latter half of 1944, however, showed a diminishing effectiveness of the T-V owing to success of noise-makers used by Allied ships as well as the generally more difficult operating conditions for U-boats, both clearly indicated in ENIGMA traffic.

## 6. Anti-aircraft armament prior to December 1943. Quadruple mounts and flak-boats.

As the struggle between the U-boat and its enemy, the airplane, progressed, it became necessary to provide the Uboats not only with means of avoiding aircraft but of waging battle with them when they could not be avoided. In the first half of 1943 anti-aircraft armament aboard U-boats was increased so that the typical 500-tonner was carrying an 33mm gun forward, a 20mm on the bandstand, and tow machine guns on the bridge, with one or two additional 20mm guns on a temporary platform below and abaft the bandstand. When the effect of this increased in armament proved negligible with existing tactics, the next step was a change in tactics whereby U-boats remained on the surface and fought it out when surprised by aircraft.

This change in procedure caught the airplanes unprepared and achieved a temporary success reflected in traffic by eighteen occasions during the month of July alone in

which U-boat commanders reported that the enemy had been "warded off." Nonetheless, a large number of U-boats were sunk by aircraft in July, and the success of the new policy dwindled in August and September when planes were reported driven off only six times altogether. A few boats had been equipped between May and September with 20mm quadruple guns, for accommodation of which the bridge was permanently enlarged. On some of the 500-ton boats these guns were mounted on the lower platform, abaft the bridge, with one or two smaller 20mm installations on the bandstand. The 33mm gun forward was generally removed from these boats.

Manseck (U-758) was among the first U-boats to be equipped with a 20mm quadruple mount, and his first engagement with it occurred on 8 and 9 June 1943 when he was attacked by four aircraft from the USS *Bogue*. The attacking aircraft, confused by the enlarged bridge, believed they were dealing with a 1600-ton supply submarine. Manseck, though badly damaged, managed to drive off his four assailants. One of them was hit in the engine but all returned to the USS *Bogue*. Manseck's report on the engagement stated:

> "Eight carrier planes warded off; one shot down, four damaged." (0527/9 June 1943)

COMSUBs was delighted. He replied: "Well done. Long live your quadruple." (1257/9), and announced a few days later that other U-boats were to be equipped with the new weapon.

There was little indication of the effectiveness of the 20mm quadruple mount from ENIGMA traffic, but there was only a moderate increase in the number of planes hit or brought down in the last months of 1943. Enigma traffic did reveal the fragility of the weapon, however, with no less than seventeen U-boats reporting their quadruple mounts out of order in October alone.

Of great importance was the fact that the increased armament had also increased the crash-diving time of the Uboats by probable a quarter of a minute. Such an increase was quite unacceptable, and experiments with a special antiaircraft U-boat, or Flak-U-boat, were instituted in May 1943, when one such boat was sent out. By November there were five of them actively operating. Conversion of a 500-tonner to a Flak-U-boat consisted of enlarging the superstructure and increasing the fire power. The 88mm gun forward was replaced by a 20mm quadruple mount, with a second quadruple mount on the rear of the greatly extended bridge, and below it a 37mm gun on a platform. Conversion took from 11 to 13 weeks in most cases. The Flak-U-boat was apparently envisioned as a floating fortress, capable of defending itself and other U-boats on the surface. Indeed, these boats were assigned as escorts in the Bay of Biscay and as protectors for refueling operations. A case in point was that of Brauel (U-256), a Flak-U-boat assigned to protect Barber (U-220) in a refueling operation at the end of October 1943. Both boats were attacked by aircraft on the 28th. Baber was sunk, but Brauel must have submerged even before ascertaining that fact, for his only report on the incident three days later merely stated that he had not seen Barber since the attack.

In protecting either themselves or other vessels, the boats were conspicuously unsuccessful, and the whole record pointed to the conclusion that the Flak-U-boat was a failure. with its one positive contribution being its service as a preliminary testing ground for the automatic 37mm gun. Even that service turned out to be of limited value in view of the necessity for long-continued experimentation even after the 37mm was fitted on other boats.

The 37mm automatic anti-aircraft gun. 7.

The failure of the Flak-U-boat led to reversion to the original approach, namely an increased in the armament of all U-boats at the expense of quick crash-diving by fitting them with the 37mm gun. A memorandum sent to COMINCH in December 1943 summarizing the above facts concerning antiaircraft armament pointed out that this reversion on to the original approach showed the same trend as other developments of the period, namely, a transformation of the Uboat from an offensive weapon to a defensive one. In support of this statement it was possible to bring to witness a statement made by COMSUBs in a long message of 13 November (1903/13 and continuations) in which he said as consolation to his commanders that enemy forces engaged by U-boats "cannot be put into action against the homeland. Therefore, you are protecting your home even in battles which seem to you at the time unsuccessful." In the same message, COMSUBs hailed the new hope of the U-boat, stating:

"In the fight against the main enemy, the opponents' air arm, the automatic 37mm gun will bring further easing . . . It is expected that form the beginning of December on, all U-boats departing from Western France will be equipped with this excellent weapon and that from the middle of December on, all home U-boats will be so equipped. In addition to the 37mm gun, U-boats will be equipped with the most modern ammunition, the effect of which amounts to that of the 20mm many times multiplied, and one hit of which generally will bring a plane down."

Unfortunately for the Germans, "this excellent weapon" was constructed and installed with such rapidity that the usual thorough test were omitted, as acknowledged in 1034/5 January 1944. Even so, there was hopeful confidence in the weapon form the first, even to the extent of ordering U-boats equipped with 37mm guns to charge their batteries in the daytime in the Bay of Biscay. (2238/6 January) This order was rescinded about a week later owing to decreased aircraft activity at night rather than to any success of failure of the 37mm.

The continued confidence of COMSUBs was demonstrated when, in planning an approaching convoy operation by a group of U-boats, he ordered that all U-boats whose 37mm guns were in order should remain on the surface if the operation extended into the daylight hours so that the mass of U-boats could "shatter and scatter" the enemy's defenses. (2236/17 February) This test of the effectiveness of the 37mm did not take place as the group operation failed completely and offered no opportunity for attack. In recapitulating the failure, COMSUBs betrayed some misgivings about his weapon when he said:

> "A continuation of the operation by day was not possible, since, with only a few U-boats in the vicinity of the convoy, the battle with the aircraft defenses could not be taken up: especially since there were carrier-borne aircraft with the convoy. This attempt will be made as soon as more U-boats are with a convoy and we can rely better on the 37mm." (0207/20 February 1944)

In the actual fact, the reports of mechanical trouble with the 37mm gun far outweighed reports of successes in the firs months of 1944, but the equipping of U-boats, including those operating in the Arctic area, continued. The continuing confidence of the U-boat command was further expressed in an Arctic Order (0420/17 May) which stated:

> "With the equipment of U-boats with the 37mm a first-rate weapon is given to the boats. It will pierce any armor of carrier or land based aircraft or flying boats, and often makes it possible for U-boats to remain on the surface and to advance. In all situations, take advantage of the power of this weapon."

Yet, in contrast to this expression of enthusiasm, COMSUBs was impelled to warn Atlantic U-boats in massage 2201/10 June not to become overconfident in their antiaircraft and search receivers and thus jeopardize the safety of the ship.

The anti-aircraft armament of U-boats continued to be the subject of many reports throughout the remainder of the war. After the Allied invasion of France, there was the usual preoccupation with difficult supply for U-boats based in France. Most of the other messages dealt with mechanical difficulties, with a few indicating definitely that the 37mm was still an object of experiment. In this connection, Raabe (U-246) was told in November (0911/7) that experiences with the new 37mm gun were very important, and messages similar in content were sent as late as January 1945.

0

# Chapter V

German-Japanese Exchange of Information

\* \* \*

- 1. Summary.
- 2. The special Significance of Berlin-Tokyo traffic.
- 3. Allied interest in the effort toward "Total Underwater Warfare."
- 4. First details of the new type U-boats.
- 5. Speeds.
- 6. Delay in completion of the new type U-boats.



#### German-Japanese Exchange of Information

#### 1. Summary.

Traffic of the Japanese Naval Attaché in Berlin was of special value to radio intelligence because it gave full details on technical matters under investigation by the German navy, and also gave an insight into the future broad policy of the Naval High Command. A very large amount of information was furnished on all sorts of technical matters, including U-boats, aircraft, weapons, radar, radar defense, and the extent of Axis knowledge of Allied weapons, devices and procedures. Of particular value to the Atlantic Section was the data on the new type XXI, XXIII, and XXVI U-boats, with which the Germans hoped to regain their former power on the high seas. With the early knowledge of the main feature of the new types, their higher underwater speed, and subsequent fuller details, it was possible to appreciate the proportions of the anticipated new German measures. Of no less importance was the ability of radio intelligence to follow closely the progress in construction of the new type boats.

## 2. The special significance of Berlin-Tokyo traffic.

Traffic between the Japanese Naval Attaché in Berlin and his superiors supplied certain unique contributions to the general picture which were not available in the administrative and operational traffic of the German navy. Whereas the technical material sent in U-boat traffic was being passed to people who already had a knowledge of the subject discussed through possession of handbooks and other aids, hence presumed a prior knowledge of most details, the Japanese were in much the same position as their enemies in that they had no such extensive prior knowledge. Therefore, when a new device or measure was reported to Tokyo by the Japanese Naval Attaché, full details had to be given and were thus made available to the Allies through decryption.

The information to be gained form Japanese Naval Attaché and diplomatic traffic was also valuable because, in addition to its full discussion of technical matters, it provided an insight into the line of major policy adopted by the German navy after the U-boat was driven from the North Atlantic in the spring of 1943. The type XXI U-boat, which was to be the mainspring of that policy, will be discussed at some length in following paragraphs. The selection of new type U-boats as a prime example of the value of Japanese Naval Attaché traffic should not, however, lead to disregard of the importance of the information furnished. Of direct Naval interest were details of midget, transport and mine-laying U-boats; new torpedoes, including the turbine torpedo still under development at the time of the German surrender; and location and anti-location devices. Of a more general interest were the details of radar and radar defense; jet-propelled and other aircraft; V-weapons and many other types of enemy weapons; and the extent of enemy knowledge of Allied weapons, devices and procedures.

3. Allied interest in the effort toward "Total Underwater Warfare."

It was apparent to the Allies as well as to the Germans that, after the utter defeat to which the U-boat had been subjected in spring of 1943, the German navy would be forced to turn to the skill of its technical departments even more urgently than before. The situation demanded quick, effective and revolutionary measures, and it was a matter of supreme importance for the Allies to find out what those measures were to be in order to plan counter-measures before any large measure of success could be achieved by the enemy. The introduction of the Zaunkönig and the schnorchel have already been discussed in other chapters. They were part of the general plan to restore to the U-boat its old power. It was known, however, that other plans were also in the making. On 6 March 1944 the Japanese Naval Attaché reported to Tokyo:

"Although German submarines were amazingly effective at first the enemy now has invented new defensive weapons and in addition devised great counter-measures which have brought about a continued decrease in the damage inflicted by submarines. Consequently the German navy had determined to improve the submarine and we believe they are making plans for the future, but judging from what we know now, we do not expect any great activity form new type submarines before autumn." The direction of German thought, as was to be expected in view of past developments, and as was indicated by the introduction of schnorchel, was toward severing the tie which bound the Uboat to the surface and made discovery by radar possible.

Schnorchel was a step in that direction, but only a step, and it was feared by the Allies that exhaustive research might lead to a U-boat which would not need to go to the surface or even near the surface during the entire period of a cruise. It was thus a great relief to be able to learn from reports of the Japanese Naval Attaché that while new type U-boats were indeed to be introduced, their chief advantage over older types provided with schnorchel would be in their increased underwater speed.

4. First details of the new type U-boats.

On 28 December 1943 (in a message not read until June of 1944), the Japanese Naval Attaché in Berlin sent to Tokyo a description of two new types of U-boats, details of which had not yet been officially released to him by the German navy. The information represented the report of Naval Inspector Tomonaga, who had been permitted to view plans and charts at the shipyard and to catch a glimpse of part of one of the vessels. The Attaché himself had first viewed the plans the preceding August at the Deschimag Shipvard, and his observations, added to those of the Inspector, provided specifications and other information sufficient to indicate the trend in U-boat construction for the remainder of the war. As was later confirmed by official information, it appeared that the chief feature of the new U-boat would be their increased underwater speed, which would be made possible by largecapacity batteries.

Two new types were described, the large type XXI, designed for long-range operations; and a small type designed for coastal operations. The small U-boat was referred to as type XVIIb but later evidence pointed to the conclusion that the U-boat under construction was actually the type XXIII, concerning which a large amount of information was later gained from Attaché traffic. As to the state of construction of the new boats, the Attaché considered that large numbers were already in the construction stage, would be completed from about August or September. (JNA #479, 28 December 1943)

### 5. Speeds.

Since the increased underwater speed of the new type Uboats was to be their chief advantage over older types, a dispatch in which pertinent figures were given, Japanese Naval Attaché #316 of 13 August 1944, was of more than passing interest. The speeds and ranges quoted were as follows:

Type XXI		Type XXIII	
(6 battery	compartments)		
Speed	Range	Speed	Range
(knots)	(miles)	(knots)	(miles)
3	450	2	250
6	265	4	175
8	165	6	113
11	110	8	70
14	45	10	43
top	24	top	22

According to Japanese Naval Attaché #420 of 12 September 1944, the tested top speed for type XXI was about 16 knots, and it was hoped that this could be increased to 17 or 18 knots. Also of significance was the type XXI's lowest submerged speed on electric motors, 0.5 - 1 knot, at which the motor was said to be noiseless as the result of reduction by rubber belts. For type XXIII the tested top speed was 12.5 -13 knots. It can be seen from the above table that use of the higher underwater speeds would be severely limited by the short ranges at which such speed could be maintained before exhaustion of the batteries. 6. Delay in completion of the new type U-boats.

The Japanese anxiety over the condition of German striking power led to continual inquires as to when the new type U-boats would be ready for combat. The serious construction difficulties due to Allied bombings and other factors were reflected in repeated postponements in estimates of that date. By the reading of Japanese messages it was possible for radio intelligence to keep informed of construction developments. On 26 July 1944, Ambassador Oshima reported concerning the type XXI boat: "At present it is in process of construction and its effect will first be felt from about September; and by November or December it is said that greater results will be effected by its use in great quantity." (#756)

Again, on 12 August (#621), Dönitz was quoted as saying that the new offensive U-boat warfare would begin "at one swoop" after a considerable number of the new U-boats had been completed, therefore in the winter of 1944-45. But on 3 December (#753) the Naval Attaché wrote with regard to combat use of new type U-boats:

> "Although the German submarine fleet and ministry of military supplies are making feverish preparations, there will probably be no results until about March of next year."

Even in March 1945, the best that could be reported concerning type XXI boats was that they would be ready on a large scale in May or June (#301, 7 March). Actually, only four of the type XXIII's made war cruises, while the only type XXI to leave port for an operational cruise was U-2511 (Schnee) which was outbound on the day of surrender.

# Chapter VI

Fuel

\* \* \*

- 1. Summary.
- 2. Availability of information of fuel.
- 3. The use of fuel in operation.
- 4. Fuel reports as an aid to radio intelligence.

### 1. Summary.

Fuel reports sent by U-boats at sea were of significance in the planning both of U-boat operations by COMSUBs and of anti-submarine operations by the Allies. The amount of fuel which a U-boat had on hand was usually appended to any other report which it made. The mass of data on fuel resulting from such frequent reports provided with ample basis for various assumptions with regard to U-boat operations. Moreover, the same information provided a basis for identification of the type of given U-boat and for determination of fuel capacities and consumption, day's runs, and prescribed speeds. There were occasions when knowledge gained from fuel reports aided in the decipherment of disguised grid positions.

Fuel

#### 2. Availability of information of fuel.

Fuel reports sent by U-boats at sea had a double significance. For COMSUBs in his conduct of the U-boat war they were essential in disposition of the U-boats and in the planning of operations. For the Allies, the reading of fuel reports was of equal importance in the conduct of the antisubmarine war. The vital nature of these reports is evidenced by the fact that U-boats were generally required to append a statement of the amount of fuel on hand to every transmission which was otherwise necessary, i.e. position, movement, contact, and success reports, as well as specific requests for provisioning. The number of such reports received by the Uboat Command varied, of course, according to the number of Uboats at sea and the extent of their activity. For example, in March, 1943, when U-boat anti-convoy operations reached their peak, 179 U-boats were at sea, and Command received a total of 325 fuel reports, an average of 10.5 per day. The maximum number on any day was 33, the minimum 2.

## 3. The use of fuel in operation.

One of the cardinal principles in U-boat operation was economical use of fuel in the patrol line and during any cruising which was not directly operational; but once contact

was made with a convoy, U-boats operated with a total disregard for fuel, only reserving an amount absolutely necessary for their own safety. When U-boats had sufficient fuel and were not engaged in a convoy operation, they normally sent routine fuel reports along with position reports. When the supply decreased to the amount required for the homeward cruise, they might request provisioning if the prospects of success in the attack area seemed promising, or simply advise COMSUBs that they were returning. A convoy sighting, however, nullified all immediate plans, and the contacting U-boat shadowed to the limit of its fuel or until other U-boats could be brought to the scene. Whenever possible, the movements of U-boat tankers were coordinated with those of the attacking force to lessen the chance of losing the convoy. In some few cases in which no U-boat tanker was available, an outgoing U-boat refueled those at sea, or U-boats engaged in an attack themselves transferred fuel in order to permit continued operation or return.

4. Fuel reports as an aid to radio intelligence.

The abundance of information regarding the fuel status of U-boats was also of inestimable value to radio intelligence activity. In February 1944 COMSUBs confirmed estimates of fuel consumption which had previously been made here on the basis of the daily fuel reports, revealing that the type VIIg boats in anti-convoy groups Command counted on a maximum daily consumption of up to 2 cbm if no operation was going on; for type IXc, up to 3 cbm under the same conditions. From the amounts reported, the Atlantic Section was able to identify or confirm the types of new U-boats as they reported from seas. The daily reports also permitted an evaluation of cruising speeds in terms of a day's run and the identification of these speeds with those ordered by COMSUBs - maximum, economical, cruising, etc. With a knowledge of the type of Uboat operating in a given area and an approximate idea of its fuel capacity, it was possible to estimate the extent of its future operations and to plot a rough course. Furthermore, it was possible to reduce enciphered positions to a specific area with the aid of knowledge of the fuel capacities and consumption of the U-boats concerned.

## Chapter VII

## **U-boat** Navigation

\* \* \*

1. Summary.

- 2. German air force Elektra-sonnen.
- 3. D/F-ing of very low frequency shore transmitters.
- 4. Navigation for "Total Underwater Warfare."



52

Elektra-sonne Facilities (as of May 1944)

#### 1. Summary.

The most important new development in navigation during the war was the use of German air force (GAF) Elektrasonnen for U-boat navigation. The use of beamed signals from these transmitters enabled U-boats to fix their position by employing only an ordinary radio receiver. A great deal of attention was given by COMSUBs to amassing information on the adequacy of navigation by this means. The results of experiments were not directly available to radio intelligence because they were included in the written communications reports of the U-boats, but there were several instances in which successful navigation by Elektra-sonne was claimed. It was found that this method was available to U-boats making long submerged cruises, as Elektra-sonne signals could be received over the schnorchel round dipole. An experimental program to determine the possibilities of D/F-ing very low frequency transmitters for navigational purposes was also carried out, but no significant results were recorded in radio traffic.

The concept of "Total Underwater Warfare" brought about increased emphasis on all methods of navigation which could be substituted for the taking of astronomical fixes. Navigation in coastal waters was a matter of particular concern because of costly accidents to U-boats due to faulty navigation. Accurate dead reckoning, terrestrial navigation, and utilization of lines of sounding were recommended for their reliability; but the exercise of appropriate caution was urged as the basic principle in coastal navigation.

2. German air force Elektra-sonnen.

The most important development of the U-boat war in the field of navigation was the utilization of GAF Elektrasonnen. The experimental observation of Elektra-sonnen as an aid to U-boat navigation was begun by boats in the Bay of Biscay in April 1943 and later extended to other more distant areas of the Atlantic. The Elektra-sonnen in use by U-boats at various times were located in Norway, Holland, France, Spain and the Danzig area. Ranges of the beacons varied, the longest range cited in traffic being that of Sonne 6, up to 1300 miles. The advantage of navigation by Elektra-sonnen lay in the fact that in addition to the opportunity for D/F-ing offered by an ordinary radio beacon, their transmission of beamed signals, turning gradually past definite sectors, made possible the fixing of definite direction line by use of an ordinary radio receiver. Accurate bearings could be obtained by a process of counting or timing dots and dashes of the beamed signals and plotting the result on charts especially prepared for Elektra-sonnen navigation. Full details of this procedure were given in an operation manual found aboard the captured U-505 in June 1944.

As was usual with newly introduced procedures and equipment, the U-boat command experienced considerable difficulty in assembling necessary information from practical experience because of inadequate reports from U-boats. There was no evidence in 1943 that any satisfactory amount of information had been reported, and as time went on the demand for greater use of Elektra-sonne grew more insistent. On 22 March 1944 encouragement was offered in a message form COMSUBs in which he stated:

> "Recent experiences have shown that after repeated practice in navigating by Elektrasonne very good results were obtained. Work with it as often as possible, particularly in the North Atlantic." (1653/22 March 1944)

A few days later the U-boats were told:

"Navigation by Elektra-sonne had not been tested fully enough in the past. U-boats have used the sonnen almost exclusively just for taking bearings and thus have yielded insufficient results. The advantage of the sonnen is that positions may be ascertained without D/F set." (1850/31 March 1944)

The long submerged periods which resulted form increasingly extensive use of schnorchel late in 1944 accentuated the importance of any aid to underwater navigation, and use of Elektra-sonnen for this purpose was advised in experience message 181 (1917/6 November 1944) in the following terms: "The commanders still devote too little attention to navigation by Elektra-sonne. Good navigation is possible even when submerged. There have been many favorable experiences. For practice you should navigate by Elektra-sonnen all the time, even if there is another fix available, There is thus a means of comparison. The commander will have to justify failure to use Elektra-sonnen."

Submerged U-boats were able to hear Elektra-sonne signals over the schnorchel round dipole, while transmission could be heard over the D/F loop if it was out of the water.

The extent to which navigation by Elektra-sonne had been developed by the closing months of the war was indicated by a message stating:

> "One U-boat returning from mid-Atlantic had a correction form estimated position of only 2 nautical miles on entering port after a 4 weeks passage without taking position by star sights. Navigation by Elektra-sonnen only. In addition a running fix outside the port of destination was taken form Sonne 8." (1819/31 January 1945).

3. D/F-ing of very low frequency shore transmitters.

On 21 January 1944 (1520/21 ff) an experimental program to determine the possibilities of long-range D/F-ing of very low frequency transmitters for navigational purposes was announced. Bearings were to be taken as frequently as possible on specified transmitters on both sides of the Atlantic with a view to determine the maximum range for sufficiently accurate bearings and the possibility of taking cross-bearings on American and European transmitters in the middle of the Atlantic. Comparison was to be made with dead reckoning or astronomical fixes, and full details, with evaluation exclusively by the U-boat commander, to be included in the boat's communication report. Because of the fact that all data were to be handed in after returning to port, it was impossible to determine by radio intelligence what the results of the experiments were. The only indication was a statement in a situation reports on the Minch area that approximate bearings
had been obtained on the Rugby very low frequency transmitters.<sup>1</sup> (1927/27 December 1944)

4. Navigation for "Total Underwater Warfare."

The attempt at "Total Underwater Warfare", which was foremost in the plans of the U-boat command at the end of 1944, brought with it considerable concern over improvement of navigation during long submerged periods. One group of series of "General Rules for Total Underwater War" directed Uboats to:

> "Avoid surfacing for astronomical fix as far as possible. Keep scrupulously exact dead reckoning, allowing for current. Use of sounding apparatus, Elektra-sonnen and radio beacons makes a thoroughly exact determination of position possible, according to available experiences. Make use of every possibility for determining positions by landmarks when near our own and enemy coasts." (2040/16 November 1944)

The "available experiences" presumably included some which had been mentioned earlier in the same month. Speaking of accurate fixes which could be obtained from lines of sounding taken by repeated crossing of prominent depth demarcations in various directions, COMSUBs had reported:

> "Förster (U-480), coming form the Atlantic after an 18-day cruise without fix, made an exact determination of position by this procedure and without any further navigational aid reached the escort pick-up point. Von Friedeburg (U-155) made his way in form Iceland passage guided by the Elektra-sonne equisignal sonne beam, then reached the escort pick-up point without difficulty by means of soundings." (2239/2 November 1944)

A new aid to sounding in the form of sonic telegraphy was also recommended on the basis of experiences of Schimmelpfennig (U-1004), who measured depths of over 1000 meters by

<sup>&</sup>lt;sup>1</sup>Rugby transmitters were used for the Broadcasts to Allied Merchant Ships (BAMS).

sending out sound by sonar and timing the interval before the return of the echo. (2005/3 November 1944) That there was need for particular attention to the problems of navigation in coastal waters was evidenced by two messages of 24 December 1944, which placed great emphasis on caution in such waters. One of the messages called attention to collisions between Uboats and other German vessels resulting form lack of navigational practice. (1908/24 December 1944) The other summed up the desired navigational policy as follows:

> "Since astronomical reckonings are not to be carried out in enemy coastal regions, the greatest value and extreme care must be put on very plentiful terrestrial navigation, painstaking dead reckoning with considerable of current according to current atlas, and utilization of soundings (line of soundings). As a basic principle, if position cannot be obtained beyond doubt, always assume that the U-boat is in as unfavorable a position as possible, and act with appropriate caution in waters dangerous for navigation." (1156/1443/24 December 1944).

#### Chapter VIII

### U-boat Communications and U.S. Navy Communications Intelligence (Intercept and High Frequency Direction Finding)

\* \* \*

- 1. Summary.
- 2. Operating procedure.
- 3. U-boat circuits.
- 4. Use of medium frequencies.
- 5. Use of very low frequencies.
- 6. Norddeich off-frequency operation. (Standing War Orders 217 and 218)
- 7. "Kurier."
- 8. U.S. intercept operations.
- 9. HF/DF operations ashore.
- 10. HF/DF operations afloat.
- 11. TINA and RFP.
- 12. Chronological account of the German struggle against D/F and radio interception.







## U-boat Communications and U.S. Navy Communications Intelligence

(Intercept and High Frequency Direction Finding)

1. Summary.

Communications between U-boats and their bases was carried out by H/F radio, with repetition on very low frequency to insure reception. Either the "Broadcast" or "Intercept" method was used by Control to deliver traffic to U-boats. The large number of circuits, designed to serve all areas in which U-boats were operating, consisted of regular U-boat circuits, convoy circuits, and special circuits. In addition to this system for communication between control and its boats, medium frequencies were used for cooperation of U-boats with each other, with surface vessels, and with aircraft, mainly for homing purposes,

The chief concern of the German communications service was to maintain contact between Command and the U-boats without offering too good an opportunity for D/F-ing and traffic interception by the Allies. Proper regard for radio discipline was in evidence in traffic at all times, but became more pronounced as unfavorable conditions for the U-boat, particularly at rendezvous and in group operations, became more acute; and the summer and fall of 1943 brought the campaign of COMSUBs against D/F to a new height.

During the period, restriction and supervision of the use of radio became stricter than ever. Restrictions were placed on the use of certain receiving sets, and COMSUBs demanded employment of off-frequencies of the Norddeich service even more insistently than before. Also the off-frequency procedure already in effect was completely revised with a view to increasing both efficiency of operation and difficulty of interception. This stage of development of the off-frequency procedure offered little difficulty to the Allied D/F organization, but a later refinement introduced in January 1945 was quite effective in combating interception.

The summer of 1944 brought the most important development in German communications in the form of "Kurier" experiments. "Kurier" was a system of high-speed automatic "flash" transmissions involving the use of special sending and receiving equipment. During several periods of experimentation, no "Kurier" signal was ever D/F'd, and if the system could have been brought into operational use, the Allied D/F organization would have been rendered helpless until counter-equipment could have been devised. 000

American efforts to intercept German naval circuits were made as early as 1938, and by the time the United States entered the war almost 100 percent coverage was obtainable. HF/DF-ing of U-boat transmissions was begun in January 1941 by shore stations and was extended to shipboard stations the next year. The D/F organization was much improved during the course of the war through liaison with the British, an increase in the number of stations, and better operating technique. The "tip-off" system was used to advantage for alerting all D/F stations simultaneously. OP-20-G cooperated fully in the establishment of shipboard HF/DF stations, in training personnel to man them. and in keeping the forces afloat abreast of all the latest trends in U-boat communication with HF/DF for the identification of transmitters.

2. Operating Procedure.

German U-boats maintained contact with and received orders from their home bases by high frequency radio communications, but to insure that U-boats received all traffic, and elaborate very low frequency repetition service was in operation over which practically all U-boat traffic was repeated.

The control stations on the U-boat circuits delivered traffic to U-boats by either the "Broadcast" or "Intercept" method. The same H/F circuits were used for both shore-ship and ship-shore traffic. The control stations observed fixed silent periods on all circuits for the reception of U-boat transmissions. In addition to these fixed silent periods, the shore stations normally observed a five-second pause at the end of each fortieth group in long transmission in order to permit U-boats with traffic of higher precedence to break in. Thus a U-boat could transmit during silent periods, during the five-second pause, or at any time when control signified that the circuit was clear by use of "VA." Neither external address nor call sign were used by U-boats. Control acknowledged a Uboat transmission by repeating the message and inserting a serial number in the heading.

#### 3. U-boat Circuits.

Communications were carried out on a large number of frequencies which were divided into circuits and selected so as to be suitable for any sea area in which the U-boats were operating. Several of these circuits were known as "Convoy circuits," and were used by U-boats while making group attacks on convoys. The following is a list of the circuits used. It is to be noted that the name of the circuit in most cases indicates the general area in which the circuit was used.

(a) Regular U-boat Circuits:

Coastal Ireland America 1, A & B America 2, C & D America 3 E & F Africa 1, A&B Africa 2, C & D Africa 3, E & F Arctic Mediterranean Aegean Penang

(b) Convoy Circuits:

Diana Hubertus Wotan

(c) Other circuits used by U-boats:

Bruno 3 (Norddeich) Anton (Kootwijk)

All of the circuits in list (a) were used at one time or another during the war. Certain circuits were dropped or put into effect depending upon the disposition of the U-boats at sea. The Coastal circuit was normally used by boats operation in the Channel and Biscay areas. Ireland was used for the eastern North Atlantic. The America and Africa circuits consisted of three separate circuits each in which two channels or frequencies were generally keyed simultaneously. Each of these two could be disconnected and separated as a separate circuit if necessary. America 1 was generally used in the same area as Ireland circuit. America 2 served the western Atlantic north of a line from about the Azores to Key West. America 3 served the Middle Atlantic, Caribbean and South American coastal areas. The Africa circuits, of which never more that two were employed at one time, served the southern East Atlantic and the Indian Ocean.

All of the above circuits were controlled form Lorient, Paris, Bernau (Berlin), or Wilhelmshaven, depending on the progress of the war.

The Arctic circuit, which was controlled from Northern Norway, served U-boats operating off Northern Norway and on the Murmansk routes. The Mediterranean circuit, controlled from Toulon, served U-boats in the Western Mediterranean, while the Aegean circuit, controlled form Salamis, served the Eastern Mediterranean. Penang acted as control for the circuit of the name and served the Indian Ocean area, supplementing the Africa services.

Of the three convoy circuits in list (b), either Diana or Hubertus was always in effect, at times both were employed simultaneously. Wotan was in force only once and for only a short period during the latter part of the war. The purpose of these special circuits was to separate communications with Uboat operating groups from the traffic with other U-boats in the area which were not members of the group. Normally Uboats guarded the area circuits until contact with a convoy was contemplated or made, then shifted to guard the designated convoy circuit. When operations were broken off, the U-boats returned to the area circuit.

In the event that communications with home stations were broken off because of ionospheric disturbances or for other reasons, provisions were made for U-boats operating as a group to maintain contact with each other by means of what was known as a "Group Circuit". The procedure was for all boats concerned to shift to a predetermined frequency, appoint one boat as control, and continue operations until conditions permitted a return to the assigned circuit.

Other circuits available for use of U-boats were Bruno 3, designated Series Norddeich by the Allies, and Anton, otherwise known as Series Kootwijk. Bruno 3 consisted of four frequencies keyed simultaneously. The frequencies were chosen from the various wave band to permit world-wide coverage both day and night. While this circuit was used mostly by U-boats, it could also be used by surface craft. In fact, it was on one of the Bruno 3 frequencies that the ill-fated *Bismarck* transmitted her last message. Far East surface blockade runners were known to guard this circuit while outside of Japanese-controlled territory. Off-frequency operation was also carried out by U-boats in connection with this series.

Circuit Anton normally consisted of four frequencies keyed together and was intended for the use of boats in the Eastern North Atlantic and Northern Norway. This circuit was available to both U-boats and surface craft. A system provoking for off-frequency operation in connection with Anton was in effect but apparently seldom, if ever, used.

4. Use of Medium Frequencies.

Medium frequencies were used by U-boats for homing purposes and sometimes for general communication in home waters. Three types of homing on M/F were noted: homing for convoy attack, sometimes in cooperation with aircraft; homing for rendezvous; and homing to port. In homing for convoy attack, the U-boat which first made contact on a convoy was ordered by control to send beacon signals to lead other Uboats to the convoy. Homing for rendezvous, usually for the purpose of supplying provisions and fuel, was accomplished by having the supply boat transmit beacon signals on M/F. Such signals were ordinarily sent only during bad weather when precise navigation was not possible. In homing to port, the beacon signal was sent by the escort vessel or by regular shore beacon transmitters.

5. Use of very low frequency.

High-powered very low frequency transmitters were used extensively by the Germans to augment the regular Uboat transmissions on H/F. All traffic carried on the regular Uboat series was repeated on very low frequency to enable reception while submerged or when ionospheric conditions prevented reception on H/F. Practically every known highpowered very low frequency transmitter in occupied Europe was employed for this purpose at one time or another. What was estimated to be one of the most powerful very low frequency transmitters in the world, called "Goliath" by the Germans, appeared on the air late in 1943. This transmitter, having a power believed to be nearly 1000 kilowatts, was capable of being shifted in frequency and had a range form 15 to 25 kcs. One U-boat reported a signal strength of 5 from the Caribbean while submerged at 60 feet.

6. Norddeich off-frequency operation. (Standing War Orders 217 and 218)

A method of transmitting by U-boats to defeat the Allied HF/DF organization was brought into operation in October 1943. This system was used in conjunction with the Norddeich (DAN) transmitters. Briefly the system was as follows: Norddeich sent on four frequencies in four different wave band simultaneously. Each wave band had ten different "offfrequencies" above and below the basic frequency available for use. Norddeich selected one off-frequency for each wave band in use and informed the U-boat of the chosen frequencies by inserting several indicating letters in the call sign idling strip. The U-boat desiring to use this system listened to determine the valid frequencies and then transmitted on the offfrequency in the wave band best heard. The above system which offered little hindrance to HF/DF operations, was continued until January 1945. At that time a more complicated system was inaugurated and continued in use until a few days before the end of the war. The latter system provided for using any one of 336 kcs above or below each basic frequency. Further, the system of indicating valid off-frequencies was changed to compose three four-letter groups which were encoded on a special table. Otherwise it was essentially the same as the former system. This new system proved difficult for the HF/DF organization because a very exact frequency calibration was required to detect each transmission. Only mediocre success was experienced in D/Fing such transmissions.

A set of four "check" transmitters were operated in conjunction with the Norddeich series for assisting U-boats to select the proper wave band in which to transmit. The transmitters were of the same power as the regular U-boat transmitters. Therefore a U-boat, after listening to all four, could select the wave band best heard, and could transmit with a good chance of being heard in Germany.

#### 7. "Kurier."

A system of high-speed automatic "flash" transmission known by the covername "Kurier" was first introduced on an experimental basis in August 1944. This equipment consisted of a separate unit designed to be attached to a radio transmitter. The unit could be sit up by a series of levers to reproduce dots, dashes, and spaces, and was capable of sending about ten letters of encoded text at a speed of approximately 600 words per minute. Nothing is known of the receiving equipment, but presumably and automatic recorder of high sensitivity was required. Obviously this system was designed as a counter-measure against D/F. Further security was obtained in the use of frequencies, in that deviation from a given basic frequency of as much as 200 kcs plus of minus was provided for. In no case were Kurier transmissions ever D/F'd, and it is significant that if this system had been brought into effective operational use, the Allied D/F organization would gave been rendered helpless until counter-equipment could have been devised.

#### 8. U.S. Intercept Operations

First efforts to intercept German naval circuits were made by OP-20-G early in 1938 from the East Coast of the United States. The results obtained were very poor, mainly because German operations at that time were confined to the Baltic and North Sea areas, with resulting poor signal strength. In October 1938, an intercept team consisting of four men was established in the flagship of Squadron 40-T, then operating in European water, results were excellent and this team remained in operation until the squadron returned to the U.S. in September 1940.<sup>1</sup> At the outbreak of World War II, all German U-boat circuits were known and were being intercepted by OP-20-G.

Interception was undertaken on a full scale by shore intercept stations on the U.S. East Coast thereafter. This work was done at Cheltenham, Maryland until January 1943 and was

<sup>&</sup>lt;sup>1</sup>For more on Squadron 40-T operations see Volume I, xvi-xix.

then transferred to Chatham, Massachusetts where a major intercept station was placed in operation. Practically 100 percent intercept coverage was obtained until all but the final week of the war. Information relating to German communications procedure obtained by radio intelligence methods was compiled and published by OP-20-G in a document known as RIP 42 early in 1941. The information contained in this publication was greatly enlarged upon when subsequent liaison with the British was effected.

#### 9. HF/DF operations ashore.

First attempts to take bearings on U-boat transmissions were begun in January 1941. At this time there were only seven HF/DF stations in operation in the Atlantic area and bearings were taken independently. However, through liaison with the British, added D/F stations, and improved operating technique, the D/F organization was fairly efficient by the time of U.S. entry into the war. Improvements were rapid thereafter, and at the war's end, fixes were being made with bearings furnished by more than forty U.S., British, and Canadian stations. Three U.S. nets, and East Coast, Caribbean, and South American, were in operation, each with plotting facilities to serve the Sea Frontier Commands required. Centralized and interlocked control by both land-line and radio was maintained, making it possible to alert or "tip-off" all D/F stations.

The use of the "tip-off" system was gradually expanded to a point at which, in addition to our own stations, it was utilized by all Canadian stations, outlying British stations and all U.S. vessels engaged in convoy escort or antisubmarine warfare operations. The "tip-off" frequencies were controlled by San Juan, sending simultaneously on four frequencies which were selected to cover the entire Atlantic. "Tip-offs" from U.S east coast stations on landlines were relayed by radio to San Juan by Jupiter. The "tip-off" system helped greatly in increasing the efficiency of the HF/DF nets and proved particularly helpful to HF/DF equipped ships at sea.

10. HF/DF operations afloat.

Every possible assistance was rendered by OP-20-G in furthering the shipboard HF/DF program as an additional anti-

submarine warfare weapon. Two technicians from OP-20-G were sent to England in 1942 to gather information relating to the operation and maintenance of this equipment. These two men assisted in establishing an HF/DF school for the training of shipboard operators in December 1943. The school was subsequently administered by Bureau of Personnel. Constant liaison with the school and forces afloat was maintained by OP-20-G personnel to insure that all concerned were in possession of the latest trends in U-boat communication procedures. Such liaison was in the nature of exchange visits by radio intelligence an D/F officers both ashore and afloat, letters, and dispatches. It is considered that this assistance was of great value to the forces afloat. A special publication dealing with German U-boat communication procedure, designed primarily for Atlantic Fleet vessels engaged in convoy escort and antesubmarine warfare, was published on 1 July 1943. This publication, CSP 1774 Series, was particularly valuable to HF/DF equipped vessels in detecting U-boat transmissions at sea.

#### 11. TINA and RFP

Both TINA and RFP were extensively utilized in conjunction with HF/DF in attempting to identify individual Uboats. TINA, the purpose of which was to identify a radio operator by his sending characteristics, consisted of making a tape recording of each U-boat transmission and taking mathematical measurements of each dot, dash, and space. RFP was a method of transmitter identification in which high-speed photographs were taken of a transmission, making possible an analysis of the transmitter's power supply.

12. Chronological account of the German struggle against D/F and radio interception.

An early illustration of precautions against HF/DF during refueling operations occurred in December 1942, when several U-boats were to be refueled by Schnoor (U-460). COMSUBs warned the boats against too frequent use of radio when approaching the provisioning point and directed that no beacon signals should be requested until several hours had passed without finding the provisioner. (2158/3 December 1942) In an earlier message of the same day (1056/3 December 1942), the boats were ordered to report their fuel stocks after provisioning, but only after having moved 30 miles away form the provisioning point. Other traffic of the same month indicated that Atlantic U-boats were making use of the Norddeich off-frequency procedure in transmitting short signals, with acknowledgment by control on the basic frequencies.

On 4 January 1943, a new Standing War Order was issued containing an outline of points to be considered before sending any radio message. (0516/4 January 1943) The purpose of the order was to eliminate the transmission of unnecessary reports and to provide for transmission of necessary ones in the shortest possible form. This was merely the first step in a campaign aimed at the tightening of radio discipline, for during the first months of 1943 there were constant reminders on the subject, with emphasis on the necessity for radio silence and the danger of tuning transmitters with radiation.

Repeated and emphatic instructions underlined the danger which could result from the use of radio during rendezvous operations and whenever groups of U-boats were in the same area, and there were many explicit reprimands for infractions. On 5 May an emphatic reiteration of the ban on tuning with radiation addressed to Arctic U-boats required that main and spare transmitter aerials be plugged in only when the situation might require quick use of the transmitter and that all-wave, Broadcast, and "Radione" receivers be used by boats in patrol lines only for reception of tactically important reports, owing to the danger of D/F.

The increased difficulty for U-boats at refueling rendezvous was reflected in COMSUBs' message 2306/5 of June 1943, in which he directed Group *Trutz* and Bartke (U-488) to carry out provisioning operations under radio silence and without any beacon signal unless the rendezvous had not taken place after searching for two days. Comparison of this order with the December 1942 order to boats refueling form Schnoor, cited above, illustrates the trend toward extreme caution which had developed in the intervening period.

A more direct indication of German appreciation of the effectiveness of the allied radio intelligence organization and a further intensification of efforts to escape D/F and radio interception became apparent from traffic of 10 August 1943. On that date COMSUBs' Current Order 38 summed up the situation as follows: "By employing long-range reconnaissance aircraft and aircraft carriers the enemy is today able to operate aircraft on offensive patrol on the basis of D/F bearings not only near the coast but also in all danger of bearings being taken on U-boats when using their radio has thereby become more serious. The inaccuracy of the bearings of between 50 and 60 miles is compensated for by radar location by the aircraft."

Because of this situation U-boats were ordered to take advantage of discovery by the enemy, occasioned by sightings and attacks, to send their reports; to be especially careful in the use of radio when its use was necessary; after using the radio to remain submerged for several hours when there was danger of being taken by surprise; to supervise radio operation and to tune without radiation; and to use alternative frequencies of the Norddeich service (0827 and 0845/10 August 1943 ff), was devoted to a complete revision of the off-frequency procedure already in effect, to go into force on 1 September (later postponed to 1 October). Under the new procedure, deviations from the basic frequencies could be changed frequently by the control station and would never be known in advance of the hour of transmission even by the transmitting U-boat. Several messages of September and October urged increased use of the alternative frequencies when giving passage reports in order to make it more difficult for the enemy to take bearings and establish the number of inward and outward bound boats.

From the middle of August to the end of November 1943, there was a renewal of preoccupation with the possibility that the Allied D/F services was profiting by receiver radiations. A message of 19 August ordered that certain types of receivers were not to be used until investigation of that possibility had been completed, and directed that very low frequency transmissions were to be received with the D/F receiver only, while the all-wave receiver was to be restricted to essential services (1922/19 August 1943). On 24 October however, Hartmann (U-441) reported a suspicion that bearings could be taken on the D/F receiver because he had been flown at shortly after switching it on (2237/24 October 1943); consequently on 5 November a new order directed outward and inward bound boats east of 18°W, as well as boats outbound from Germany as far as Naval Grid Square AE (Iceland Area), to receive very low frequency only when submerged. H/F reception on the surface was permissible only if a boat was equipped with a "Main" receiver. (2049/5 November 1943) The ban on some of the other receivers was lifted on 8/12, however, presumably after satisfactory results in radiation tests (1837/8 December 1943).

The emphasis on radio discipline and restriction of transmissions continued in 1944, with few significant developments in the first seven months of the year. An attempt was made to speed up the transmissions of short signals and short weather reports in January, and provisional Standing War Order 254, providing for visual signals between cooperating aircraft and U-boats as a means of avoiding D/F, was issued on the 30th of that month. In the spring, weather reports became so important to the German High Command that the possibility of D/F fixes had to be accepted in order to get the weather information through (1416/4 May 1944). However, boats were ordered to proceed submerged for several hours and to change position constantly after sending their reports.

The summer of 1944 brought a new and potentially important development in German communications in the form of experiments with "Kurier" procedure. The experiments started on 4 August and continued, with some interruptions for correction of faulty equipment, until 28 August, when the tests were canceled temporarily because transmitting installations were still not reliable enough. During this period there had been a few successful transmissions, but a large number failed to be received or could not be deciphered owing to failure to attain the required fine adjustment of the transmitting installation.

Another period of trial started in November 1944, was discontinued in December, and resumed in January 1945. During December tests were made in transmission of "Kurier" signals over the schnorchel round dipole. There was no indication of the results actually obtained, but COMSUBs held little hope of success because the radiation obtained through use of the schnorchel round dipole was insufficient. At 2325 on 27 January the first operational "Kurier" signal was sent by Schumann (U-245), operating under the cover-name "Brutus", but on 2 February the use of "Kurier" procedure was discontinued and never resumed, probably because of the evacuation of Bernau, where the receiving installation was located.

0 

One final development of importance during the last months of the war was the introduction on 25 January 1945 of a new and complicated cipher for determining valid Norddeich off-frequencies, directions for which had been given in a long series of messages between 20 and 26 November 1944. The new system was effective to a considerable extent in evading D/F, but was never used as extensively as the former "KONRAD" system, probably because of the many failures to get through to Control which were occasioned by the lack of necessary accurate tuning to proper frequencies.

# OTHER BOOKS IN THE INTELLIGENCE SERIES INCLUDE

I-4	The Defection of Igor Gouzenko, Volume I
I - 5	The Defection of Igor Gouzenko, Volume II
I-6	The Defection of Igor Gouzenko, Volume III
I-7	Intelligence and Cryptanalytic Activities of the Japanese During World War II, J.W. Bennett, W.A. Hobart, J.B. Spitzer
I-8	Evolution and Organization of Intelligence Activities In the United States, Harold C. Relyea
I-9	Selection of Personnel for Clandestine Operations, Assessment of Men, Donald W. Fiske, et al.
I - 10	The History of Special Branch, M.I.S., in World War II, Alfred McCormack
I - 11	Ultra in the Atlantic, Volume I, Allied Communications Intelligence and the Battle of the Atlantic, Jeffrey K. Bray
I - 12	Ultra in the Atlantic, Volume II, U-Boat Operations, Jeffrey K. Bray
I - 13	Ultra in the Atlantic, Volume III, German Naval Communications Intelligence, Jeffrey K. Bray

ISBN: 0-89412-238-X

0000000000

00000000